

# Summary for Input Data



Property Reference	C12-00-02	Issued on Date	15/10/2025
Assessment Reference	Design V1	Prop Type Ref	C12-00-02
Property	C12-00-02, Horsham Enterprise Park		
SAP Rating	83 B	DER	5.11
Environmental	97 A	% DER < TER	13.80
CO <sub>2</sub> Emissions (t/year)	0.23	DFEE	62.97
Compliance Check	See BREL	% DFEE < TFEE	29.81
% DPER < TPER	27.46	DPER	8.13
		TPER	73.86

Assessor Details	Miss Charlotte Russell	Assessor ID	DK97-0001
Client			

## SUMMARY FOR INPUT DATA FOR: New Build (As Designed)

Orientation	Northwest	
Property Tenure	ND	
Transaction Type	6	
Terrain Type	Suburban	
1.0 Property Type	Flat, Mid-Terrace	
Position of Flat	Ground-floor flat	
Which Floor	0	
2.0 Number of Storeys	1	
3.0 Date Built	2025	
3.0 Property Age Band	L	
4.0 Sheltered Sides	2	
5.0 Sunlight/Shade	Average or unknown	
6.0 Thermal Mass Parameter	Precise calculation	
Thermal Mass	286.13	kJ/m <sup>2</sup> K
7.0 Electricity Tariff	Standard	
Smart electricity meter fitted	Yes	
Smart gas meter fitted	No	

7.0 Measurements		Heat Loss Perimeter	Internal Floor Area	Average Storey Height
		Ground floor: 12.40 m	52.70 m <sup>2</sup>	2.50 m

8.0 Living Area	23.92	m <sup>2</sup>
-----------------	-------	----------------

9.0 External Walls		Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Res	Shelter	Openings	Area Calculation Type
External Wall	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.15	110.00	15.50	5.19	0.00	None	10.31	Enter Gross Area
Sheltered	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.18	110.00	15.50	13.38	0.90	Stairwell Access Corridor 4	2.12	Enter Gross Area

9.1 Party Walls		Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )	Shelter Res	Shelter
Party Wall	Filled Cavity with Edge Sealing	Single plasterboard on dabs both sides, lightweight aggregate blocks, cavity or cavity fill	0.00	110.00	42.50	0.00	None

9.2 Internal Walls		Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Internal Walls		Plasterboard on timber frame	9.00	79.98

10.1 Party Ceilings		Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Ceiling		Precast concrete plank floor (screed laid on rubber), carpeted	30.00	52.70

## 11.0 Heat Loss Floors

# Summary for Input Data

Description	Type	Storey Index	Construction	U-Value (W/m <sup>2</sup> K)	Shelter Code	Shelter Factor	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Ground Floor	Ground Floor - Solid	Lowest occupied	Suspended concrete floor, carpeted	0.10	None	0.00	75.00	52.70
<b>12.0 Opening Types</b>								
Description	Data Source	Type	Glazing	Glazing Gap	Filling Type	G-value	Frame Type	Frame Factor
Solid Door Glazing	Manufacturer	Solid Door Window	Double Low-E Soft 0.05			0.00 0.63		0.80 1.20
<b>13.0 Openings</b>								
Name	Opening Type	Location	Orientation	Area (m <sup>2</sup> )	Pitch			
FSD	Solid Door	Sheltered	North West	2.12	0			
RW	Glazing	External Wall	South East	3.46	0			
RGD	Glazing	External Wall	South East	4.69	0			
FW	Glazing	External Wall	North West	2.16	0			
<b>14.0 Conservatory</b>								
None								
<b>15.0 Draught Proofing</b>								
100								
<b>16.0 Draught Lobby</b>								
No								
<b>17.0 Thermal Bridging</b>								
<b>17.1 List of Bridges</b>								
Bridge Type	Source Type	Length	Psi	Adjusted Reference:	Imported			
E2 Other lintels (including other steel lintels)	Independently assessed	6.68	0.02	0.02 RCD	No			
E3 Sill	Independently assessed	3.65	0.02	0.02 RCD	No			
E4 Jamb	Independently assessed	17.00	0.01	0.01 RCD	No			
E5 Ground floor (normal)	Independently assessed	12.40	0.08	0.08 RCD	No			
E7 Party floor between dwellings (in blocks of flats)	Independently assessed	12.40	0.05	0.05 RCD	No			
E16 Corner (normal)	Independently assessed	0.00	0.05	0.05 RCD	No			
P1 Party wall - Ground floor	Table K1 - Default	17.00	0.32	0.32 Default	No			
P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	17.00	0.00	0.00 Default	No			
E18 Party wall between dwellings	Independently assessed	10.00	0.06	0.06 RCD	No			
E17 Corner (inverted – internal area greater than external area)	Independently assessed	0.00	-0.10	-0.10 RCD	No			
Y-value	0.10				W/m <sup>2</sup> K			
Description	Bridge							
<b>19.0 Mechanical Ventilation</b>								
<b>Mechanical Ventilation</b>								
Mechanical Ventilation System Present	Yes							
Approved Installation	Yes							
Mechanical Ventilation data Type	Database							
Type	Balanced mechanical ventilation with heat recovery							
MV Reference Number	500500							
Configuration	2							
MVHR Duct Insulated	Uninsulated Ducts							
Manufacturer SFP	0.59							
Duct Type	Rigid							
MVHR Efficiency	89.00							
Wet Rooms	2							
SFP from Installer Commissioning Certificate	No							
MVHR System Location	Inside heated envelope (installed exclusively)							
Duct Installation Specification	Level 2							
<b>19.1 Mechanical extract ventilation - Decentralised</b>								
SFP	Fan/Room Type	Count						
0.13	In Room Fan	1						
	Kitchen							
0.11	In Room Fan Other	3						
	Wet Room							
0.00	In Duct Fan Kitchen	0						
0.00	In Duct Fan Other	0						
	Wet Room							
0.10	Through Wall Fan	0						
	Kitchen							
0.10	Through Wall Fan	0						
	Other Wet Room							
<b>20.0 Fans, Open Fireplaces, Flues</b>								

# Summary for Input Data

Number of open chimneys	0										
Number of open flues	0										
Number of chimneys/flues attached to closed fire	0										
Number of flues attached to solid fuel boiler	0										
Number of flues attached to other heater	0										
Number of blocked chimneys	0										
Number of intermittent extract fans	0										
Number of passive vents	0										
Number of flueless gas fires	0										
<b>21.0 Fixed Cooling System</b>											
	No										
<b>22.0 Pressure Testing</b>											
Designed AP <sub>50</sub>	3.00										
Property Tested?	Yes										
Test Method	Blower Door										
<b>22.0 Lighting</b>											
No Fixed Lighting	No										
	<table border="1"> <thead> <tr> <th>Name</th> <th>Efficacy</th> <th>Power</th> <th>Capacity</th> <th>Count</th> </tr> </thead> <tbody> <tr> <td>Low energy Lighting</td> <td>85.00</td> <td>5.00</td> <td>425.00</td> <td>10</td> </tr> </tbody> </table>	Name	Efficacy	Power	Capacity	Count	Low energy Lighting	85.00	5.00	425.00	10
Name	Efficacy	Power	Capacity	Count							
Low energy Lighting	85.00	5.00	425.00	10							
<b>24.0 Main Heating 1</b>											
Percentage of Heat	SAP table										
Database Ref. No.	100.00										
Fuel Type	0										
SAP Code	Electricity										
In Winter	691										
In Summer	100.00										
Controls SAP Code	194.18										
Delayed Start Stat	2603										
Burner Control	No										
HETAS approved System	Modulating										
Is MHS Pumped	No										
Heating Pump Age	Pump in heated space										
Heat Emitter	2013 or later										
Underfloor Heating	Radiators										
Flow Temperature	Yes - Pipes in thin screed										
Flow Temperature Value	Enter value										
	55.00										
<b>25.0 Main Heating 2</b>											
Percentage of Heat	Database										
Database Ref. No.	0.00										
Fuel Type	100834										
SAP Code	Electricity										
In Winter	0										
In Summer	301.93										
Model Name	194.18										
Manufacturer	Compact P										
Controls	Nilan AS										
Delayed Start Stat	2100										
HETAS approved System	No										
	No										

# Summary for Input Data

Flow Temperature	Enter value										
<b>26.0 Heat Networks</b>	None										
<b>27.0 Secondary Heating</b>	None										
<b>28.0 Water Heating</b>											
Water Heating	Main Heating 2										
SAP Code	914										
Flue Gas Heat Recovery System	No										
Waste Water Heat Recovery Instantaneous System 1	No										
Waste Water Heat Recovery Instantaneous System 2	No										
Waste Water Heat Recovery Storage System	No										
Solar Panel	No										
Water use <= 125 litres/person/day	Yes										
Summer Immersion	No										
Cold Water Source	From mains										
Bath Count	1										
Baths connected to WWHRS	0										
Supplementary Immersion	No										
Immersion Only Heating Hot Water	No										
<b>28.1 Showers</b>											
<b>Description</b>	<b>Shower Type</b>	<b>Flow Rate</b> [l/min]	<b>Rated Power</b> [kW]	<b>Connected</b>	<b>Connected To</b>						
8 lpm	Unknown	8.00		No							
<b>28.3 Waste Water Heat Recovery System</b>											
<b>29.0 Hot Water Cylinder</b>		Internal Store									
Cylinder Stat	No										
Cylinder In Heated Space	No										
Independent Time Control	No										
Insulation Type	Measured Loss										
Insulation Thickness	0										
Cylinder Volume	180.00	L									
Loss	0.84	kWh/day									
In Airing Cupboard	No										
<b>31.0 Thermal Store</b>		None									
<b>34.0 Small-scale Hydro</b>		None									
Electricity Generated	0.00										
Apportioned	0.00	kWh/Year									
Connected to dwelling's electricity meter	Yes										
Electricity Generation	Annual										
Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
<b>Recommendations</b>											
<b>Lower cost measures</b>											
None											
<b>Further measures to achieve even higher standards</b>											
None											

# Predicted Energy Assessment


C12-00-02, Horsham Enterprise Park

Dwelling type:  
Date of assessment:  
Produced by:  
Total floor area:  
DRRN:

Flat, Mid-Terrace  
15/10/2025  
Charlotte Russell  
52.7 m<sup>2</sup>

This document is a Predicted Energy Assessment for properties marketed when they are incomplete. It includes a predicted energy rating which might not represent the final energy rating of the property on completion. Once the property is completed, this rating will be updated and an official Energy Performance Certificate will be created for the property. This will include more detailed information about the energy performance of the completed property.

The energy performance has been assessed using the Government approved SAP 10 methodology and is rated in terms of the energy use per square meter of floor area; the energy efficiency is based on fuel costs and the environmental impact is based on carbon dioxide (CO<sub>2</sub>) emissions.



The energy efficiency rating is a measure of the overall efficiency of a home. The higher the rating the more energy efficient the home is and the lower the fuel bills are likely to be.

The environmental impact rating is a measure of a home's impact on the environment in terms of carbon dioxide (CO<sub>2</sub>) emissions. The higher the rating the less impact it has on the environment.

# Thermal Bridging



Property Reference	C12-00-02		Issued on Date	15/10/2025
Assessment Reference	Design V1		Prop Type Ref	Mid-Terrace Flat
Property	C12-00-02, Horsham Enterprise Park			
SAP Rating	83 B	DER	5.11	TER
Environmental	97 A	% DER < TER		62.97
CO <sub>2</sub> Emissions (t/year)	0.23	DFEE	27.38	TFEE
Compliance Check	See BREL	% DFEE < TFEE		8.13
% DPER < TPER	27.46	DPER	53.58	TPER

Assessor Details	Miss Charlotte Russell	Assessor ID	DK97-0001
Client			

	Junction details	Source Type	Psi (W/mK)	Length (m)	Result	Reference
External wall	E2 Other lintels (including other steel lintels)	Independently assessed	0.022	6.68	0.15	RCD
External wall	E3 Sill	Independently assessed	0.016	3.65	0.06	RCD
External wall	E4 Jamb	Independently assessed	0.011	17.00	0.19	RCD
External wall	E5 Ground floor (normal)	Independently assessed	0.076	12.40	0.94	RCD
External wall	E7 Party floor between dwellings (in blocks of flats)	Independently assessed	0.053	12.40	0.66	RCD
External wall	E16 Corner (normal)	Independently assessed	0.051	0.00	0.00	RCD
Party wall	P1 Party wall - Ground floor	Table K1 - Default	0.320	17.00	5.44	Default
Party wall	P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	0.000	17.00	0.00	Default
External wall	E18 Party wall between dwellings	Independently assessed	0.057	10.00	0.57	RCD
External wall	E17 Corner (inverted – internal area greater than external area)	Independently assessed	-0.104	0.00	-0.00	RCD

Total: 96.13 W/mK:

Y-Value: 0.10 W/m<sup>2</sup>K:

# Summary for Input Data



Property Reference	C12-01-01	Issued on Date	15/10/2025
Assessment Reference	Design V1	Prop Type Ref	C12-01-01
Property	C12-01-01, Horsham Enterprise Park		
SAP Rating	80 C	DER	5.39
Environmental	96 A	% DER < TER	63.03
CO <sub>2</sub> Emissions (t/year)	0.34	DFEE	32.37
Compliance Check	See BREL	% DFEE < TFEE	21.94
% DPER < TPER	27.75	DPER	56.17
TPER	77.74		

Assessor Details	Miss Charlotte Russell	Assessor ID	DK97-0001
Client			

## SUMMARY FOR INPUT DATA FOR: New Build (As Designed)

Orientation	Northwest
Property Tenure	ND
Transaction Type	6
Terrain Type	Suburban
1.0 Property Type	Flat, Mid-Terrace
Position of Flat	Mid-floor flat
Which Floor	1
2.0 Number of Storeys	1
3.0 Date Built	2025
3.0 Property Age Band	L
4.0 Sheltered Sides	2
5.0 Sunlight/Shade	Average or unknown
6.0 Thermal Mass Parameter	Precise calculation
Thermal Mass	263.44
	kJ/m <sup>2</sup> K
7.0 Electricity Tariff	Standard
Smart electricity meter fitted	Yes
Smart gas meter fitted	No

7.0 Measurements	Heat Loss Perimeter	Internal Floor Area	Average Storey Height
	Ground floor: 28.34 m	74.97 m <sup>2</sup>	2.50 m

8.0 Living Area	27.27	m <sup>2</sup>
-----------------	-------	----------------

9.0 External Walls	Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Res	Shelter	Openings	Area Calculation Type
External Wall	External Wall	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.15	110.00	48.05	33.44	0.00	None	14.61	Enter Gross Area
Sheltered	Sheltered	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.18	110.00	22.80	20.68	0.90	Stairwell Access Corridor 4	2.12	Enter Gross Area

9.1 Party Walls	Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )	Shelter Res	Shelter
Party Wall	Party Wall	Filled Cavity with Edge Sealing	Single plasterboard on dabs both sides, lightweight aggregate blocks, cavity or cavity fill	0.00	110.00	15.75	0.00	None

9.2 Internal Walls	Description	Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Internal Walls	Internal Walls	Plasterboard on timber frame	9.00	132.62

10.1 Party Ceilings	Description	Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Ceiling	Ceiling	Precast concrete plank floor (screed laid on rubber), carpeted	30.00	74.97

## 11.0 Heat Loss Floors

# Summary for Input Data

Description	Type	Storey Index	Construction	U-Value (W/m <sup>2</sup> K)	Shelter Code	Shelter Factor	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )																																																																								
Exposed Floor	Exposed Floor - Solid	Lowest occupied	Other	0.12	None	0.00	75.00	74.97																																																																								
<b>12.0 Opening Types</b>																																																																																
Description	Data Source	Type	Glazing	Glazing Gap	Filling Type	G-value	Frame Type	Frame Factor	U Value (W/m <sup>2</sup> K)																																																																							
Solid Door Glazing	Manufacturer Manufacturer	Solid Door Window	Double Low-E Soft 0.05			0.00 0.63		0.80	1.20 1.20																																																																							
<b>13.0 Openings</b>																																																																																
Name	Opening Type	Location	Orientation	Area (m <sup>2</sup> )	Pitch																																																																											
FSD	Solid Door	Sheltered	North West	2.12	0																																																																											
RW	Glazing	External Wall	South East	5.52	0																																																																											
LSGD	Glazing	External Wall	North East	2.32	0																																																																											
LSW	Glazing	External Wall	North East	6.77	0																																																																											
<b>14.0 Conservatory</b>																																																																																
None																																																																																
<b>15.0 Draught Proofing</b>																																																																																
100 %																																																																																
<b>16.0 Draught Lobby</b>																																																																																
No																																																																																
<b>17.0 Thermal Bridging</b>																																																																																
<b>17.1 List of Bridges</b>																																																																																
<table border="1"> <thead> <tr> <th>Bridge Type</th><th>Source Type</th><th>Length</th><th>Psi</th><th>Adjusted Reference:</th><th>Imported</th></tr> </thead> <tbody> <tr> <td>E2 Other lintels (including other steel lintels)</td><td>Independently assessed</td><td>9.01</td><td>0.02</td><td>0.02 RCD</td><td>No</td></tr> <tr> <td>E3 Sill</td><td>Independently assessed</td><td>7.00</td><td>0.02</td><td>0.02 RCD</td><td>No</td></tr> <tr> <td>E4 Jamb</td><td>Independently assessed</td><td>21.64</td><td>0.01</td><td>0.01 RCD</td><td>No</td></tr> <tr> <td>E20 Exposed floor (normal)</td><td>Independently assessed</td><td>28.34</td><td>0.05</td><td>0.05 RCD</td><td>No</td></tr> <tr> <td>E7 Party floor between dwellings (in blocks of flats)</td><td>Independently assessed</td><td>28.34</td><td>0.05</td><td>0.05 RCD</td><td>No</td></tr> <tr> <td>E16 Corner (normal)</td><td>Independently assessed</td><td>7.50</td><td>0.05</td><td>0.05 RCD</td><td>No</td></tr> <tr> <td>P7 Party Wall - Exposed floor (normal)</td><td>Table K1 - Default</td><td>6.30</td><td>0.48</td><td>0.48 Default</td><td>No</td></tr> <tr> <td>P3 Party wall - Intermediate floor between dwellings (in blocks of flats)</td><td>Table K1 - Default</td><td>6.30</td><td>0.00</td><td>0.00 Default</td><td>No</td></tr> <tr> <td>E18 Party wall between dwellings</td><td>Independently assessed</td><td>2.50</td><td>0.06</td><td>0.06 RCD</td><td>No</td></tr> <tr> <td>E17 Corner (inverted – internal area greater than external area)</td><td>Independently assessed</td><td>0.00</td><td>-0.10</td><td>-0.10 RCD</td><td>No</td></tr> <tr> <td>E25 Staggered party wall between dwellings</td><td>Table K1 - Default</td><td>2.50</td><td>0.24</td><td>0.24 E25 - Default</td><td>No</td></tr> </tbody> </table>									Bridge Type	Source Type	Length	Psi	Adjusted Reference:	Imported	E2 Other lintels (including other steel lintels)	Independently assessed	9.01	0.02	0.02 RCD	No	E3 Sill	Independently assessed	7.00	0.02	0.02 RCD	No	E4 Jamb	Independently assessed	21.64	0.01	0.01 RCD	No	E20 Exposed floor (normal)	Independently assessed	28.34	0.05	0.05 RCD	No	E7 Party floor between dwellings (in blocks of flats)	Independently assessed	28.34	0.05	0.05 RCD	No	E16 Corner (normal)	Independently assessed	7.50	0.05	0.05 RCD	No	P7 Party Wall - Exposed floor (normal)	Table K1 - Default	6.30	0.48	0.48 Default	No	P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	6.30	0.00	0.00 Default	No	E18 Party wall between dwellings	Independently assessed	2.50	0.06	0.06 RCD	No	E17 Corner (inverted – internal area greater than external area)	Independently assessed	0.00	-0.10	-0.10 RCD	No	E25 Staggered party wall between dwellings	Table K1 - Default	2.50	0.24	0.24 E25 - Default	No
Bridge Type	Source Type	Length	Psi	Adjusted Reference:	Imported																																																																											
E2 Other lintels (including other steel lintels)	Independently assessed	9.01	0.02	0.02 RCD	No																																																																											
E3 Sill	Independently assessed	7.00	0.02	0.02 RCD	No																																																																											
E4 Jamb	Independently assessed	21.64	0.01	0.01 RCD	No																																																																											
E20 Exposed floor (normal)	Independently assessed	28.34	0.05	0.05 RCD	No																																																																											
E7 Party floor between dwellings (in blocks of flats)	Independently assessed	28.34	0.05	0.05 RCD	No																																																																											
E16 Corner (normal)	Independently assessed	7.50	0.05	0.05 RCD	No																																																																											
P7 Party Wall - Exposed floor (normal)	Table K1 - Default	6.30	0.48	0.48 Default	No																																																																											
P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	6.30	0.00	0.00 Default	No																																																																											
E18 Party wall between dwellings	Independently assessed	2.50	0.06	0.06 RCD	No																																																																											
E17 Corner (inverted – internal area greater than external area)	Independently assessed	0.00	-0.10	-0.10 RCD	No																																																																											
E25 Staggered party wall between dwellings	Table K1 - Default	2.50	0.24	0.24 E25 - Default	No																																																																											
Y-value																																																																																
0.05 W/m <sup>2</sup> K																																																																																
Description																																																																																
Bridge																																																																																
<b>19.0 Mechanical Ventilation</b>																																																																																
<b>Mechanical Ventilation</b>																																																																																
Mechanical Ventilation System Present																																																																																
Yes																																																																																
Approved Installation																																																																																
Yes																																																																																
Mechanical Ventilation data Type																																																																																
Database																																																																																
Type																																																																																
Balanced mechanical ventilation with heat recovery																																																																																
MV Reference Number																																																																																
500500																																																																																
Configuration																																																																																
2																																																																																
MVHR Duct Insulated																																																																																
Uninsulated Ducts																																																																																
Manufacturer SFP																																																																																
0.59																																																																																
Duct Type																																																																																
Rigid																																																																																
MVHR Efficiency																																																																																
89.00																																																																																
Wet Rooms																																																																																
2																																																																																
SFP from Installer Commissioning Certificate																																																																																
No																																																																																
MVHR System Location																																																																																
Inside heated envelope (installed exclusively)																																																																																
Duct Installation Specification																																																																																
Level 2																																																																																
<b>19.1 Mechanical extract ventilation - Decentralised</b>																																																																																
<b>SFP</b>	<b>Fan/Room Type</b>	<b>Count</b>																																																																														
0.13	In Room Fan	1																																																																														
	Kitchen																																																																															
0.11	In Room Fan Other	3																																																																														
	Wet Room																																																																															
0.00	In Duct Fan Kitchen	0																																																																														
0.00	In Duct Fan Other	0																																																																														
	Wet Room																																																																															
0.10	Through Wall Fan	0																																																																														
	Kitchen																																																																															
0.10	Through Wall Fan	0																																																																														
	Other Wet Room																																																																															

# Summary for Input Data

## 20.0 Fans, Open Fireplaces, Flues

Number of open chimneys	0
Number of open flues	0
Number of chimneys/flues attached to closed fire	0
Number of flues attached to solid fuel boiler	0
Number of flues attached to other heater	0
Number of blocked chimneys	0
Number of intermittent extract fans	0
Number of passive vents	0
Number of flueless gas fires	0

## 21.0 Fixed Cooling System

No
----

## 22.0 Pressure Testing

Designed AP <sub>50</sub>	Yes
	3.00
Property Tested?	Yes
Test Method	Blower Door

## 22.0 Lighting

No Fixed Lighting

Name	Efficacy	Power	Capacity	Count
Low energy Lighting	85.00	5.00	425.00	10

## 24.0 Main Heating 1

Percentage of Heat	100.00	%
Database Ref. No.	0	
Fuel Type	Electricity	
SAP Code	691	
In Winter	100.00	
In Summer	194.18	
Controls SAP Code	2603	
Delayed Start Stat	No	
Burner Control	Modulating	
HETAS approved System	No	
Is MHS Pumped	Pump in heated space	
Heating Pump Age	2013 or later	
Heat Emitter	Radiators	
Underfloor Heating	Yes - Pipes in thin screed	
Flow Temperature	Enter value	
Flow Temperature Value	55.00	

## 25.0 Main Heating 2

Percentage of Heat	0.00	%
Database Ref. No.	100834	
Fuel Type	Electricity	
SAP Code	0	
In Winter	308.21	
In Summer	194.18	
Model Name	Compact P	
Manufacturer	Nilan AS	
Controls	2100	
Delayed Start Stat	No	
HETAS approved System	No	

# Summary for Input Data

Flow Temperature	Enter value										
<b>26.0 Heat Networks</b>	None										
<b>27.0 Secondary Heating</b>	None										
<b>28.0 Water Heating</b>											
Water Heating	Main Heating 2										
SAP Code	914										
Flue Gas Heat Recovery System	No										
Waste Water Heat Recovery Instantaneous System 1	No										
Waste Water Heat Recovery Instantaneous System 2	No										
Waste Water Heat Recovery Storage System	No										
Solar Panel	No										
Water use <= 125 litres/person/day	Yes										
Summer Immersion	No										
Cold Water Source	From mains										
Bath Count	1										
Baths connected to WWHRS	0										
Supplementary Immersion	No										
Immersion Only Heating Hot Water	No										
<b>28.1 Showers</b>											
<b>Description</b>	<b>Shower Type</b>	<b>Flow Rate</b> [l/min]	<b>Rated Power</b> [kW]	<b>Connected</b>	<b>Connected To</b>						
8 lpm	Unknown	8.00		No							
<b>28.3 Waste Water Heat Recovery System</b>											
<b>29.0 Hot Water Cylinder</b>		Internal Store									
Cylinder Stat	No										
Cylinder In Heated Space	No										
Independent Time Control	No										
Insulation Type	Measured Loss										
Insulation Thickness	0										
Cylinder Volume	180.00	L									
Loss	0.84	kWh/day									
In Airing Cupboard	No										
<b>31.0 Thermal Store</b>		None									
<b>34.0 Small-scale Hydro</b>		None									
Electricity Generated	0.00										
Apportioned	0.00	kWh/Year									
Connected to dwelling's electricity meter	Yes										
Electricity Generation	Annual										
Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
<b>Recommendations</b>											
Lower cost measures											
None											
Further measures to achieve even higher standards											
None											

# Predicted Energy Assessment


C12-01-01, Horsham Enterprise Park

Dwelling type:  
Date of assessment:  
Produced by:  
Total floor area:  
DRRN:

Flat, Mid-Terrace  
15/10/2025  
Charlotte Russell  
74.97 m<sup>2</sup>

This document is a Predicted Energy Assessment for properties marketed when they are incomplete. It includes a predicted energy rating which might not represent the final energy rating of the property on completion. Once the property is completed, this rating will be updated and an official Energy Performance Certificate will be created for the property. This will include more detailed information about the energy performance of the completed property.

The energy performance has been assessed using the Government approved SAP 10 methodology and is rated in terms of the energy use per square meter of floor area; the energy efficiency is based on fuel costs and the environmental impact is based on carbon dioxide (CO<sub>2</sub>) emissions.



The energy efficiency rating is a measure of the overall efficiency of a home. The higher the rating the more energy efficient the home is and the lower the fuel bills are likely to be.

The environmental impact rating is a measure of a home's impact on the environment in terms of carbon dioxide (CO<sub>2</sub>) emissions. The higher the rating the less impact it has on the environment.

# Thermal Bridging



Property Reference	C12-01-01		Issued on Date	15/10/2025		
Assessment Reference	Design V1		Prop Type Ref	Mid-Terrace Flat		
Property	C12-01-01, Horsham Enterprise Park					
SAP Rating	80 C	DER	5.39	TER	14.58	
Environmental	96 A	% DER < TER		63.03		
CO <sub>2</sub> Emissions (t/year)	0.34	DFEE	32.37	TFEE	41.46	
Compliance Check	See BREL	% DFEE < TFEE		21.94		
% DPER < TPER	27.75	DPER	56.17	TPER	77.74	
Assessor Details	Miss Charlotte Russell			Assessor ID	DK97-0001	
Client						
	Junction details	Source Type	Psi (W/mK)	Length (m)	Result	Reference
External wall	E2 Other lintels (including other steel lintels)	Independently assessed	0.022	9.01	0.20	RCD
External wall	E3 Sill	Independently assessed	0.016	7.00	0.11	RCD
External wall	E4 Jamb	Independently assessed	0.011	21.64	0.24	RCD
External wall	E20 Exposed floor (normal)	Independently assessed	0.054	28.34	1.53	RCD
External wall	E7 Party floor between dwellings (in blocks of flats)	Independently assessed	0.053	28.34	1.50	RCD
External wall	E16 Corner (normal)	Independently assessed	0.051	7.50	0.38	RCD
Party wall	P7 Party Wall - Exposed floor (normal)	Table K1 - Default	0.480	6.30	3.02	Default
Party wall	P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	0.000	6.30	0.00	Default
External wall	E18 Party wall between dwellings	Independently assessed	0.057	2.50	0.14	RCD
External wall	E17 Corner (inverted – internal area greater than external area)	Independently assessed	-0.104	0.00	-0.00	RCD
External wall	E25 Staggered party wall between dwellings	Table K1 - Default	0.240	2.50	0.60	E25 - Default

Total: 119.43 W/mK:

Y-Value: 0.05 W/m<sup>2</sup>K:

# Summary for Input Data



Property Reference	C12-02-02	Issued on Date	15/10/2025
Assessment Reference	Design V1	Prop Type Ref	C12-02-02
Property	C12-02-02, Horsham Enterprise Park		
SAP Rating	87 B	DER	3.94
Environmental	97 A	% DER < TER	12.20
CO <sub>2</sub> Emissions (t/year)	0.19	DFEE	18.07
Compliance Check	See BREL	% DFEE < TFEE	22.06
% DPER < TPER	35.85	DPER	41.89
TPER	65.31		

Assessor Details	Miss Charlotte Russell	Assessor ID	DK97-0001
Client			

## SUMMARY FOR INPUT DATA FOR: New Build (As Designed)

Orientation	Northwest	
Property Tenure	ND	
Transaction Type	6	
Terrain Type	Suburban	
1.0 Property Type	Flat, Mid-Terrace	
Position of Flat	Mid-floor flat	
Which Floor	2	
2.0 Number of Storeys	1	
3.0 Date Built	2025	
3.0 Property Age Band	L	
4.0 Sheltered Sides	2	
5.0 Sunlight/Shade	Average or unknown	
6.0 Thermal Mass Parameter	Precise calculation	
Thermal Mass	256.60	kJ/m <sup>2</sup> K
7.0 Electricity Tariff	Standard	
Smart electricity meter fitted	Yes	
Smart gas meter fitted	No	

7.0 Measurements	Heat Loss Perimeter	Internal Floor Area	Average Storey Height
	Ground floor: 15.74 m	52.93 m <sup>2</sup>	2.50 m

8.0 Living Area	25.03	m <sup>2</sup>
-----------------	-------	----------------

9.0 External Walls	Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Res	Shelter	Openings	Area Calculation Type
External Wall	External Wall	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.15	110.00	28.60	19.21	0.00	None	9.39	Enter Gross Area
Sheltered	Sheltered	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.18	110.00	10.75	8.63	0.90	Stairwell Access Corridor 4	2.12	Enter Gross Area

9.1 Party Walls	Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )	Shelter Res	Shelter
Party Wall	Party Wall	Filled Cavity with Edge Sealing	Single plasterboard on dabs both sides, lightweight aggregate blocks, cavity or cavity fill	0.00	110.00	37.00	0.00	None

9.2 Internal Walls	Description	Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Internal Walls	Internal Walls	Plasterboard on timber frame	9.00	69.68

10.1 Party Ceilings	Description	Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Ceiling	Ceiling	Precast concrete plank floor (screed laid on rubber), carpeted	30.00	52.93

## 11.1 Party Floors

# Summary for Input Data

Description	Storey Index	Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )	
Party Floor	Lowest occupied	Precast concrete planks floor, screed, carpeted	40.00	52.93	
<b>12.0 Opening Types</b>					
Description	Data Source	Type	Glazing	Glazing Gap	
Solid Door Glazing	Manufacturer	Solid Door Window	Double Low-E Soft 0.05	0.00 0.63	
<b>13.0 Openings</b>					
Name	Opening Type	Location	Orientation	Area (m <sup>2</sup> )	
FSD	Solid Door Glazing	Sheltered External Wall	North West	2.12	
RW	Glazing	External Wall	South East	3.46	
RGD	Glazing	External Wall	South East	4.69	
FW	Glazing	External Wall	North West	1.24	
<b>14.0 Conservatory</b>					
None					
<b>15.0 Draught Proofing</b>					
100 %					
<b>16.0 Draught Lobby</b>					
No					
<b>17.0 Thermal Bridging</b>					
<b>17.1 List of Bridges</b>					
Bridge Type	Source Type	Length	Psi	Adjusted Reference:	Imported
E2 Other lintels (including other steel lintels)	Independently assessed	6.00	0.02	RCD	No
E3 Sill	Independently assessed	2.97	0.02	RCD	No
E4 Jamb	Independently assessed	18.92	0.01	RCD	No
E7 Party floor between dwellings (in blocks of flats)	Independently assessed	31.48	0.05	RCD	No
E16 Corner (normal)	Independently assessed	2.50	0.05	RCD	No
P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	29.60	0.00	Default	No
E18 Party wall between dwellings	Independently assessed	10.00	0.06	RCD	No
E17 Corner (inverted – internal area greater than external area)	Independently assessed	2.50	-0.10	RCD	No
E25 Staggered party wall between dwellings	Table K1 - Default	0.00	0.24	E25 - Default	No
Y-value	0.06			W/m <sup>2</sup> K	
Description	Bridge				
<b>19.0 Mechanical Ventilation</b>					
<b>Mechanical Ventilation</b>					
Mechanical Ventilation System Present	Yes				
Approved Installation	Yes				
Mechanical Ventilation data Type	Database				
Type	Balanced mechanical ventilation with heat recovery				
MV Reference Number	500500				
Configuration	2				
MVHR Duct Insulated	Uninsulated Ducts				
Manufacturer SFP	0.59				
Duct Type	Rigid				
MVHR Efficiency	89.00				
Wet Rooms	2				
SFP from Installer Commissioning Certificate	No				
MVHR System Location	Inside heated envelope (installed exclusively)				
Duct Installation Specification	Level 2				
<b>19.1 Mechanical extract ventilation - Decentralised</b>					
SFP	Fan/Room Type	Count			
0.13	In Room Fan	1			
	Kitchen				
0.11	In Room Fan Other	3			
	Wet Room				
0.00	In Duct Fan Kitchen	0			
0.00	In Duct Fan Other	0			
	Wet Room				
0.10	Through Wall Fan	0			
	Kitchen				
0.10	Through Wall Fan	0			
	Other Wet Room				

# Summary for Input Data

## 20.0 Fans, Open Fireplaces, Flues

Number of open chimneys	0
Number of open flues	0
Number of chimneys/flues attached to closed fire	0
Number of flues attached to solid fuel boiler	0
Number of flues attached to other heater	0
Number of blocked chimneys	0
Number of intermittent extract fans	0
Number of passive vents	0
Number of flueless gas fires	0

## 21.0 Fixed Cooling System

No
----

## 22.0 Pressure Testing

Designed AP <sub>50</sub>	Yes	
	3.00	m <sup>3</sup> /(h.m <sup>2</sup> ) @ 50 Pa
Property Tested?	Yes	
Test Method	Blower Door	

## 22.0 Lighting

No Fixed Lighting	No				
	Name Low energy Lighting	Efficacy 85.00	Power 5.00	Capacity 425.00	Count 10

## 24.0 Main Heating 1

Percentage of Heat	100.00	%
Database Ref. No.	0	
Fuel Type	Electricity	
SAP Code	691	
In Winter	100.00	
In Summer	194.18	
Controls SAP Code	2603	
Delayed Start Stat	No	
Burner Control	Modulating	
HETAS approved System	No	
Is MHS Pumped	Pump in heated space	
Heating Pump Age	2013 or later	
Heat Emitter	Radiators	
Underfloor Heating	Yes - Pipes in thin screed	
Flow Temperature	Enter value	
Flow Temperature Value	55.00	

## 25.0 Main Heating 2

Percentage of Heat	0.00	%
Database Ref. No.	100834	
Fuel Type	Electricity	
SAP Code	0	
In Winter	294.62	
In Summer	194.18	
Model Name	Compact P	
Manufacturer	Nilan AS	
Controls	2100	
Delayed Start Stat	No	
HETAS approved System	No	

# Summary for Input Data

Flow Temperature	Enter value										
<b>26.0 Heat Networks</b>	None										
<b>27.0 Secondary Heating</b>	None										
<b>28.0 Water Heating</b>											
Water Heating	Main Heating 2										
SAP Code	914										
Flue Gas Heat Recovery System	No										
Waste Water Heat Recovery Instantaneous System 1	No										
Waste Water Heat Recovery Instantaneous System 2	No										
Waste Water Heat Recovery Storage System	No										
Solar Panel	No										
Water use <= 125 litres/person/day	Yes										
Summer Immersion	No										
Cold Water Source	From mains										
Bath Count	1										
Baths connected to WWHRS	0										
Supplementary Immersion	No										
Immersion Only Heating Hot Water	No										
<b>28.1 Showers</b>											
<b>Description</b>	<b>Shower Type</b>	<b>Flow Rate</b> [l/min]	<b>Rated Power</b> [kW]	<b>Connected</b>	<b>Connected To</b>						
8 lpm	Unknown	8.00		No							
<b>28.3 Waste Water Heat Recovery System</b>											
<b>29.0 Hot Water Cylinder</b>		Internal Store									
Cylinder Stat	No										
Cylinder In Heated Space	No										
Independent Time Control	No										
Insulation Type	Measured Loss										
Insulation Thickness	0										
Cylinder Volume	180.00	L									
Loss	0.84	kWh/day									
In Airing Cupboard	No										
<b>31.0 Thermal Store</b>		None									
<b>34.0 Small-scale Hydro</b>		None									
Electricity Generated	0.00										
Apportioned	0.00	kWh/Year									
Connected to dwelling's electricity meter	Yes										
Electricity Generation	Annual										
Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
<b>Recommendations</b>											
Lower cost measures											
None											
Further measures to achieve even higher standards											
None											

# Predicted Energy Assessment


C12-02-02, Horsham Enterprise Park

Dwelling type:  
Date of assessment:  
Produced by:  
Total floor area:  
DRRN:

Flat, Mid-Terrace  
15/10/2025  
Charlotte Russell  
52.93 m<sup>2</sup>

This document is a Predicted Energy Assessment for properties marketed when they are incomplete. It includes a predicted energy rating which might not represent the final energy rating of the property on completion. Once the property is completed, this rating will be updated and an official Energy Performance Certificate will be created for the property. This will include more detailed information about the energy performance of the completed property.

The energy performance has been assessed using the Government approved SAP 10 methodology and is rated in terms of the energy use per square meter of floor area; the energy efficiency is based on fuel costs and the environmental impact is based on carbon dioxide (CO<sub>2</sub>) emissions.



The energy efficiency rating is a measure of the overall efficiency of a home. The higher the rating the more energy efficient the home is and the lower the fuel bills are likely to be.

The environmental impact rating is a measure of a home's impact on the environment in terms of carbon dioxide (CO<sub>2</sub>) emissions. The higher the rating the less impact it has on the environment.

# Thermal Bridging



Property Reference	C12-02-02		Issued on Date	15/10/2025		
Assessment Reference	Design V1		Prop Type Ref	Mid-Terrace Flat		
Property	C12-02-02, Horsham Enterprise Park					
SAP Rating	87 B	DER	3.94	TER	12.20	
Environmental	97 A	% DER < TER		67.70		
CO <sub>2</sub> Emissions (t/year)	0.19	DFEE	18.07	TFEE	22.06	
Compliance Check	See BREL	% DFEE < TFEE		18.08		
% DPER < TPER	35.85	DPER	41.89	TPER	65.31	
Assessor Details	Miss Charlotte Russell			Assessor ID	DK97-0001	
Client						
	Junction details	Source Type	Psi (W/mK)	Length (m)	Result	Reference
External wall	E2 Other lintels (including other steel lintels)	Independently assessed	0.022	6.00	0.13	RCD
External wall	E3 Sill	Independently assessed	0.016	2.97	0.05	RCD
External wall	E4 Jamb	Independently assessed	0.011	18.92	0.21	RCD
External wall	E7 Party floor between dwellings (in blocks of flats)	Independently assessed	0.053	31.48	1.67	RCD
External wall	E16 Corner (normal)	Independently assessed	0.051	2.50	0.13	RCD
Party wall	P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	0.000	29.60	0.00	Default
External wall	E18 Party wall between dwellings	Independently assessed	0.057	10.00	0.57	RCD
External wall	E17 Corner (inverted – internal area greater than external area)	Independently assessed	-0.104	2.50	-0.26	RCD
External wall	E25 Staggered party wall between dwellings	Table K1 - Default	0.240	0.00	0.00	E25 - Default

Total: 103.97 W/mK:

Y-Value: 0.06 W/m<sup>2</sup>K:

# Summary for Input Data



Property Reference	C12-02-05	Issued on Date	15/10/2025
Assessment Reference	Design V1	Prop Type Ref	C12-02-05
Property	C12-02-05, Horsham Enterprise Park		
SAP Rating	83 B	DER	5.36
Environmental	96 A	% DER < TER	15.27
CO <sub>2</sub> Emissions (t/year)	0.24	DFEE	29.30
Compliance Check	See BREL	% DFEE < TFEE	64.90
% DPER < TPER	31.42	DPER	36.17
		TPER	19.00
			81.86

Assessor Details	Miss Charlotte Russell	Assessor ID	DK97-0001
Client			

## SUMMARY FOR INPUT DATA FOR: New Build (As Designed)

Orientation	Southeast
Property Tenure	ND
Transaction Type	6
Terrain Type	Suburban
1.0 Property Type	Flat, Detached
Position of Flat	Mid-floor flat
Which Floor	2
2.0 Number of Storeys	1
3.0 Date Built	2025
3.0 Property Age Band	L
4.0 Sheltered Sides	2
5.0 Sunlight/Shade	Average or unknown
6.0 Thermal Mass Parameter	Precise calculation
Thermal Mass	279.31
	kJ/m <sup>2</sup> K
7.0 Electricity Tariff	Standard
Smart electricity meter fitted	Yes
Smart gas meter fitted	No

7.0 Measurements	Heat Loss Perimeter	Internal Floor Area	Average Storey Height
	Ground floor: 34.32 m	52.51 m <sup>2</sup>	2.50 m

8.0 Living Area	24.92	m <sup>2</sup>
-----------------	-------	----------------

9.0 External Walls		Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Res	Shelter	Openings	Area Calculation Type
External Wall	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.15	110.00	57.67	49.80	0.00	None	7.87	Enter Gross Area
Sheltered	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.18	110.00	28.13	26.01	0.90	Stairwell Access Corridor 4	2.12	Enter Gross Area

9.2 Internal Walls		Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Internal Walls		Plasterboard on timber frame	9.00	61.26

10.1 Party Ceilings		Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Ceiling		Precast concrete plank floor (screed laid on rubber), carpeted	30.00	52.51

11.1 Party Floors		Storey Index	Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Party Floor	Lowest occupied		Precast concrete planks floor, screed, carpeted	40.00	52.51

## 12.0 Opening Types

# Summary for Input Data

Description	Data Source	Type	Glazing	Glazing Gap	Filling Type	G-value	Frame Type	Frame Factor	U Value (W/m <sup>2</sup> K)
Solid Door Glazing	Manufacturer	Solid Door Window	Double Low-E Soft 0.05			0.00 0.63		0.80	1.20 1.20
<b>13.0 Openings</b>									
<b>Name</b>	<b>Opening Type</b>	<b>Location</b>	<b>Orientation</b>	<b>Area (m<sup>2</sup>)</b>	<b>Pitch</b>				
FSD	Solid Door Glazing	Sheltered External Wall External Wall	South East North East North East	2.12 3.71 2.32	0 0 0				
RSW	Glazing			1.84	0				
RSGD	Glazing								
LSW	Glazing								
<b>14.0 Conservatory</b>		None							
<b>15.0 Draught Proofing</b>		100				%			
<b>16.0 Draught Lobby</b>		No							
<b>17.0 Thermal Bridging</b>		Calculate Bridges							
<b>17.1 List of Bridges</b>									
<b>Bridge Type</b>	<b>Source Type</b>	<b>Length</b>	<b>Psi</b>	<b>Adjusted Reference:</b>	<b>Imported</b>				
E2 Other lintels (including other steel lintels)	Independently assessed	4.93	0.02	0.02 RCD	No				
E3 Sill	Independently assessed	2.92	0.02	0.02 RCD	No				
E4 Jamb	Independently assessed	11.56	0.01	0.01 RCD	No				
E7 Party floor between dwellings (in blocks of flats)	Independently assessed	68.64	0.05	0.05 RCD	No				
E16 Corner (normal)	Independently assessed	15.00	0.05	0.05 RCD	No				
P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	0.00	0.00	0.00 Default	No				
E18 Party wall between dwellings	Independently assessed	0.00	0.06	0.06 RCD	No				
E17 Corner (inverted – internal area greater than external area)	Independently assessed	5.00	-0.10	-0.10 RCD	No				
E25 Staggered party wall between dwellings	Table K1 - Default	0.00	0.24	0.24 E25 - Default	No				
Y-value	0.05					W/m <sup>2</sup> K			
Description	Bridge								
<b>19.0 Mechanical Ventilation</b>									
<b>Mechanical Ventilation</b>									
Mechanical Ventilation System Present	Yes								
Approved Installation	Yes								
Mechanical Ventilation data Type	Database								
Type	Balanced mechanical ventilation with heat recovery								
MV Reference Number	500500								
Configuration	2								
MVHR Duct Insulated	Uninsulated Ducts								
Manufacturer SFP	0.59								
Duct Type	Rigid								
MVHR Efficiency	89.00								
Wet Rooms	2								
SFP from Installer Commissioning Certificate	No								
MVHR System Location	Inside heated envelope (installed exclusively)								
Duct Installation Specification	Level 2								
<b>19.1 Mechanical extract ventilation - Decentralised</b>									
<b>SFP</b>	<b>Fan/Room Type</b>	<b>Count</b>							
0.13	In Room Fan	1							
	Kitchen								
0.11	In Room Fan Other	3							
	Wet Room								
0.00	In Duct Fan Kitchen	0							
0.00	In Duct Fan Other	0							
	Wet Room								
0.10	Through Wall Fan	0							
	Kitchen								
0.10	Through Wall Fan	0							
	Other Wet Room								
<b>20.0 Fans, Open Fireplaces, Flues</b>									
Number of open chimneys	0								
Number of open flues	0								
Number of chimneys/flues attached to closed fire	0								

# Summary for Input Data

Number of flues attached to solid fuel boiler	0																																																																																								
Number of flues attached to other heater	0																																																																																								
Number of blocked chimneys	0																																																																																								
Number of intermittent extract fans	0																																																																																								
Number of passive vents	0																																																																																								
Number of flueless gas fires	0																																																																																								
<b>21.0 Fixed Cooling System</b>	No																																																																																								
<b>22.0 Pressure Testing</b>	Yes																																																																																								
Designed AP <sub>50</sub>	3.00	m <sup>3</sup> /(h.m <sup>2</sup> ) @ 50 Pa																																																																																							
Property Tested?	Yes																																																																																								
Test Method	Blower Door																																																																																								
<b>22.0 Lighting</b>	<table border="1"> <tr> <td>No</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>Name</td> <td>Efficacy</td> <td>Power</td> <td>Capacity</td> </tr> <tr> <td></td> <td>Low energy Lighting</td> <td>85.00</td> <td>5.00</td> <td>425.00</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>Count</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>10</td> </tr> </table>				No						Name	Efficacy	Power	Capacity		Low energy Lighting	85.00	5.00	425.00					Count					10																																																												
No																																																																																									
	Name	Efficacy	Power	Capacity																																																																																					
	Low energy Lighting	85.00	5.00	425.00																																																																																					
				Count																																																																																					
				10																																																																																					
<b>24.0 Main Heating 1</b>	<table border="1"> <tr> <td>SAP table</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>100.00</td> <td></td> <td></td> <td></td> <td>%</td> </tr> <tr> <td>0</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Electricity</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>691</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>100.00</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>194.18</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>2603</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>No</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Modulating</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>No</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Pump in heated space</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>2013 or later</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Radiators</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Yes - Pipes in thin screed</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Enter value</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>55.00</td> <td></td> <td></td> <td></td> <td></td> </tr> </table>				SAP table					100.00				%	0					Electricity					691					100.00					194.18					2603					No					Modulating					No					Pump in heated space					2013 or later					Radiators					Yes - Pipes in thin screed					Enter value					55.00				
SAP table																																																																																									
100.00				%																																																																																					
0																																																																																									
Electricity																																																																																									
691																																																																																									
100.00																																																																																									
194.18																																																																																									
2603																																																																																									
No																																																																																									
Modulating																																																																																									
No																																																																																									
Pump in heated space																																																																																									
2013 or later																																																																																									
Radiators																																																																																									
Yes - Pipes in thin screed																																																																																									
Enter value																																																																																									
55.00																																																																																									
<b>25.0 Main Heating 2</b>	<table border="1"> <tr> <td>Database</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>0.00</td> <td></td> <td></td> <td></td> <td>%</td> </tr> <tr> <td>100834</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Electricity</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>0</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>299.98</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>194.18</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Compact P</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Nilan AS</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>2100</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>No</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>No</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Enter value</td> <td></td> <td></td> <td></td> <td></td> </tr> </table>				Database					0.00				%	100834					Electricity					0					299.98					194.18					Compact P					Nilan AS					2100					No					No					Enter value																								
Database																																																																																									
0.00				%																																																																																					
100834																																																																																									
Electricity																																																																																									
0																																																																																									
299.98																																																																																									
194.18																																																																																									
Compact P																																																																																									
Nilan AS																																																																																									
2100																																																																																									
No																																																																																									
No																																																																																									
Enter value																																																																																									
<b>26.0 Heat Networks</b>	None																																																																																								

# Summary for Input Data

27.0 Secondary Heating	None										
<b>28.0 Water Heating</b>											
Water Heating	Main Heating 2										
SAP Code	914										
Flue Gas Heat Recovery System	No										
Waste Water Heat Recovery Instantaneous System 1	No										
Waste Water Heat Recovery Instantaneous System 2	No										
Waste Water Heat Recovery Storage System	No										
Solar Panel	No										
Water use <= 125 litres/person/day	Yes										
Summer Immersion	No										
Cold Water Source	From mains										
Bath Count	1										
Baths connected to WWHRS	0										
Supplementary Immersion	No										
Immersion Only Heating Hot Water	No										
<b>28.1 Showers</b>											
Description	Shower Type	Flow Rate [l/min]	Rated Power [kW]	Connected	Connected To						
8 lpm	Unknown	8.00		No							
<b>28.3 Waste Water Heat Recovery System</b>											
<b>29.0 Hot Water Cylinder</b>	Internal Store										
Cylinder Stat	No										
Cylinder In Heated Space	No										
Independent Time Control	No										
Insulation Type	Measured Loss										
Insulation Thickness	0										
Cylinder Volume	180.00	L									
Loss	0.84	kWh/day									
In Airing Cupboard	No										
<b>31.0 Thermal Store</b>	None										
<b>34.0 Small-scale Hydro</b>	None										
Electricity Generated	0.00										
Apportioned	0.00	kWh/Year									
Connected to dwelling's electricity meter	Yes										
Electricity Generation	Annual										
Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec

## Recommendations

### Lower cost measures

None

### Further measures to achieve even higher standards

None

# Predicted Energy Assessment


C12-02-05, Horsham Enterprise Park

Dwelling type:  
Date of assessment:  
Produced by:  
Total floor area:  
DRRN:

Flat, Detached  
15/10/2025  
Charlotte Russell  
52.51 m<sup>2</sup>

This document is a Predicted Energy Assessment for properties marketed when they are incomplete. It includes a predicted energy rating which might not represent the final energy rating of the property on completion. Once the property is completed, this rating will be updated and an official Energy Performance Certificate will be created for the property. This will include more detailed information about the energy performance of the completed property.

The energy performance has been assessed using the Government approved SAP 10 methodology and is rated in terms of the energy use per square meter of floor area; the energy efficiency is based on fuel costs and the environmental impact is based on carbon dioxide (CO<sub>2</sub>) emissions.



The energy efficiency rating is a measure of the overall efficiency of a home. The higher the rating the more energy efficient the home is and the lower the fuel bills are likely to be.

The environmental impact rating is a measure of a home's impact on the environment in terms of carbon dioxide (CO<sub>2</sub>) emissions. The higher the rating the less impact it has on the environment.

# Thermal Bridging



Property Reference	C12-02-05		Issued on Date	15/10/2025		
Assessment Reference	Design V1		Prop Type Ref	Detached Flat		
Property	C12-02-05, Horsham Enterprise Park					
SAP Rating	83 B	DER	5.36	TER	15.27	
Environmental	96 A	% DER < TER		64.90		
CO <sub>2</sub> Emissions (t/year)	0.24	DFEE	29.30	TFEE	36.17	
Compliance Check	See BREL	% DFEE < TFEE		19.00		
% DPER < TPER	31.42	DPER	56.14	TPER	81.86	
Assessor Details	Miss Charlotte Russell			Assessor ID	DK97-0001	
Client						
	Junction details	Source Type	Psi (W/mK)	Length (m)	Result	Reference
External wall	E2 Other lintels (including other steel lintels)	Independently assessed	0.022	4.93	0.11	RCD
External wall	E3 Sill	Independently assessed	0.016	2.92	0.05	RCD
External wall	E4 Jamb	Independently assessed	0.011	11.56	0.13	RCD
External wall	E7 Party floor between dwellings (in blocks of flats)	Independently assessed	0.053	68.64	3.64	RCD
External wall	E16 Corner (normal)	Independently assessed	0.051	15.00	0.76	RCD
Party wall	P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	0.000	0.00	0.00	Default
External wall	E18 Party wall between dwellings	Independently assessed	0.057	0.00	0.00	RCD
External wall	E17 Corner (inverted – internal area greater than external area)	Independently assessed	-0.104	5.00	-0.52	RCD
External wall	E25 Staggered party wall between dwellings	Table K1 - Default	0.240	0.00	0.00	E25 - Default

Total: 108.05 W/mK:

Y-Value: 0.05 W/m<sup>2</sup>K:

# Summary for Input Data



Property Reference	C12-03-03	Issued on Date	15/10/2025
Assessment Reference	Design V1	Prop Type Ref	C12-03-03
Property	C12-03-03, Horsham Enterprise Park		
SAP Rating	86 B	DER	4.21
Environmental	97 A	% DER < TER	66.67
CO <sub>2</sub> Emissions (t/year)	0.2	DFEE	20.74
Compliance Check	See BREL	% DFEE < TFEE	24.01
% DPER < TPER	34.06	DPER	44.56
TPER	13.60	TPER	67.58

Assessor Details	Miss Charlotte Russell	Assessor ID	DK97-0001
Client			

## SUMMARY FOR INPUT DATA FOR: New Build (As Designed)

Orientation	Northwest
Property Tenure	ND
Transaction Type	6
Terrain Type	Suburban
1.0 Property Type	Flat, Mid-Terrace
Position of Flat	Mid-floor flat
Which Floor	3
2.0 Number of Storeys	1
3.0 Date Built	2025
3.0 Property Age Band	L
4.0 Sheltered Sides	2
5.0 Sunlight/Shade	Average or unknown
6.0 Thermal Mass Parameter	Precise calculation
Thermal Mass	216.14
	kJ/m <sup>2</sup> K
7.0 Electricity Tariff	Standard
Smart electricity meter fitted	Yes
Smart gas meter fitted	No

7.0 Measurements		Heat Loss Perimeter	Internal Floor Area	Average Storey Height
		Ground floor: 12.40 m	52.70 m <sup>2</sup>	2.50 m

8.0 Living Area	23.92	m <sup>2</sup>
-----------------	-------	----------------

Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Res	Shelter	Openings	Area Calculation Type
External Wall	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.15	110.00	31.00	18.57	0.00	None	12.43	Enter Gross Area

Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )	Shelter Res	Shelter
Party Wall	Filled Cavity with Edge Sealing	Single plasterboard on dabs both sides, lightweight aggregate blocks, cavity or cavity fill	0.00	110.00	42.50	0.00	None

Description	Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Internal Walls	Plasterboard on timber frame	9.00	79.98

Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Code	Shelter Factor	Calculus	Openings Type
External Roof	External Flat Roof	Plasterboard, insulated flat roof	0.11	9.00	8.49	8.49	None	0.00	Enter Gross Area	0.00

## 10.1 Party Ceilings

# Summary for Input Data

Description	Construction			Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Party Ceiling	Precast concrete planks floor, screed, carpeted			30.00	44.21
<b>11.1 Party Floors</b>					
Description	Storey Index	Construction		Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Party Floor	Lowest occupied	Precast concrete planks floor, screed, carpeted		40.00	52.70
<b>12.0 Opening Types</b>					
Description	Data Source	Type	Glazing	Glazing Gap	Filling Type
Solid Door Glazing	Manufacturer	Solid Door Window	Double Low-E Soft 0.05	0.00	0.63
					0.80
					1.20
					1.20
<b>13.0 Openings</b>					
Name	Opening Type	Location	Orientation	Area (m <sup>2</sup> )	Pitch
FSD	Solid Door	External Wall	North West	2.12	0
RW	Glazing	External Wall	South East	3.46	0
RGD	Glazing	External Wall	South East	4.69	0
FW	Glazing	External Wall	North West	2.16	0
<b>14.0 Conservatory</b>					
		None			
<b>15.0 Draught Proofing</b>					
		100			%
<b>16.0 Draught Lobby</b>					
		No			
<b>17.0 Thermal Bridging</b>					
<b>17.1 List of Bridges</b>					
Bridge Type	Source Type	Length	Psi	Adjusted Reference:	Imported
E2 Other lintels (including other steel lintels)	Independently assessed	6.68	0.02	RCD	No
E3 Sill	Independently assessed	3.65	0.02	RCD	No
E4 Jamb	Independently assessed	17.00	0.01	RCD	No
E7 Party floor between dwellings (in blocks of flats)	Independently assessed	18.60	0.05	RCD	No
E16 Corner (normal)	Independently assessed	0.00	0.05	RCD	No
P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	31.26	0.00	Default	No
E18 Party wall between dwellings	Independently assessed	10.00	0.06	RCD	No
E17 Corner (inverted – internal area greater than external area)	Independently assessed	0.00	-0.10	RCD	No
E25 Staggered party wall between dwellings	Table K1 - Default	0.00	0.24	E25 - Default	No
E14 Flat roof	Independently assessed	6.20	0.04	ROI	No
E24 Eaves (insulation at ceiling level - inverted)	Table K1 - Default	6.20	0.15	0.15	No
P4 Party wall - Roof (insulation at ceiling level)	Table K1 - Default	2.74	0.48	0.48	No
Y-value	0.11				W/m <sup>2</sup> K
Description	Bridge				
<b>19.0 Mechanical Ventilation</b>					
<b>Mechanical Ventilation</b>					
Mechanical Ventilation System Present	Yes				
Approved Installation	Yes				
Mechanical Ventilation data Type	Database				
Type	Balanced mechanical ventilation with heat recovery				
MV Reference Number	500500				
Configuration	2				
MVHR Duct Insulated	Uninsulated Ducts				
Manufacturer SFP	0.59				
Duct Type	Rigid				
MVHR Efficiency	89.00				
Wet Rooms	2				
SFP from Installer Commissioning Certificate	No				
MVHR System Location	Inside heated envelope (installed exclusively)				
Duct Installation Specification	Level 2				
<b>19.1 Mechanical extract ventilation - Decentralised</b>					
SFP	Fan/Room Type	Count			
0.13	In Room Fan	1			
	Kitchen				
0.11	In Room Fan Other	3			
	Wet Room				

# Summary for Input Data

0.00	In Duct Fan Kitchen	0
0.00	In Duct Fan Other	0
	Wet Room	
0.10	Through Wall Fan	0
	Kitchen	
0.10	Through Wall Fan	0
	Other Wet Room	

## 20.0 Fans, Open Fireplaces, Flues

Number of open chimneys	0
Number of open flues	0
Number of chimneys/flues attached to closed fire	0
Number of flues attached to solid fuel boiler	0
Number of flues attached to other heater	0
Number of blocked chimneys	0
Number of intermittent extract fans	0
Number of passive vents	0
Number of flueless gas fires	0

## 21.0 Fixed Cooling System

22.0 Pressure Testing	Yes
-----------------------	-----

Designed AP <sub>50</sub>	3.00	m <sup>3</sup> /(h.m <sup>2</sup> ) @ 50 Pa
Property Tested?	Yes	
Test Method	Blower Door	

## 22.0 Lighting

No Fixed Lighting	No				
	Name	Efficacy	Power	Capacity	Count
	Low energy Lighting	85.00	5.00	425.00	10

## 24.0 Main Heating 1

Percentage of Heat	100.00	%
Database Ref. No.	0	
Fuel Type	Electricity	
SAP Code	691	
In Winter	100.00	
In Summer	194.18	
Controls SAP Code	2603	
Delayed Start Stat	No	
Burner Control	Modulating	
HETAS approved System	No	
Is MHS Pumped	Pump in heated space	
Heating Pump Age	2013 or later	
Heat Emitter	Radiators	
Underfloor Heating	Yes - Pipes in thin screed	
Flow Temperature	Enter value	
Flow Temperature Value	55.00	

## 25.0 Main Heating 2

Percentage of Heat	0.00	%
Database Ref. No.	100834	
Fuel Type	Electricity	
SAP Code	0	
In Winter	296.74	
In Summer	194.18	
Model Name	Compact P	

# Summary for Input Data

Manufacturer	Nilan AS										
Controls	2100										
Delayed Start Stat	No										
HETAS approved System	No										
Flow Temperature	Enter value										
<b>26.0 Heat Networks</b>											
27.0 Secondary Heating	None										
<b>28.0 Water Heating</b>											
Water Heating	Main Heating 2										
SAP Code	914										
Flue Gas Heat Recovery System	No										
Waste Water Heat Recovery Instantaneous System 1	No										
Waste Water Heat Recovery Instantaneous System 2	No										
Waste Water Heat Recovery Storage System	No										
Solar Panel	No										
Water use <= 125 litres/person/day	Yes										
Summer Immersion	No										
Cold Water Source	From mains										
Bath Count	1										
Baths connected to WWHRS	0										
Supplementary Immersion	No										
Immersion Only Heating Hot Water	No										
<b>28.1 Showers</b>											
Description	Shower Type	Flow Rate [l/min]	Rated Power [kW]	Connected	Connected To						
8 lpm	Unknown	8.00		No							
<b>28.3 Waste Water Heat Recovery System</b>											
<b>29.0 Hot Water Cylinder</b>		Internal Store									
Cylinder Stat	No										
Cylinder In Heated Space	No										
Independent Time Control	No										
Insulation Type	Measured Loss										
Insulation Thickness	0										
Cylinder Volume	180.00	L									
Loss	0.84	kWh/day									
In Airing Cupboard	No										
<b>31.0 Thermal Store</b>		None									
<b>34.0 Small-scale Hydro</b>		None									
Electricity Generated	0.00										
Apportioned	0.00	kWh/Year									
Connected to dwelling's electricity meter	Yes										
Electricity Generation	Annual										
Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
<b>Recommendations</b>											
Lower cost measures											
None											
Further measures to achieve even higher standards											
None											

# Predicted Energy Assessment


C12-03-03, Horsham Enterprise Park

Dwelling type:  
Date of assessment:  
Produced by:  
Total floor area:  
DRRN:

Flat, Mid-Terrace  
15/10/2025  
Charlotte Russell  
52.7 m<sup>2</sup>

This document is a Predicted Energy Assessment for properties marketed when they are incomplete. It includes a predicted energy rating which might not represent the final energy rating of the property on completion. Once the property is completed, this rating will be updated and an official Energy Performance Certificate will be created for the property. This will include more detailed information about the energy performance of the completed property.

The energy performance has been assessed using the Government approved SAP 10 methodology and is rated in terms of the energy use per square meter of floor area; the energy efficiency is based on fuel costs and the environmental impact is based on carbon dioxide (CO<sub>2</sub>) emissions.



The energy efficiency rating is a measure of the overall efficiency of a home. The higher the rating the more energy efficient the home is and the lower the fuel bills are likely to be.

The environmental impact rating is a measure of a home's impact on the environment in terms of carbon dioxide (CO<sub>2</sub>) emissions. The higher the rating the less impact it has on the environment.

# Thermal Bridging

Property Reference	C12-03-03		Issued on Date	15/10/2025		
Assessment Reference	Design V1		Prop Type Ref	Mid-Terrace Flat		
Property	C12-03-03, Horsham Enterprise Park					
SAP Rating	86 B	DER	4.21	TER	12.63	
Environmental	97 A	% DER < TER		66.67		
CO <sub>2</sub> Emissions (t/year)	0.2	DFEE	20.74	TFEE	24.01	
Compliance Check	See BREL	% DFEE < TFEE		13.60		
% DPER < TPER	34.06	DPER	44.56	TPER	67.58	
Assessor Details	Miss Charlotte Russell			Assessor ID	DK97-0001	
Client						
	Junction details	Source Type	Psi (W/mK)	Length (m)	Result	Reference
External wall	E2 Other lintels (including other steel lintels)	Independently assessed	0.022	6.68	0.15	RCD
External wall	E3 Sill	Independently assessed	0.016	3.65	0.06	RCD
External wall	E4 Jamb	Independently assessed	0.011	17.00	0.19	RCD
External wall	E7 Party floor between dwellings (in blocks of flats)	Independently assessed	0.053	18.60	0.99	RCD
External wall	E16 Corner (normal)	Independently assessed	0.051	0.00	0.00	RCD
Party wall	P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	0.000	31.26	0.00	Default
External wall	E18 Party wall between dwellings	Independently assessed	0.057	10.00	0.57	RCD
External wall	E17 Corner (inverted – internal area greater than external area)	Independently assessed	-0.104	0.00	-0.00	RCD
External wall	E25 Staggered party wall between dwellings	Table K1 - Default	0.240	0.00	0.00	E25 - Default
External wall	E14 Flat roof	Independently assessed	0.040	6.20	0.25	ROI
External wall	E24 Eaves (insulation at ceiling level - inverted)	Table K1 - Default	0.150	6.20	0.93	
Party wall	P4 Party wall - Roof (insulation at ceiling level)	Table K1 - Default	0.480	2.74	1.32	

Total: 102.33 W/mK:

Y-Value: 0.11 W/m<sup>2</sup>K:

# Summary for Input Data



Property Reference	C12-03-05	Issued on Date	15/10/2025
Assessment Reference	Design V1	Prop Type Ref	C12-03-05
Property	C12-03-05, Horsham Enterprise Park		
SAP Rating	80 C	DER	6.21
Environmental	96 A	% DER < TER	62.84
CO <sub>2</sub> Emissions (t/year)	0.28	DFEE	35.01
Compliance Check	See BREL	% DFEE < TFEE	42.56
% DPER < TPER	27.70	DPER	64.82
TPER	89.65		

Assessor Details	Miss Charlotte Russell	Assessor ID	DK97-0001
Client			

## SUMMARY FOR INPUT DATA FOR: New Build (As Designed)

Orientation	Southeast	
Property Tenure	ND	
Transaction Type	6	
Terrain Type	Suburban	
1.0 Property Type	Flat, Detached	
Position of Flat	Top-floor flat	
Which Floor	3	
2.0 Number of Storeys	1	
3.0 Date Built	2025	
3.0 Property Age Band	L	
4.0 Sheltered Sides	2	
5.0 Sunlight/Shade	Average or unknown	
6.0 Thermal Mass Parameter	Precise calculation	
Thermal Mass	218.31	kJ/m <sup>2</sup> K
7.0 Electricity Tariff	Standard	
Smart electricity meter fitted	Yes	
Smart gas meter fitted	No	

7.0 Measurements	Heat Loss Perimeter	Internal Floor Area	Average Storey Height
	Ground floor: 34.32 m	52.51 m <sup>2</sup>	2.50 m

8.0 Living Area	24.92	m <sup>2</sup>
-----------------	-------	----------------

9.0 External Walls	Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Res	Shelter	Openings	Area Calculation Type
External Wall	External Wall	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.15	110.00	57.67	49.80	0.00	None	7.87	Enter Gross Area
Sheltered	Sheltered	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.18	110.00	28.13	26.01	0.90	Stairwell Access Corridor 4	2.12	Enter Gross Area

9.2 Internal Walls	Description	Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Internal Walls	Internal Walls	Plasterboard on timber frame	9.00	61.26

10.0 External Roofs	Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Code	Shelter Factor	Openings	Calculation Type
External Roof	External Roof	External Flat Roof	Plasterboard, insulated flat roof	0.11	9.00	52.51	52.51	None	0.00	Enter Gross Area	0.00

11.1 Party Floors	Description	Storey Index	Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Party Floor	Party Floor	Lowest occupied	Precast concrete planks floor, screed, carpeted	40.00	52.51

# Summary for Input Data

## 12.0 Opening Types

Description	Data Source	Type	Glazing	Glazing Gap	Filling Type	G-value	Frame Type	Frame Factor	U Value (W/m <sup>2</sup> K)
Solid Door Glazing	Manufacturer	Solid Door Window	Double Low-E Soft 0.05			0.00 0.63		0.80	1.20 1.20

## 13.0 Openings

Name	Opening Type	Location	Orientation	Area (m <sup>2</sup> )	Pitch
FSD	Solid Door Glazing	Sheltered External Wall	South East North East	2.12 3.71	0 0
RSW	Glazing	External Wall	North East	2.32	0
RSGD	Glazing	External Wall	South West	1.84	0
LSW	Glazing				

## 14.0 Conservatory

None

## 15.0 Draught Proofing

100

%

## 16.0 Draught Lobby

No

## 17.0 Thermal Bridging

Calculate Bridges

### 17.1 List of Bridges

Bridge Type	Source Type	Length	Psi	Adjusted Reference:	Imported
E2 Other lintels (including other steel lintels)	Independently assessed	4.93	0.02	0.02 RCD	No
E3 Sill	Independently assessed	2.92	0.02	0.02 RCD	No
E4 Jamb	Independently assessed	11.56	0.01	0.01 RCD	No
E7 Party floor between dwellings (in blocks of flats)	Independently assessed	34.32	0.05	0.05 RCD	No
E16 Corner (normal)	Independently assessed	15.00	0.05	0.05 RCD	No
P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	0.00	0.00	0.00 Default	No
E18 Party wall between dwellings	Independently assessed	0.00	0.06	0.06 RCD	No
E17 Corner (inverted – internal area greater than external area)	Independently assessed	5.00	-0.10	-0.10 RCD	No
E25 Staggered party wall between dwellings	Table K1 - Default	0.00	0.24	0.24 E25 - Default	No
E14 Flat roof	Independently assessed	34.32	0.04	0.04 ROI	No

Y-value

0.03

W/m<sup>2</sup>K

Description

Bridge

## 19.0 Mechanical Ventilation

### Mechanical Ventilation

Mechanical Ventilation System Present	Yes
Approved Installation	Yes
Mechanical Ventilation data Type	Database
Type	Balanced mechanical ventilation with heat recovery
MV Reference Number	500500
Configuration	2
MVHR Duct Insulated	Uninsulated Ducts
Manufacturer SFP	0.59
Duct Type	Rigid
MVHR Efficiency	89.00
Wet Rooms	2
SFP from Installer Commissioning Certificate	No
MVHR System Location	Inside heated envelope (installed exclusively)
Duct Installation Specification	Level 2

## 19.1 Mechanical extract ventilation - Decentralised

SFP	Fan/Room Type	Count
0.13	In Room Fan	1
	Kitchen	
0.11	In Room Fan Other	3
	Wet Room	
0.00	In Duct Fan Kitchen	0
0.00	In Duct Fan Other	0
	Wet Room	
0.10	Through Wall Fan	0
	Kitchen	
0.10	Through Wall Fan	0
	Other Wet Room	

## 20.0 Fans, Open Fireplaces, Flues

Number of open chimneys

0

# Summary for Input Data

Number of open flues	0										
Number of chimneys/flues attached to closed fire	0										
Number of flues attached to solid fuel boiler	0										
Number of flues attached to other heater	0										
Number of blocked chimneys	0										
Number of intermittent extract fans	0										
Number of passive vents	0										
Number of flueless gas fires	0										
<b>21.0 Fixed Cooling System</b>	No										
<b>22.0 Pressure Testing</b>	Yes										
Designed AP <sub>50</sub>	3.00										
Property Tested?	Yes										
Test Method	Blower Door										
<b>22.0 Lighting</b>	No										
No Fixed Lighting	<table border="1"> <thead> <tr> <th>Name</th> <th>Efficacy</th> <th>Power</th> <th>Capacity</th> <th>Count</th> </tr> </thead> <tbody> <tr> <td>Low energy Lighting</td> <td>85.00</td> <td>5.00</td> <td>425.00</td> <td>10</td> </tr> </tbody> </table>	Name	Efficacy	Power	Capacity	Count	Low energy Lighting	85.00	5.00	425.00	10
Name	Efficacy	Power	Capacity	Count							
Low energy Lighting	85.00	5.00	425.00	10							
<b>24.0 Main Heating 1</b>	SAP table										
Percentage of Heat	100.00										
Database Ref. No.	0										
Fuel Type	Electricity										
SAP Code	691										
In Winter	100.00										
In Summer	194.18										
Controls SAP Code	2603										
Delayed Start Stat	No										
Burner Control	Modulating										
HETAS approved System	No										
Is MHS Pumped	Pump in heated space										
Heating Pump Age	2013 or later										
Heat Emitter	Radiators										
Underfloor Heating	Yes - Pipes in thin screed										
Flow Temperature	Enter value										
Flow Temperature Value	55.00										
<b>25.0 Main Heating 2</b>	Database										
Percentage of Heat	0.00										
Database Ref. No.	100834										
Fuel Type	Electricity										
SAP Code	0										
In Winter	302.93										
In Summer	194.18										
Model Name	Compact P										
Manufacturer	Nilan AS										
Controls	2100										
Delayed Start Stat	No										
HETAS approved System	No										
Flow Temperature	Enter value										

# Summary for Input Data

26.0 Heat Networks	None										
27.0 Secondary Heating	None										
<b>28.0 Water Heating</b>											
Water Heating	Main Heating 2										
SAP Code	914										
Flue Gas Heat Recovery System	No										
Waste Water Heat Recovery Instantaneous System 1	No										
Waste Water Heat Recovery Instantaneous System 2	No										
Waste Water Heat Recovery Storage System	No										
Solar Panel	No										
Water use <= 125 litres/person/day	Yes										
Summer Immersion	No										
Cold Water Source	From mains										
Bath Count	1										
Baths connected to WWHRS	0										
Supplementary Immersion	No										
Immersion Only Heating Hot Water	No										
<b>28.1 Showers</b>											
<b>Description</b>	<b>Shower Type</b>	<b>Flow Rate [l/min]</b>	<b>Rated Power [kW]</b>	<b>Connected</b>	<b>Connected To</b>						
8 lpm	Unknown	8.00		No							
<b>28.3 Waste Water Heat Recovery System</b>											
<b>29.0 Hot Water Cylinder</b>	Internal Store										
Cylinder Stat	No										
Cylinder In Heated Space	No										
Independent Time Control	No										
Insulation Type	Measured Loss										
Insulation Thickness	0										
Cylinder Volume	180.00			L							
Loss	0.84				kWh/day						
In Airing Cupboard	No										
<b>31.0 Thermal Store</b>	None										
<b>34.0 Small-scale Hydro</b>	None										
Electricity Generated	0.00										
Apportioned	0.00			kWh/Year							
Connected to dwelling's electricity meter	Yes										
Electricity Generation	Annual										
Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec

**Recommendations**
**Lower cost measures**

None

**Further measures to achieve even higher standards**

None

# Predicted Energy Assessment


C12-03-05, Horsham Enterprise Park

Dwelling type:  
Date of assessment:  
Produced by:  
Total floor area:  
DRRN:

Flat, Detached  
15/10/2025  
Charlotte Russell  
52.51 m<sup>2</sup>

This document is a Predicted Energy Assessment for properties marketed when they are incomplete. It includes a predicted energy rating which might not represent the final energy rating of the property on completion. Once the property is completed, this rating will be updated and an official Energy Performance Certificate will be created for the property. This will include more detailed information about the energy performance of the completed property.

The energy performance has been assessed using the Government approved SAP 10 methodology and is rated in terms of the energy use per square meter of floor area; the energy efficiency is based on fuel costs and the environmental impact is based on carbon dioxide (CO<sub>2</sub>) emissions.



The energy efficiency rating is a measure of the overall efficiency of a home. The higher the rating the more energy efficient the home is and the lower the fuel bills are likely to be.

The environmental impact rating is a measure of a home's impact on the environment in terms of carbon dioxide (CO<sub>2</sub>) emissions. The higher the rating the less impact it has on the environment.

# Thermal Bridging



Property Reference	C12-03-05		Issued on Date	15/10/2025
Assessment Reference	Design V1		Prop Type Ref	Detached Flat
Property	C12-03-05, Horsham Enterprise Park			
SAP Rating	80 C	DER	6.21	TER
Environmental	96 A	% DER < TER		62.84
CO <sub>2</sub> Emissions (t/year)	0.28	DFEE	35.01	TFEE
Compliance Check	See BREL	% DFEE < TFEE		17.75
% DPER < TPER	27.70	DPER	64.82	TPER
Assessor Details	Miss Charlotte Russell			Assessor ID
Client				

	Junction details	Source Type	Psi (W/mK)	Length (m)	Result	Reference
External wall	E2 Other lintels (including other steel lintels)	Independently assessed	0.022	4.93	0.11	RCD
External wall	E3 Sill	Independently assessed	0.016	2.92	0.05	RCD
External wall	E4 Jamb	Independently assessed	0.011	11.56	0.13	RCD
External wall	E7 Party floor between dwellings (in blocks of flats)	Independently assessed	0.053	34.32	1.82	RCD
External wall	E16 Corner (normal)	Independently assessed	0.051	15.00	0.76	RCD
Party wall	P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	0.000	0.00	0.00	Default
External wall	E18 Party wall between dwellings	Independently assessed	0.057	0.00	0.00	RCD
External wall	E17 Corner (inverted – internal area greater than external area)	Independently assessed	-0.104	5.00	-0.52	RCD
External wall	E25 Staggered party wall between dwellings	Table K1 - Default	0.240	0.00	0.00	E25 - Default
External wall	E14 Flat roof	Independently assessed	0.040	34.32	1.37	ROI

Total: 108.05 W/mK:

Y-Value: 0.03 W/m<sup>2</sup>K:

# Summary for Input Data



Property Reference	C12-04-01			Issued on Date	15/10/2025					
Assessment Reference	Design V1		Prop Type Ref	C12-04-01						
Property	C12-04-01, Horsham Enterprise Park									
SAP Rating	79 C	DER	6.30	TER	15.69					
Environmental	96 A	% DER < TER			59.85					
CO <sub>2</sub> Emissions (t/year)	0.28	DFEE	36.44	TFEE	37.56					
Compliance Check	See BREL	% DFEE < TFEE			3.00					
% DPER < TPER	21.81	DPER	65.72	TPER	84.05					
Assessor Details	Miss Charlotte Russell			Assessor ID	DK97-0001					
Client										
<b>SUMMARY FOR INPUT DATA FOR: New Build (As Designed)</b>										
Orientation	Northwest									
Property Tenure	ND									
Transaction Type	6									
Terrain Type	Suburban									
1.0 Property Type	Flat, End-Terrace									
Position of Flat	Top-floor flat									
Which Floor	4									
2.0 Number of Storeys	1									
3.0 Date Built	2025									
3.0 Property Age Band	L									
4.0 Sheltered Sides	2									
5.0 Sunlight/Shade	Average or unknown									
6.0 Thermal Mass Parameter	Precise calculation									
Thermal Mass	179.36 kJ/m <sup>2</sup> K									
7.0 Electricity Tariff	Standard									
Smart electricity meter fitted	Yes									
Smart gas meter fitted	No									
7.0 Measurements										
		Heat Loss Perimeter		Internal Floor Area		Average Storey Height				
		Ground floor: 23.73 m		51.34 m <sup>2</sup>		2.50 m				
8.0 Living Area	21.75 m <sup>2</sup>									
9.0 External Walls										
Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Res	Shelter	Openings	Area Calculation Type
External Wall	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.15	110.00	40.58	22.78	0.00	None	17.80	Enter Gross Area
Sheltered Wall	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.18	110.00	18.75	18.75	0.00	None	0.00	Enter Gross Area
9.1 Party Walls										
Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )	Shelter Res	Shelter			
Party Wall	Filled Cavity with Edge Sealing	Single plasterboard on dabs both sides, lightweight aggregate blocks, cavity or cavity fill	0.00	110.00	12.32	0.00	None			
9.2 Internal Walls										
Description							Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )		
Internal Walls	Plasterboard on timber frame						9.00	85.48		
10.0 External Roofs										
Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Code	Shelter Factor	Calculus	Openings Type
External Roof	External Flat Roof	Plasterboard, insulated flat roof	0.11	9.00	51.34	51.34	None	0.00	Enter Gross Area	0.00

# Summary for Input Data

## 11.1 Party Floors

Description	Storey Index	Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Party Floor	Lowest occupied	Precast concrete planks floor, screed, carpeted	40.00	51.34

## 12.0 Opening Types

Description	Data Source	Type	Glazing	Glazing Gap	Filling Type	G-value	Frame Type	Frame Factor	U Value (W/m <sup>2</sup> K)
Solid Door Glazing	Manufacturer	Solid Door Window	Double Low-E Soft 0.05			0.00 0.63		0.80	1.20 1.20

## 13.0 Openings

Name	Opening Type	Location	Orientation	Area (m <sup>2</sup> )	Pitch
FSD	Solid Door	External Wall	North West	2.12	0
RW	Glazing	External Wall	South East	7.84	0
LSW	Glazing	External Wall	North East	5.52	0
LSGD	Glazing	External Wall	North East	2.32	0

## 14.0 Conservatory

None

## 15.0 Draught Proofing

100

%

## 16.0 Draught Lobby

No

## 17.0 Thermal Bridging

Calculate Bridges

### 17.1 List of Bridges

Bridge Type	Source Type	Length	Psi	Adjusted Reference:	Imported
E2 Other lintels (including other steel lintels)	Independently assessed	7.77	0.02	RCD	No
E3 Sill	Independently assessed	5.76	0.02	RCD	No
E4 Jamb	Independently assessed	22.76	0.01	RCD	No
E7 Party floor between dwellings (in blocks of flats)	Independently assessed	23.73	0.05	RCD	No
E16 Corner (normal)	Independently assessed	7.50	0.05	RCD	No
P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	4.93	0.00	Default	No
E18 Party wall between dwellings	Independently assessed	2.50	0.06	RCD	No
E17 Corner (inverted – internal area greater than external area)	Independently assessed	0.00	-0.10	RCD	No
E25 Staggered party wall between dwellings	Table K1 - Default	2.50	0.24	E25 - Default	No
E14 Flat roof	Independently assessed	23.73	0.04	ROI	No
P4 Party wall - Roof (insulation at ceiling level)	Table K1 - Default	4.93	0.48	0.48	No

Y-value

0.06

W/m<sup>2</sup>K

Description

Bridge

## 19.0 Mechanical Ventilation

### Mechanical Ventilation

Mechanical Ventilation System Present	Yes
Approved Installation	Yes
Mechanical Ventilation data Type	Database
Type	Balanced mechanical ventilation with heat recovery
MV Reference Number	500500
Configuration	2
MVHR Duct Insulated	Uninsulated Ducts
Manufacturer SFP	0.59
Duct Type	Rigid
MVHR Efficiency	89.00
Wet Rooms	2
SFP from Installer Commissioning Certificate	No
MVHR System Location	Inside heated envelope (installed exclusively)
Duct Installation Specification	Level 2

## 19.1 Mechanical extract ventilation - Decentralised

SFP	Fan/Room Type	Count
0.13	In Room Fan	1
	Kitchen	
0.11	In Room Fan Other	3
	Wet Room	
0.00	In Duct Fan Kitchen	0
0.00	In Duct Fan Other	0
	Wet Room	
0.10	Through Wall Fan	0
	Kitchen	

# Summary for Input Data

0.10 Through Wall Fan 0  
Other Wet Room

## 20.0 Fans, Open Fireplaces, Flues

Number of open chimneys	0
Number of open flues	0
Number of chimneys/flues attached to closed fire	0
Number of flues attached to solid fuel boiler	0
Number of flues attached to other heater	0
Number of blocked chimneys	0
Number of intermittent extract fans	0
Number of passive vents	0
Number of flueless gas fires	0

## 21.0 Fixed Cooling System

No

## 22.0 Pressure Testing

Designed AP <sub>50</sub>	3.00	m <sup>3</sup> /(h.m <sup>2</sup> ) @ 50 Pa
Property Tested?	Yes	
Test Method	Blower Door	

## 22.0 Lighting

No Fixed Lighting

No	Name	Efficacy	Power	Capacity	Count
	Low energy Lighting	85.00	5.00	425.00	10

## 24.0 Main Heating 1

Percentage of Heat	100.00	%
Database Ref. No.	0	
Fuel Type	Electricity	
SAP Code	691	
In Winter	100.00	
In Summer	194.18	
Controls SAP Code	2603	
Delayed Start Stat	No	
Burner Control	Modulating	
HETAS approved System	No	
Is MHS Pumped	Pump in heated space	
Heating Pump Age	2013 or later	
Heat Emitter	Radiators	
Underfloor Heating	Yes - Pipes in thin screed	
Flow Temperature	Enter value	
Flow Temperature Value	55.00	

## 25.0 Main Heating 2

Percentage of Heat	0.00	%
Database Ref. No.	100834	
Fuel Type	Electricity	
SAP Code	0	
In Winter	305.55	
In Summer	194.18	
Model Name	Compact P	
Manufacturer	Nilan AS	
Controls	2100	

# Summary for Input Data

Delayed Start Stat	No										
HETAS approved System	No										
Flow Temperature	Enter value										
<b>26.0 Heat Networks</b>	None										
<b>27.0 Secondary Heating</b>	None										
<b>28.0 Water Heating</b>											
Water Heating	Main Heating 2										
SAP Code	914										
Flue Gas Heat Recovery System	No										
Waste Water Heat Recovery Instantaneous System 1	No										
Waste Water Heat Recovery Instantaneous System 2	No										
Waste Water Heat Recovery Storage System	No										
Solar Panel	No										
Water use <= 125 litres/person/day	Yes										
Summer Immersion	No										
Cold Water Source	From mains										
Bath Count	1										
Baths connected to WWHRS	0										
Supplementary Immersion	No										
Immersion Only Heating Hot Water	No										
<b>28.1 Showers</b>											
<b>Description</b>	<b>Shower Type</b>	<b>Flow Rate [l/min]</b>	<b>Rated Power [kW]</b>	<b>Connected</b>	<b>Connected To</b>						
8 lpm	Unknown	8.00		No							
<b>28.3 Waste Water Heat Recovery System</b>											
<b>29.0 Hot Water Cylinder</b>											
Cylinder Stat	Internal Store										
Cylinder In Heated Space	No										
Independent Time Control	No										
Insulation Type	Measured Loss										
Insulation Thickness	0										
Cylinder Volume	180.00	L									
Loss	0.84	kWh/day									
In Airing Cupboard	No										
<b>31.0 Thermal Store</b>											
<b>34.0 Small-scale Hydro</b>											
Electricity Generated	0.00										
Apportioned	0.00	kWh/Year									
Connected to dwelling's electricity meter	Yes										
Electricity Generation	Annual										
Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec

**Recommendations**

**Lower cost measures**

None

**Further measures to achieve even higher standards**

None

# Predicted Energy Assessment


C12-04-01, Horsham Enterprise Park

Dwelling type:  
Date of assessment:  
Produced by:  
Total floor area:  
DRRN:

Flat, End-Terrace  
15/10/2025  
Charlotte Russell  
51.34 m<sup>2</sup>

This document is a Predicted Energy Assessment for properties marketed when they are incomplete. It includes a predicted energy rating which might not represent the final energy rating of the property on completion. Once the property is completed, this rating will be updated and an official Energy Performance Certificate will be created for the property. This will include more detailed information about the energy performance of the completed property.

The energy performance has been assessed using the Government approved SAP 10 methodology and is rated in terms of the energy use per square meter of floor area; the energy efficiency is based on fuel costs and the environmental impact is based on carbon dioxide (CO<sub>2</sub>) emissions.



The energy efficiency rating is a measure of the overall efficiency of a home. The higher the rating the more energy efficient the home is and the lower the fuel bills are likely to be.

The environmental impact rating is a measure of a home's impact on the environment in terms of carbon dioxide (CO<sub>2</sub>) emissions. The higher the rating the less impact it has on the environment.

# Thermal Bridging

Property Reference	C12-04-01		Issued on Date	15/10/2025		
Assessment Reference	Design V1		Prop Type Ref	End-Terrace Flat		
Property	C12-04-01, Horsham Enterprise Park					
SAP Rating	79 C	DER	6.30	TER	15.69	
Environmental	96 A	% DER < TER			59.85	
CO <sub>2</sub> Emissions (t/year)	0.28	DFEE	36.44	TFEE	37.56	
Compliance Check	See BREL	% DFEE < TFEE			3.00	
% DPER < TPER	21.81	DPER	65.72	TPER	84.05	
Assessor Details	Miss Charlotte Russell			Assessor ID	DK97-0001	
Client						
	Junction details	Source Type	Psi (W/mK)	Length (m)	Result	Reference
External wall	E2 Other lintels (including other steel lintels)	Independently assessed	0.022	7.77	0.17	RCD
External wall	E3 Sill	Independently assessed	0.016	5.76	0.09	RCD
External wall	E4 Jamb	Independently assessed	0.011	22.76	0.25	RCD
External wall	E7 Party floor between dwellings (in blocks of flats)	Independently assessed	0.053	23.73	1.26	RCD
External wall	E16 Corner (normal)	Independently assessed	0.051	7.50	0.38	RCD
Party wall	P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	0.000	4.93	0.00	Default
External wall	E18 Party wall between dwellings	Independently assessed	0.057	2.50	0.14	RCD
External wall	E17 Corner (inverted – internal area greater than external area)	Independently assessed	-0.104	0.00	-0.00	RCD
External wall	E25 Staggered party wall between dwellings	Table K1 - Default	0.240	2.50	0.60	E25 - Default
External wall	E14 Flat roof	Independently assessed	0.040	23.73	0.95	ROI
Party wall	P4 Party wall - Roof (insulation at ceiling level)	Table K1 - Default	0.480	4.93	2.37	

Total: 106.11 W/mK:

Y-Value: 0.06 W/m<sup>2</sup>K:

# Summary for Input Data



Property Reference	C12-04-02			Issued on Date	15/10/2025					
Assessment Reference	Design V1		Prop Type Ref	C12-04-02						
Property	C12-04-02, Horsham Enterprise Park									
SAP Rating	81 B	DER	5.67	TER	14.43					
Environmental	96 A	% DER < TER			60.71					
CO <sub>2</sub> Emissions (t/year)	0.26	DFEE	31.49	TFEE	32.14					
Compliance Check	See BREL	% DFEE < TFEE			2.03					
% DPER < TPER	23.23	DPER	59.31	TPER	77.26					
Assessor Details	Miss Charlotte Russell			Assessor ID	DK97-0001					
Client										
<b>SUMMARY FOR INPUT DATA FOR: New Build (As Designed)</b>										
Orientation	Northwest									
Property Tenure	ND									
Transaction Type	6									
Terrain Type	Suburban									
1.0 Property Type	Flat, Mid-Terrace									
Position of Flat	Top-floor flat									
Which Floor	4									
2.0 Number of Storeys	1									
3.0 Date Built	2025									
3.0 Property Age Band	L									
4.0 Sheltered Sides	2									
5.0 Sunlight/Shade	Average or unknown									
6.0 Thermal Mass Parameter	Precise calculation									
Thermal Mass	191.29			kJ/m <sup>2</sup> K						
7.0 Electricity Tariff	Standard									
Smart electricity meter fitted	Yes									
Smart gas meter fitted	No									
7.0 Measurements										
		Heat Loss Perimeter		Internal Floor Area		Average Storey Height				
		Ground floor: 18.12 m		52.15 m <sup>2</sup>		2.50 m				
8.0 Living Area	25.45			m <sup>2</sup>						
9.0 External Walls										
Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Res	Shelter	Openings	Area Calculation Type
External Wall	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.15	110.00	34.56	20.98	0.00	None	13.58	Enter Gross Area
Sheltered Wall	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.18	110.00	10.75	10.75	0.00	None	0.00	Enter Gross Area
9.1 Party Walls										
Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )	Shelter Res	Shelter			
Party Wall	Filled Cavity with Edge Sealing	Single plasterboard on dabs both sides, lightweight aggregate blocks, cavity or cavity fill	0.00	110.00	30.15	0.00	None			
9.2 Internal Walls										
Description							Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )		
Internal Walls	Plasterboard on timber frame						9.00	68.18		
10.0 External Roofs										
Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Code	Shelter Factor	Calculus	Openings Type
External Roof	External Flat Roof	Plasterboard, insulated flat roof	0.11	9.00	52.15	52.15	None	0.00	Enter Gross Area	0.00

# Summary for Input Data

## 11.1 Party Floors

Description	Storey Index	Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Party Floor	Lowest occupied	Precast concrete planks floor, screed, carpeted	40.00	52.15

## 12.0 Opening Types

Description	Data Source	Type	Glazing	Glazing Gap	Filling Type	G-value	Frame Type	Frame Factor	U Value (W/m <sup>2</sup> K)
Solid Door Glazing	Manufacturer	Solid Door Window	Double Low-E Soft 0.05			0.00 0.63		0.80	1.20 1.20

## 13.0 Openings

Name	Opening Type	Location	Orientation	Area (m <sup>2</sup> )	Pitch
FSD	Solid Door	External Wall	North West	2.12	0
RW	Glazing	External Wall	South East	10.22	0
FW	Glazing	External Wall	North West	1.24	0

## 14.0 Conservatory

None

## 15.0 Draught Proofing

100

%

## 16.0 Draught Lobby

No

## 17.0 Thermal Bridging

Calculate Bridges

### 17.1 List of Bridges

Bridge Type	Source Type	Length	Psi	Adjusted Reference:	Imported
E2 Other lintels (including other steel lintels)	Independently assessed	6.33	0.02	RCD	No
E3 Sill	Independently assessed	5.32	0.02	RCD	No
E4 Jamb	Independently assessed	20.84	0.01	RCD	No
E7 Party floor between dwellings (in blocks of flats)	Independently assessed	18.12	0.05	RCD	No
E16 Corner (normal)	Independently assessed	2.50	0.05	RCD	No
P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	12.06	0.00	Default	No
E18 Party wall between dwellings	Independently assessed	10.00	0.06	RCD	No
E17 Corner (inverted – internal area greater than external area)	Independently assessed	2.50	-0.10	RCD	No
E25 Staggered party wall between dwellings	Table K1 - Default	0.00	0.24	E25 - Default	No
E14 Flat roof	Independently assessed	18.12	0.04	ROI	No
P4 Party wall - Roof (insulation at ceiling level)	Table K1 - Default	12.06	0.48	0.48	No

Y-value

0.09

W/m<sup>2</sup>K

Description

Bridge

## 19.0 Mechanical Ventilation

### Mechanical Ventilation

Mechanical Ventilation System Present	Yes
Approved Installation	Yes
Mechanical Ventilation data Type	Database
Type	Balanced mechanical ventilation with heat recovery
MV Reference Number	500500
Configuration	2
MVHR Duct Insulated	Uninsulated Ducts
Manufacturer SFP	0.59
Duct Type	Rigid
MVHR Efficiency	89.00
Wet Rooms	2
SFP from Installer Commissioning Certificate	No
MVHR System Location	Inside heated envelope (installed exclusively)
Duct Installation Specification	Level 2

## 19.1 Mechanical extract ventilation - Decentralised

SFP	Fan/Room Type	Count
0.13	In Room Fan	1
	Kitchen	
0.11	In Room Fan Other	3
	Wet Room	
0.00	In Duct Fan Kitchen	0
0.00	In Duct Fan Other	0
	Wet Room	
0.10	Through Wall Fan	0
	Kitchen	

# Summary for Input Data

0.10 Through Wall Fan 0  
Other Wet Room

## 20.0 Fans, Open Fireplaces, Flues

Number of open chimneys	0
Number of open flues	0
Number of chimneys/flues attached to closed fire	0
Number of flues attached to solid fuel boiler	0
Number of flues attached to other heater	0
Number of blocked chimneys	0
Number of intermittent extract fans	0
Number of passive vents	0
Number of flueless gas fires	0

## 21.0 Fixed Cooling System

No

## 22.0 Pressure Testing

Designed AP <sub>50</sub>	3.00	m <sup>3</sup> /(h.m <sup>2</sup> ) @ 50 Pa
Property Tested?	Yes	
Test Method	Blower Door	

## 22.0 Lighting

No Fixed Lighting

No	Name	Efficacy	Power	Capacity	Count
	Low energy Lighting	85.00	5.00	425.00	10

## 24.0 Main Heating 1

Percentage of Heat	100.00	%
Database Ref. No.	0	
Fuel Type	Electricity	
SAP Code	691	
In Winter	100.00	
In Summer	194.18	
Controls SAP Code	2603	
Delayed Start Stat	No	
Burner Control	Modulating	
HETAS approved System	No	
Is MHS Pumped	Pump in heated space	
Heating Pump Age	2013 or later	
Heat Emitter	Radiators	
Underfloor Heating	Yes - Pipes in thin screed	
Flow Temperature	Enter value	
Flow Temperature Value	55.00	

## 25.0 Main Heating 2

Percentage of Heat	0.00	%
Database Ref. No.	100834	
Fuel Type	Electricity	
SAP Code	0	
In Winter	304.01	
In Summer	194.18	
Model Name	Compact P	
Manufacturer	Nilan AS	
Controls	2100	

# Summary for Input Data

Delayed Start Stat	No										
HETAS approved System	No										
Flow Temperature	Enter value										
<b>26.0 Heat Networks</b>	None										
<b>27.0 Secondary Heating</b>	None										
<b>28.0 Water Heating</b>											
Water Heating	Main Heating 2										
SAP Code	914										
Flue Gas Heat Recovery System	No										
Waste Water Heat Recovery Instantaneous System 1	No										
Waste Water Heat Recovery Instantaneous System 2	No										
Waste Water Heat Recovery Storage System	No										
Solar Panel	No										
Water use <= 125 litres/person/day	Yes										
Summer Immersion	No										
Cold Water Source	From mains										
Bath Count	1										
Baths connected to WWHRS	0										
Supplementary Immersion	No										
Immersion Only Heating Hot Water	No										
<b>28.1 Showers</b>											
<b>Description</b>	<b>Shower Type</b>	<b>Flow Rate [l/min]</b>	<b>Rated Power [kW]</b>	<b>Connected</b>	<b>Connected To</b>						
8 lpm	Unknown	8.00		No							
<b>28.3 Waste Water Heat Recovery System</b>											
<b>29.0 Hot Water Cylinder</b>											
Cylinder Stat	Internal Store										
Cylinder In Heated Space	No										
Independent Time Control	No										
Insulation Type	Measured Loss										
Insulation Thickness	0										
Cylinder Volume	180.00	L									
Loss	0.84	kWh/day									
In Airing Cupboard	No										
<b>31.0 Thermal Store</b>											
<b>34.0 Small-scale Hydro</b>											
Electricity Generated	0.00										
Apportioned	0.00	kWh/Year									
Connected to dwelling's electricity meter	Yes										
Electricity Generation	Annual										
Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec

**Recommendations**
**Lower cost measures**

None

**Further measures to achieve even higher standards**

None

# Predicted Energy Assessment


C12-04-02, Horsham Enterprise Park

Dwelling type:  
Date of assessment:  
Produced by:  
Total floor area:  
DRRN:

Flat, Mid-Terrace  
15/10/2025  
Charlotte Russell  
52.15 m<sup>2</sup>

This document is a Predicted Energy Assessment for properties marketed when they are incomplete. It includes a predicted energy rating which might not represent the final energy rating of the property on completion. Once the property is completed, this rating will be updated and an official Energy Performance Certificate will be created for the property. This will include more detailed information about the energy performance of the completed property.

The energy performance has been assessed using the Government approved SAP 10 methodology and is rated in terms of the energy use per square meter of floor area; the energy efficiency is based on fuel costs and the environmental impact is based on carbon dioxide (CO<sub>2</sub>) emissions.



The energy efficiency rating is a measure of the overall efficiency of a home. The higher the rating the more energy efficient the home is and the lower the fuel bills are likely to be.

The environmental impact rating is a measure of a home's impact on the environment in terms of carbon dioxide (CO<sub>2</sub>) emissions. The higher the rating the less impact it has on the environment.

# Thermal Bridging



Property Reference	C12-04-02		Issued on Date	15/10/2025		
Assessment Reference	Design V1		Prop Type Ref	Mid-Terrace Flat		
Property	C12-04-02, Horsham Enterprise Park					
SAP Rating	81 B	DER	5.67	TER	14.43	
Environmental	96 A	% DER < TER		60.71		
CO <sub>2</sub> Emissions (t/year)	0.26	DFEE	31.49	TFEE	32.14	
Compliance Check	See BREL	% DFEE < TFEE		2.03		
% DPER < TPER	23.23	DPER	59.31	TPER	77.26	
Assessor Details	Miss Charlotte Russell			Assessor ID	DK97-0001	
Client						
	Junction details	Source Type	Psi (W/mK)	Length (m)	Result	Reference
External wall	E2 Other lintels (including other steel lintels)	Independently assessed	0.022	6.33	0.14	RCD
External wall	E3 Sill	Independently assessed	0.016	5.32	0.09	RCD
External wall	E4 Jamb	Independently assessed	0.011	20.84	0.23	RCD
External wall	E7 Party floor between dwellings (in blocks of flats)	Independently assessed	0.053	18.12	0.96	RCD
External wall	E16 Corner (normal)	Independently assessed	0.051	2.50	0.13	RCD
Party wall	P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	0.000	12.06	0.00	Default
External wall	E18 Party wall between dwellings	Independently assessed	0.057	10.00	0.57	RCD
External wall	E17 Corner (inverted – internal area greater than external area)	Independently assessed	-0.104	2.50	-0.26	RCD
External wall	E25 Staggered party wall between dwellings	Table K1 - Default	0.240	0.00	0.00	E25 - Default
External wall	E14 Flat roof	Independently assessed	0.040	18.12	0.72	ROI
Party wall	P4 Party wall - Roof (insulation at ceiling level)	Table K1 - Default	0.480	12.06	5.79	

Total: 107.85 W/mK:

Y-Value: 0.09 W/m<sup>2</sup>K:

# Summary for Input Data



Property Reference	C12-04-03	Issued on Date	15/10/2025
Assessment Reference	Design V1	Prop Type Ref	C12-04-03
Property	C12-04-03, Horsham Enterprise Park		
SAP Rating	81 B	DER	4.86
Environmental	96 A	% DER < TER	61.43
CO <sub>2</sub> Emissions (t/year)	0.31	DFEE	28.47
Compliance Check	See BREL	% DFEE < TFEE	32.21
% DPER < TPER	24.23	DPER	50.83
TPER	67.08		

Assessor Details	Miss Charlotte Russell	Assessor ID	DK97-0001
Client			

## SUMMARY FOR INPUT DATA FOR: New Build (As Designed)

Orientation	Northwest
Property Tenure	ND
Transaction Type	6
Terrain Type	Suburban
1.0 Property Type	Flat, End-Terrace
Position of Flat	Top-floor flat
Which Floor	4
2.0 Number of Storeys	1
3.0 Date Built	2025
3.0 Property Age Band	L
4.0 Sheltered Sides	2
5.0 Sunlight/Shade	Average or unknown
6.0 Thermal Mass Parameter	Precise calculation
Thermal Mass	167.11
	kJ/m <sup>2</sup> K
7.0 Electricity Tariff	Standard
Smart electricity meter fitted	Yes
Smart gas meter fitted	No

7.0 Measurements		Heat Loss Perimeter	Internal Floor Area	Average Storey Height
Ground floor:		28.13 m	74.87 m <sup>2</sup>	2.50 m

8.0 Living Area	31.76	m <sup>2</sup>
-----------------	-------	----------------

9.0 External Walls	Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Res	Shelter	Openings	Area Calculation Type
External Wall	External Wall	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.15	110.00	70.33	53.30	0.00	None	17.03	Enter Gross Area

9.1 Party Walls	Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )	Shelter Res	Shelter	Shelter
Party Wall	Party Wall	Filled Cavity with Edge Sealing	Single plasterboard on dabs both sides, lightweight aggregate blocks, cavity or cavity fill	0.00	110.00	17.83	0.00	None	None

9.2 Internal Walls	Description	Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Internal Walls	Internal Walls	Plasterboard on timber frame	9.00	113.20

10.0 External Roofs	Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Code	Shelter Factor	Shelter Type	Openings
External Roof	External Roof	External Flat Roof	Plasterboard, insulated flat roof	0.11	9.00	74.87	74.87	None	0.00	Enter Gross Area	0.00

## 11.1 Party Floors

# Summary for Input Data

Description	Storey Index	Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Party Floor	Lowest occupied	Precast concrete planks floor, screed, carpeted	40.00	74.87
<b>12.0 Opening Types</b>				
Description	Data Source	Type	Glazing	Glazing Gap
Solid Door Glazing	Manufacturer	Solid Door Window	Double Low-E Soft 0.05	0.00 0.63
<b>13.0 Openings</b>				
Name	Opening Type	Location	Orientation	Area (m <sup>2</sup> )
FSD	Solid Door Glazing	External Wall	North West	2.12
RW	Glazing	External Wall	South East	10.99
RSGD	Glazing	External Wall	South West	2.32
RSW	Glazing	External Wall	South West	1.60
<b>14.0 Conservatory</b>				
None				
<b>15.0 Draught Proofing</b>				
100 %				
<b>16.0 Draught Lobby</b>				
No				
<b>17.0 Thermal Bridging</b>				
Calculate Bridges				
<b>17.1 List of Bridges</b>				
Bridge Type	Source Type	Length	Psi	Adjusted Reference:
E2 Other lintels (including other steel lintels)	Independently assessed	9.13	0.02	RCD
E3 Sill	Independently assessed	7.12	0.02	RCD
E4 Jamb	Independently assessed	27.40	0.01	RCD
E7 Party floor between dwellings (in blocks of flats)	Independently assessed	28.13	0.05	RCD
E16 Corner (normal)	Independently assessed	5.00	0.05	RCD
P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	7.13	0.00	Default
E18 Party wall between dwellings	Independently assessed	5.00	0.06	RCD
E17 Corner (inverted – internal area greater than external area)	Independently assessed	0.00	-0.10	RCD
E25 Staggered party wall between dwellings	Table K1 - Default	0.00	0.24	E25 - Default
E14 Flat roof	Independently assessed	28.13	0.04	ROI
P4 Party wall - Roof (insulation at ceiling level)	Table K1 - Default	7.13	0.48	No
Y-value	0.05			W/m <sup>2</sup> K
Description	Bridge			
<b>19.0 Mechanical Ventilation</b>				
<b>Mechanical Ventilation</b>				
Mechanical Ventilation System Present	Yes			
Approved Installation	Yes			
Mechanical Ventilation data Type	Database			
Type	Balanced mechanical ventilation with heat recovery			
MV Reference Number	500500			
Configuration	2			
MVHR Duct Insulated	Uninsulated Ducts			
Manufacturer SFP	0.59			
Duct Type	Rigid			
MVHR Efficiency	89.00			
Wet Rooms	2			
SFP from Installer Commissioning Certificate	No			
MVHR System Location	Inside heated envelope (installed exclusively)			
Duct Installation Specification	Level 2			
<b>19.1 Mechanical extract ventilation - Decentralised</b>				
SFP	Fan/Room Type	Count		
0.13	In Room Fan	1		
	Kitchen			
0.11	In Room Fan Other	3		
	Wet Room			
0.00	In Duct Fan Kitchen	0		
0.00	In Duct Fan Other	0		
	Wet Room			
0.10	Through Wall Fan	0		
	Kitchen			

# Summary for Input Data

0.10      Through Wall Fan    0  
Other Wet Room

## 20.0 Fans, Open Fireplaces, Flues

Number of open chimneys	0
Number of open flues	0
Number of chimneys/flues attached to closed fire	0
Number of flues attached to solid fuel boiler	0
Number of flues attached to other heater	0
Number of blocked chimneys	0
Number of intermittent extract fans	0
Number of passive vents	0
Number of flueless gas fires	0

## 21.0 Fixed Cooling System

No

## 22.0 Pressure Testing

Designed AP <sub>50</sub>	3.00	m <sup>3</sup> /(h.m <sup>2</sup> ) @ 50 Pa
Property Tested?	Yes	
Test Method	Blower Door	

## 22.0 Lighting

No Fixed Lighting

No	Name	Efficacy	Power	Capacity	Count
	Low energy Lighting	85.00	5.00	425.00	10

## 24.0 Main Heating 1

Percentage of Heat	100.00	%
Database Ref. No.	0	
Fuel Type	Electricity	
SAP Code	691	
In Winter	100.00	
In Summer	194.18	
Controls SAP Code	2603	
Delayed Start Stat	No	
Burner Control	Modulating	
HETAS approved System	No	
Is MHS Pumped	Pump in heated space	
Heating Pump Age	2013 or later	
Heat Emitter	Radiators	
Underfloor Heating	Yes - Pipes in thin screed	
Flow Temperature	Enter value	
Flow Temperature Value	55.00	

## 25.0 Main Heating 2

Percentage of Heat	0.00	%
Database Ref. No.	100834	
Fuel Type	Electricity	
SAP Code	0	
In Winter	307.85	
In Summer	194.18	
Model Name	Compact P	
Manufacturer	Nilan AS	
Controls	2100	

# Summary for Input Data

Delayed Start Stat	No										
HETAS approved System	No										
Flow Temperature	Enter value										
<b>26.0 Heat Networks</b>	None										
<b>27.0 Secondary Heating</b>	None										
<b>28.0 Water Heating</b>											
Water Heating	Main Heating 2										
SAP Code	914										
Flue Gas Heat Recovery System	No										
Waste Water Heat Recovery Instantaneous System 1	No										
Waste Water Heat Recovery Instantaneous System 2	No										
Waste Water Heat Recovery Storage System	No										
Solar Panel	No										
Water use <= 125 litres/person/day	Yes										
Summer Immersion	No										
Cold Water Source	From mains										
Bath Count	1										
Baths connected to WWHRS	0										
Supplementary Immersion	No										
Immersion Only Heating Hot Water	No										
<b>28.1 Showers</b>											
<b>Description</b>	<b>Shower Type</b>	<b>Flow Rate [l/min]</b>	<b>Rated Power [kW]</b>	<b>Connected</b>	<b>Connected To</b>						
8 lpm	Unknown	8.00		No							
<b>28.3 Waste Water Heat Recovery System</b>											
<b>29.0 Hot Water Cylinder</b>											
Cylinder Stat	Internal Store										
Cylinder In Heated Space	No										
Independent Time Control	No										
Insulation Type	Measured Loss										
Insulation Thickness	0										
Cylinder Volume	180.00	L									
Loss	0.84	kWh/day									
In Airing Cupboard	No										
<b>31.0 Thermal Store</b>											
<b>34.0 Small-scale Hydro</b>											
Electricity Generated	0.00										
Apportioned	0.00	kWh/Year									
Connected to dwelling's electricity meter	Yes										
Electricity Generation	Annual										
Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec

**Recommendations**

**Lower cost measures**

None

**Further measures to achieve even higher standards**

None

# Predicted Energy Assessment


C12-04-03, Horsham Enterprise Park

Dwelling type:  
Date of assessment:  
Produced by:  
Total floor area:  
DRRN:

Flat, End-Terrace  
15/10/2025  
Charlotte Russell  
74.87 m<sup>2</sup>

This document is a Predicted Energy Assessment for properties marketed when they are incomplete. It includes a predicted energy rating which might not represent the final energy rating of the property on completion. Once the property is completed, this rating will be updated and an official Energy Performance Certificate will be created for the property. This will include more detailed information about the energy performance of the completed property.

The energy performance has been assessed using the Government approved SAP 10 methodology and is rated in terms of the energy use per square meter of floor area; the energy efficiency is based on fuel costs and the environmental impact is based on carbon dioxide (CO<sub>2</sub>) emissions.



The energy efficiency rating is a measure of the overall efficiency of a home. The higher the rating the more energy efficient the home is and the lower the fuel bills are likely to be.

The environmental impact rating is a measure of a home's impact on the environment in terms of carbon dioxide (CO<sub>2</sub>) emissions. The higher the rating the less impact it has on the environment.

# Thermal Bridging



Property Reference	C12-04-03			Issued on Date	15/10/2025	
Assessment Reference	Design V1		Prop Type Ref	End-Terrace Flat		
Property	C12-04-03, Horsham Enterprise Park					
SAP Rating	81 B	DER	4.86	TER	12.60	
Environmental	96 A	% DER < TER			61.43	
CO <sub>2</sub> Emissions (t/year)	0.31	DFEE	28.47	TFEE	32.21	
Compliance Check	See BREL	% DFEE < TFEE			11.61	
% DPER < TPER	24.23	DPER	50.83	TPER	67.08	
Assessor Details	Miss Charlotte Russell			Assessor ID	DK97-0001	
Client						
	Junction details	Source Type	Psi (W/mK)	Length (m)	Result	Reference
External wall	E2 Other lintels (including other steel lintels)	Independently assessed	0.022	9.13	0.20	RCD
External wall	E3 Sill	Independently assessed	0.016	7.12	0.11	RCD
External wall	E4 Jamb	Independently assessed	0.011	27.40	0.30	RCD
External wall	E7 Party floor between dwellings (in blocks of flats)	Independently assessed	0.053	28.13	1.49	RCD
External wall	E16 Corner (normal)	Independently assessed	0.051	5.00	0.26	RCD
Party wall	P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	0.000	7.13	0.00	Default
External wall	E18 Party wall between dwellings	Independently assessed	0.057	5.00	0.29	RCD
External wall	E17 Corner (inverted – internal area greater than external area)	Independently assessed	-0.104	0.00	-0.00	RCD
External wall	E25 Staggered party wall between dwellings	Table K1 - Default	0.240	0.00	0.00	E25 - Default
External wall	E14 Flat roof	Independently assessed	0.040	28.13	1.13	ROI
Party wall	P4 Party wall - Roof (insulation at ceiling level)	Table K1 - Default	0.480	7.13	3.42	

Total: 124.17 W/mK:  
 Y-Value: 0.05 W/m<sup>2</sup>K:

# Summary for Input Data



Property Reference	C13-00-01	Issued on Date	15/10/2025
Assessment Reference	Design V1	Prop Type Ref	C13-00-01
Property	C13-00-01, Horsham Enterprise Park		
SAP Rating	83 B	DER	5.28
Environmental	96 A	% DER < TER	64.66
CO <sub>2</sub> Emissions (t/year)	0.24	DFEE	28.52
Compliance Check	See BREL	% DFEE < TFEE	35.04
% DPER < TPER	30.93	DPER	55.29
TPER	80.05		

Assessor Details	Miss Charlotte Russell	Assessor ID	DK97-0001
Client			

## SUMMARY FOR INPUT DATA FOR: New Build (As Designed)

Orientation	Northwest	
Property Tenure	ND	
Transaction Type	6	
Terrain Type	Suburban	
1.0 Property Type	Flat, End-Terrace	
Position of Flat	Ground-floor flat	
Which Floor	0	
2.0 Number of Storeys	1	
3.0 Date Built	2025	
3.0 Property Age Band	L	
4.0 Sheltered Sides	2	
5.0 Sunlight/Shade	Average or unknown	
6.0 Thermal Mass Parameter	Precise calculation	
Thermal Mass	291.62	kJ/m <sup>2</sup> K
7.0 Electricity Tariff	Standard	
Smart electricity meter fitted	Yes	
Smart gas meter fitted	No	

7.0 Measurements	Heat Loss Perimeter	Internal Floor Area	Average Storey Height
	Ground floor: 22.04 m	52.93 m <sup>2</sup>	2.50 m

8.0 Living Area	25.03	m <sup>2</sup>
-----------------	-------	----------------

9.0 External Walls	Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Res	Shelter	Openings	Area Calculation Type
External Wall	External Wall	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.15	110.00	16.93	7.54	0.00	None	9.39	Enter Gross Area
Sheltered	Sheltered	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.18	110.00	38.18	36.06	0.90	Stairwell Access Corridor 4	2.12	Enter Gross Area

9.1 Party Walls	Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )	Shelter Res	Shelter
Party Wall	Party Wall	Filled Cavity with Edge Sealing	Single plasterboard on dabs both sides, lightweight aggregate blocks, cavity or cavity fill	0.00	110.00	21.25	0.00	None

9.2 Internal Walls	Description	Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Internal Walls	Internal Walls	Plasterboard on timber frame	9.00	69.68

10.1 Party Ceilings	Description	Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Ceiling	Ceiling	Precast concrete plank floor (screed laid on rubber), carpeted	30.00	52.93

## 11.0 Heat Loss Floors

# Summary for Input Data

Description	Type	Storey Index	Construction	U-Value (W/m <sup>2</sup> K)	Shelter Code	Shelter Factor	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )																																																																		
Ground Floor	Ground Floor - Solid	Lowest occupied	Suspended concrete floor, carpeted	0.10	None	0.00	75.00	52.93																																																																		
<b>12.0 Opening Types</b>																																																																										
Description	Data Source	Type	Glazing	Glazing Gap	Filling Type	G-value	Frame Type	Frame Factor																																																																		
Solid Door Glazing	Manufacturer	Solid Door Window	Double Low-E Soft 0.05			0.00 0.63		0.80 1.20																																																																		
<b>13.0 Openings</b>																																																																										
Name	Opening Type	Location	Orientation	Area (m <sup>2</sup> )	Pitch																																																																					
FSD	Solid Door	Sheltered	North West	2.12	0																																																																					
RW	Glazing	External Wall	South East	3.46	0																																																																					
RGD	Glazing	External Wall	South East	4.69	0																																																																					
FW	Glazing	External Wall	North West	1.24	0																																																																					
<b>14.0 Conservatory</b>																																																																										
None																																																																										
<b>15.0 Draught Proofing</b>																																																																										
100																																																																										
<b>16.0 Draught Lobby</b>																																																																										
No																																																																										
<b>17.0 Thermal Bridging</b>																																																																										
<b>17.1 List of Bridges</b>																																																																										
<table border="1"> <thead> <tr> <th>Bridge Type</th> <th>Source Type</th> <th>Length</th> <th>Psi</th> <th>Adjusted Reference:</th> <th>Imported</th> </tr> </thead> <tbody> <tr> <td>E2 Other lintels (including other steel lintels)</td> <td>Independently assessed</td> <td>6.00</td> <td>0.02</td> <td>0.02 RCD</td> <td>No</td> </tr> <tr> <td>E3 Sill</td> <td>Independently assessed</td> <td>2.97</td> <td>0.02</td> <td>0.02 RCD</td> <td>No</td> </tr> <tr> <td>E4 Jamb</td> <td>Independently assessed</td> <td>14.28</td> <td>0.01</td> <td>0.01 RCD</td> <td>No</td> </tr> <tr> <td>E5 Ground floor (normal)</td> <td>Independently assessed</td> <td>22.04</td> <td>0.08</td> <td>0.08 RCD</td> <td>No</td> </tr> <tr> <td>E7 Party floor between dwellings (in blocks of flats)</td> <td>Independently assessed</td> <td>22.04</td> <td>0.05</td> <td>0.05 RCD</td> <td>No</td> </tr> <tr> <td>E16 Corner (normal)</td> <td>Independently assessed</td> <td>7.50</td> <td>0.05</td> <td>0.05 RCD</td> <td>No</td> </tr> <tr> <td>P1 Party wall - Ground floor</td> <td>Table K1 - Default</td> <td>8.50</td> <td>0.32</td> <td>0.32 Default</td> <td>No</td> </tr> <tr> <td>P3 Party wall - Intermediate floor between dwellings (in blocks of flats)</td> <td>Table K1 - Default</td> <td>8.50</td> <td>0.00</td> <td>0.00 Default</td> <td>No</td> </tr> <tr> <td>E18 Party wall between dwellings</td> <td>Independently assessed</td> <td>5.00</td> <td>0.06</td> <td>0.06 RCD</td> <td>No</td> </tr> <tr> <td>E17 Corner (inverted – internal area greater than external area)</td> <td>Independently assessed</td> <td>2.50</td> <td>-0.10</td> <td>-0.10 RCD</td> <td>No</td> </tr> </tbody> </table>									Bridge Type	Source Type	Length	Psi	Adjusted Reference:	Imported	E2 Other lintels (including other steel lintels)	Independently assessed	6.00	0.02	0.02 RCD	No	E3 Sill	Independently assessed	2.97	0.02	0.02 RCD	No	E4 Jamb	Independently assessed	14.28	0.01	0.01 RCD	No	E5 Ground floor (normal)	Independently assessed	22.04	0.08	0.08 RCD	No	E7 Party floor between dwellings (in blocks of flats)	Independently assessed	22.04	0.05	0.05 RCD	No	E16 Corner (normal)	Independently assessed	7.50	0.05	0.05 RCD	No	P1 Party wall - Ground floor	Table K1 - Default	8.50	0.32	0.32 Default	No	P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	8.50	0.00	0.00 Default	No	E18 Party wall between dwellings	Independently assessed	5.00	0.06	0.06 RCD	No	E17 Corner (inverted – internal area greater than external area)	Independently assessed	2.50	-0.10	-0.10 RCD	No
Bridge Type	Source Type	Length	Psi	Adjusted Reference:	Imported																																																																					
E2 Other lintels (including other steel lintels)	Independently assessed	6.00	0.02	0.02 RCD	No																																																																					
E3 Sill	Independently assessed	2.97	0.02	0.02 RCD	No																																																																					
E4 Jamb	Independently assessed	14.28	0.01	0.01 RCD	No																																																																					
E5 Ground floor (normal)	Independently assessed	22.04	0.08	0.08 RCD	No																																																																					
E7 Party floor between dwellings (in blocks of flats)	Independently assessed	22.04	0.05	0.05 RCD	No																																																																					
E16 Corner (normal)	Independently assessed	7.50	0.05	0.05 RCD	No																																																																					
P1 Party wall - Ground floor	Table K1 - Default	8.50	0.32	0.32 Default	No																																																																					
P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	8.50	0.00	0.00 Default	No																																																																					
E18 Party wall between dwellings	Independently assessed	5.00	0.06	0.06 RCD	No																																																																					
E17 Corner (inverted – internal area greater than external area)	Independently assessed	2.50	-0.10	-0.10 RCD	No																																																																					
Y-value																																																																										
0.06																																																																										
W/m <sup>2</sup> K																																																																										
Description																																																																										
Bridge																																																																										
<b>19.0 Mechanical Ventilation</b>																																																																										
<b>Mechanical Ventilation</b>																																																																										
Mechanical Ventilation System Present																																																																										
Yes																																																																										
Approved Installation																																																																										
Yes																																																																										
Mechanical Ventilation data Type																																																																										
Database																																																																										
Type																																																																										
Balanced mechanical ventilation with heat recovery																																																																										
MV Reference Number																																																																										
500500																																																																										
Configuration																																																																										
2																																																																										
MVHR Duct Insulated																																																																										
Uninsulated Ducts																																																																										
Manufacturer SFP																																																																										
0.59																																																																										
Duct Type																																																																										
Rigid																																																																										
MVHR Efficiency																																																																										
89.00																																																																										
Wet Rooms																																																																										
2																																																																										
SFP from Installer Commissioning Certificate																																																																										
No																																																																										
MVHR System Location																																																																										
Inside heated envelope (installed exclusively)																																																																										
Duct Installation Specification																																																																										
Level 2																																																																										
<b>19.1 Mechanical extract ventilation - Decentralised</b>																																																																										
<table border="1"> <thead> <tr> <th>SFP</th> <th>Fan/Room Type</th> <th>Count</th> </tr> </thead> <tbody> <tr> <td>0.13</td> <td>In Room Fan</td> <td>1</td> </tr> <tr> <td></td> <td>Kitchen</td> <td></td> </tr> <tr> <td>0.11</td> <td>In Room Fan Other</td> <td>3</td> </tr> <tr> <td></td> <td>Wet Room</td> <td></td> </tr> <tr> <td>0.00</td> <td>In Duct Fan Kitchen</td> <td>0</td> </tr> <tr> <td>0.00</td> <td>In Duct Fan Other</td> <td>0</td> </tr> <tr> <td></td> <td>Wet Room</td> <td></td> </tr> <tr> <td>0.10</td> <td>Through Wall Fan</td> <td>0</td> </tr> <tr> <td></td> <td>Kitchen</td> <td></td> </tr> <tr> <td>0.10</td> <td>Through Wall Fan</td> <td>0</td> </tr> <tr> <td></td> <td>Other Wet Room</td> <td></td> </tr> </tbody> </table>									SFP	Fan/Room Type	Count	0.13	In Room Fan	1		Kitchen		0.11	In Room Fan Other	3		Wet Room		0.00	In Duct Fan Kitchen	0	0.00	In Duct Fan Other	0		Wet Room		0.10	Through Wall Fan	0		Kitchen		0.10	Through Wall Fan	0		Other Wet Room																															
SFP	Fan/Room Type	Count																																																																								
0.13	In Room Fan	1																																																																								
	Kitchen																																																																									
0.11	In Room Fan Other	3																																																																								
	Wet Room																																																																									
0.00	In Duct Fan Kitchen	0																																																																								
0.00	In Duct Fan Other	0																																																																								
	Wet Room																																																																									
0.10	Through Wall Fan	0																																																																								
	Kitchen																																																																									
0.10	Through Wall Fan	0																																																																								
	Other Wet Room																																																																									
<b>20.0 Fans, Open Fireplaces, Flues</b>																																																																										

# Summary for Input Data

Number of open chimneys	0										
Number of open flues	0										
Number of chimneys/flues attached to closed fire	0										
Number of flues attached to solid fuel boiler	0										
Number of flues attached to other heater	0										
Number of blocked chimneys	0										
Number of intermittent extract fans	0										
Number of passive vents	0										
Number of flueless gas fires	0										
<b>21.0 Fixed Cooling System</b>											
	No										
<b>22.0 Pressure Testing</b>											
Designed AP <sub>50</sub>	3.00										
Property Tested?	Yes										
Test Method	Blower Door										
<b>22.0 Lighting</b>											
No Fixed Lighting	<table border="1"> <thead> <tr> <th>Name</th> <th>Efficacy</th> <th>Power</th> <th>Capacity</th> <th>Count</th> </tr> </thead> <tbody> <tr> <td>Low energy Lighting</td> <td>85.00</td> <td>5.00</td> <td>425.00</td> <td>10</td> </tr> </tbody> </table>	Name	Efficacy	Power	Capacity	Count	Low energy Lighting	85.00	5.00	425.00	10
Name	Efficacy	Power	Capacity	Count							
Low energy Lighting	85.00	5.00	425.00	10							
<b>24.0 Main Heating 1</b>											
Percentage of Heat	SAP table										
Database Ref. No.	100.00										
Fuel Type	0										
SAP Code	Electricity										
In Winter	691										
In Summer	100.00										
Controls SAP Code	194.18										
Delayed Start Stat	2603										
Burner Control	No										
HETAS approved System	Modulating										
Is MHS Pumped	No										
Heating Pump Age	Pump in heated space										
Heat Emitter	2013 or later										
Underfloor Heating	Radiators										
Flow Temperature	Yes - Pipes in thin screed										
Flow Temperature Value	Enter value										
Flow Temperature Value	55.00										
<b>25.0 Main Heating 2</b>											
Percentage of Heat	Database										
Database Ref. No.	0.00										
Fuel Type	100834										
SAP Code	Electricity										
In Winter	0										
In Summer	302.49										
Model Name	194.18										
Manufacturer	Compact P										
Controls	Nilan AS										
Delayed Start Stat	2100										
HETAS approved System	No										
HETAS approved System	No										

# Summary for Input Data

Flow Temperature	Enter value										
<b>26.0 Heat Networks</b>	None										
<b>27.0 Secondary Heating</b>	None										
<b>28.0 Water Heating</b>											
Water Heating	Main Heating 2										
SAP Code	914										
Flue Gas Heat Recovery System	No										
Waste Water Heat Recovery Instantaneous System 1	No										
Waste Water Heat Recovery Instantaneous System 2	No										
Waste Water Heat Recovery Storage System	No										
Solar Panel	No										
Water use <= 125 litres/person/day	Yes										
Summer Immersion	No										
Cold Water Source	From mains										
Bath Count	1										
Baths connected to WWHRS	0										
Supplementary Immersion	No										
Immersion Only Heating Hot Water	No										
<b>28.1 Showers</b>											
<b>Description</b>	<b>Shower Type</b>	<b>Flow Rate</b> [l/min]	<b>Rated Power</b> [kW]	<b>Connected</b>	<b>Connected To</b>						
8 lpm	Unknown	8.00		No							
<b>28.3 Waste Water Heat Recovery System</b>											
<b>29.0 Hot Water Cylinder</b>		Internal Store									
Cylinder Stat	No										
Cylinder In Heated Space	No										
Independent Time Control	No										
Insulation Type	Measured Loss										
Insulation Thickness	0										
Cylinder Volume	180.00	L									
Loss	0.84	kWh/day									
In Airing Cupboard	No										
<b>31.0 Thermal Store</b>		None									
<b>34.0 Small-scale Hydro</b>		None									
Electricity Generated	0.00										
Apportioned	0.00	kWh/Year									
Connected to dwelling's electricity meter	Yes										
Electricity Generation	Annual										
Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
<b>Recommendations</b>											
<b>Lower cost measures</b>											
None											
<b>Further measures to achieve even higher standards</b>											
None											

# Predicted Energy Assessment


C13-00-01, Horsham Enterprise Park

Dwelling type:  
Date of assessment:  
Produced by:  
Total floor area:  
DRRN:

Flat, End-Terrace  
15/10/2025  
Charlotte Russell  
52.93 m<sup>2</sup>

This document is a Predicted Energy Assessment for properties marketed when they are incomplete. It includes a predicted energy rating which might not represent the final energy rating of the property on completion. Once the property is completed, this rating will be updated and an official Energy Performance Certificate will be created for the property. This will include more detailed information about the energy performance of the completed property.

The energy performance has been assessed using the Government approved SAP 10 methodology and is rated in terms of the energy use per square meter of floor area; the energy efficiency is based on fuel costs and the environmental impact is based on carbon dioxide (CO<sub>2</sub>) emissions.



The energy efficiency rating is a measure of the overall efficiency of a home. The higher the rating the more energy efficient the home is and the lower the fuel bills are likely to be.

The environmental impact rating is a measure of a home's impact on the environment in terms of carbon dioxide (CO<sub>2</sub>) emissions. The higher the rating the less impact it has on the environment.

# Thermal Bridging

Property Reference	C13-00-01		Issued on Date	15/10/2025
Assessment Reference	Design V1		Prop Type Ref	End-Terrace Flat
Property	C13-00-01, Horsham Enterprise Park			
SAP Rating	83 B	DER	5.28	TER
Environmental	96 A	% DER < TER		64.66
CO <sub>2</sub> Emissions (t/year)	0.24	DFEE	28.52	TFEE
Compliance Check	See BREL	% DFEE < TFEE		18.62
% DPER < TPER	30.93	DPER	55.29	TPER

Assessor Details	Miss Charlotte Russell	Assessor ID	DK97-0001
Client			

	Junction details	Source Type	Psi (W/mK)	Length (m)	Result	Reference
External wall	E2 Other lintels (including other steel lintels)	Independently assessed	0.022	6.00	0.13	RCD
External wall	E3 Sill	Independently assessed	0.016	2.97	0.05	RCD
External wall	E4 Jamb	Independently assessed	0.011	14.28	0.16	RCD
External wall	E5 Ground floor (normal)	Independently assessed	0.076	22.04	1.68	RCD
External wall	E7 Party floor between dwellings (in blocks of flats)	Independently assessed	0.053	22.04	1.17	RCD
External wall	E16 Corner (normal)	Independently assessed	0.051	7.50	0.38	RCD
Party wall	P1 Party wall - Ground floor	Table K1 - Default	0.320	8.50	2.72	Default
Party wall	P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	0.000	8.50	0.00	Default
External wall	E18 Party wall between dwellings	Independently assessed	0.057	5.00	0.29	RCD
External wall	E17 Corner (inverted – internal area greater than external area)	Independently assessed	-0.104	2.50	-0.26	RCD

Total: 99.33 W/mK:

Y-Value: 0.06 W/m<sup>2</sup>K:

# Summary for Input Data



Property Reference	C13-00-03	Issued on Date	15/10/2025
Assessment Reference	Design V1	Prop Type Ref	C13-00-03
Property	C13-00-03, Horsham Enterprise Park		
SAP Rating	81 B	DER	5.08
Environmental	96 A	% DER < TER	62.23
CO <sub>2</sub> Emissions (t/year)	0.32	DFEE	30.14
Compliance Check	See BREL	% DFEE < TFEE	36.12
% DPER < TPER	26.03	DPER	53.05
TPER	71.72		

Assessor Details	Miss Charlotte Russell	Assessor ID	DK97-0001
Client			

## SUMMARY FOR INPUT DATA FOR: New Build (As Designed)

Orientation	Southwest
Property Tenure	ND
Transaction Type	6
Terrain Type	Suburban
1.0 Property Type	Flat, End-Terrace
Position of Flat	Ground-floor flat
Which Floor	0
2.0 Number of Storeys	1
3.0 Date Built	2025
3.0 Property Age Band	L
4.0 Sheltered Sides	2
5.0 Sunlight/Shade	Average or unknown
6.0 Thermal Mass Parameter	Precise calculation
Thermal Mass	268.33
	kJ/m <sup>2</sup> K
7.0 Electricity Tariff	Standard
Smart electricity meter fitted	Yes
Smart gas meter fitted	No

7.0 Measurements		Heat Loss Perimeter	Internal Floor Area	Average Storey Height
Ground floor:		26.74 m	75.68 m <sup>2</sup>	2.50 m

8.0 Living Area	27.79	m <sup>2</sup>
-----------------	-------	----------------

9.0 External Walls		Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Res	Shelter	Openings	Area Calculation Type
External Wall	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.15	110.00	62.60	51.05	0.00	None	11.55	Enter Gross Area
Sheltered	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.18	110.00	4.25	2.13	0.90	Stairwell Access Corridor 4	2.12	Enter Gross Area

9.1 Party Walls		Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )	Shelter Res	Shelter
Party Wall	Filled Cavity with Edge Sealing	Single plasterboard on dabs both sides, lightweight aggregate blocks, cavity or cavity fill	0.00	110.00	21.25	0.00	None

9.2 Internal Walls		Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Internal Walls		Plasterboard on timber frame	9.00	127.40

10.1 Party Ceilings		Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Ceiling		Precast concrete plank floor (screed laid on rubber), carpeted	30.00	75.68

## 11.0 Heat Loss Floors

# Summary for Input Data

Description	Type	Storey Index	Construction	U-Value (W/m²K)	Shelter Code	Shelter Factor	Kappa (kJ/m²K)	Area (m²)	
Ground Floor	Ground Floor - Solid	Lowest occupied	Suspended concrete floor, carpeted	0.10	None	0.00	75.00	75.68	
<b>12.0 Opening Types</b>									
Description	Data Source	Type	Glazing	Glazing Gap	Filling Type	G-value	Frame Type	Frame Factor	U Value (W/m²K)
Solid Door Glazing	Manufacturer	Solid Door Window	Double Low-E Soft 0.05			0.00 0.63		0.80	1.20 1.20
<b>13.0 Openings</b>									
Name	Opening Type	Location	Orientation	Area (m²)	Pitch				
FSD	Solid Door	Sheltered	South West	2.12	0				
RW	Glazing	External Wall	North East	3.71	0				
RGD	Glazing	External Wall	North East	2.32	0				
LSW	Glazing	External Wall	North West	1.84	0				
RSW	Glazing	External Wall	South East	3.68	0				
<b>14.0 Conservatory</b>									
None									
<b>15.0 Draught Proofing</b>									
100 %									
<b>16.0 Draught Lobby</b>									
No									
<b>17.0 Thermal Bridging</b>									
Calculate Bridges									
<b>17.1 List of Bridges</b>									
Bridge Type	Source Type	Length	Psi	Adjusted Reference:	Imported				
E2 Other lintels (including other steel lintels)	Independently assessed	7.65	0.02	0.02 RCD	No				
E3 Sill	Independently assessed	5.64	0.02	0.02 RCD	No				
E4 Jamb	Independently assessed	17.00	0.01	0.01 RCD	No				
E5 Ground floor (normal)	Independently assessed	26.74	0.08	0.08 RCD	No				
E7 Party floor between dwellings (in blocks of flats)	Independently assessed	26.74	0.05	0.05 RCD	No				
E16 Corner (normal)	Independently assessed	7.50	0.05	0.05 RCD	No				
P1 Party wall - Ground floor	Table K1 - Default	8.50	0.32	0.32 Default	No				
P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	8.50	0.00	0.00 Default	No				
E18 Party wall between dwellings	Independently assessed	1.00	0.06	0.06 RCD	No				
E17 Corner (inverted – internal area greater than external area)	Independently assessed	0.00	-0.10	-0.10 RCD	No				
E25 Staggered party wall between dwellings	Table K1 - Default	2.50	0.24	0.24 Default	No				
Y-value	0.05				W/m²K				
Description	Bridge								
<b>19.0 Mechanical Ventilation</b>									
<b>Mechanical Ventilation</b>									
Mechanical Ventilation System Present	Yes								
Approved Installation	Yes								
Mechanical Ventilation data Type	Database								
Type	Balanced mechanical ventilation with heat recovery								
MV Reference Number	500500								
Configuration	2								
MVHR Duct Insulated	Uninsulated Ducts								
Manufacturer SFP	0.59								
Duct Type	Rigid								
MVHR Efficiency	89.00								
Wet Rooms	2								
SFP from Installer Commissioning Certificate	No								
MVHR System Location	Inside heated envelope (installed exclusively)								
Duct Installation Specification	Level 2								
<b>19.1 Mechanical extract ventilation - Decentralised</b>									
SFP	Fan/Room Type	Count							
0.13	In Room Fan	1							
	Kitchen								
0.11	In Room Fan Other	3							
	Wet Room								
0.00	In Duct Fan Kitchen	0							
0.00	In Duct Fan Other	0							
	Wet Room								
0.10	Through Wall Fan	0							
	Kitchen								
0.10	Through Wall Fan	0							
	Other Wet Room								

# Summary for Input Data

## 20.0 Fans, Open Fireplaces, Flues

Number of open chimneys	0
Number of open flues	0
Number of chimneys/flues attached to closed fire	0
Number of flues attached to solid fuel boiler	0
Number of flues attached to other heater	0
Number of blocked chimneys	0
Number of intermittent extract fans	0
Number of passive vents	0
Number of flueless gas fires	0

## 21.0 Fixed Cooling System

No
----

## 22.0 Pressure Testing

Designed AP <sub>50</sub>	Yes
	3.00
Property Tested?	Yes
Test Method	Blower Door

## 22.0 Lighting

No Fixed Lighting

Name	Efficacy	Power	Capacity	Count
Low energy Lighting	85.00	5.00	425.00	10

## 24.0 Main Heating 1

Percentage of Heat	100.00	%
Database Ref. No.	0	
Fuel Type	Electricity	
SAP Code	691	
In Winter	100.00	
In Summer	194.18	
Controls SAP Code	2603	
Delayed Start Stat	No	
Burner Control	Modulating	
HETAS approved System	No	
Is MHS Pumped	Pump in heated space	
Heating Pump Age	2013 or later	
Heat Emitter	Radiators	
Underfloor Heating	Yes - Pipes in thin screed	
Flow Temperature	Enter value	
Flow Temperature Value	55.00	

## 25.0 Main Heating 2

Percentage of Heat	0.00	%
Database Ref. No.	100834	
Fuel Type	Electricity	
SAP Code	0	
In Winter	308.22	
In Summer	194.18	
Model Name	Compact P	
Manufacturer	Nilan AS	
Controls	2100	
Delayed Start Stat	No	
HETAS approved System	No	

# Summary for Input Data

Flow Temperature	Enter value										
<b>26.0 Heat Networks</b>	None										
<b>27.0 Secondary Heating</b>	None										
<b>28.0 Water Heating</b>											
Water Heating	Main Heating 2										
SAP Code	914										
Flue Gas Heat Recovery System	No										
Waste Water Heat Recovery Instantaneous System 1	No										
Waste Water Heat Recovery Instantaneous System 2	No										
Waste Water Heat Recovery Storage System	No										
Solar Panel	No										
Water use <= 125 litres/person/day	Yes										
Summer Immersion	No										
Cold Water Source	From mains										
Bath Count	1										
Baths connected to WWHRS	0										
Supplementary Immersion	No										
Immersion Only Heating Hot Water	No										
<b>28.1 Showers</b>											
<b>Description</b>	<b>Shower Type</b>	<b>Flow Rate</b> [l/min]	<b>Rated Power</b> [kW]	<b>Connected</b>	<b>Connected To</b>						
8 lpm	Unknown	8.00		No							
<b>28.3 Waste Water Heat Recovery System</b>											
<b>29.0 Hot Water Cylinder</b>		Internal Store									
Cylinder Stat	No										
Cylinder In Heated Space	No										
Independent Time Control	No										
Insulation Type	Measured Loss										
Insulation Thickness	0										
Cylinder Volume	180.00	L									
Loss	0.84	kWh/day									
In Airing Cupboard	No										
<b>31.0 Thermal Store</b>		None									
<b>34.0 Small-scale Hydro</b>		None									
Electricity Generated	0.00										
Apportioned	0.00	kWh/Year									
Connected to dwelling's electricity meter	Yes										
Electricity Generation	Annual										
Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
<b>Recommendations</b>											
<b>Lower cost measures</b>											
None											
<b>Further measures to achieve even higher standards</b>											
None											

# Predicted Energy Assessment


C13-00-03, Horsham Enterprise Park

Dwelling type:  
Date of assessment:  
Produced by:  
Total floor area:  
DRRN:

Flat, End-Terrace  
15/10/2025  
Charlotte Russell  
75.68 m<sup>2</sup>

This document is a Predicted Energy Assessment for properties marketed when they are incomplete. It includes a predicted energy rating which might not represent the final energy rating of the property on completion. Once the property is completed, this rating will be updated and an official Energy Performance Certificate will be created for the property. This will include more detailed information about the energy performance of the completed property.

The energy performance has been assessed using the Government approved SAP 10 methodology and is rated in terms of the energy use per square meter of floor area; the energy efficiency is based on fuel costs and the environmental impact is based on carbon dioxide (CO<sub>2</sub>) emissions.



The energy efficiency rating is a measure of the overall efficiency of a home. The higher the rating the more energy efficient the home is and the lower the fuel bills are likely to be.

The environmental impact rating is a measure of a home's impact on the environment in terms of carbon dioxide (CO<sub>2</sub>) emissions. The higher the rating the less impact it has on the environment.

# Thermal Bridging

Property Reference	C13-00-03			Issued on Date	15/10/2025			
Assessment Reference	Design V1		Prop Type Ref	End-Terrace Flat				
Property	C13-00-03, Horsham Enterprise Park							
SAP Rating	81 B	DER	5.08	TER	13.45			
Environmental	96 A	% DER < TER			62.23			
CO <sub>2</sub> Emissions (t/year)	0.32	DFEE	30.14	TFEE	36.12			
Compliance Check	See BREL	% DFEE < TFEE			16.57			
% DPER < TPER	26.03	DPER	53.05	TPER	71.72			
Assessor Details	Miss Charlotte Russell			Assessor ID	DK97-0001			
Client								
	Junction details	Source Type	Psi (W/mK)	Length (m)	Result	Reference		
External wall	E2 Other lintels (including other steel lintels)	Independently assessed	0.022	7.65	0.17	RCD		
External wall	E3 Sill	Independently assessed	0.016	5.64	0.09	RCD		
External wall	E4 Jamb	Independently assessed	0.011	17.00	0.19	RCD		
External wall	E5 Ground floor (normal)	Independently assessed	0.076	26.74	2.03	RCD		
External wall	E7 Party floor between dwellings (in blocks of flats)	Independently assessed	0.053	26.74	1.42	RCD		
External wall	E16 Corner (normal)	Independently assessed	0.051	7.50	0.38	RCD		
Party wall	P1 Party wall - Ground floor	Table K1 - Default	0.320	8.50	2.72	Default		
Party wall	P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	0.000	8.50	0.00	Default		
External wall	E18 Party wall between dwellings	Independently assessed	0.057	1.00	0.06	RCD		
External wall	E17 Corner (inverted – internal area greater than external area)	Independently assessed	-0.104	0.00	-0.00	RCD		
External wall	E25 Staggered party wall between dwellings	Table K1 - Default	0.240	2.50	0.60	Default		

Total: 111.77 W/mK:

Y-Value: 0.05 W/m<sup>2</sup>K:

# Summary for Input Data



Property Reference	C13-01-05			Issued on Date	15/10/2025					
Assessment Reference	Design V1		Prop Type Ref	C13-01-05						
Property	C13-01-05, Horsham Enterprise Park									
SAP Rating	65 D	DER	15.87	TER	38.77					
Environmental	93 A	% DER < TER			59.07					
CO <sub>2</sub> Emissions (t/year)	0.35	DFEE	94.76	TFEE	114.83					
Compliance Check	See BREL	% DFEE < TFEE			17.48					
% DPER < TPER	21.90	DPER	163.70	TPER	209.60					
Assessor Details	Miss Charlotte Russell			Assessor ID	DK97-0001					
Client										
<b>SUMMARY FOR INPUT DATA FOR: New Build (As Designed)</b>										
Orientation	Southeast									
Property Tenure	ND									
Transaction Type	6									
Terrain Type	Suburban									
1.0 Property Type	Flat, Detached									
Position of Flat	Mid-floor flat									
Which Floor	1									
2.0 Number of Storeys	1									
3.0 Date Built	2025									
3.0 Property Age Band	L									
4.0 Sheltered Sides	2									
5.0 Sunlight/Shade	Average or unknown									
6.0 Thermal Mass Parameter	Precise calculation									
Thermal Mass	709.49 kJ/m <sup>2</sup> K									
7.0 Electricity Tariff	Standard									
Smart electricity meter fitted	Yes									
Smart gas meter fitted	No									
7.0 Measurements										
		Heat Loss Perimeter		Internal Floor Area		Average Storey Height				
		Ground floor: 34.32 m		25.51 m <sup>2</sup>		2.50 m				
8.0 Living Area	24.92 m <sup>2</sup>									
9.0 External Walls										
Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Res	Shelter	Openings	Area Calculation Type
External Wall	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.15	110.00	57.68	48.50	0.00	None	9.18	Enter Gross Area
Sheltered	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.18	110.00	28.13	26.01	0.90	Stairwell Access Corridor 4	2.12	Enter Gross Area
9.2 Internal Walls										
Description							Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )		
Internal Walls	Plasterboard on timber frame						9.00	61.26		
10.1 Party Ceilings										
Description							Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )		
Ceiling	Precast concrete plank floor (screed laid on rubber), carpeted						30.00	52.51		
11.0 Heat Loss Floors										
Description	Type	Storey Index	Construction	U-Value (W/m <sup>2</sup> K)	Shelter Code	Shelter Factor	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )		
Exposed Floor	Exposed Floor - Solid	Lowest occupied	Other	0.12	None	0.00	75.00	75.68		
12.0 Opening Types										

# Summary for Input Data

Description	Data Source	Type	Glazing	Glazing Gap	Filling Type	G-value	Frame Type	Frame Factor	U Value (W/m <sup>2</sup> K)
Solid Door Glazing	Manufacturer	Solid Door Window	Double Low-E Soft 0.05			0.00 0.63		0.80	1.20 1.20
<b>13.0 Openings</b>									
<b>Name</b>	<b>Opening Type</b>	<b>Location</b>	<b>Orientation</b>	<b>Area (m<sup>2</sup>)</b>	<b>Pitch</b>				
FSD	Solid Door Glazing	Sheltered External Wall External Wall	South East South West South West	2.12 2.32 3.71	0 0 0				
LSGD				3.15	0				
LSW	Glazing								
RSW	Glazing								
<b>14.0 Conservatory</b>		<b>None</b>							
<b>15.0 Draught Proofing</b>		<b>100</b>				<b>%</b>			
<b>16.0 Draught Lobby</b>		<b>No</b>							
<b>17.0 Thermal Bridging</b>		<b>Calculate Bridges</b>							
<b>17.1 List of Bridges</b>									
<b>Bridge Type</b>	<b>Source Type</b>	<b>Length</b>	<b>Psi</b>	<b>Adjusted Reference:</b>	<b>Imported</b>				
E2 Other lintels (including other steel lintels)	Independently assessed	4.93	0.02	0.02 RCD	No				
E3 Sill	Independently assessed	2.92	0.02	0.02 RCD	No				
E4 Jamb	Independently assessed	13.48	0.01	0.01 RCD	No				
E20 Exposed floor (normal)	Table K1 - Default	34.32	0.32	0.32 Default	No				
E7 Party floor between dwellings (in blocks of flats)	Independently assessed	34.32	0.05	0.05 RCD	No				
E16 Corner (normal)	Independently assessed	15.00	0.05	0.05 RCD	No				
P1 Party wall - Ground floor	Table K1 - Default	0.00	0.32	0.32 Default	No				
P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	0.00	0.00	0.00 Default	No				
E18 Party wall between dwellings	Independently assessed	0.00	0.06	0.06 RCD	No				
E17 Corner (inverted – internal area greater than external area)	Independently assessed	5.00	-0.10	-0.10 RCD	No				
E25 Staggered party wall between dwellings	Table K1 - Default	0.00	0.24	0.24 Default	No				
<b>Y-value</b>	<b>0.08</b>			<b>W/m<sup>2</sup>K</b>					
<b>Description</b>	<b>Bridge</b>								
<b>19.0 Mechanical Ventilation</b>									
<b>Mechanical Ventilation</b>									
Mechanical Ventilation System Present	<b>Yes</b>								
Approved Installation	<b>Yes</b>								
Mechanical Ventilation data Type	<b>Database</b>								
Type	<b>Balanced mechanical ventilation with heat recovery</b>								
MV Reference Number	<b>500500</b>								
Configuration	<b>2</b>								
MVHR Duct Insulated	<b>Uninsulated Ducts</b>								
Manufacturer SFP	<b>0.59</b>								
Duct Type	<b>Rigid</b>								
MVHR Efficiency	<b>89.00</b>								
Wet Rooms	<b>2</b>								
SFP from Installer Commissioning Certificate	<b>No</b>								
MVHR System Location	<b>Inside heated envelope (installed exclusively)</b>								
Duct Installation Specification	<b>Level 2</b>								
<b>19.1 Mechanical extract ventilation - Decentralised</b>									
<b>SFP</b>	<b>Fan/Room Type</b>	<b>Count</b>							
0.13	In Room Fan	1							
	Kitchen								
0.11	In Room Fan Other	3							
	Wet Room								
0.00	In Duct Fan Kitchen	0							
0.00	In Duct Fan Other	0							
	Wet Room								
0.10	Through Wall Fan	0							
	Kitchen								
0.10	Through Wall Fan	0							
	Other Wet Room								
<b>20.0 Fans, Open Fireplaces, Flues</b>									
Number of open chimneys	<b>0</b>								
Number of open flues	<b>0</b>								

# Summary for Input Data

Number of chimneys/flues attached to closed fire	0										
Number of flues attached to solid fuel boiler	0										
Number of flues attached to other heater	0										
Number of blocked chimneys	0										
Number of intermittent extract fans	0										
Number of passive vents	0										
Number of flueless gas fires	0										
<b>21.0 Fixed Cooling System</b>											
	No										
<b>22.0 Pressure Testing</b>											
Designed AP <sub>50</sub>	3.00										
Property Tested?	Yes										
Test Method	Blower Door										
<b>22.0 Lighting</b>											
No Fixed Lighting	No										
	<table border="1"> <thead> <tr> <th>Name</th> <th>Efficacy</th> <th>Power</th> <th>Capacity</th> <th>Count</th> </tr> </thead> <tbody> <tr> <td>Low energy Lighting</td> <td>85.00</td> <td>5.00</td> <td>425.00</td> <td>10</td> </tr> </tbody> </table>	Name	Efficacy	Power	Capacity	Count	Low energy Lighting	85.00	5.00	425.00	10
Name	Efficacy	Power	Capacity	Count							
Low energy Lighting	85.00	5.00	425.00	10							
<b>24.0 Main Heating 1</b>											
Percentage of Heat	100.00										
Database Ref. No.	0										
Fuel Type	Electricity										
SAP Code	691										
In Winter	100.00										
In Summer	194.18										
Controls SAP Code	2603										
Delayed Start Stat	No										
Burner Control	Modulating										
HETAS approved System	No										
Is MHS Pumped	Pump in heated space										
Heating Pump Age	2013 or later										
Heat Emitter	Radiators										
Underfloor Heating	Yes - Pipes in thin screed										
Flow Temperature	Enter value										
Flow Temperature Value	55.00										
<b>25.0 Main Heating 2</b>											
Percentage of Heat	0.00										
Database Ref. No.	100834										
Fuel Type	Electricity										
SAP Code	0										
In Winter	305.96										
In Summer	194.18										
Model Name	Compact P										
Manufacturer	Nilan AS										
Controls	2100										
Delayed Start Stat	No										
HETAS approved System	No										
Flow Temperature	Enter value										
<b>26.0 Heat Networks</b>											
	None										

# Summary for Input Data

27.0 Secondary Heating	None							
<b>28.0 Water Heating</b>								
Water Heating	Main Heating 2							
SAP Code	914							
Flue Gas Heat Recovery System	No							
Waste Water Heat Recovery Instantaneous System 1	No							
Waste Water Heat Recovery Instantaneous System 2	No							
Waste Water Heat Recovery Storage System	No							
Solar Panel	No							
Water use <= 125 litres/person/day	Yes							
Summer Immersion	No							
Cold Water Source	From mains							
Bath Count	1							
Baths connected to WWHRS	0							
Supplementary Immersion	No							
Immersion Only Heating Hot Water	No							
<b>28.1 Showers</b>								
<b>Description</b>	<b>Shower Type</b>							
8 lpm	Unknown							
	<b>Flow Rate [l/min]</b>							
	8.00							
	<b>Rated Power [kW]</b>							
	No							
<b>28.3 Waste Water Heat Recovery System</b>								
<b>29.0 Hot Water Cylinder</b>								
Cylinder Stat	Internal Store							
Cylinder In Heated Space	No							
Independent Time Control	No							
Insulation Type	Measured Loss							
Insulation Thickness	0							
Cylinder Volume	180.00							
Loss	0.84							
In Airing Cupboard	No							
<b>31.0 Thermal Store</b>	None							
<b>34.0 Small-scale Hydro</b>								
Electricity Generated	None							
Apportioned	0.00							
Connected to dwelling's electricity meter	0.00							
Electricity Generation	Yes							
Jan	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
<b>Recommendations</b>								
<b>Lower cost measures</b>								
None								
<b>Further measures to achieve even higher standards</b>								
None								

# Predicted Energy Assessment


C13-01-05, Horsham Enterprise Park

Dwelling type:  
Date of assessment:  
Produced by:  
Total floor area:  
DRRN:

Flat, Detached  
15/10/2025  
Charlotte Russell  
25.51 m<sup>2</sup>

This document is a Predicted Energy Assessment for properties marketed when they are incomplete. It includes a predicted energy rating which might not represent the final energy rating of the property on completion. Once the property is completed, this rating will be updated and an official Energy Performance Certificate will be created for the property. This will include more detailed information about the energy performance of the completed property.

The energy performance has been assessed using the Government approved SAP 10 methodology and is rated in terms of the energy use per square meter of floor area; the energy efficiency is based on fuel costs and the environmental impact is based on carbon dioxide (CO<sub>2</sub>) emissions.



The energy efficiency rating is a measure of the overall efficiency of a home. The higher the rating the more energy efficient the home is and the lower the fuel bills are likely to be.

The environmental impact rating is a measure of a home's impact on the environment in terms of carbon dioxide (CO<sub>2</sub>) emissions. The higher the rating the less impact it has on the environment.

# Thermal Bridging

Property Reference	C13-01-05		Issued on Date	15/10/2025		
Assessment Reference	Design V1		Prop Type Ref	Detached Flat		
Property	C13-01-05, Horsham Enterprise Park					
SAP Rating	65 D	DER	15.87	TER	38.77	
Environmental	93 A	% DER < TER		59.07		
CO <sub>2</sub> Emissions (t/year)	0.35	DFEE	94.76	TFEE	114.83	
Compliance Check	See BREL	% DFEE < TFEE		17.48		
% DPER < TPER	21.90	DPER	163.70	TPER	209.60	
Assessor Details	Miss Charlotte Russell			Assessor ID	DK97-0001	
Client						
	Junction details	Source Type	Psi (W/mK)	Length (m)	Result	Reference
External wall	E2 Other lintels (including other steel lintels)	Independently assessed	0.022	4.93	0.11	RCD
External wall	E3 Sill	Independently assessed	0.016	2.92	0.05	RCD
External wall	E4 Jamb	Independently assessed	0.011	13.48	0.15	RCD
External wall	E20 Exposed floor (normal)	Table K1 - Default	0.320	34.32	10.98	Default
External wall	E7 Party floor between dwellings (in blocks of flats)	Independently assessed	0.053	34.32	1.82	RCD
External wall	E16 Corner (normal)	Independently assessed	0.051	15.00	0.76	RCD
Party wall	P1 Party wall - Ground floor	Table K1 - Default	0.320	0.00	0.00	Default
Party wall	P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	0.000	0.00	0.00	Default
External wall	E18 Party wall between dwellings	Independently assessed	0.057	0.00	0.00	RCD
External wall	E17 Corner (inverted – internal area greater than external area)	Independently assessed	-0.104	5.00	-0.52	RCD
External wall	E25 Staggered party wall between dwellings	Table K1 - Default	0.240	0.00	0.00	Default

Total: 109.97 W/mK:

Y-Value: 0.08 W/m<sup>2</sup>K:

# Summary for Input Data



Property Reference	C13-02-05	Issued on Date	15/10/2025
Assessment Reference	Design V1	Prop Type Ref	C13-02-05
Property	C13-02-05, Horsham Enterprise Park		
SAP Rating	80 C	DER	9.18
Environmental	96 A	% DER < TER	27.72
CO <sub>2</sub> Emissions (t/year)	0.2	DFEE	50.80
Compliance Check	See BREL	TFEE	65.05
% DPER < TPER	36.24	% DFEE < TFEE	21.91
DPER	95.70	TPER	150.11

Assessor Details	Miss Charlotte Russell	Assessor ID	DK97-0001
Client			

## SUMMARY FOR INPUT DATA FOR: New Build (As Designed)

Orientation	Southeast	
Property Tenure	ND	
Transaction Type	6	
Terrain Type	Suburban	
1.0 Property Type	Flat, Detached	
Position of Flat	Mid-floor flat	
Which Floor	1	
2.0 Number of Storeys	1	
3.0 Date Built	2025	
3.0 Property Age Band	L	
4.0 Sheltered Sides	2	
5.0 Sunlight/Shade	Average or unknown	
6.0 Thermal Mass Parameter	Precise calculation	
Thermal Mass	569.33	kJ/m <sup>2</sup> K
7.0 Electricity Tariff	Standard	
Smart electricity meter fitted	Yes	
Smart gas meter fitted	No	

7.0 Measurements	Heat Loss Perimeter	Internal Floor Area	Average Storey Height
	Ground floor: 34.32 m	25.51 m <sup>2</sup>	2.50 m

8.0 Living Area	24.92	m <sup>2</sup>
-----------------	-------	----------------

9.0 External Walls	Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Res	Shelter	Openings	Area Calculation Type
External Wall		Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.15	110.00	57.68	48.50	0.00	None	9.18	Enter Gross Area
Sheltered		Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.18	110.00	28.13	26.01	0.90	Stairwell Access Corridor 4	2.12	Enter Gross Area

9.2 Internal Walls	Description	Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Internal Walls		Plasterboard on timber frame	9.00	61.26

10.1 Party Ceilings	Description	Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Ceiling		Precast concrete plank floor (screed laid on rubber), carpeted	30.00	52.51

11.1 Party Floors	Description	Storey Index	Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Party Floor		Lowest occupied	Precast concrete planks floor, screed, carpeted	40.00	52.51

## 12.0 Opening Types

# Summary for Input Data

Description	Data Source	Type	Glazing	Glazing Gap	Filling Type	G-value	Frame Type	Frame Factor	U Value (W/m²K)
Solid Door Glazing	Manufacturer	Solid Door Window	Double Low-E Soft 0.05			0.00 0.63		0.80	1.20 1.20
<b>13.0 Openings</b>									
Name	Opening Type	Location	Orientation	Area (m²)	Pitch				
FSD	Solid Door Glazing	Sheltered External Wall	South East South West	2.12 2.32	0				
LSGD	Glazing	External Wall	South West	3.71	0				
LSW	Glazing	External Wall	North East	3.15	0				
RSW	Glazing	External Wall							
<b>14.0 Conservatory</b>									
15.0 Draught Proofing	100				%				
<b>16.0 Draught Lobby</b>									
<b>17.0 Thermal Bridging</b>									
<b>17.1 List of Bridges</b>									
Bridge Type	Source Type	Length	Psi	Adjusted Reference:	Imported				
E2 Other lintels (including other steel lintels)	Independently assessed	4.93	0.02	0.02 RCD	No				
E3 Sill	Independently assessed	2.92	0.02	0.02 RCD	No				
E4 Jamb	Independently assessed	13.48	0.01	0.01 RCD	No				
E7 Party floor between dwellings (in blocks of flats)	Independently assessed	68.64	0.05	0.05 RCD	No				
E16 Corner (normal)	Independently assessed	15.00	0.05	0.05 RCD	No				
P1 Party wall - Ground floor	Table K1 - Default	0.00	0.32	0.32 Default	No				
P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	0.00	0.00	0.00 Default	No				
E18 Party wall between dwellings	Independently assessed	0.00	0.06	0.06 RCD	No				
E17 Corner (inverted – internal area greater than external area)	Independently assessed	5.00	-0.10	-0.10 RCD	No				
E25 Staggered party wall between dwellings	Table K1 - Default	0.00	0.24	0.24 Default	No				
Y-value	0.05				W/m²K				
Description	Bridge								
<b>19.0 Mechanical Ventilation</b>									
<b>Mechanical Ventilation</b>									
Mechanical Ventilation System Present	Yes								
Approved Installation	Yes								
Mechanical Ventilation data Type	Database								
Type	Balanced mechanical ventilation with heat recovery								
MV Reference Number	500500								
Configuration	2								
MVHR Duct Insulated	Uninsulated Ducts								
Manufacturer SFP	0.59								
Duct Type	Rigid								
MVHR Efficiency	89.00								
Wet Rooms	2								
SFP from Installer Commissioning Certificate	No								
MVHR System Location	Inside heated envelope (installed exclusively)								
Duct Installation Specification	Level 2								
<b>19.1 Mechanical extract ventilation - Decentralised</b>									
SFP	Fan/Room Type	Count							
0.13	In Room Fan	1							
	Kitchen								
0.11	In Room Fan Other	3							
	Wet Room								
0.00	In Duct Fan Kitchen	0							
0.00	In Duct Fan Other	0							
	Wet Room								
0.10	Through Wall Fan	0							
	Kitchen								
0.10	Through Wall Fan	0							
	Other Wet Room								
<b>20.0 Fans, Open Fireplaces, Flues</b>									
Number of open chimneys	0								
Number of open flues	0								

# Summary for Input Data

Number of chimneys/flues attached to closed fire	0										
Number of flues attached to solid fuel boiler	0										
Number of flues attached to other heater	0										
Number of blocked chimneys	0										
Number of intermittent extract fans	0										
Number of passive vents	0										
Number of flueless gas fires	0										
<b>21.0 Fixed Cooling System</b>											
	No										
<b>22.0 Pressure Testing</b>											
Designed AP <sub>50</sub>	3.00										
Property Tested?	Yes										
Test Method	Blower Door										
<b>22.0 Lighting</b>											
No Fixed Lighting	No										
	<table border="1"> <thead> <tr> <th>Name</th> <th>Efficacy</th> <th>Power</th> <th>Capacity</th> <th>Count</th> </tr> </thead> <tbody> <tr> <td>Low energy Lighting</td> <td>85.00</td> <td>5.00</td> <td>425.00</td> <td>10</td> </tr> </tbody> </table>	Name	Efficacy	Power	Capacity	Count	Low energy Lighting	85.00	5.00	425.00	10
Name	Efficacy	Power	Capacity	Count							
Low energy Lighting	85.00	5.00	425.00	10							
<b>24.0 Main Heating 1</b>											
Percentage of Heat	100.00										
Database Ref. No.	0										
Fuel Type	Electricity										
SAP Code	691										
In Winter	100.00										
In Summer	194.18										
Controls SAP Code	2603										
Delayed Start Stat	No										
Burner Control	Modulating										
HETAS approved System	No										
Is MHS Pumped	Pump in heated space										
Heating Pump Age	2013 or later										
Heat Emitter	Radiators										
Underfloor Heating	Yes - Pipes in thin screed										
Flow Temperature	Enter value										
Flow Temperature Value	55.00										
<b>25.0 Main Heating 2</b>											
Percentage of Heat	0.00										
Database Ref. No.	100834										
Fuel Type	Electricity										
SAP Code	0										
In Winter	296.38										
In Summer	194.18										
Model Name	Compact P										
Manufacturer	Nilan AS										
Controls	2100										
Delayed Start Stat	No										
HETAS approved System	No										
Flow Temperature	Enter value										
<b>26.0 Heat Networks</b>											
	None										

# Summary for Input Data

27.0 Secondary Heating	None										
<b>28.0 Water Heating</b>											
Water Heating	Main Heating 2										
SAP Code	914										
Flue Gas Heat Recovery System	No										
Waste Water Heat Recovery Instantaneous System 1	No										
Waste Water Heat Recovery Instantaneous System 2	No										
Waste Water Heat Recovery Storage System	No										
Solar Panel	No										
Water use <= 125 litres/person/day	Yes										
Summer Immersion	No										
Cold Water Source	From mains										
Bath Count	1										
Baths connected to WWHRS	0										
Supplementary Immersion	No										
Immersion Only Heating Hot Water	No										
<b>28.1 Showers</b>											
Description	Shower Type	Flow Rate [l/min]	Rated Power [kW]	Connected	Connected To						
8 lpm	Unknown	8.00		No							
<b>28.3 Waste Water Heat Recovery System</b>											
<b>29.0 Hot Water Cylinder</b>	Internal Store										
Cylinder Stat	No										
Cylinder In Heated Space	No										
Independent Time Control	No										
Insulation Type	Measured Loss										
Insulation Thickness	0										
Cylinder Volume	180.00	L									
Loss	0.84	kWh/day									
In Airing Cupboard	No										
<b>31.0 Thermal Store</b>	None										
<b>34.0 Small-scale Hydro</b>	None										
Electricity Generated	0.00										
Apportioned	0.00	kWh/Year									
Connected to dwelling's electricity meter	Yes										
Electricity Generation	Annual										
Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec

## Recommendations

### Lower cost measures

None

### Further measures to achieve even higher standards

None

# Predicted Energy Assessment


C13-02-05, Horsham Enterprise Park

Dwelling type:  
Date of assessment:  
Produced by:  
Total floor area:  
DRRN:

Flat, Detached  
15/10/2025  
Charlotte Russell  
25.51 m<sup>2</sup>

This document is a Predicted Energy Assessment for properties marketed when they are incomplete. It includes a predicted energy rating which might not represent the final energy rating of the property on completion. Once the property is completed, this rating will be updated and an official Energy Performance Certificate will be created for the property. This will include more detailed information about the energy performance of the completed property.

The energy performance has been assessed using the Government approved SAP 10 methodology and is rated in terms of the energy use per square meter of floor area; the energy efficiency is based on fuel costs and the environmental impact is based on carbon dioxide (CO<sub>2</sub>) emissions.



The energy efficiency rating is a measure of the overall efficiency of a home. The higher the rating the more energy efficient the home is and the lower the fuel bills are likely to be.

The environmental impact rating is a measure of a home's impact on the environment in terms of carbon dioxide (CO<sub>2</sub>) emissions. The higher the rating the less impact it has on the environment.

# Thermal Bridging

Property Reference	C13-02-05		Issued on Date	15/10/2025
Assessment Reference	Design V1		Prop Type Ref	Detached Flat
Property	C13-02-05, Horsham Enterprise Park			
SAP Rating	80 C	DER	9.18	TER
Environmental	96 A	% DER < TER		66.88
CO <sub>2</sub> Emissions (t/year)	0.2	DFEE	50.80	TFEE
Compliance Check	See BREL	% DFEE < TFEE		21.91
% DPER < TPER	36.24	DPER	95.70	TPER

Assessor Details	Miss Charlotte Russell	Assessor ID	DK97-0001
Client			

	Junction details	Source Type	Psi (W/mK)	Length (m)	Result	Reference
External wall	E2 Other lintels (including other steel lintels)	Independently assessed	0.022	4.93	0.11	RCD
External wall	E3 Sill	Independently assessed	0.016	2.92	0.05	RCD
External wall	E4 Jamb	Independently assessed	0.011	13.48	0.15	RCD
External wall	E7 Party floor between dwellings (in blocks of flats)	Independently assessed	0.053	68.64	3.64	RCD
External wall	E16 Corner (normal)	Independently assessed	0.051	15.00	0.76	RCD
Party wall	P1 Party wall - Ground floor	Table K1 - Default	0.320	0.00	0.00	Default
Party wall	P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	0.000	0.00	0.00	Default
External wall	E18 Party wall between dwellings	Independently assessed	0.057	0.00	0.00	RCD
External wall	E17 Corner (inverted – internal area greater than external area)	Independently assessed	-0.104	5.00	-0.52	RCD
External wall	E25 Staggered party wall between dwellings	Table K1 - Default	0.240	0.00	0.00	Default

Total: 109.97 W/mK:

Y-Value: 0.05 W/m<sup>2</sup>K:

# Summary for Input Data



Property Reference	C13-03-02			Issued on Date	15/10/2025					
Assessment Reference	Design V1		Prop Type Ref	C13-03-02						
Property	C13-03-02, Horsham Enterprise Park									
SAP Rating	86 B	DER	4.29	TER	12.80					
Environmental	97 A	% DER < TER			66.48					
CO <sub>2</sub> Emissions (t/year)	0.2	DFEE	21.02	TFEE	24.84					
Compliance Check	See BREL	% DFEE < TFEE			15.37					
% DPER < TPER	33.72	DPER	45.40	TPER	68.49					
Assessor Details	Miss Charlotte Russell			Assessor ID	DK97-0001					
Client										
<b>SUMMARY FOR INPUT DATA FOR: New Build (As Designed)</b>										
Orientation	Northwest									
Property Tenure	ND									
Transaction Type	6									
Terrain Type	Suburban									
1.0 Property Type	Flat, End-Terrace									
Position of Flat	Mid-floor flat									
Which Floor	3									
2.0 Number of Storeys	1									
3.0 Date Built	2025									
3.0 Property Age Band	L									
4.0 Sheltered Sides	2									
5.0 Sunlight/Shade	Average or unknown									
6.0 Thermal Mass Parameter	Precise calculation									
Thermal Mass	245.90 kJ/m <sup>2</sup> K									
7.0 Electricity Tariff	Standard									
Smart electricity meter fitted	Yes									
Smart gas meter fitted	No									
7.0 Measurements										
		Heat Loss Perimeter		Internal Floor Area		Average Storey Height				
		Ground floor: 15.74 m		52.93 m <sup>2</sup>		2.50 m				
8.0 Living Area	25.03 m <sup>2</sup>									
9.0 External Walls										
Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Res	Shelter	Openings	Area Calculation Type
External Wall	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.15	110.00	28.60	19.21	0.00	None	9.39	Enter Gross Area
Sheltered	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.18	110.00	10.75	8.63	0.90	Stairwell Access Corridor 4	2.12	Enter Gross Area
9.1 Party Walls										
Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )	Shelter Res	Shelter			
Party Wall	Filled Cavity with Edge Sealing	Single plasterboard on dabs both sides, lightweight aggregate blocks, cavity or cavity fill	0.00	110.00	37.00	0.00	None			
9.2 Internal Walls										
Description							Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )		
Internal Walls	Plasterboard on timber frame						9.00	69.68		
10.0 External Roofs										
Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Code	Shelter Factor	Calculation Type	Openings
Flat Roof	External Flat Roof	Plasterboard, insulated flat roof	0.11	9.00	9.27	9.27	None	0.00	Enter Gross Area	0.00

# Summary for Input Data

## 10.1 Party Ceilings

Description	Construction		Kappa (kJ/m²K)	Area (m²)
Ceiling	Precast concrete plank floor (screed laid on rubber), carpeted		30.00	43.65

## 11.1 Party Floors

Description	Storey Index	Construction	Kappa (kJ/m²K)	Area (m²)
Party Floor	Lowest occupied	Precast concrete planks floor, screed, carpeted	40.00	52.93

## 12.0 Opening Types

Description	Data Source	Type	Glazing	Glazing Gap	Filling Type	G-value	Frame Type	Frame Factor	U Value (W/m²K)
Solid Door Glazing	Manufacturer	Solid Door Window	Double Low-E Soft 0.05			0.00 0.63		0.80	1.20 1.20

## 13.0 Openings

Name	Opening Type	Location	Orientation	Area (m²)	Pitch
FSD	Solid Door	Sheltered	North West	2.12	0
RW	Glazing	External Wall	South East	3.46	0
RGD	Glazing	External Wall	South East	4.69	0
FW	Glazing	External Wall	North West	1.24	0

## 14.0 Conservatory

None

## 15.0 Draught Proofing

100

%

## 16.0 Draught Lobby

No

## 17.0 Thermal Bridging

Calculate Bridges

### 17.1 List of Bridges

Bridge Type	Source Type	Length	Psi	Adjusted Reference:	Imported
E2 Other lintels (including other steel lintels)	Independently assessed	6.00	0.02	RCD	No
E3 Sill	Independently assessed	2.97	0.02	RCD	No
E4 Jamb	Independently assessed	14.28	0.01	RCD	No
E7 Party floor between dwellings (in blocks of flats)	Independently assessed	24.71	0.05	RCD	No
E16 Corner (normal)	Independently assessed	2.50	0.05	RCD	No
P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	26.86	0.00	Default	No
E18 Party wall between dwellings	Independently assessed	10.00	0.06	RCD	No
E17 Corner (inverted – internal area greater than external area)	Independently assessed	2.50	-0.10	RCD	No
E14 Flat roof	Independently assessed	6.77	0.04	ROI	No
P4 Party wall - Roof (insulation at ceiling level)	Table K1 - Default	2.74	0.48	0.48	No
E24 Eaves (insulation at ceiling level - inverted)	Table K1 - Default	6.77	0.15	0.15	No

Y-value

0.10

W/m²K

Description

Bridge

## 19.0 Mechanical Ventilation

### Mechanical Ventilation

Mechanical Ventilation System Present	Yes
Approved Installation	Yes
Mechanical Ventilation data Type	Database
Type	Balanced mechanical ventilation with heat recovery
MV Reference Number	500500
Configuration	2
MVHR Duct Insulated	Uninsulated Ducts
Manufacturer SFP	0.59
Duct Type	Rigid
MVHR Efficiency	89.00
Wet Rooms	2
SFP from Installer Commissioning Certificate	No
MVHR System Location	Inside heated envelope (installed exclusively)
Duct Installation Specification	Level 2

## 19.1 Mechanical extract ventilation - Decentralised

SFP	Fan/Room Type	Count
0.13	In Room Fan	1
	Kitchen	
0.11	In Room Fan Other	3
	Wet Room	

# Summary for Input Data

0.00	In Duct Fan Kitchen	0
0.00	In Duct Fan Other	0
	Wet Room	
0.10	Through Wall Fan	0
	Kitchen	
0.10	Through Wall Fan	0
	Other Wet Room	

## 20.0 Fans, Open Fireplaces, Flues

Number of open chimneys	0
Number of open flues	0
Number of chimneys/flues attached to closed fire	0
Number of flues attached to solid fuel boiler	0
Number of flues attached to other heater	0
Number of blocked chimneys	0
Number of intermittent extract fans	0
Number of passive vents	0
Number of flueless gas fires	0

## 21.0 Fixed Cooling System

22.0 Pressure Testing	Yes
-----------------------	-----

Designed AP <sub>50</sub>	3.00	m <sup>3</sup> /(h.m <sup>2</sup> ) @ 50 Pa
Property Tested?	Yes	
Test Method	Blower Door	

## 22.0 Lighting

No Fixed Lighting	No				
	Name	Efficacy	Power	Capacity	Count
	Low energy Lighting	85.00	5.00	425.00	10

## 24.0 Main Heating 1

Percentage of Heat	100.00	%
Database Ref. No.	0	
Fuel Type	Electricity	
SAP Code	691	
In Winter	100.00	
In Summer	194.18	
Controls SAP Code	2603	
Delayed Start Stat	No	
Burner Control	Modulating	
HETAS approved System	No	
Is MHS Pumped	Pump in heated space	
Heating Pump Age	2013 or later	
Heat Emitter	Radiators	
Underfloor Heating	Yes - Pipes in thin screed	
Flow Temperature	Enter value	
Flow Temperature Value	55.00	

## 25.0 Main Heating 2

Percentage of Heat	0.00	%
Database Ref. No.	100834	
Fuel Type	Electricity	
SAP Code	0	
In Winter	297.31	
In Summer	194.18	
Model Name	Compact P	

# Summary for Input Data

Manufacturer	Nilan AS										
Controls	2100										
Delayed Start Stat	No										
HETAS approved System	No										
Flow Temperature	Enter value										
<b>26.0 Heat Networks</b>											
27.0 Secondary Heating	None										
<b>28.0 Water Heating</b>											
Water Heating	Main Heating 2										
SAP Code	914										
Flue Gas Heat Recovery System	No										
Waste Water Heat Recovery Instantaneous System 1	No										
Waste Water Heat Recovery Instantaneous System 2	No										
Waste Water Heat Recovery Storage System	No										
Solar Panel	No										
Water use <= 125 litres/person/day	Yes										
Summer Immersion	No										
Cold Water Source	From mains										
Bath Count	1										
Baths connected to WWHRS	0										
Supplementary Immersion	No										
Immersion Only Heating Hot Water	No										
<b>28.1 Showers</b>											
Description	Shower Type	Flow Rate [l/min]	Rated Power [kW]	Connected	Connected To						
8 lpm	Unknown	8.00		No							
<b>28.3 Waste Water Heat Recovery System</b>											
<b>29.0 Hot Water Cylinder</b>		Internal Store									
Cylinder Stat	No										
Cylinder In Heated Space	No										
Independent Time Control	No										
Insulation Type	Measured Loss										
Insulation Thickness	0										
Cylinder Volume	180.00	L									
Loss	0.84	kWh/day									
In Airing Cupboard	No										
<b>31.0 Thermal Store</b>		None									
<b>34.0 Small-scale Hydro</b>		None									
Electricity Generated	0.00										
Apportioned	0.00	kWh/Year									
Connected to dwelling's electricity meter	Yes										
Electricity Generation	Annual										
Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
<b>Recommendations</b>											
Lower cost measures											
None											
Further measures to achieve even higher standards											
None											

# Predicted Energy Assessment


C13-03-02, Horsham Enterprise Park

Dwelling type:  
Date of assessment:  
Produced by:  
Total floor area:  
DRRN:

Flat, End-Terrace  
15/10/2025  
Charlotte Russell  
52.93 m<sup>2</sup>

This document is a Predicted Energy Assessment for properties marketed when they are incomplete. It includes a predicted energy rating which might not represent the final energy rating of the property on completion. Once the property is completed, this rating will be updated and an official Energy Performance Certificate will be created for the property. This will include more detailed information about the energy performance of the completed property.

The energy performance has been assessed using the Government approved SAP 10 methodology and is rated in terms of the energy use per square meter of floor area; the energy efficiency is based on fuel costs and the environmental impact is based on carbon dioxide (CO<sub>2</sub>) emissions.



The energy efficiency rating is a measure of the overall efficiency of a home. The higher the rating the more energy efficient the home is and the lower the fuel bills are likely to be.

The environmental impact rating is a measure of a home's impact on the environment in terms of carbon dioxide (CO<sub>2</sub>) emissions. The higher the rating the less impact it has on the environment.

# Thermal Bridging

Property Reference	C13-03-02		Issued on Date	15/10/2025		
Assessment Reference	Design V1		Prop Type Ref	End-Terrace Flat		
Property	C13-03-02, Horsham Enterprise Park					
SAP Rating	86 B	DER	4.29	TER	12.80	
Environmental	97 A	% DER < TER		66.48		
CO <sub>2</sub> Emissions (t/year)	0.2	DFEE	21.02	TFEE	24.84	
Compliance Check	See BREL	% DFEE < TFEE		15.37		
% DPER < TPER	33.72	DPER	45.40	TPER	68.49	
Assessor Details	Miss Charlotte Russell			Assessor ID	DK97-0001	
Client						
	Junction details	Source Type	Psi (W/mK)	Length (m)	Result	Reference
External wall	E2 Other lintels (including other steel lintels)	Independently assessed	0.022	6.00	0.13	RCD
External wall	E3 Sill	Independently assessed	0.016	2.97	0.05	RCD
External wall	E4 Jamb	Independently assessed	0.011	14.28	0.16	RCD
External wall	E7 Party floor between dwellings (in blocks of flats)	Independently assessed	0.053	24.71	1.31	RCD
External wall	E16 Corner (normal)	Independently assessed	0.051	2.50	0.13	RCD
Party wall	P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	0.000	26.86	0.00	Default
External wall	E18 Party wall between dwellings	Independently assessed	0.057	10.00	0.57	RCD
External wall	E17 Corner (inverted – internal area greater than external area)	Independently assessed	-0.104	2.50	-0.26	RCD
External wall	E14 Flat roof	Independently assessed	0.040	6.77	0.27	ROI
Party wall	P4 Party wall - Roof (insulation at ceiling level)	Table K1 - Default	0.480	2.74	1.32	
External wall	E24 Eaves (insulation at ceiling level - inverted)	Table K1 - Default	0.150	6.77	1.02	Default

Total: 106.10 W/mK:

Y-Value: 0.10 W/m<sup>2</sup>K:

# Summary for Input Data



Property Reference	C13-03-04	Issued on Date	15/10/2025
Assessment Reference	Design V1	Prop Type Ref	C13-03-04
Property	C13-03-04, Horsham Enterprise Park		
SAP Rating	82 B	DER	4.66
Environmental	96 A	% DER < TER	62.78
CO <sub>2</sub> Emissions (t/year)	0.3	DFEE	26.99
Compliance Check	See BREL	% DFEE < TFEE	31.69
% DPER < TPER	26.76	DPER	48.84
TPER	66.69		

Assessor Details	Miss Charlotte Russell	Assessor ID	DK97-0001
Client			

## SUMMARY FOR INPUT DATA FOR: New Build (As Designed)

Orientation	Southwest
Property Tenure	ND
Transaction Type	6
Terrain Type	Suburban
1.0 Property Type	Flat, End-Terrace
Position of Flat	Mid-floor flat
Which Floor	3
2.0 Number of Storeys	1
3.0 Date Built	2025
3.0 Property Age Band	L
4.0 Sheltered Sides	2
5.0 Sunlight/Shade	Average or unknown
6.0 Thermal Mass Parameter	Precise calculation
Thermal Mass	201.82
	kJ/m <sup>2</sup> K
7.0 Electricity Tariff	Standard
Smart electricity meter fitted	Yes
Smart gas meter fitted	No

7.0 Measurements		Heat Loss Perimeter	Internal Floor Area	Average Storey Height
Ground floor:		26.74 m	75.68 m <sup>2</sup>	2.50 m

8.0 Living Area	27.79	m <sup>2</sup>
-----------------	-------	----------------

9.0 External Walls	Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Res	Shelter	Openings	Area Calculation Type
External Wall	External Wall	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.15	110.00	66.85	53.18	0.00	None	13.67	Enter Gross Area

9.1 Party Walls	Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )	Shelter Res	Shelter
Party Wall	Party Wall	Filled Cavity with Edge Sealing	Single plasterboard on dabs both sides, lightweight aggregate blocks, cavity or cavity fill	0.00	110.00	21.25	0.00	None

9.2 Internal Walls	Description	Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Internal Walls	Internal Walls	Plasterboard on timber frame	9.00	127.40

10.0 External Roofs	Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Code	Shelter Factor	Shelter Type	Openings
External Roof	External Roof	External Flat Roof	Plasterboard, insulated flat roof	0.11	9.00	39.11	39.11	None	0.00	Enter Gross Area	0.00

## 10.1 Party Ceilings

# Summary for Input Data

Description	Construction			Kappa (kJ/m²K)	Area (m²)
Ceiling	Precast concrete plank floor (screed laid on rubber), carpeted			30.00	36.58
<b>11.1 Party Floors</b>					
Description	Storey Index	Construction		Kappa (kJ/m²K)	Area (m²)
Party Floor	Lowest occupied	Precast concrete planks floor, screed, carpeted		40.00	75.68
<b>12.0 Opening Types</b>					
Description	Data Source	Type	Glazing	Glazing Gap	Filling Type
Solid Door Glazing	Manufacturer	Solid Door Window	Double Low-E Soft 0.05	0.00	0.63
					0.80
					1.20
					1.20
<b>13.0 Openings</b>					
Name	Opening Type	Location	Orientation	Area (m²)	Pitch
FSD	Solid Door	External Wall	South West	2.12	0
RW	Glazing	External Wall	North East	3.71	0
RGD	Glazing	External Wall	North East	2.32	0
LSW	Glazing	External Wall	North West	1.84	0
RSW	Glazing	External Wall	South East	3.68	0
<b>14.0 Conservatory</b>					
None					
<b>15.0 Draught Proofing</b>					
100 %					
<b>16.0 Draught Lobby</b>					
No					
<b>17.0 Thermal Bridging</b>					
<b>17.1 List of Bridges</b>					
Bridge Type	Source Type	Length	Psi	Adjusted Reference:	Imported
E2 Other lintels (including other steel lintels)	Independently assessed	7.65	0.02	RCD	No
E3 Sill	Independently assessed	5.64	0.02	RCD	No
E4 Jamb	Independently assessed	17.00	0.01	RCD	No
E7 Party floor between dwellings (in blocks of flats)	Independently assessed	26.74	0.05	RCD	No
E16 Corner (normal)	Independently assessed	7.50	0.05	RCD	No
P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	15.63	0.00	Default	No
E18 Party wall between dwellings	Independently assessed	1.00	0.06	RCD	No
E17 Corner (inverted – internal area greater than external area)	Independently assessed	0.00	-0.10	RCD	No
E25 Staggered party wall between dwellings	Table K1 - Default	2.50	0.24	Default	No
P4 Party wall - Roof (insulation at ceiling level)	Table K1 - Default	1.37	0.48	Default	No
E14 Flat roof	Independently assessed	1.70	0.04	ROI	No
E24 Eaves (insulation at ceiling level - inverted)	Table K1 - Default	17.39	0.15	Default	No
Y-value	0.06			W/m²K	
Description	Bridge				
<b>19.0 Mechanical Ventilation</b>					
<b>Mechanical Ventilation</b>					
Mechanical Ventilation System Present	Yes				
Approved Installation	Yes				
Mechanical Ventilation data Type	Database				
Type	Balanced mechanical ventilation with heat recovery				
MV Reference Number	500500				
Configuration	2				
MVHR Duct Insulated	Uninsulated Ducts				
Manufacturer SFP	0.59				
Duct Type	Rigid				
MVHR Efficiency	89.00				
Wet Rooms	2				
SFP from Installer Commissioning Certificate	No				
MVHR System Location	Inside heated envelope (installed exclusively)				
Duct Installation Specification	Level 2				
<b>19.1 Mechanical extract ventilation - Decentralised</b>					
SFP	Fan/Room Type	Count			
0.13	In Room Fan	1			
	Kitchen				

# Summary for Input Data

0.11	In Room Fan Other	3
0.00	Wet Room	
0.00	In Duct Fan Kitchen	0
0.00	In Duct Fan Other	0
0.10	Wet Room	
0.10	Through Wall Fan	0
	Kitchen	
0.10	Through Wall Fan	0
	Other Wet Room	

## 20.0 Fans, Open Fireplaces, Flues

Number of open chimneys	0
Number of open flues	0
Number of chimneys/flues attached to closed fire	0
Number of flues attached to solid fuel boiler	0
Number of flues attached to other heater	0
Number of blocked chimneys	0
Number of intermittent extract fans	0
Number of passive vents	0
Number of flueless gas fires	0

## 21.0 Fixed Cooling System

21.0 Fixed Cooling System	No
22.0 Pressure Testing	Yes
Designed AP <sub>50</sub>	3.00
Property Tested?	Yes
Test Method	Blower Door

## 22.0 Lighting

No Fixed Lighting	No				
		Name	Efficacy	Power	Capacity
		Low energy Lighting	85.00	5.00	425.00
					Count
					10

## 24.0 Main Heating 1

Percentage of Heat	100.00	%
Database Ref. No.	0	
Fuel Type	Electricity	
SAP Code	691	
In Winter	100.00	
In Summer	194.18	
Controls SAP Code	2603	
Delayed Start Stat	No	
Burner Control	Modulating	
HETAS approved System	No	
Is MHS Pumped	Pump in heated space	
Heating Pump Age	2013 or later	
Heat Emitter	Radiators	
Underfloor Heating	Yes - Pipes in thin screed	
Flow Temperature	Enter value	
Flow Temperature Value	55.00	

## 25.0 Main Heating 2

Percentage of Heat	0.00	%
Database Ref. No.	100834	
Fuel Type	Electricity	
SAP Code	0	
In Winter	307.01	

# Summary for Input Data

In Summer	194.18										
Model Name	Compact P										
Manufacturer	Nilan AS										
Controls	2100										
Delayed Start Stat	No										
HETAS approved System	No										
Flow Temperature	Enter value										
<b>26.0 Heat Networks</b>											
26.0 Heat Networks	None										
<b>27.0 Secondary Heating</b>											
27.0 Secondary Heating	None										
<b>28.0 Water Heating</b>											
Water Heating	Main Heating 2										
SAP Code	914										
Flue Gas Heat Recovery System	No										
Waste Water Heat Recovery Instantaneous System 1	No										
Waste Water Heat Recovery Instantaneous System 2	No										
Waste Water Heat Recovery Storage System	No										
Solar Panel	No										
Water use <= 125 litres/person/day	Yes										
Summer Immersion	No										
Cold Water Source	From mains										
Bath Count	1										
Baths connected to WWHRS	0										
Supplementary Immersion	No										
Immersion Only Heating Hot Water	No										
<b>28.1 Showers</b>											
Description	Shower Type	Flow Rate [l/min]	Rated Power [kW]	Connected	Connected To						
8 lpm	Unknown	8.00		No							
<b>28.3 Waste Water Heat Recovery System</b>											
<b>29.0 Hot Water Cylinder</b>											
Cylinder Stat	Internal Store										
Cylinder In Heated Space	No										
Independent Time Control	No										
Insulation Type	Measured Loss										
Insulation Thickness	0										
Cylinder Volume	180.00	L									
Loss	0.84	kWh/day									
In Airing Cupboard	No										
<b>31.0 Thermal Store</b>											
<b>34.0 Small-scale Hydro</b>											
Electricity Generated	0.00										
Apportioned	0.00	kWh/Year									
Connected to dwelling's electricity meter	Yes										
Electricity Generation	Annual										
Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
<b>Recommendations</b>											
Lower cost measures											
None											
Further measures to achieve even higher standards											

# Summary for Input Data



**None**

# Predicted Energy Assessment


C13-03-04, Horsham Enterprise Park

Dwelling type:  
Date of assessment:  
Produced by:  
Total floor area:  
DRRN:

Flat, End-Terrace  
15/10/2025  
Charlotte Russell  
75.68 m<sup>2</sup>

This document is a Predicted Energy Assessment for properties marketed when they are incomplete. It includes a predicted energy rating which might not represent the final energy rating of the property on completion. Once the property is completed, this rating will be updated and an official Energy Performance Certificate will be created for the property. This will include more detailed information about the energy performance of the completed property.

The energy performance has been assessed using the Government approved SAP 10 methodology and is rated in terms of the energy use per square meter of floor area; the energy efficiency is based on fuel costs and the environmental impact is based on carbon dioxide (CO<sub>2</sub>) emissions.



The energy efficiency rating is a measure of the overall efficiency of a home. The higher the rating the more energy efficient the home is and the lower the fuel bills are likely to be.

The environmental impact rating is a measure of a home's impact on the environment in terms of carbon dioxide (CO<sub>2</sub>) emissions. The higher the rating the less impact it has on the environment.

# Thermal Bridging

Property Reference	C13-03-04		Issued on Date	15/10/2025		
Assessment Reference	Design V1		Prop Type Ref	End-Terrace Flat		
Property	C13-03-04, Horsham Enterprise Park					
SAP Rating	82 B	DER	4.66	TER	12.52	
Environmental	96 A	% DER < TER		62.78		
CO <sub>2</sub> Emissions (t/year)	0.3	DFEE	26.99	TFEE	31.69	
Compliance Check	See BREL	% DFEE < TFEE		14.83		
% DPER < TPER	26.76	DPER	48.84	TPER	66.69	
Assessor Details	Miss Charlotte Russell			Assessor ID	DK97-0001	
Client						
	Junction details	Source Type	Psi (W/mK)	Length (m)	Result	Reference
External wall	E2 Other lintels (including other steel lintels)	Independently assessed	0.022	7.65	0.17	RCD
External wall	E3 Sill	Independently assessed	0.016	5.64	0.09	RCD
External wall	E4 Jamb	Independently assessed	0.011	17.00	0.19	RCD
External wall	E7 Party floor between dwellings (in blocks of flats)	Independently assessed	0.053	26.74	1.42	RCD
External wall	E16 Corner (normal)	Independently assessed	0.051	7.50	0.38	RCD
Party wall	P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	0.000	15.63	0.00	Default
External wall	E18 Party wall between dwellings	Independently assessed	0.057	1.00	0.06	RCD
External wall	E17 Corner (inverted – internal area greater than external area)	Independently assessed	-0.104	0.00	-0.00	RCD
External wall	E25 Staggered party wall between dwellings	Table K1 - Default	0.240	2.50	0.60	Default
Party wall	P4 Party wall - Roof (insulation at ceiling level)	Table K1 - Default	0.480	1.37	0.66	
External wall	E14 Flat roof	Independently assessed	0.040	1.70	0.07	ROI
External wall	E24 Eaves (insulation at ceiling level - inverted)	Table K1 - Default	0.150	17.39	2.61	Default

Total: 104.12 W/mK:

Y-Value: 0.06 W/m<sup>2</sup>K:

# Summary for Input Data



Property Reference	C13-04-01			Issued on Date	15/10/2025					
Assessment Reference	Design V1		Prop Type Ref	C13-04-01						
Property	C13-04-01, Horsham Enterprise Park									
SAP Rating	81 B	DER	5.74	TER	15.06					
Environmental	96 A	% DER < TER			61.89					
CO <sub>2</sub> Emissions (t/year)	0.26	DFEE	32.62	TFEE	34.60					
Compliance Check	See BREL	% DFEE < TFEE			5.74					
% DPER < TPER	25.58	DPER	60.04	TPER	80.68					
Assessor Details	Miss Charlotte Russell			Assessor ID	DK97-0001					
Client										
<b>SUMMARY FOR INPUT DATA FOR: New Build (As Designed)</b>										
Orientation	Northwest									
Property Tenure	ND									
Transaction Type	6									
Terrain Type	Suburban									
1.0 Property Type	Flat, End-Terrace									
Position of Flat	Top-floor flat									
Which Floor	4									
2.0 Number of Storeys	1									
3.0 Date Built	2025									
3.0 Property Age Band	L									
4.0 Sheltered Sides	2									
5.0 Sunlight/Shade	Average or unknown									
6.0 Thermal Mass Parameter	Precise calculation									
Thermal Mass	179.36 kJ/m <sup>2</sup> K									
7.0 Electricity Tariff	Standard									
Smart electricity meter fitted	Yes									
Smart gas meter fitted	No									
7.0 Measurements										
		Heat Loss Perimeter		Internal Floor Area		Average Storey Height				
		Ground floor: 23.73 m		51.34 m <sup>2</sup>		2.50 m				
8.0 Living Area	21.75 m <sup>2</sup>									
9.0 External Walls										
Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Res	Shelter	Openings	Area Calculation Type
External Wall	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.15	110.00	40.58	22.78	0.00	None	17.80	Enter Gross Area
Sheltered Wall	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.18	110.00	18.75	18.75	0.00	None	0.00	Enter Gross Area
9.1 Party Walls										
Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )	Shelter Res	Shelter			
Party Wall	Filled Cavity with Edge Sealing	Single plasterboard on dabs both sides, lightweight aggregate blocks, cavity or cavity fill	0.00	110.00	12.32	0.00	None			
9.2 Internal Walls										
Description							Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )		
Internal Walls	Plasterboard on timber frame						9.00	85.48		
10.0 External Roofs										
Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Code	Shelter Factor	Calulation Type	Openings
External Roof	External Flat Roof	Plasterboard, insulated flat roof	0.11	9.00	51.34	51.34	None	0.00	Enter Gross Area	0.00

# Summary for Input Data

## 11.1 Party Floors

Description	Storey Index	Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Party Floor	Lowest occupied	Precast concrete planks floor, screed, carpeted	40.00	51.34

## 12.0 Opening Types

Description	Data Source	Type	Glazing	Glazing Gap	Filling Type	G-value	Frame Type	Frame Factor	U Value (W/m <sup>2</sup> K)
Solid Door Glazing	Manufacturer	Solid Door Window	Double Low-E Soft 0.05			0.00 0.63		0.80	1.20 1.20

## 13.0 Openings

Name	Opening Type	Location	Orientation	Area (m <sup>2</sup> )	Pitch
FSD	Solid Door	External Wall	North West	2.12	0
RW	Glazing	External Wall	South East	7.84	0
RSW	Glazing	External Wall	South West	5.52	0
RSGD	Glazing	External Wall	South West	2.32	0

## 14.0 Conservatory

None

## 15.0 Draught Proofing

100

%

## 16.0 Draught Lobby

No

## 17.0 Thermal Bridging

Calculate Bridges

### 17.1 List of Bridges

Bridge Type	Source Type	Length	Psi	Adjusted Reference:	Imported
E2 Other lintels (including other steel lintels)	Independently assessed	7.77	0.02	RCD	No
E3 Sill	Independently assessed	5.76	0.02	RCD	No
E4 Jamb	Independently assessed	22.76	0.01	RCD	No
E7 Party floor between dwellings (in blocks of flats)	Independently assessed	23.73	0.05	RCD	No
E16 Corner (normal)	Independently assessed	7.50	0.05	RCD	No
P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	4.93	0.00	Default	No
E18 Party wall between dwellings	Independently assessed	2.50	0.06	RCD	No
E17 Corner (inverted – internal area greater than external area)	Independently assessed	0.00	-0.10	RCD	No
E25 Staggered party wall between dwellings	Table K1 - Default	2.50	0.24	E25 - Default	No
E14 Flat roof	Independently assessed	23.73	0.04	ROI	No
P4 Party wall - Roof (insulation at ceiling level)	Table K1 - Default	4.93	0.48	0.48	No

Y-value

0.06

W/m<sup>2</sup>K

Description

Bridge

## 19.0 Mechanical Ventilation

### Mechanical Ventilation

Mechanical Ventilation System Present	Yes
Approved Installation	Yes
Mechanical Ventilation data Type	Database
Type	Balanced mechanical ventilation with heat recovery
MV Reference Number	500500
Configuration	2
MVHR Duct Insulated	Uninsulated Ducts
Manufacturer SFP	0.59
Duct Type	Rigid
MVHR Efficiency	89.00
Wet Rooms	2
SFP from Installer Commissioning Certificate	No
MVHR System Location	Inside heated envelope (installed exclusively)
Duct Installation Specification	Level 2

## 19.1 Mechanical extract ventilation - Decentralised

SFP	Fan/Room Type	Count
0.13	In Room Fan	1
	Kitchen	
0.11	In Room Fan Other	3
	Wet Room	
0.00	In Duct Fan Kitchen	0
0.00	In Duct Fan Other	0
	Wet Room	
0.10	Through Wall Fan	0
	Kitchen	

# Summary for Input Data

0.10 Through Wall Fan 0  
Other Wet Room

## 20.0 Fans, Open Fireplaces, Flues

Number of open chimneys	0
Number of open flues	0
Number of chimneys/flues attached to closed fire	0
Number of flues attached to solid fuel boiler	0
Number of flues attached to other heater	0
Number of blocked chimneys	0
Number of intermittent extract fans	0
Number of passive vents	0
Number of flueless gas fires	0

## 21.0 Fixed Cooling System

No

## 22.0 Pressure Testing

Designed AP <sub>50</sub>	3.00	m <sup>3</sup> /(h.m <sup>2</sup> ) @ 50 Pa
Property Tested?	Yes	
Test Method	Blower Door	

## 22.0 Lighting

No Fixed Lighting

No	Name	Efficacy	Power	Capacity	Count
	Low energy Lighting	85.00	5.00	425.00	10

## 24.0 Main Heating 1

Percentage of Heat	100.00	%
Database Ref. No.	0	
Fuel Type	Electricity	
SAP Code	691	
In Winter	100.00	
In Summer	194.18	
Controls SAP Code	2603	
Delayed Start Stat	No	
Burner Control	Modulating	
HETAS approved System	No	
Is MHS Pumped	Pump in heated space	
Heating Pump Age	2013 or later	
Heat Emitter	Radiators	
Underfloor Heating	Yes - Pipes in thin screed	
Flow Temperature	Enter value	
Flow Temperature Value	55.00	

## 25.0 Main Heating 2

Percentage of Heat	0.00	%
Database Ref. No.	100834	
Fuel Type	Electricity	
SAP Code	0	
In Winter	305.55	
In Summer	194.18	
Model Name	Compact P	
Manufacturer	Nilan AS	
Controls	2100	

# Summary for Input Data

Delayed Start Stat	No										
HETAS approved System	No										
Flow Temperature	Enter value										
<b>26.0 Heat Networks</b>	None										
<b>27.0 Secondary Heating</b>	None										
<b>28.0 Water Heating</b>											
Water Heating	Main Heating 2										
SAP Code	914										
Flue Gas Heat Recovery System	No										
Waste Water Heat Recovery Instantaneous System 1	No										
Waste Water Heat Recovery Instantaneous System 2	No										
Waste Water Heat Recovery Storage System	No										
Solar Panel	No										
Water use <= 125 litres/person/day	Yes										
Summer Immersion	No										
Cold Water Source	From mains										
Bath Count	1										
Baths connected to WWHRS	0										
Supplementary Immersion	No										
Immersion Only Heating Hot Water	No										
<b>28.1 Showers</b>											
<b>Description</b>	<b>Shower Type</b>	<b>Flow Rate [l/min]</b>	<b>Rated Power [kW]</b>	<b>Connected</b>	<b>Connected To</b>						
8 lpm	Unknown	8.00		No							
<b>28.3 Waste Water Heat Recovery System</b>											
<b>29.0 Hot Water Cylinder</b>											
Cylinder Stat	Internal Store										
Cylinder In Heated Space	No										
Independent Time Control	No										
Insulation Type	Measured Loss										
Insulation Thickness	0										
Cylinder Volume	180.00	L									
Loss	0.84	kWh/day									
In Airing Cupboard	No										
<b>31.0 Thermal Store</b>											
<b>34.0 Small-scale Hydro</b>											
Electricity Generated	0.00										
Apportioned	0.00	kWh/Year									
Connected to dwelling's electricity meter	Yes										
Electricity Generation	Annual										
Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec

**Recommendations**

**Lower cost measures**

None

**Further measures to achieve even higher standards**

None

# Predicted Energy Assessment


C13-04-01, Horsham Enterprise Park

Dwelling type:  
Date of assessment:  
Produced by:  
Total floor area:  
DRRN:

Flat, End-Terrace  
15/10/2025  
Charlotte Russell  
51.34 m<sup>2</sup>

This document is a Predicted Energy Assessment for properties marketed when they are incomplete. It includes a predicted energy rating which might not represent the final energy rating of the property on completion. Once the property is completed, this rating will be updated and an official Energy Performance Certificate will be created for the property. This will include more detailed information about the energy performance of the completed property.

The energy performance has been assessed using the Government approved SAP 10 methodology and is rated in terms of the energy use per square meter of floor area; the energy efficiency is based on fuel costs and the environmental impact is based on carbon dioxide (CO<sub>2</sub>) emissions.



The energy efficiency rating is a measure of the overall efficiency of a home. The higher the rating the more energy efficient the home is and the lower the fuel bills are likely to be.

The environmental impact rating is a measure of a home's impact on the environment in terms of carbon dioxide (CO<sub>2</sub>) emissions. The higher the rating the less impact it has on the environment.

# Thermal Bridging



Property Reference	C13-04-01		Issued on Date	15/10/2025		
Assessment Reference	Design V1		Prop Type Ref	End-Terrace Flat		
Property	C13-04-01, Horsham Enterprise Park					
SAP Rating	81 B	DER	5.74	TER	15.06	
Environmental	96 A	% DER < TER		61.89		
CO <sub>2</sub> Emissions (t/year)	0.26	DFEE	32.62	TFEE	34.60	
Compliance Check	See BREL	% DFEE < TFEE		5.74		
% DPER < TPER	25.58	DPER	60.04	TPER	80.68	
Assessor Details	Miss Charlotte Russell			Assessor ID	DK97-0001	
Client						
	Junction details	Source Type	Psi (W/mK)	Length (m)	Result	Reference
External wall	E2 Other lintels (including other steel lintels)	Independently assessed	0.022	7.77	0.17	RCD
External wall	E3 Sill	Independently assessed	0.016	5.76	0.09	RCD
External wall	E4 Jamb	Independently assessed	0.011	22.76	0.25	RCD
External wall	E7 Party floor between dwellings (in blocks of flats)	Independently assessed	0.053	23.73	1.26	RCD
External wall	E16 Corner (normal)	Independently assessed	0.051	7.50	0.38	RCD
Party wall	P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	0.000	4.93	0.00	Default
External wall	E18 Party wall between dwellings	Independently assessed	0.057	2.50	0.14	RCD
External wall	E17 Corner (inverted – internal area greater than external area)	Independently assessed	-0.104	0.00	-0.00	RCD
External wall	E25 Staggered party wall between dwellings	Table K1 - Default	0.240	2.50	0.60	E25 - Default
External wall	E14 Flat roof	Independently assessed	0.040	23.73	0.95	ROI
Party wall	P4 Party wall - Roof (insulation at ceiling level)	Table K1 - Default	0.480	4.93	2.37	

Total: 106.11 W/mK:

Y-Value: 0.06 W/m<sup>2</sup>K:

# Summary for Input Data



Property Reference	C13-04-02			Issued on Date	15/10/2025					
Assessment Reference	Design V1		Prop Type Ref	C13-04-02						
Property	C13-04-02, Horsham Enterprise Park									
SAP Rating	81 B	DER	5.67	TER	14.43					
Environmental	96 A	% DER < TER			60.71					
CO <sub>2</sub> Emissions (t/year)	0.26	DFEE	31.49	TFEE	32.14					
Compliance Check	See BREL	% DFEE < TFEE			2.03					
% DPER < TPER	23.23	DPER	59.31	TPER	77.26					
Assessor Details	Miss Charlotte Russell			Assessor ID	DK97-0001					
Client										
<b>SUMMARY FOR INPUT DATA FOR: New Build (As Designed)</b>										
Orientation	Northwest									
Property Tenure	ND									
Transaction Type	6									
Terrain Type	Suburban									
1.0 Property Type	Flat, Mid-Terrace									
Position of Flat	Top-floor flat									
Which Floor	4									
2.0 Number of Storeys	1									
3.0 Date Built	2025									
3.0 Property Age Band	L									
4.0 Sheltered Sides	2									
5.0 Sunlight/Shade	Average or unknown									
6.0 Thermal Mass Parameter	Precise calculation									
Thermal Mass	191.29 kJ/m <sup>2</sup> K									
7.0 Electricity Tariff	Standard									
Smart electricity meter fitted	Yes									
Smart gas meter fitted	No									
7.0 Measurements										
		Heat Loss Perimeter		Internal Floor Area	Average Storey Height					
		Ground floor: 18.12 m		52.15 m <sup>2</sup>	2.50 m					
8.0 Living Area	25.45 m <sup>2</sup>									
9.0 External Walls										
Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Res	Shelter	Openings	Area Calculation Type
External Wall	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.15	110.00	34.56	20.98	0.00	None	13.58	Enter Gross Area
Sheltered Wall	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.18	110.00	10.75	10.75	0.00	None	0.00	Enter Gross Area
9.1 Party Walls										
Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )	Shelter Res	Shelter			
Party Wall	Filled Cavity with Edge Sealing	Single plasterboard on dabs both sides, lightweight aggregate blocks, cavity or cavity fill	0.00	110.00	30.15	0.00	None			
9.2 Internal Walls										
Description							Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )		
Internal Walls	Plasterboard on timber frame						9.00	68.18		
10.0 External Roofs										
Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Code	Shelter Factor	Calculus	Openings Type
External Roof	External Flat Roof	Plasterboard, insulated flat roof	0.11	9.00	52.15	52.15	None	0.00	Enter Gross Area	0.00

# Summary for Input Data

## 11.1 Party Floors

Description	Storey Index	Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Party Floor	Lowest occupied	Precast concrete planks floor, screed, carpeted	40.00	52.15

## 12.0 Opening Types

Description	Data Source	Type	Glazing	Glazing Gap	Filling Type	G-value	Frame Type	Frame Factor	U Value (W/m <sup>2</sup> K)
Solid Door Glazing	Manufacturer	Solid Door Window	Double Low-E Soft 0.05			0.00 0.63		0.80	1.20 1.20

## 13.0 Openings

Name	Opening Type	Location	Orientation	Area (m <sup>2</sup> )	Pitch
FSD	Solid Door	External Wall	North West	2.12	0
RW	Glazing	External Wall	South East	10.22	0
FW	Glazing	External Wall	North West	1.24	0

## 14.0 Conservatory

None

## 15.0 Draught Proofing

100

%

## 16.0 Draught Lobby

No

## 17.0 Thermal Bridging

Calculate Bridges

### 17.1 List of Bridges

Bridge Type	Source Type	Length	Psi	Adjusted Reference:	Imported
E2 Other lintels (including other steel lintels)	Independently assessed	6.33	0.02	RCD	No
E3 Sill	Independently assessed	5.32	0.02	RCD	No
E4 Jamb	Independently assessed	20.84	0.01	RCD	No
E7 Party floor between dwellings (in blocks of flats)	Independently assessed	18.12	0.05	RCD	No
E16 Corner (normal)	Independently assessed	2.50	0.05	RCD	No
P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	12.06	0.00	Default	No
E18 Party wall between dwellings	Independently assessed	10.00	0.06	RCD	No
E17 Corner (inverted – internal area greater than external area)	Independently assessed	2.50	-0.10	RCD	No
E25 Staggered party wall between dwellings	Table K1 - Default	0.00	0.24	E25 - Default	No
E14 Flat roof	Independently assessed	18.12	0.04	ROI	No
P4 Party wall - Roof (insulation at ceiling level)	Table K1 - Default	12.06	0.48	0.48	No

Y-value

0.09

W/m<sup>2</sup>K

Description

Bridge

## 19.0 Mechanical Ventilation

### Mechanical Ventilation

Mechanical Ventilation System Present	Yes
Approved Installation	Yes
Mechanical Ventilation data Type	Database
Type	Balanced mechanical ventilation with heat recovery
MV Reference Number	500500
Configuration	2
MVHR Duct Insulated	Uninsulated Ducts
Manufacturer SFP	0.59
Duct Type	Rigid
MVHR Efficiency	89.00
Wet Rooms	2
SFP from Installer Commissioning Certificate	No
MVHR System Location	Inside heated envelope (installed exclusively)
Duct Installation Specification	Level 2

## 19.1 Mechanical extract ventilation - Decentralised

SFP	Fan/Room Type	Count
0.13	In Room Fan	1
	Kitchen	
0.11	In Room Fan Other	3
	Wet Room	
0.00	In Duct Fan Kitchen	0
0.00	In Duct Fan Other	0
	Wet Room	
0.10	Through Wall Fan	0
	Kitchen	

# Summary for Input Data

0.10 Through Wall Fan 0  
Other Wet Room

## 20.0 Fans, Open Fireplaces, Flues

Number of open chimneys	0
Number of open flues	0
Number of chimneys/flues attached to closed fire	0
Number of flues attached to solid fuel boiler	0
Number of flues attached to other heater	0
Number of blocked chimneys	0
Number of intermittent extract fans	0
Number of passive vents	0
Number of flueless gas fires	0

## 21.0 Fixed Cooling System

No

## 22.0 Pressure Testing

Designed AP <sub>50</sub>	3.00	m <sup>3</sup> /(h.m <sup>2</sup> ) @ 50 Pa
Property Tested?	Yes	
Test Method	Blower Door	

## 22.0 Lighting

No Fixed Lighting

No	Name	Efficacy	Power	Capacity	Count
	Low energy Lighting	85.00	5.00	425.00	10

## 24.0 Main Heating 1

Percentage of Heat	100.00	%
Database Ref. No.	0	
Fuel Type	Electricity	
SAP Code	691	
In Winter	100.00	
In Summer	194.18	
Controls SAP Code	2603	
Delayed Start Stat	No	
Burner Control	Modulating	
HETAS approved System	No	
Is MHS Pumped	Pump in heated space	
Heating Pump Age	2013 or later	
Heat Emitter	Radiators	
Underfloor Heating	Yes - Pipes in thin screed	
Flow Temperature	Enter value	
Flow Temperature Value	55.00	

## 25.0 Main Heating 2

Percentage of Heat	0.00	%
Database Ref. No.	100834	
Fuel Type	Electricity	
SAP Code	0	
In Winter	304.01	
In Summer	194.18	
Model Name	Compact P	
Manufacturer	Nilan AS	
Controls	2100	

# Summary for Input Data

Delayed Start Stat	No										
HETAS approved System	No										
Flow Temperature	Enter value										
<b>26.0 Heat Networks</b>	None										
<b>27.0 Secondary Heating</b>	None										
<b>28.0 Water Heating</b>											
Water Heating	Main Heating 2										
SAP Code	914										
Flue Gas Heat Recovery System	No										
Waste Water Heat Recovery Instantaneous System 1	No										
Waste Water Heat Recovery Instantaneous System 2	No										
Waste Water Heat Recovery Storage System	No										
Solar Panel	No										
Water use <= 125 litres/person/day	Yes										
Summer Immersion	No										
Cold Water Source	From mains										
Bath Count	1										
Baths connected to WWHRS	0										
Supplementary Immersion	No										
Immersion Only Heating Hot Water	No										
<b>28.1 Showers</b>											
<b>Description</b>	<b>Shower Type</b>	<b>Flow Rate [l/min]</b>	<b>Rated Power [kW]</b>	<b>Connected</b>	<b>Connected To</b>						
8 lpm	Unknown	8.00		No							
<b>28.3 Waste Water Heat Recovery System</b>											
<b>29.0 Hot Water Cylinder</b>											
Cylinder Stat	Internal Store										
Cylinder In Heated Space	No										
Independent Time Control	No										
Insulation Type	Measured Loss										
Insulation Thickness	0										
Cylinder Volume	180.00	L									
Loss	0.84	kWh/day									
In Airing Cupboard	No										
<b>31.0 Thermal Store</b>											
<b>34.0 Small-scale Hydro</b>											
Electricity Generated	0.00										
Apportioned	0.00	kWh/Year									
Connected to dwelling's electricity meter	Yes										
Electricity Generation	Annual										
Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec

**Recommendations**

**Lower cost measures**

None

**Further measures to achieve even higher standards**

None

# Predicted Energy Assessment


C13-04-02, Horsham Enterprise Park

Dwelling type:  
Date of assessment:  
Produced by:  
Total floor area:  
DRRN:

Flat, Mid-Terrace  
15/10/2025  
Charlotte Russell  
52.15 m<sup>2</sup>

This document is a Predicted Energy Assessment for properties marketed when they are incomplete. It includes a predicted energy rating which might not represent the final energy rating of the property on completion. Once the property is completed, this rating will be updated and an official Energy Performance Certificate will be created for the property. This will include more detailed information about the energy performance of the completed property.

The energy performance has been assessed using the Government approved SAP 10 methodology and is rated in terms of the energy use per square meter of floor area; the energy efficiency is based on fuel costs and the environmental impact is based on carbon dioxide (CO<sub>2</sub>) emissions.



The energy efficiency rating is a measure of the overall efficiency of a home. The higher the rating the more energy efficient the home is and the lower the fuel bills are likely to be.

The environmental impact rating is a measure of a home's impact on the environment in terms of carbon dioxide (CO<sub>2</sub>) emissions. The higher the rating the less impact it has on the environment.

# Thermal Bridging



Property Reference	C13-04-02		Issued on Date	15/10/2025		
Assessment Reference	Design V1		Prop Type Ref	Mid-Terrace Flat		
Property	C13-04-02, Horsham Enterprise Park					
SAP Rating	81 B	DER	5.67	TER	14.43	
Environmental	96 A	% DER < TER		60.71		
CO <sub>2</sub> Emissions (t/year)	0.26	DFEE	31.49	TFEE	32.14	
Compliance Check	See BREL	% DFEE < TFEE		2.03		
% DPER < TPER	23.23	DPER	59.31	TPER	77.26	
Assessor Details	Miss Charlotte Russell			Assessor ID	DK97-0001	
Client						
	Junction details	Source Type	Psi (W/mK)	Length (m)	Result	Reference
External wall	E2 Other lintels (including other steel lintels)	Independently assessed	0.022	6.33	0.14	RCD
External wall	E3 Sill	Independently assessed	0.016	5.32	0.09	RCD
External wall	E4 Jamb	Independently assessed	0.011	20.84	0.23	RCD
External wall	E7 Party floor between dwellings (in blocks of flats)	Independently assessed	0.053	18.12	0.96	RCD
External wall	E16 Corner (normal)	Independently assessed	0.051	2.50	0.13	RCD
Party wall	P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	0.000	12.06	0.00	Default
External wall	E18 Party wall between dwellings	Independently assessed	0.057	10.00	0.57	RCD
External wall	E17 Corner (inverted – internal area greater than external area)	Independently assessed	-0.104	2.50	-0.26	RCD
External wall	E25 Staggered party wall between dwellings	Table K1 - Default	0.240	0.00	0.00	E25 - Default
External wall	E14 Flat roof	Independently assessed	0.040	18.12	0.72	ROI
Party wall	P4 Party wall - Roof (insulation at ceiling level)	Table K1 - Default	0.480	12.06	5.79	

Total: 107.85 W/mK:  
 Y-Value: 0.09 W/m<sup>2</sup>K:

# Summary for Input Data



Property Reference	C13-04-03	Issued on Date	15/10/2025
Assessment Reference	Design V1	Prop Type Ref	C13-04-03
Property	C13-04-03, Horsham Enterprise Park		
SAP Rating	80 C	DER	5.32
Environmental	96 A	% DER < TER	59.73
CO <sub>2</sub> Emissions (t/year)	0.34	DFEE	32.15
Compliance Check	See BREL	% DFEE < TFEE	35.20
% DPER < TPER	21.13	DPER	55.46
TPER	70.32		

Assessor Details	Miss Charlotte Russell	Assessor ID	DK97-0001
Client			

## SUMMARY FOR INPUT DATA FOR: New Build (As Designed)

Orientation	Northwest
Property Tenure	ND
Transaction Type	6
Terrain Type	Suburban
1.0 Property Type	Flat, End-Terrace
Position of Flat	Top-floor flat
Which Floor	4
2.0 Number of Storeys	1
3.0 Date Built	2025
3.0 Property Age Band	L
4.0 Sheltered Sides	2
5.0 Sunlight/Shade	Average or unknown
6.0 Thermal Mass Parameter	Precise calculation
Thermal Mass	161.35
	kJ/m <sup>2</sup> K
7.0 Electricity Tariff	Standard
Smart electricity meter fitted	Yes
Smart gas meter fitted	No

7.0 Measurements		Heat Loss Perimeter	Internal Floor Area	Average Storey Height
Ground floor:		28.13 m	74.87 m <sup>2</sup>	2.50 m

8.0 Living Area	31.76	m <sup>2</sup>
-----------------	-------	----------------

9.0 External Walls	Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Res	Shelter	Openings	Area Calculation Type
External Wall	External Wall	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.15	110.00	70.33	49.38	0.00	None	20.95	Enter Gross Area

9.1 Party Walls	Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )	Shelter Res	Shelter
Party Wall	Party Wall	Filled Cavity with Edge Sealing	Single plasterboard on dabs both sides, lightweight aggregate blocks, cavity or cavity fill	0.00	110.00	17.83	0.00	None

9.2 Internal Walls	Description	Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Internal Walls	Internal Walls	Plasterboard on timber frame	9.00	113.20

10.0 External Roofs	Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Code	Shelter Factor	Shelter Type	Openings
External Roof	External Roof	External Flat Roof	Plasterboard, insulated flat roof	0.11	9.00	74.87	74.87	None	0.00	Enter Gross Area	0.00

## 11.1 Party Floors

# Summary for Input Data

Description	Storey Index	Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )			
Party Floor	Lowest occupied	Precast concrete planks floor, screed, carpeted	40.00	74.87			
<b>12.0 Opening Types</b>							
Description	Data Source	Type	Glazing	Glazing Gap			
Solid Door Glazing	Manufacturer	Solid Door Window	Double Low-E Soft 0.05	0.00 0.63			
<b>13.0 Openings</b>							
Name	Opening Type	Location	Orientation	Area (m <sup>2</sup> )			
FSD	Solid Door	External Wall	North West	2.12			
RW	Glazing	External Wall	South East	10.99			
LSGD	Glazing	External Wall	North East	2.32			
LSW	Glazing	External Wall	North East	1.60			
FW	Glazing	External Wall	North West	3.92			
<b>14.0 Conservatory</b>							
None							
<b>15.0 Draught Proofing</b>							
100 %							
<b>16.0 Draught Lobby</b>							
No							
<b>17.0 Thermal Bridging</b>							
Calculate Bridges							
<b>17.1 List of Bridges</b>							
Bridge Type	Source Type	Length	Psi	Adjusted Reference:			
E2 Other lintels (including other steel lintels)	Independently assessed	9.13	0.02	RCD			
E3 Sill	Independently assessed	7.12	0.02	RCD			
E4 Jamb	Independently assessed	32.04	0.01	RCD			
E7 Party floor between dwellings (in blocks of flats)	Independently assessed	28.13	0.05	RCD			
E16 Corner (normal)	Independently assessed	5.00	0.05	RCD			
P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	7.13	0.00	Default			
E18 Party wall between dwellings	Independently assessed	5.00	0.06	RCD			
E17 Corner (inverted – internal area greater than external area)	Independently assessed	0.00	-0.10	RCD			
E25 Staggered party wall between dwellings	Table K1 - Default	0.00	0.24	E25 - Default			
E14 Flat roof	Independently assessed	28.13	0.04	ROI			
P4 Party wall - Roof (insulation at ceiling level)	Table K1 - Default	7.13	0.48	No			
Y-value	0.05	W/m <sup>2</sup> K					
Description	Bridge						
<b>19.0 Mechanical Ventilation</b>							
<b>Mechanical Ventilation</b>							
Mechanical Ventilation System Present	Yes						
Approved Installation	Yes						
Mechanical Ventilation data Type	Database						
Type	Balanced mechanical ventilation with heat recovery						
MV Reference Number	500500						
Configuration	2						
MVHR Duct Insulated	Uninsulated Ducts						
Manufacturer SFP	0.59						
Duct Type	Rigid						
MVHR Efficiency	89.00						
Wet Rooms	2						
SFP from Installer Commissioning Certificate	No						
MVHR System Location	Inside heated envelope (installed exclusively)						
Duct Installation Specification	Level 2						
<b>19.1 Mechanical extract ventilation - Decentralised</b>							
SFP	Fan/Room Type	Count					
0.13	In Room Fan	1					
	Kitchen						
0.11	In Room Fan Other	3					
	Wet Room						
0.00	In Duct Fan Kitchen	0					
0.00	In Duct Fan Other	0					
	Wet Room						
0.10	Through Wall Fan	0					
	Kitchen						

# Summary for Input Data

0.10 Through Wall Fan 0  
Other Wet Room

## 20.0 Fans, Open Fireplaces, Flues

Number of open chimneys	0
Number of open flues	0
Number of chimneys/flues attached to closed fire	0
Number of flues attached to solid fuel boiler	0
Number of flues attached to other heater	0
Number of blocked chimneys	0
Number of intermittent extract fans	0
Number of passive vents	0
Number of flueless gas fires	0

## 21.0 Fixed Cooling System

No

## 22.0 Pressure Testing

Designed AP <sub>50</sub>	3.00	m <sup>3</sup> /(h.m <sup>2</sup> ) @ 50 Pa
Property Tested?	Yes	
Test Method	Blower Door	

## 22.0 Lighting

No Fixed Lighting

No	Name	Efficacy	Power	Capacity	Count
	Low energy Lighting	85.00	5.00	425.00	10

## 24.0 Main Heating 1

Percentage of Heat	100.00	%
Database Ref. No.	0	
Fuel Type	Electricity	
SAP Code	691	
In Winter	100.00	
In Summer	194.18	
Controls SAP Code	2603	
Delayed Start Stat	No	
Burner Control	Modulating	
HETAS approved System	No	
Is MHS Pumped	Pump in heated space	
Heating Pump Age	2013 or later	
Heat Emitter	Radiators	
Underfloor Heating	Yes - Pipes in thin screed	
Flow Temperature	Enter value	
Flow Temperature Value	55.00	

## 25.0 Main Heating 2

Percentage of Heat	0.00	%
Database Ref. No.	100834	
Fuel Type	Electricity	
SAP Code	0	
In Winter	307.47	
In Summer	194.18	
Model Name	Compact P	
Manufacturer	Nilan AS	
Controls	2100	

# Summary for Input Data

Delayed Start Stat	No										
HETAS approved System	No										
Flow Temperature	Enter value										
<b>26.0 Heat Networks</b>	None										
<b>27.0 Secondary Heating</b>	None										
<b>28.0 Water Heating</b>											
Water Heating	Main Heating 2										
SAP Code	914										
Flue Gas Heat Recovery System	No										
Waste Water Heat Recovery Instantaneous System 1	No										
Waste Water Heat Recovery Instantaneous System 2	No										
Waste Water Heat Recovery Storage System	No										
Solar Panel	No										
Water use <= 125 litres/person/day	Yes										
Summer Immersion	No										
Cold Water Source	From mains										
Bath Count	1										
Baths connected to WWHRS	0										
Supplementary Immersion	No										
Immersion Only Heating Hot Water	No										
<b>28.1 Showers</b>											
<b>Description</b>	<b>Shower Type</b>	<b>Flow Rate [l/min]</b>	<b>Rated Power [kW]</b>	<b>Connected</b>	<b>Connected To</b>						
8 lpm	Unknown	8.00		No							
<b>28.3 Waste Water Heat Recovery System</b>											
<b>29.0 Hot Water Cylinder</b>											
Cylinder Stat	Internal Store										
Cylinder In Heated Space	No										
Independent Time Control	No										
Insulation Type	Measured Loss										
Insulation Thickness	0										
Cylinder Volume	180.00	L									
Loss	0.84	kWh/day									
In Airing Cupboard	No										
<b>31.0 Thermal Store</b>											
<b>34.0 Small-scale Hydro</b>											
Electricity Generated	0.00										
Apportioned	0.00	kWh/Year									
Connected to dwelling's electricity meter	Yes										
Electricity Generation	Annual										
Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec

**Recommendations**

**Lower cost measures**

None

**Further measures to achieve even higher standards**

None

# Predicted Energy Assessment


C13-04-03, Horsham Enterprise Park

Dwelling type:  
Date of assessment:  
Produced by:  
Total floor area:  
DRRN:

Flat, End-Terrace  
15/10/2025  
Charlotte Russell  
74.87 m<sup>2</sup>

This document is a Predicted Energy Assessment for properties marketed when they are incomplete. It includes a predicted energy rating which might not represent the final energy rating of the property on completion. Once the property is completed, this rating will be updated and an official Energy Performance Certificate will be created for the property. This will include more detailed information about the energy performance of the completed property.

The energy performance has been assessed using the Government approved SAP 10 methodology and is rated in terms of the energy use per square meter of floor area; the energy efficiency is based on fuel costs and the environmental impact is based on carbon dioxide (CO<sub>2</sub>) emissions.



The energy efficiency rating is a measure of the overall efficiency of a home. The higher the rating the more energy efficient the home is and the lower the fuel bills are likely to be.

The environmental impact rating is a measure of a home's impact on the environment in terms of carbon dioxide (CO<sub>2</sub>) emissions. The higher the rating the less impact it has on the environment.

# Thermal Bridging

Property Reference	C13-04-03		Issued on Date	15/10/2025		
Assessment Reference	Design V1		Prop Type Ref	End-Terrace Flat		
Property	C13-04-03, Horsham Enterprise Park					
SAP Rating	80 C	DER	5.32	TER	13.21	
Environmental	96 A	% DER < TER			59.73	
CO <sub>2</sub> Emissions (t/year)	0.34	DFEE	32.15	TFEE	35.20	
Compliance Check	See BREL	% DFEE < TFEE			8.66	
% DPER < TPER	21.13	DPER	55.46	TPER	70.32	
Assessor Details	Miss Charlotte Russell			Assessor ID	DK97-0001	
Client						
	Junction details	Source Type	Psi (W/mK)	Length (m)	Result	Reference
External wall	E2 Other lintels (including other steel lintels)	Independently assessed	0.022	9.13	0.20	RCD
External wall	E3 Sill	Independently assessed	0.016	7.12	0.11	RCD
External wall	E4 Jamb	Independently assessed	0.011	32.04	0.35	RCD
External wall	E7 Party floor between dwellings (in blocks of flats)	Independently assessed	0.053	28.13	1.49	RCD
External wall	E16 Corner (normal)	Independently assessed	0.051	5.00	0.26	RCD
Party wall	P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	0.000	7.13	0.00	Default
External wall	E18 Party wall between dwellings	Independently assessed	0.057	5.00	0.29	RCD
External wall	E17 Corner (inverted – internal area greater than external area)	Independently assessed	-0.104	0.00	-0.00	RCD
External wall	E25 Staggered party wall between dwellings	Table K1 - Default	0.240	0.00	0.00	E25 - Default
External wall	E14 Flat roof	Independently assessed	0.040	28.13	1.13	ROI
Party wall	P4 Party wall - Roof (insulation at ceiling level)	Table K1 - Default	0.480	7.13	3.42	

Total: 128.81 W/mK:

Y-Value: 0.05 W/m<sup>2</sup>K:

# Summary for Input Data



Property Reference	C14-00-02	Issued on Date	15/10/2025
Assessment Reference	Design V1	Prop Type Ref	C14-00-02
Property	C14-00-02, Horsham Enterprise Park		
SAP Rating	75 C	DER	6.42
Environmental	95 A	% DER < TER	61.51
CO <sub>2</sub> Emissions (t/year)	0.42	DFEE	43.46
Compliance Check	See BREL	% DFEE < TFEE	17.85
% DPER < TPER	24.86	DPER	66.71
TPER	88.78		

Assessor Details	Miss Charlotte Russell	Assessor ID	DK97-0001
Client			

## SUMMARY FOR INPUT DATA FOR: New Build (As Designed)

Orientation	Northwest	
Property Tenure	ND	
Transaction Type	6	
Terrain Type	Suburban	
1.0 Property Type	Flat, End-Terrace	
Position of Flat	Ground-floor flat	
Which Floor	0	
2.0 Number of Storeys	1	
3.0 Date Built	2025	
3.0 Property Age Band	L	
4.0 Sheltered Sides	2	
5.0 Sunlight/Shade	Average or unknown	
6.0 Thermal Mass Parameter	Precise calculation	
Thermal Mass	352.41	kJ/m <sup>2</sup> K
7.0 Electricity Tariff	Standard	
Smart electricity meter fitted	Yes	
Smart gas meter fitted	No	

7.0 Measurements		Heat Loss Perimeter	Internal Floor Area	Average Storey Height
Ground floor:		30.83 m	78.74 m <sup>2</sup>	3.90 m

8.0 Living Area	25.00	m <sup>2</sup>
-----------------	-------	----------------

9.0 External Walls		Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Res	Shelter	Openings	Area Calculation Type
External Wall	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.15	110.00	72.19	62.76	0.00	None	9.43	Enter Gross Area
Sheltered	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.18	110.00	48.05	45.93	0.90	Stairwell Access Corridor 4	2.12	Enter Gross Area

9.1 Party Walls		Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )	Shelter Res	Shelter
Party Wall	Filled Cavity with Edge Sealing	Single plasterboard on dabs both sides, lightweight aggregate blocks, cavity or cavity fill	0.00	110.00	24.14	0.00	None

9.2 Internal Walls		Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Internal Walls		Plasterboard on timber frame	9.00	191.12

10.1 Party Ceilings		Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Ceiling		Precast concrete plank floor (screed laid on rubber), carpeted	30.00	78.74

## 11.0 Heat Loss Floors

# Summary for Input Data

Description	Type	Storey Index	Construction	U-Value (W/m <sup>2</sup> K)	Shelter Code	Shelter Factor	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Ground Floor	Ground Floor - Solid	Lowest occupied	Suspended concrete floor, carpeted	0.10	None	0.00	75.00	78.74
<b>12.0 Opening Types</b>								
Description	Data Source	Type	Glazing	Glazing Gap	Filling Type	G-value	Frame Type	Frame Factor
Solid Door Glazing	Manufacturer	Solid Door Window	Double Low-E Soft 0.05			0.00 0.63		0.80 1.20
<b>13.0 Openings</b>								
Name	Opening Type	Location	Orientation	Area (m <sup>2</sup> )	Pitch			
FSD	Solid Door	Sheltered	North West	2.12	0			
RSW	Glazing	External Wall	South West	4.46	0			
RSGD	Glazing	External Wall	South West	4.97	0			
<b>14.0 Conservatory</b>								
None								
<b>15.0 Draught Proofing</b>								
100 %								
<b>16.0 Draught Lobby</b>								
No								
<b>17.0 Thermal Bridging</b>								
Calculate Bridges								
<b>17.1 List of Bridges</b>								
Bridge Type	Source Type	Length	Psi	Adjusted Reference:	Imported			
E2 Other lintels (including other steel lintels)	Independently assessed	5.54	0.02	0.02 RCD	No			
E3 Sill	Independently assessed	2.72	0.02	0.02 RCD	No			
E4 Jamb	Independently assessed	16.26	0.01	0.01 RCD	No			
E5 Ground floor (normal)	Independently assessed	30.83	0.08	0.08 RCD	No			
E7 Party floor between dwellings (in blocks of flats)	Independently assessed	30.83	0.05	0.05 RCD	No			
E16 Corner (normal)	Independently assessed	11.70	0.05	0.05 RCD	No			
P1 Party wall - Ground floor	Table K1 - Default	6.19	0.32	0.32 Default	No			
P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	6.19	0.00	0.00 Default	No			
E18 Party wall between dwellings	Independently assessed	7.80	0.06	0.06 RCD	No			
E17 Corner (inverted – internal area greater than external area)	Independently assessed	3.90	-0.10	-0.10 RCD	No			
Y-value	0.03			W/m <sup>2</sup> K				
Description	Bridge							
<b>19.0 Mechanical Ventilation</b>								
<b>Mechanical Ventilation</b>								
Mechanical Ventilation System Present	Yes							
Approved Installation	Yes							
Mechanical Ventilation data Type	Database							
Type	Balanced mechanical ventilation with heat recovery							
MV Reference Number	500500							
Configuration	2							
MVHR Duct Insulated	Uninsulated Ducts							
Manufacturer SFP	0.59							
Duct Type	Rigid							
MVHR Efficiency	89.00							
Wet Rooms	2							
SFP from Installer Commissioning Certificate	No							
MVHR System Location	Inside heated envelope (installed exclusively)							
Duct Installation Specification	Level 2							
<b>19.1 Mechanical extract ventilation - Decentralised</b>								
SFP	Fan/Room Type	Count						
0.13	In Room Fan	1						
	Kitchen							
0.11	In Room Fan Other	3						
	Wet Room							
0.00	In Duct Fan Kitchen	0						
0.00	In Duct Fan Other	0						
	Wet Room							
0.10	Through Wall Fan	0						
	Kitchen							
0.10	Through Wall Fan	0						
	Other Wet Room							
<b>20.0 Fans, Open Fireplaces, Flues</b>								

# Summary for Input Data

Number of open chimneys	0										
Number of open flues	0										
Number of chimneys/flues attached to closed fire	0										
Number of flues attached to solid fuel boiler	0										
Number of flues attached to other heater	0										
Number of blocked chimneys	0										
Number of intermittent extract fans	0										
Number of passive vents	0										
Number of flueless gas fires	0										
<b>21.0 Fixed Cooling System</b>											
	No										
<b>22.0 Pressure Testing</b>											
Designed AP <sub>50</sub>	3.00										
Property Tested?	Yes										
Test Method	Blower Door										
<b>22.0 Lighting</b>											
No Fixed Lighting	No										
	<table border="1"> <thead> <tr> <th>Name</th> <th>Efficacy</th> <th>Power</th> <th>Capacity</th> <th>Count</th> </tr> </thead> <tbody> <tr> <td>Low energy Lighting</td> <td>85.00</td> <td>5.00</td> <td>425.00</td> <td>10</td> </tr> </tbody> </table>	Name	Efficacy	Power	Capacity	Count	Low energy Lighting	85.00	5.00	425.00	10
Name	Efficacy	Power	Capacity	Count							
Low energy Lighting	85.00	5.00	425.00	10							
<b>24.0 Main Heating 1</b>											
Percentage of Heat	SAP table										
Database Ref. No.	100.00										
Fuel Type	0										
SAP Code	Electricity										
In Winter	691										
In Summer	100.00										
Controls SAP Code	194.18										
Delayed Start Stat	2603										
Burner Control	No										
HETAS approved System	Modulating										
Is MHS Pumped	No										
Heating Pump Age	Pump in heated space										
Heat Emitter	2013 or later										
Underfloor Heating	Radiators										
Flow Temperature	Yes - Pipes in thin screed										
Flow Temperature Value	Enter value										
	55.00										
<b>25.0 Main Heating 2</b>											
Percentage of Heat	Database										
Database Ref. No.	0.00										
Fuel Type	100834										
SAP Code	Electricity										
In Winter	0										
In Summer	400.06										
Model Name	194.18										
Manufacturer	Compact P										
Controls	Nilan AS										
Delayed Start Stat	2100										
HETAS approved System	No										
	No										

# Summary for Input Data

Flow Temperature	Enter value										
<b>26.0 Heat Networks</b>	None										
<b>27.0 Secondary Heating</b>	None										
<b>28.0 Water Heating</b>											
Water Heating	Main Heating 2										
SAP Code	914										
Flue Gas Heat Recovery System	No										
Waste Water Heat Recovery Instantaneous System 1	No										
Waste Water Heat Recovery Instantaneous System 2	No										
Waste Water Heat Recovery Storage System	No										
Solar Panel	No										
Water use <= 125 litres/person/day	Yes										
Summer Immersion	No										
Cold Water Source	From mains										
Bath Count	1										
Baths connected to WWHRS	0										
Supplementary Immersion	No										
Immersion Only Heating Hot Water	No										
<b>28.1 Showers</b>											
<b>Description</b>	<b>Shower Type</b>	<b>Flow Rate</b> [l/min]	<b>Rated Power</b> [kW]	<b>Connected</b>	<b>Connected To</b>						
8 lpm	Unknown	8.00		No							
<b>28.3 Waste Water Heat Recovery System</b>											
<b>29.0 Hot Water Cylinder</b>		Internal Store									
Cylinder Stat	No										
Cylinder In Heated Space	No										
Independent Time Control	No										
Insulation Type	Measured Loss										
Insulation Thickness	0										
Cylinder Volume	180.00	L									
Loss	0.84	kWh/day									
In Airing Cupboard	No										
<b>31.0 Thermal Store</b>		None									
<b>34.0 Small-scale Hydro</b>		None									
Electricity Generated	0.00										
Apportioned	0.00	kWh/Year									
Connected to dwelling's electricity meter	Yes										
Electricity Generation	Annual										
Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
<b>Recommendations</b>											
Lower cost measures											
None											
Further measures to achieve even higher standards											
None											

# Predicted Energy Assessment


C14-00-02, Horsham Enterprise Park

Dwelling type:  
Date of assessment:  
Produced by:  
Total floor area:  
DRRN:

Flat, End-Terrace  
15/10/2025  
Charlotte Russell  
78.74 m<sup>2</sup>

This document is a Predicted Energy Assessment for properties marketed when they are incomplete. It includes a predicted energy rating which might not represent the final energy rating of the property on completion. Once the property is completed, this rating will be updated and an official Energy Performance Certificate will be created for the property. This will include more detailed information about the energy performance of the completed property.

The energy performance has been assessed using the Government approved SAP 10 methodology and is rated in terms of the energy use per square meter of floor area; the energy efficiency is based on fuel costs and the environmental impact is based on carbon dioxide (CO<sub>2</sub>) emissions.



The energy efficiency rating is a measure of the overall efficiency of a home. The higher the rating the more energy efficient the home is and the lower the fuel bills are likely to be.

The environmental impact rating is a measure of a home's impact on the environment in terms of carbon dioxide (CO<sub>2</sub>) emissions. The higher the rating the less impact it has on the environment.

# Thermal Bridging

Property Reference	C14-00-02		Issued on Date	15/10/2025
Assessment Reference	Design V1		Prop Type Ref	End-Terrace Flat
Property	C14-00-02, Horsham Enterprise Park			
SAP Rating	75 C	DER	6.42	TER
Environmental	95 A	% DER < TER		61.51
CO <sub>2</sub> Emissions (t/year)	0.42	DFEE	43.46	TFEE
Compliance Check	See BREL	% DFEE < TFEE		17.85
% DPER < TPER	24.86	DPER	66.71	TPER

Assessor Details	Miss Charlotte Russell	Assessor ID	DK97-0001
Client			

	Junction details	Source Type	Psi (W/mK)	Length (m)	Result	Reference
External wall	E2 Other lintels (including other steel lintels)	Independently assessed	0.022	5.54	0.12	RCD
External wall	E3 Sill	Independently assessed	0.016	2.72	0.04	RCD
External wall	E4 Jamb	Independently assessed	0.011	16.26	0.18	RCD
External wall	E5 Ground floor (normal)	Independently assessed	0.076	30.83	2.34	RCD
External wall	E7 Party floor between dwellings (in blocks of flats)	Independently assessed	0.053	30.83	1.63	RCD
External wall	E16 Corner (normal)	Independently assessed	0.051	11.70	0.60	RCD
Party wall	P1 Party wall - Ground floor	Table K1 - Default	0.320	6.19	1.98	Default
Party wall	P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	0.000	6.19	0.00	Default
External wall	E18 Party wall between dwellings	Independently assessed	0.057	7.80	0.44	RCD
External wall	E17 Corner (inverted – internal area greater than external area)	Independently assessed	-0.104	3.90	-0.41	RCD

Total: 121.96 W/mK:

Y-Value: 0.03 W/m<sup>2</sup>K:

# Summary for Input Data



Property Reference	C14-00-04	Issued on Date	15/10/2025
Assessment Reference	Design V1	Prop Type Ref	C14-00-04
Property	C14-00-04, Horsham Enterprise Park		
SAP Rating	74 C	DER	7.56
Environmental	94 A	% DER < TER	58.89
CO <sub>2</sub> Emissions (t/year)	0.39	DFEE	49.83
Compliance Check	See BREL	% DFEE < TFEE	11.33
% DPER < TPER	19.95	DPER	78.45
TPER	98.00		

Assessor Details	Miss Charlotte Russell	Assessor ID	DK97-0001
Client			

## SUMMARY FOR INPUT DATA FOR: New Build (As Designed)

Orientation	Southeast	
Property Tenure	ND	
Transaction Type	6	
Terrain Type	Suburban	
1.0 Property Type	Flat, Mid-Terrace	
Position of Flat	Ground-floor flat	
Which Floor	0	
2.0 Number of Storeys	1	
3.0 Date Built	2025	
3.0 Property Age Band	L	
4.0 Sheltered Sides	2	
5.0 Sunlight/Shade	Average or unknown	
6.0 Thermal Mass Parameter	Precise calculation	
Thermal Mass	369.33	kJ/m <sup>2</sup> K
7.0 Electricity Tariff	Standard	
Smart electricity meter fitted	Yes	
Smart gas meter fitted	No	

7.0 Measurements	Heat Loss Perimeter	Internal Floor Area	Average Storey Height
	Ground floor: 20.37 m	62.15 m <sup>2</sup>	3.90 m

8.0 Living Area	21.76	m <sup>2</sup>
-----------------	-------	----------------

9.0 External Walls	Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Res	Shelter	Openings	Area Calculation Type
External Wall	External Wall	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.15	110.00	37.13	26.22	0.00	None	10.91	Enter Gross Area
Sheltered	Sheltered	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.18	110.00	42.32	40.20	0.90	Stairwell Access Corridor 4	2.12	Enter Gross Area

9.1 Party Walls	Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )	Shelter Res	Shelter
Party Wall	Party Wall	Filled Cavity with Edge Sealing	Single plasterboard on dabs both sides, lightweight aggregate blocks, cavity or cavity fill	0.00	110.00	47.70	0.00	None

9.2 Internal Walls	Description	Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Internal Walls	Internal Walls	Plasterboard on timber frame	9.00	154.32

10.1 Party Ceilings	Description	Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Ceiling	Ceiling	Precast concrete plank floor (screed laid on rubber), carpeted	30.00	62.15

## 11.0 Heat Loss Floors

# Summary for Input Data

Description	Type	Storey Index	Construction	U-Value (W/m <sup>2</sup> K)	Shelter Code	Shelter Factor	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Ground Floor	Ground Floor - Solid	Lowest occupied	Suspended concrete floor, carpeted	0.10	None	0.00	75.00	62.15

**12.0 Opening Types**

Description	Data Source	Type	Glazing	Glazing Gap	Filling Type	G-value	Frame Type	Frame Factor	U Value (W/m <sup>2</sup> K)
Solid Door Glazing	Manufacturer	Solid Door Window	Double Low-E Soft 0.05			0.00 0.63		0.80	1.20 1.20

**13.0 Openings**

Name	Opening Type	Location	Orientation	Area (m <sup>2</sup> )	Pitch
FSD	Solid Door	Sheltered	South East	2.12	0
RW	Glazing	External Wall	North West	5.94	0
RGD	Glazing	External Wall	North West	4.97	0

**14.0 Conservatory**

None
------

**15.0 Draught Proofing**

100	%
-----	---

**16.0 Draught Lobby**

No
----

**17.0 Thermal Bridging**

Calculate Bridges
-------------------

**17.1 List of Bridges**

Bridge Type	Source Type	Length	Psi	Adjusted Reference:	Imported	
E2 Other lintels (including other steel lintels)	Independently assessed	6.44	0.02	RCD	No	
E3 Sill	Independently assessed	3.62	0.02	RCD	No	
E4 Jamb	Independently assessed	16.26	0.01	RCD	No	
E5 Ground floor (normal)	Independently assessed	20.37	0.08	RCD	No	
E7 Party floor between dwellings (in blocks of flats)	Independently assessed	20.37	0.05	RCD	No	
E16 Corner (normal)	Independently assessed	3.90	0.05	RCD	No	
P1 Party wall - Ground floor	Table K1 - Default	12.23	0.32	Default	No	
P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	12.23	0.00	Default	No	
E18 Party wall between dwellings	Independently assessed	11.70	0.06	RCD	No	
E25 Staggered party wall between dwellings	Independently assessed	3.90	0.05	RCD	No	
E17 Corner (inverted – internal area greater than external area)	Independently assessed	3.90	-0.10	-0.10	RCD	No

Y-value

0.05	W/m <sup>2</sup> K
------	--------------------

Description

Bridge
--------

**19.0 Mechanical Ventilation**

**Mechanical Ventilation**

Mechanical Ventilation System Present	Yes
Approved Installation	Yes
Mechanical Ventilation data Type	Database
Type	Balanced mechanical ventilation with heat recovery
MV Reference Number	500500
Configuration	2
MVHR Duct Insulated	Uninsulated Ducts
Manufacturer SFP	0.59
Duct Type	Rigid
MVHR Efficiency	89.00
Wet Rooms	2
SFP from Installer Commissioning Certificate	No
MVHR System Location	Inside heated envelope (installed exclusively)
Duct Installation Specification	Level 2

**19.1 Mechanical extract ventilation - Decentralised**

SFP	Fan/Room Type	Count
0.13	In Room Fan	1
	Kitchen	
0.11	In Room Fan Other	3
	Wet Room	
0.00	In Duct Fan Kitchen	0
0.00	In Duct Fan Other	0
	Wet Room	
0.10	Through Wall Fan	0
	Kitchen	
0.10	Through Wall Fan	0
	Other Wet Room	

**20.0 Fans, Open Fireplaces, Flues**

# Summary for Input Data

Number of open chimneys	0										
Number of open flues	0										
Number of chimneys/flues attached to closed fire	0										
Number of flues attached to solid fuel boiler	0										
Number of flues attached to other heater	0										
Number of blocked chimneys	0										
Number of intermittent extract fans	0										
Number of passive vents	0										
Number of flueless gas fires	0										
<b>21.0 Fixed Cooling System</b>											
	No										
<b>22.0 Pressure Testing</b>											
Designed AP <sub>50</sub>	3.00										
Property Tested?	Yes										
Test Method	Blower Door										
<b>22.0 Lighting</b>											
No Fixed Lighting	No										
	<table border="1"> <thead> <tr> <th>Name</th> <th>Efficacy</th> <th>Power</th> <th>Capacity</th> <th>Count</th> </tr> </thead> <tbody> <tr> <td>Low energy Lighting</td> <td>85.00</td> <td>5.00</td> <td>425.00</td> <td>10</td> </tr> </tbody> </table>	Name	Efficacy	Power	Capacity	Count	Low energy Lighting	85.00	5.00	425.00	10
Name	Efficacy	Power	Capacity	Count							
Low energy Lighting	85.00	5.00	425.00	10							
<b>24.0 Main Heating 1</b>											
Percentage of Heat	SAP table										
Database Ref. No.	100.00										
Fuel Type	0										
SAP Code	Electricity										
In Winter	691										
In Summer	100.00										
Controls SAP Code	194.18										
Delayed Start Stat	2603										
Burner Control	No										
HETAS approved System	Modulating										
Is MHS Pumped	No										
Heating Pump Age	Pump in heated space										
Heat Emitter	2013 or later										
Underfloor Heating	Radiators										
Flow Temperature	Yes - Pipes in thin screed										
Flow Temperature Value	Enter value										
	55.00										
<b>25.0 Main Heating 2</b>											
Percentage of Heat	Database										
Database Ref. No.	0.00										
Fuel Type	100834										
SAP Code	Electricity										
In Winter	0										
In Summer	346.12										
Model Name	194.18										
Manufacturer	Compact P										
Controls	Nilan AS										
Delayed Start Stat	2100										
HETAS approved System	No										
	No										

# Summary for Input Data

Flow Temperature	Enter value										
<b>26.0 Heat Networks</b>	None										
<b>27.0 Secondary Heating</b>	None										
<b>28.0 Water Heating</b>											
Water Heating	Main Heating 2										
SAP Code	914										
Flue Gas Heat Recovery System	No										
Waste Water Heat Recovery Instantaneous System 1	No										
Waste Water Heat Recovery Instantaneous System 2	No										
Waste Water Heat Recovery Storage System	No										
Solar Panel	No										
Water use <= 125 litres/person/day	Yes										
Summer Immersion	No										
Cold Water Source	From mains										
Bath Count	1										
Baths connected to WWHRS	0										
Supplementary Immersion	No										
Immersion Only Heating Hot Water	No										
<b>28.1 Showers</b>											
<b>Description</b>	<b>Shower Type</b>	<b>Flow Rate</b> [l/min]	<b>Rated Power</b> [kW]	<b>Connected</b>	<b>Connected To</b>						
8 lpm	Unknown	8.00		No							
<b>28.3 Waste Water Heat Recovery System</b>											
<b>29.0 Hot Water Cylinder</b>		Internal Store									
Cylinder Stat	No										
Cylinder In Heated Space	No										
Independent Time Control	No										
Insulation Type	Measured Loss										
Insulation Thickness	0										
Cylinder Volume	180.00	L									
Loss	0.84	kWh/day									
In Airing Cupboard	No										
<b>31.0 Thermal Store</b>		None									
<b>34.0 Small-scale Hydro</b>		None									
Electricity Generated	0.00										
Apportioned	0.00	kWh/Year									
Connected to dwelling's electricity meter	Yes										
Electricity Generation	Annual										
Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
<b>Recommendations</b>											
<b>Lower cost measures</b>											
None											
<b>Further measures to achieve even higher standards</b>											
None											

# Predicted Energy Assessment




C14-00-04, Horsham Enterprise Park

Dwelling type:  
Date of assessment:  
Produced by:  
Total floor area:  
DRRN:

Flat, Mid-Terrace  
15/10/2025  
Charlotte Russell  
62.15 m<sup>2</sup>

This document is a Predicted Energy Assessment for properties marketed when they are incomplete. It includes a predicted energy rating which might not represent the final energy rating of the property on completion. Once the property is completed, this rating will be updated and an official Energy Performance Certificate will be created for the property. This will include more detailed information about the energy performance of the completed property.

The energy performance has been assessed using the Government approved SAP 10 methodology and is rated in terms of the energy use per square meter of floor area; the energy efficiency is based on fuel costs and the environmental impact is based on carbon dioxide (CO<sub>2</sub>) emissions.



The energy efficiency rating is a measure of the overall efficiency of a home. The higher the rating the more energy efficient the home is and the lower the fuel bills are likely to be.

The environmental impact rating is a measure of a home's impact on the environment in terms of carbon dioxide (CO<sub>2</sub>) emissions. The higher the rating the less impact it has on the environment.

# Thermal Bridging

Property Reference	C14-00-04		Issued on Date	15/10/2025
Assessment Reference	Design V1		Prop Type Ref	Mid-Terrace Flat
Property	C14-00-04, Horsham Enterprise Park			
SAP Rating	74 C	DER	7.56	TER
Environmental	94 A	% DER < TER		58.89
CO <sub>2</sub> Emissions (t/year)	0.39	DFEE	49.83	TFEE
Compliance Check	See BREL	% DFEE < TFEE		11.33
% DPER < TPER	19.95	DPER	78.45	TPER

Assessor Details	Miss Charlotte Russell	Assessor ID	DK97-0001
Client			

	Junction details	Source Type	Psi (W/mK)	Length (m)	Result	Reference
External wall	E2 Other lintels (including other steel lintels)	Independently assessed	0.022	6.44	0.14	RCD
External wall	E3 Sill	Independently assessed	0.016	3.62	0.06	RCD
External wall	E4 Jamb	Independently assessed	0.011	16.26	0.18	RCD
External wall	E5 Ground floor (normal)	Independently assessed	0.076	20.37	1.55	RCD
External wall	E7 Party floor between dwellings (in blocks of flats)	Independently assessed	0.053	20.37	1.08	RCD
External wall	E16 Corner (normal)	Independently assessed	0.051	3.90	0.20	RCD
Party wall	P1 Party wall - Ground floor	Table K1 - Default	0.320	12.23	3.91	Default
Party wall	P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	0.000	12.23	0.00	Default
External wall	E18 Party wall between dwellings	Independently assessed	0.057	11.70	0.67	RCD
External wall	E25 Staggered party wall between dwellings	Independently assessed	0.046	3.90	0.18	RCD
External wall	E17 Corner (inverted – internal area greater than external area)	Independently assessed	-0.104	3.90	-0.41	RCD

Total: 114.92 W/mK:  
 Y-Value: 0.05 W/m<sup>2</sup>K:

# Summary for Input Data



Property Reference	C14-00-06	Issued on Date	15/10/2025
Assessment Reference	Design V1	Prop Type Ref	C14-00-06
Property	C14-00-06, Horsham Enterprise Park		
SAP Rating	73 C	DER	7.08
Environmental	94 A	% DER < TER	61.46
CO <sub>2</sub> Emissions (t/year)	0.45	DFEE	47.90
Compliance Check	See BREL	% DFEE < TFEE	20.56
% DPER < TPER	24.96	DPER	73.37
TPER	97.78		

Assessor Details	Miss Charlotte Russell	Assessor ID	DK97-0001
Client			

## SUMMARY FOR INPUT DATA FOR: New Build (As Designed)

Orientation	Northwest	
Property Tenure	ND	
Transaction Type	6	
Terrain Type	Suburban	
1.0 Property Type	Flat, Detached	
Position of Flat	Ground-floor flat	
Which Floor	0	
2.0 Number of Storeys	1	
3.0 Date Built	2025	
3.0 Property Age Band	L	
4.0 Sheltered Sides	2	
5.0 Sunlight/Shade	Average or unknown	
6.0 Thermal Mass Parameter	Precise calculation	
Thermal Mass	372.90	kJ/m <sup>2</sup> K
7.0 Electricity Tariff	Standard	
Smart electricity meter fitted	Yes	
Smart gas meter fitted	No	

7.0 Measurements		Heat Loss Perimeter	Internal Floor Area	Average Storey Height
Ground floor:		41.22 m	76.87 m <sup>2</sup>	3.90 m

8.0 Living Area	28.36	m <sup>2</sup>
-----------------	-------	----------------

9.0 External Walls		Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Res	Shelter	Openings	Area Calculation Type
External Wall	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.15	110.00	99.45	87.07	0.00	None	12.38	Enter Gross Area
Sheltered	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.18	110.00	61.31	59.19	0.90	Stairwell Access Corridor 4	2.12	Enter Gross Area

9.2 Internal Walls		Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Internal Walls		Plasterboard on timber frame	9.00	158.86

10.1 Party Ceilings		Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Ceiling		Precast concrete plank floor (screed laid on rubber), carpeted	30.00	76.87

11.0 Heat Loss Floors		Type	Storey Index	Construction	U-Value (W/m <sup>2</sup> K)	Shelter Code	Shelter Factor	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Ground Floor		Ground Floor - Solid	Lowest occupied	Suspended concrete floor, carpeted	0.10	None	0.00	75.00	76.87

12.0 Opening Types		Data Source	Type	Glazing	Glazing Gap	Filling Type	G-value	Frame Type	Frame Factor	U Value (W/m <sup>2</sup> K)
--------------------	--	-------------	------	---------	-------------	--------------	---------	------------	--------------	------------------------------

# Summary for Input Data

Solid Door Glazing	Manufacturer	Solid Door Window	Double Low-E Soft 0.05	0.00 0.63	0.80	1.20 1.20
<b>13.0 Openings</b>						
Name FSD RW RGD	Opening Type Solid Door Glazing Glazing	Location Sheltered External Wall External Wall	Orientation North West South East South East	Area (m <sup>2</sup> ) 2.12 7.41 4.97	Pitch 0 0 0	
<b>14.0 Conservatory</b>						
None						
<b>15.0 Draught Proofing</b>						
100 %						
<b>16.0 Draught Lobby</b>						
No						
<b>17.0 Thermal Bridging</b>						
Calculate Bridges						
<b>17.1 List of Bridges</b>						
Bridge Type E2 Other lintels (including other steel lintels) E3 Sill E4 Jamb E5 Ground floor (normal) E7 Party floor between dwellings (in blocks of flats) E16 Corner (normal) P1 Party wall - Ground floor P3 Party wall - Intermediate floor between dwellings (in blocks of flats) E18 Party wall between dwellings E25 Staggered party wall between dwellings	Source Type Independently assessed Independently assessed Independently assessed Independently assessed Independently assessed Independently assessed Table K1 - Default Table K1 - Default	Length 7.34 4.52 16.26 41.22 41.22 3.90 0.00 0.00	Psi 0.02 0.02 0.01 0.08 0.05 0.05 0.32 0.00	Adjusted Reference: RCD RCD RCD RCD RCD RCD Default Default	Imported No No No No No No No No	
Y-value	0.03 W/m <sup>2</sup> K					
Description	Bridge					
<b>19.0 Mechanical Ventilation</b>						
<b>Mechanical Ventilation</b>						
Mechanical Ventilation System Present	Yes					
Approved Installation	Yes					
Mechanical Ventilation data Type	Database					
Type	Balanced mechanical ventilation with heat recovery					
MV Reference Number	500500					
Configuration	2					
MVHR Duct Insulated	Uninsulated Ducts					
Manufacturer SFP	0.59					
Duct Type	Rigid					
MVHR Efficiency	89.00					
Wet Rooms	2					
SFP from Installer Commissioning Certificate	No					
MVHR System Location	Inside heated envelope (installed exclusively)					
Duct Installation Specification	Level 2					
<b>19.1 Mechanical extract ventilation - Decentralised</b>						
SFP 0.13 0.11 0.00 0.00 0.10 0.10	Fan/Room Type In Room Fan Kitchen In Room Fan Other Wet Room In Duct Fan Kitchen In Duct Fan Other Wet Room Through Wall Fan Kitchen Through Wall Fan Other Wet Room	Count 1  3  0 0  0  0				
<b>20.0 Fans, Open Fireplaces, Flues</b>						
Number of open chimneys	0					
Number of open flues	0					
Number of chimneys/flues attached to closed fire	0					
Number of flues attached to solid fuel boiler	0					

# Summary for Input Data

Number of flues attached to other heater	0											
Number of blocked chimneys	0											
Number of intermittent extract fans	0											
Number of passive vents	0											
Number of flueless gas fires	0											
<b>21.0 Fixed Cooling System</b>												
	No											
<b>22.0 Pressure Testing</b>												
Designed AP <sub>50</sub>	3.00											
Property Tested?	Yes											
Test Method	Blower Door											
<b>22.0 Lighting</b>												
No Fixed Lighting	<table border="1"> <tr> <td>No</td> </tr> <tr> <td>Name</td> <td>Efficacy</td> <td>Power</td> <td>Capacity</td> <td>Count</td> </tr> <tr> <td>Low energy Lighting</td> <td>85.00</td> <td>5.00</td> <td>425.00</td> <td>10</td> </tr> </table>	No	Name	Efficacy	Power	Capacity	Count	Low energy Lighting	85.00	5.00	425.00	10
No												
Name	Efficacy	Power	Capacity	Count								
Low energy Lighting	85.00	5.00	425.00	10								
<b>24.0 Main Heating 1</b>												
Percentage of Heat	100.00											
Database Ref. No.	0											
Fuel Type	Electricity											
SAP Code	691											
In Winter	100.00											
In Summer	194.18											
Controls SAP Code	2603											
Delayed Start Stat	No											
Burner Control	Modulating											
HETAS approved System	No											
Is MHS Pumped	Pump in heated space											
Heating Pump Age	2013 or later											
Heat Emitter	Radiators											
Underfloor Heating	Yes - Pipes in thin screed											
Flow Temperature	Enter value											
Flow Temperature Value	55.00											
<b>25.0 Main Heating 2</b>												
Percentage of Heat	0.00											
Database Ref. No.	100834											
Fuel Type	Electricity											
SAP Code	0											
In Winter	390.02											
In Summer	194.18											
Model Name	Compact P											
Manufacturer	Nilan AS											
Controls	2100											
Delayed Start Stat	No											
HETAS approved System	No											
Flow Temperature	Enter value											
<b>26.0 Heat Networks</b>												
	None											
<b>27.0 Secondary Heating</b>												
	None											

# Summary for Input Data

## 28.0 Water Heating

Water Heating	Main Heating 2
SAP Code	914
Flue Gas Heat Recovery System	No
Waste Water Heat Recovery Instantaneous System 1	No
Waste Water Heat Recovery Instantaneous System 2	No
Waste Water Heat Recovery Storage System	No
Solar Panel	No
Water use <= 125 litres/person/day	Yes
Summer Immersion	No
Cold Water Source	From mains
Bath Count	1
Baths connected to WWHRS	0
Supplementary Immersion	No
Immersion Only Heating Hot Water	No

## 28.1 Showers

Description	Shower Type	Flow Rate [l/min]	Rated Power [kW]	Connected	Connected To
8 lpm	Unknown	8.00		No	

## 28.3 Waste Water Heat Recovery System

29.0 Hot Water Cylinder	Internal Store
Cylinder Stat	No
Cylinder In Heated Space	No
Independent Time Control	No
Insulation Type	Measured Loss
Insulation Thickness	0
Cylinder Volume	180.00
Loss	0.84
In Airing Cupboard	No

## 31.0 Thermal Store

None
------

## 34.0 Small-scale Hydro

Electricity Generated	None
Apportioned	0.00
Connected to dwelling's electricity meter	0.00
Electricity Generation	Yes

Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----

## Recommendations

### Lower cost measures

None

### Further measures to achieve even higher standards

None

# Predicted Energy Assessment


C14-00-06, Horsham Enterprise Park

Dwelling type:  
Date of assessment:  
Produced by:  
Total floor area:  
DRRN:

Flat, Detached  
15/10/2025  
Charlotte Russell  
76.87 m<sup>2</sup>

This document is a Predicted Energy Assessment for properties marketed when they are incomplete. It includes a predicted energy rating which might not represent the final energy rating of the property on completion. Once the property is completed, this rating will be updated and an official Energy Performance Certificate will be created for the property. This will include more detailed information about the energy performance of the completed property.

The energy performance has been assessed using the Government approved SAP 10 methodology and is rated in terms of the energy use per square meter of floor area; the energy efficiency is based on fuel costs and the environmental impact is based on carbon dioxide (CO<sub>2</sub>) emissions.



The energy efficiency rating is a measure of the overall efficiency of a home. The higher the rating the more energy efficient the home is and the lower the fuel bills are likely to be.

The environmental impact rating is a measure of a home's impact on the environment in terms of carbon dioxide (CO<sub>2</sub>) emissions. The higher the rating the less impact it has on the environment.

# Thermal Bridging

Property Reference	C14-00-06		Issued on Date	15/10/2025
Assessment Reference	Design V1		Prop Type Ref	Detached Flat
Property	C14-00-06, Horsham Enterprise Park			
SAP Rating	73 C	DER	7.08	TER
Environmental	94 A	% DER < TER		61.46
CO <sub>2</sub> Emissions (t/year)	0.45	DFEE	47.90	TFEE
Compliance Check	See BREL	% DFEE < TFEE		20.56
% DPER < TPER	24.96	DPER	73.37	TPER

Assessor Details	Miss Charlotte Russell	Assessor ID	DK97-0001
Client			

	Junction details	Source Type	Psi (W/mK)	Length (m)	Result	Reference
External wall	E2 Other lintels (including other steel lintels)	Independently assessed	0.022	7.34	0.16	RCD
External wall	E3 Sill	Independently assessed	0.016	4.52	0.07	RCD
External wall	E4 Jamb	Independently assessed	0.011	16.26	0.18	RCD
External wall	E5 Ground floor (normal)	Independently assessed	0.076	41.22	3.13	RCD
External wall	E7 Party floor between dwellings (in blocks of flats)	Independently assessed	0.053	41.22	2.18	RCD
External wall	E16 Corner (normal)	Independently assessed	0.051	3.90	0.20	RCD
Party wall	P1 Party wall - Ground floor	Table K1 - Default	0.320	0.00	0.00	Default
Party wall	P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	0.000	0.00	0.00	Default
External wall	E18 Party wall between dwellings	Independently assessed	0.057	15.60	0.89	RCD
External wall	E25 Staggered party wall between dwellings	Independently assessed	0.046	0.00	0.00	RCD

Total: 130.06 W/mK:

Y-Value: 0.03 W/m<sup>2</sup>K:

# Summary for Input Data



Property Reference	C14-00-09	Issued on Date	15/10/2025
Assessment Reference	Design V1	Prop Type Ref	C14-00-09
Property	C14-00-09, Horsham Enterprise Park		
SAP Rating	71 C	DER	7.88
Environmental	94 A	% DER < TER	59.11
CO <sub>2</sub> Emissions (t/year)	0.47	DFEE	53.22
Compliance Check	See BREL	% DFEE < TFEE	15.70
% DPER < TPER	20.52	DPER	81.57
TPER	19.27	TFEE	63.13
Assessor Details	Miss Charlotte Russell	Assessor ID	DK97-0001
Client			

## SUMMARY FOR INPUT DATA FOR: New Build (As Designed)

Orientation	Southeast	
Property Tenure	ND	
Transaction Type	6	
Terrain Type	Suburban	
1.0 Property Type	Flat, End-Terrace	
Position of Flat	Ground-floor flat	
Which Floor	0	
2.0 Number of Storeys	1	
3.0 Date Built	2025	
3.0 Property Age Band	L	
4.0 Sheltered Sides	2	
5.0 Sunlight/Shade	Average or unknown	
6.0 Thermal Mass Parameter	Precise calculation	
Thermal Mass	359.74	kJ/m <sup>2</sup> K
7.0 Electricity Tariff	Standard	
Smart electricity meter fitted	Yes	
Smart gas meter fitted	No	

7.0 Measurements	Heat Loss Perimeter	Internal Floor Area	Average Storey Height
	Ground floor: 30.90 m	71.14 m <sup>2</sup>	3.90 m

8.0 Living Area	22.86	m <sup>2</sup>
-----------------	-------	----------------

9.0 External Walls	Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Res	Shelter	Openings	Area Calculation Type
External Wall	External Wall	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.15	110.00	67.55	53.67	0.00	None	13.88	Enter Gross Area
Sheltered	Sheltered	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.18	110.00	52.96	50.84	0.90	Stairwell Access Corridor 4	2.12	Enter Gross Area

9.1 Party Walls	Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )	Shelter Res	Shelter
Party Wall	Party Wall	Filled Cavity with Edge Sealing	Single plasterboard on dabs both sides, lightweight aggregate blocks, cavity or cavity fill	0.00	110.00	21.37	0.00	None

9.2 Internal Walls	Description	Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Internal Walls	Internal Walls	Plasterboard on timber frame	9.00	158.86

10.1 Party Ceilings	Description	Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Ceiling	Ceiling	Precast concrete plank floor (screed laid on rubber), carpeted	30.00	71.14

## 11.0 Heat Loss Floors

# Summary for Input Data

Description	Type	Storey Index	Construction	U-Value (W/m <sup>2</sup> K)	Shelter Code	Shelter Factor	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Ground Floor	Ground Floor - Solid	Lowest occupied	Suspended concrete floor, carpeted	0.10	None	0.00	75.00	71.14

**12.0 Opening Types**

Description	Data Source	Type	Glazing	Glazing Gap	Filling Type	G-value	Frame Type	Frame Factor	U Value (W/m <sup>2</sup> K)
Solid Door Glazing	Manufacturer	Solid Door Window	Double Low-E Soft 0.05			0.00 0.63		0.80	1.20 1.20

**13.0 Openings**

Name	Opening Type	Location	Orientation	Area (m <sup>2</sup> )	Pitch
FSD	Solid Door	Sheltered	South East	2.12	0
RW	Glazing	External Wall	North West	5.94	0
RGD	Glazing	External Wall	North West	4.97	0
RSW	Glazing	External Wall	North East	2.97	0

**14.0 Conservatory**

None	
------	--

**15.0 Draught Proofing**

100	%
-----	---

**16.0 Draught Lobby**

No
----

**17.0 Thermal Bridging**

Calculate Bridges
-------------------

**17.1 List of Bridges**

Bridge Type	Source Type	Length	Psi	Adjusted Reference:	Imported
E2 Other lintels (including other steel lintels)	Independently assessed	8.25	0.02	0.02 RCD	No
E3 Sill	Independently assessed	5.43	0.02	0.02 RCD	No
E4 Jamb	Independently assessed	19.54	0.01	0.01 RCD	No
E5 Ground floor (normal)	Independently assessed	30.90	0.08	0.08 RCD	No
E7 Party floor between dwellings (in blocks of flats)	Independently assessed	30.90	0.05	0.05 RCD	No
E16 Corner (normal)	Independently assessed	15.60	0.05	0.05 RCD	No
P1 Party wall - Ground floor	Table K1 - Default	5.48	0.32	0.32 Default	No
P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	5.48	0.00	0.00 Default	No
E18 Party wall between dwellings	Independently assessed	3.90	0.06	0.06 RCD	No
E25 Staggered party wall between dwellings	Independently assessed	3.90	0.05	0.05 RCD	No
E17 Corner (inverted – internal area greater than external area)	Independently assessed	3.90	-0.10	-0.10 RCD	No

Y-value

0.04	W/m <sup>2</sup> K
------	--------------------

Description

Bridge
--------

**19.0 Mechanical Ventilation**

**Mechanical Ventilation**

Mechanical Ventilation System Present	Yes
Approved Installation	Yes
Mechanical Ventilation data Type	Database
Type	Balanced mechanical ventilation with heat recovery
MV Reference Number	500500
Configuration	2
MVHR Duct Insulated	Uninsulated Ducts
Manufacturer SFP	0.59
Duct Type	Rigid
MVHR Efficiency	89.00
Wet Rooms	2
SFP from Installer Commissioning Certificate	No
MVHR System Location	Inside heated envelope (installed exclusively)
Duct Installation Specification	Level 2

**19.1 Mechanical extract ventilation - Decentralised**

SFP	Fan/Room Type	Count
0.13	In Room Fan	1
	Kitchen	
0.11	In Room Fan Other	3
	Wet Room	
0.00	In Duct Fan Kitchen	0
0.00	In Duct Fan Other	0
	Wet Room	
0.10	Through Wall Fan	0
	Kitchen	
0.10	Through Wall Fan	0
	Other Wet Room	

# Summary for Input Data

## 20.0 Fans, Open Fireplaces, Flues

Number of open chimneys	0
Number of open flues	0
Number of chimneys/flues attached to closed fire	0
Number of flues attached to solid fuel boiler	0
Number of flues attached to other heater	0
Number of blocked chimneys	0
Number of intermittent extract fans	0
Number of passive vents	0
Number of flueless gas fires	0

## 21.0 Fixed Cooling System

No
----

## 22.0 Pressure Testing

Designed AP <sub>50</sub>	3.00	m <sup>3</sup> /(h.m <sup>2</sup> ) @ 50 Pa
Property Tested?	Yes	
Test Method	Blower Door	

## 22.0 Lighting

No Fixed Lighting	No	Name	Efficacy	Power	Capacity	Count
		Low energy Lighting	85.00	5.00	425.00	10

## 24.0 Main Heating 1

Percentage of Heat	100.00	%
Database Ref. No.	0	
Fuel Type	Electricity	
SAP Code	691	
In Winter	100.00	
In Summer	194.18	
Controls SAP Code	2603	
Delayed Start Stat	No	
Burner Control	Modulating	
HETAS approved System	No	
Is MHS Pumped	Pump in heated space	
Heating Pump Age	2013 or later	
Heat Emitter	Radiators	
Underfloor Heating	Yes - Pipes in thin screed	
Flow Temperature	Enter value	
Flow Temperature Value	55.00	

## 25.0 Main Heating 2

Percentage of Heat	0.00	%
Database Ref. No.	100834	
Fuel Type	Electricity	
SAP Code	0	
In Winter	371.19	
In Summer	194.18	
Model Name	Compact P	
Manufacturer	Nilan AS	
Controls	2100	
Delayed Start Stat	No	
HETAS approved System	No	

# Summary for Input Data

Flow Temperature	Enter value										
<b>26.0 Heat Networks</b>	None										
<b>27.0 Secondary Heating</b>	None										
<b>28.0 Water Heating</b>											
Water Heating	Main Heating 2										
SAP Code	914										
Flue Gas Heat Recovery System	No										
Waste Water Heat Recovery Instantaneous System 1	No										
Waste Water Heat Recovery Instantaneous System 2	No										
Waste Water Heat Recovery Storage System	No										
Solar Panel	No										
Water use <= 125 litres/person/day	Yes										
Summer Immersion	No										
Cold Water Source	From mains										
Bath Count	1										
Baths connected to WWHRS	0										
Supplementary Immersion	No										
Immersion Only Heating Hot Water	No										
<b>28.1 Showers</b>											
<b>Description</b>	<b>Shower Type</b>	<b>Flow Rate</b> [l/min]	<b>Rated Power</b> [kW]	<b>Connected</b>	<b>Connected To</b>						
8 lpm	Unknown	8.00		No							
<b>28.3 Waste Water Heat Recovery System</b>											
<b>29.0 Hot Water Cylinder</b>		Internal Store									
Cylinder Stat	No										
Cylinder In Heated Space	No										
Independent Time Control	No										
Insulation Type	Measured Loss										
Insulation Thickness	0										
Cylinder Volume	180.00	L									
Loss	0.84	kWh/day									
In Airing Cupboard	No										
<b>31.0 Thermal Store</b>		None									
<b>34.0 Small-scale Hydro</b>		None									
Electricity Generated	0.00										
Apportioned	0.00	kWh/Year									
Connected to dwelling's electricity meter	Yes										
Electricity Generation	Annual										
Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
<b>Recommendations</b>											
Lower cost measures											
None											
Further measures to achieve even higher standards											
None											

# Predicted Energy Assessment


C14-00-09, Horsham Enterprise Park

Dwelling type:  
Date of assessment:  
Produced by:  
Total floor area:  
DRRN:

Flat, End-Terrace  
15/10/2025  
Charlotte Russell  
71.14 m<sup>2</sup>

This document is a Predicted Energy Assessment for properties marketed when they are incomplete. It includes a predicted energy rating which might not represent the final energy rating of the property on completion. Once the property is completed, this rating will be updated and an official Energy Performance Certificate will be created for the property. This will include more detailed information about the energy performance of the completed property.

The energy performance has been assessed using the Government approved SAP 10 methodology and is rated in terms of the energy use per square meter of floor area; the energy efficiency is based on fuel costs and the environmental impact is based on carbon dioxide (CO<sub>2</sub>) emissions.



The energy efficiency rating is a measure of the overall efficiency of a home. The higher the rating the more energy efficient the home is and the lower the fuel bills are likely to be.

The environmental impact rating is a measure of a home's impact on the environment in terms of carbon dioxide (CO<sub>2</sub>) emissions. The higher the rating the less impact it has on the environment.

# Thermal Bridging

Property Reference	C14-00-09		Issued on Date	15/10/2025
Assessment Reference	Design V1		Prop Type Ref	End-Terrace Flat
Property	C14-00-09, Horsham Enterprise Park			
SAP Rating	71 C	DER	7.88	TER
Environmental	94 A	% DER < TER		59.11
CO <sub>2</sub> Emissions (t/year)	0.47	DFEE	53.22	TFEE
Compliance Check	See BREL	% DFEE < TFEE		15.70
% DPER < TPER	20.52	DPER	81.57	TPER

Assessor Details	Miss Charlotte Russell	Assessor ID	DK97-0001
Client			

	Junction details	Source Type	Psi (W/mK)	Length (m)	Result	Reference
External wall	E2 Other lintels (including other steel lintels)	Independently assessed	0.022	8.25	0.18	RCD
External wall	E3 Sill	Independently assessed	0.016	5.43	0.09	RCD
External wall	E4 Jamb	Independently assessed	0.011	19.54	0.21	RCD
External wall	E5 Ground floor (normal)	Independently assessed	0.076	30.90	2.35	RCD
External wall	E7 Party floor between dwellings (in blocks of flats)	Independently assessed	0.053	30.90	1.64	RCD
External wall	E16 Corner (normal)	Independently assessed	0.051	15.60	0.80	RCD
Party wall	P1 Party wall - Ground floor	Table K1 - Default	0.320	5.48	1.75	Default
Party wall	P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	0.000	5.48	0.00	Default
External wall	E18 Party wall between dwellings	Independently assessed	0.057	3.90	0.22	RCD
External wall	E25 Staggered party wall between dwellings	Independently assessed	0.046	3.90	0.18	RCD
External wall	E17 Corner (inverted – internal area greater than external area)	Independently assessed	-0.104	3.90	-0.41	RCD

Total: 133.28 W/mK:  
 Y-Value: 0.04 W/m<sup>2</sup>K:

# Summary for Input Data



Property Reference	C14-00-11	Issued on Date	15/10/2025
Assessment Reference	Design V1	Prop Type Ref	C14-00-11
Property	C14-00-11, Horsham Enterprise Park		
SAP Rating	74 C	DER	6.38
Environmental	95 A	% DER < TER	61.10
CO <sub>2</sub> Emissions (t/year)	0.47	DFEE	44.11
Compliance Check	See BREL	% DFEE < TFEE	54.21
% DPER < TPER	24.00	DPER	66.18
TPER	87.08		

Assessor Details	Miss Charlotte Russell	Assessor ID	DK97-0001
Client			

## SUMMARY FOR INPUT DATA FOR: New Build (As Designed)

Orientation	Northeast	
Property Tenure	ND	
Transaction Type	6	
Terrain Type	Suburban	
1.0 Property Type	Flat, Semi-Detached	
Position of Flat	Ground-floor flat	
Which Floor	0	
2.0 Number of Storeys	1	
3.0 Date Built	2025	
3.0 Property Age Band	L	
4.0 Sheltered Sides	2	
5.0 Sunlight/Shade	Average or unknown	
6.0 Thermal Mass Parameter	Precise calculation	
Thermal Mass	353.85	kJ/m <sup>2</sup> K
7.0 Electricity Tariff	Standard	
Smart electricity meter fitted	Yes	
Smart gas meter fitted	No	

7.0 Measurements	Heat Loss Perimeter	Internal Floor Area	Average Storey Height
	Ground floor: 35.90 m	88.75 m <sup>2</sup>	3.90 m

8.0 Living Area	33.43	m <sup>2</sup>
-----------------	-------	----------------

9.0 External Walls	Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Res	Shelter	Openings	Area Calculation Type
External Wall	External Wall	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.15	110.00	82.25	68.37	0.00	None	13.88	Enter Gross Area
Sheltered	Sheltered	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.18	110.00	57.76	55.64	0.90	Stairwell Access Corridor 4	2.12	Enter Gross Area

9.1 Party Walls	Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )	Shelter Res	Shelter
Party Wall	Party Wall	Filled Cavity with Edge Sealing	Single plasterboard on dabs both sides, lightweight aggregate blocks, cavity or cavity fill	0.00	110.00	26.13	0.00	None

9.2 Internal Walls	Description	Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Internal Walls	Internal Walls	Plasterboard on timber frame	9.00	224.42

10.1 Party Ceilings	Description	Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Ceiling	Ceiling	Precast concrete plank floor (screed laid on rubber), carpeted	30.00	88.75

## 11.0 Heat Loss Floors

# Summary for Input Data

Description	Type	Storey Index	Construction	U-Value (W/m <sup>2</sup> K)	Shelter Code	Shelter Factor	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Ground Floor	Ground Floor - Solid	Lowest occupied	Suspended concrete floor, carpeted	0.10	None	0.00	75.00	88.75
<b>12.0 Opening Types</b>								
Description	Data Source	Type	Glazing	Glazing Gap	Filling Type	G-value	Frame Type	Frame Factor
Solid Door Glazing	Manufacturer	Solid Door Window	Double Low-E Soft 0.05			0.00 0.63		1.20 1.20 0.80
<b>13.0 Openings</b>								
Name	Opening Type	Location	Orientation	Area (m <sup>2</sup> )	Pitch			
FSD	Solid Door	Sheltered	North East	2.12	0			
RW	Glazing	External Wall	South West	8.91	0			
RGD	Glazing	External Wall	South West	4.97	0			
<b>14.0 Conservatory</b>								
None								
<b>15.0 Draught Proofing</b>								
100 %								
<b>16.0 Draught Lobby</b>								
No								
<b>17.0 Thermal Bridging</b>								
Calculate Bridges								
<b>17.1 List of Bridges</b>								
Bridge Type	Source Type	Length	Psi	Adjusted Reference:	Imported			
E2 Other lintels (including other steel lintels)	Independently assessed	8.25	0.02	0.02 RCD	No			
E3 Sill	Independently assessed	5.43	0.02	0.02 RCD	No			
E4 Jamb	Independently assessed	19.54	0.01	0.01 RCD	No			
E5 Ground floor (normal)	Independently assessed	35.90	0.08	0.08 RCD	No			
E7 Party floor between dwellings (in blocks of flats)	Independently assessed	35.90	0.05	0.05 RCD	No			
E16 Corner (normal)	Independently assessed	19.50	0.05	0.05 RCD	No			
P1 Party wall - Ground floor	Table K1 - Default	6.70	0.32	0.32 Default	No			
P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	6.70	0.00	0.00 Default	No			
E18 Party wall between dwellings	Independently assessed	3.90	0.06	0.06 RCD	No			
E17 Corner (inverted – internal area greater than external area)	Independently assessed	7.80	-0.10	-0.10 RCD	No			
Y-value	0.03			W/m <sup>2</sup> K				
Description	Bridge							
<b>19.0 Mechanical Ventilation</b>								
<b>Mechanical Ventilation</b>								
Mechanical Ventilation System Present	Yes							
Approved Installation	Yes							
Mechanical Ventilation data Type	Database							
Type	Balanced mechanical ventilation with heat recovery							
MV Reference Number	500500							
Configuration	2							
MVHR Duct Insulated	Uninsulated Ducts							
Manufacturer SFP	0.59							
Duct Type	Rigid							
MVHR Efficiency	89.00							
Wet Rooms	2							
SFP from Installer Commissioning Certificate	No							
MVHR System Location	Inside heated envelope (installed exclusively)							
Duct Installation Specification	Level 2							
<b>19.1 Mechanical extract ventilation - Decentralised</b>								
SFP	Fan/Room Type	Count						
0.13	In Room Fan	1						
	Kitchen							
0.11	In Room Fan Other	3						
	Wet Room							
0.00	In Duct Fan Kitchen	0						
0.00	In Duct Fan Other	0						
	Wet Room							
0.10	Through Wall Fan	0						
	Kitchen							
0.10	Through Wall Fan	0						
	Other Wet Room							
<b>20.0 Fans, Open Fireplaces, Flues</b>								

# Summary for Input Data

Number of open chimneys	0										
Number of open flues	0										
Number of chimneys/flues attached to closed fire	0										
Number of flues attached to solid fuel boiler	0										
Number of flues attached to other heater	0										
Number of blocked chimneys	0										
Number of intermittent extract fans	0										
Number of passive vents	0										
Number of flueless gas fires	0										
<b>21.0 Fixed Cooling System</b>											
	No										
<b>22.0 Pressure Testing</b>											
Designed AP <sub>50</sub>	3.00										
Property Tested?	Yes										
Test Method	Blower Door										
<b>22.0 Lighting</b>											
No Fixed Lighting	No										
	<table border="1"> <thead> <tr> <th>Name</th> <th>Efficacy</th> <th>Power</th> <th>Capacity</th> <th>Count</th> </tr> </thead> <tbody> <tr> <td>Low energy Lighting</td> <td>85.00</td> <td>5.00</td> <td>425.00</td> <td>10</td> </tr> </tbody> </table>	Name	Efficacy	Power	Capacity	Count	Low energy Lighting	85.00	5.00	425.00	10
Name	Efficacy	Power	Capacity	Count							
Low energy Lighting	85.00	5.00	425.00	10							
<b>24.0 Main Heating 1</b>											
Percentage of Heat	SAP table										
Database Ref. No.	100.00										
Fuel Type	0										
SAP Code	Electricity										
In Winter	691										
In Summer	100.00										
Controls SAP Code	194.18										
Delayed Start Stat	2603										
Burner Control	No										
HETAS approved System	Modulating										
Is MHS Pumped	No										
Heating Pump Age	Pump in heated space										
Heat Emitter	2013 or later										
Underfloor Heating	Radiators										
Flow Temperature	Yes - Pipes in thin screed										
Flow Temperature Value	Enter value										
	55.00										
<b>25.0 Main Heating 2</b>											
Percentage of Heat	Database										
Database Ref. No.	0.00										
Fuel Type	100834										
SAP Code	Electricity										
In Winter	0										
In Summer	439.68										
Model Name	194.18										
Manufacturer	Compact P										
Controls	Nilan AS										
Delayed Start Stat	2100										
HETAS approved System	No										
	No										

# Summary for Input Data

Flow Temperature	Enter value										
<b>26.0 Heat Networks</b>	None										
<b>27.0 Secondary Heating</b>	None										
<b>28.0 Water Heating</b>											
Water Heating	Main Heating 2										
SAP Code	914										
Flue Gas Heat Recovery System	No										
Waste Water Heat Recovery Instantaneous System 1	No										
Waste Water Heat Recovery Instantaneous System 2	No										
Waste Water Heat Recovery Storage System	No										
Solar Panel	No										
Water use <= 125 litres/person/day	Yes										
Summer Immersion	No										
Cold Water Source	From mains										
Bath Count	1										
Baths connected to WWHRS	0										
Supplementary Immersion	No										
Immersion Only Heating Hot Water	No										
<b>28.1 Showers</b>											
<b>Description</b>	<b>Shower Type</b>	<b>Flow Rate</b> [l/min]	<b>Rated Power</b> [kW]	<b>Connected</b>	<b>Connected To</b>						
8 lpm	Unknown	8.00		No							
<b>28.3 Waste Water Heat Recovery System</b>											
<b>29.0 Hot Water Cylinder</b>		Internal Store									
Cylinder Stat	No										
Cylinder In Heated Space	No										
Independent Time Control	No										
Insulation Type	Measured Loss										
Insulation Thickness	0										
Cylinder Volume	180.00	L									
Loss	0.84	kWh/day									
In Airing Cupboard	No										
<b>31.0 Thermal Store</b>		None									
<b>34.0 Small-scale Hydro</b>		None									
Electricity Generated	0.00										
Apportioned	0.00	kWh/Year									
Connected to dwelling's electricity meter	Yes										
Electricity Generation	Annual										
Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
<b>Recommendations</b>											
Lower cost measures											
None											
Further measures to achieve even higher standards											
None											

# Predicted Energy Assessment


C14-00-11, Horsham Enterprise Park

Dwelling type:  
Date of assessment:  
Produced by:  
Total floor area:  
DRRN:

Flat, Semi-Detached  
15/10/2025  
Charlotte Russell  
88.75 m<sup>2</sup>

This document is a Predicted Energy Assessment for properties marketed when they are incomplete. It includes a predicted energy rating which might not represent the final energy rating of the property on completion. Once the property is completed, this rating will be updated and an official Energy Performance Certificate will be created for the property. This will include more detailed information about the energy performance of the completed property.

The energy performance has been assessed using the Government approved SAP 10 methodology and is rated in terms of the energy use per square meter of floor area; the energy efficiency is based on fuel costs and the environmental impact is based on carbon dioxide (CO<sub>2</sub>) emissions.



The energy efficiency rating is a measure of the overall efficiency of a home. The higher the rating the more energy efficient the home is and the lower the fuel bills are likely to be.

The environmental impact rating is a measure of a home's impact on the environment in terms of carbon dioxide (CO<sub>2</sub>) emissions. The higher the rating the less impact it has on the environment.

# Thermal Bridging



Property Reference	C14-00-11	Issued on Date	15/10/2025
Assessment Reference	Design V1	Prop Type Ref	Semi-Detached Flat
Property	C14-00-11, Horsham Enterprise Park		
SAP Rating	74 C	DER	6.38
Environmental	95 A	% DER < TER	61.10
CO <sub>2</sub> Emissions (t/year)	0.47	DFEE	44.11
Compliance Check	See BREL	% DFEE < TFEE	18.63
% DPER < TPER	24.00	DPER	66.18
TPER	87.08		

Assessor Details	Miss Charlotte Russell	Assessor ID	DK97-0001
Client			

	Junction details	Source Type	Psi (W/mK)	Length (m)	Result	Reference
External wall	E2 Other lintels (including other steel lintels)	Independently assessed	0.022	8.25	0.18	RCD
External wall	E3 Sill	Independently assessed	0.016	5.43	0.09	RCD
External wall	E4 Jamb	Independently assessed	0.011	19.54	0.21	RCD
External wall	E5 Ground floor (normal)	Independently assessed	0.076	35.90	2.73	RCD
External wall	E7 Party floor between dwellings (in blocks of flats)	Independently assessed	0.053	35.90	1.90	RCD
External wall	E16 Corner (normal)	Independently assessed	0.051	19.50	0.99	RCD
Party wall	P1 Party wall - Ground floor	Table K1 - Default	0.320	6.70	2.14	Default
Party wall	P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	0.000	6.70	0.00	Default
External wall	E18 Party wall between dwellings	Independently assessed	0.057	3.90	0.22	RCD
External wall	E17 Corner (inverted – internal area greater than external area)	Independently assessed	-0.104	7.80	-0.81	RCD

Total: 149.62 W/mK:

Y-Value: 0.03 W/m<sup>2</sup>K:

# Summary for Input Data



Property Reference	C14-01-02	Issued on Date	15/10/2025
Assessment Reference	Design V1	Prop Type Ref	C14-01-02
Property	C14-01-02, Horsham Enterprise Park		
SAP Rating	85 B	DER	4.57
Environmental	97 A	% DER < TER	13.51
CO <sub>2</sub> Emissions (t/year)	0.21	DFEE	24.91
Compliance Check	See BREL	% DFEE < TFEE	66.17
% DPER < TPER	33.05	DPER	29.38
TPER	48.22	TPER	15.21
TPER	72.02		

Assessor Details	Miss Charlotte Russell	Assessor ID	DK97-0001
Client			

## SUMMARY FOR INPUT DATA FOR: New Build (As Designed)

Orientation	Northwest
Property Tenure	ND
Transaction Type	6
Terrain Type	Suburban
1.0 Property Type	Flat, End-Terrace
Position of Flat	Mid-floor flat
Which Floor	1
2.0 Number of Storeys	1
3.0 Date Built	2025
3.0 Property Age Band	L
4.0 Sheltered Sides	2
5.0 Sunlight/Shade	Average or unknown
6.0 Thermal Mass Parameter	Precise calculation
Thermal Mass	305.97
	kJ/m <sup>2</sup> K
7.0 Electricity Tariff	Standard
Smart electricity meter fitted	Yes
Smart gas meter fitted	No

7.0 Measurements	Heat Loss Perimeter	Internal Floor Area	Average Storey Height
	Ground floor: 16.48 m	53.05 m <sup>2</sup>	3.20 m

8.0 Living Area	27.27	m <sup>2</sup>
-----------------	-------	----------------

9.0 External Walls	Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Res	Shelter	Openings	Area Calculation Type
External Wall	External Wall	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.15	110.00	47.23	40.77	0.00	None	6.46	Enter Gross Area
Sheltered	Sheltered	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.18	110.00	5.50	3.38	0.90	Stairwell Access Corridor 4	2.12	Enter Gross Area

9.1 Party Walls	Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )	Shelter Res	Shelter
Party Wall	Party Wall	Filled Cavity with Edge Sealing	Single plasterboard on dabs both sides, lightweight aggregate blocks, cavity or cavity fill	0.00	110.00	41.73	0.00	None

9.2 Internal Walls	Description	Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Internal Walls	Internal Walls	Plasterboard on timber frame	9.00	105.48

10.1 Party Ceilings	Description	Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Ceiling	Ceiling	Precast concrete plank floor (screed laid on rubber), carpeted	30.00	53.05

## 11.1 Party Floors

# Summary for Input Data

Description	Storey Index	Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )				
Party Floor 1	Lowest occupied	Precast concrete planks floor, screed, carpeted	40.00	53.05				
<b>12.0 Opening Types</b>								
Description	Data Source	Type	Glazing	Glazing Gap				
Solid Door Glazing	Manufacturer	Solid Door Window	Double Low-E Soft 0.05	0.00 0.63				
<b>13.0 Openings</b>								
Name	Opening Type	Location	Orientation	Area (m <sup>2</sup> )				
FSD	Solid Door Glazing	Sheltered External Wall	North West	2.12				
RSW	Glazing	External Wall	South West	1.49				
RSGD	Glazing	External Wall	South West	4.97				
<b>14.0 Conservatory</b>								
None								
<b>15.0 Draught Proofing</b>								
100 %								
<b>16.0 Draught Lobby</b>								
No								
<b>17.0 Thermal Bridging</b>								
<b>17.1 List of Bridges</b>								
Bridge Type	Source Type	Length	Psi	Adjusted Reference:	Imported			
E2 Other lintels (including other steel lintels)	Independently assessed	3.73	0.02	0.02	RCD	No		
E3 Sill	Independently assessed	0.91	0.02	0.02	RCD	No		
E4 Jamb	Independently assessed	12.98	0.01	0.01	RCD	No		
E7 Party floor between dwellings (in blocks of flats)	Independently assessed	32.96	0.05	0.05	RCD	No		
E16 Corner (normal)	Independently assessed	3.20	0.05	0.05	RCD	No		
P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	26.08	0.00	0.00	Default	No		
E18 Party wall between dwellings	Independently assessed	9.60	0.06	0.06	RCD	No		
E17 Corner (inverted – internal area greater than external area)	Independently assessed	0.00	-0.10	-0.10	RCD	No		
E25 Staggered party wall between dwellings	Table K1 - Default	3.20	0.24	0.24	E25 - Default	No		
Y-value	0.07	W/m <sup>2</sup> K						
Description	Bridge							
<b>19.0 Mechanical Ventilation</b>								
<b>Mechanical Ventilation</b>								
Mechanical Ventilation System Present	Yes							
Approved Installation	Yes							
Mechanical Ventilation data Type	Database							
Type	Balanced mechanical ventilation with heat recovery							
MV Reference Number	500500							
Configuration	2							
MVHR Duct Insulated	Uninsulated Ducts							
Manufacturer SFP	0.59							
Duct Type	Rigid							
MVHR Efficiency	89.00							
Wet Rooms	2							
SFP from Installer Commissioning Certificate	No							
MVHR System Location	Inside heated envelope (installed exclusively)							
Duct Installation Specification	Level 2							
<b>19.1 Mechanical extract ventilation - Decentralised</b>								
SFP	Fan/Room Type	Count						
0.13	In Room Fan	1						
	Kitchen							
0.11	In Room Fan Other	3						
	Wet Room							
0.00	In Duct Fan Kitchen	0						
0.00	In Duct Fan Other	0						
	Wet Room							
0.10	Through Wall Fan	0						
	Kitchen							
0.10	Through Wall Fan	0						
	Other Wet Room							
<b>20.0 Fans, Open Fireplaces, Flues</b>								

# Summary for Input Data

Number of open chimneys	0										
Number of open flues	0										
Number of chimneys/flues attached to closed fire	0										
Number of flues attached to solid fuel boiler	0										
Number of flues attached to other heater	0										
Number of blocked chimneys	0										
Number of intermittent extract fans	0										
Number of passive vents	0										
Number of flueless gas fires	0										
<b>21.0 Fixed Cooling System</b>											
	No										
<b>22.0 Pressure Testing</b>											
Designed AP <sub>50</sub>	3.00										
Property Tested?	Yes										
Test Method	Blower Door										
<b>22.0 Lighting</b>											
No Fixed Lighting	No										
	<table border="1"> <thead> <tr> <th>Name</th> <th>Efficacy</th> <th>Power</th> <th>Capacity</th> <th>Count</th> </tr> </thead> <tbody> <tr> <td>Low energy Lighting</td> <td>85.00</td> <td>5.00</td> <td>425.00</td> <td>10</td> </tr> </tbody> </table>	Name	Efficacy	Power	Capacity	Count	Low energy Lighting	85.00	5.00	425.00	10
Name	Efficacy	Power	Capacity	Count							
Low energy Lighting	85.00	5.00	425.00	10							
<b>24.0 Main Heating 1</b>											
Percentage of Heat	SAP table										
Database Ref. No.	100.00										
Fuel Type	0										
SAP Code	Electricity										
In Winter	691										
In Summer	100.00										
Controls SAP Code	194.18										
Delayed Start Stat	2603										
Burner Control	No										
HETAS approved System	Modulating										
Is MHS Pumped	No										
Heating Pump Age	Pump in heated space										
Heat Emitter	2013 or later										
Underfloor Heating	Radiators										
Flow Temperature	Yes - Pipes in thin screed										
Flow Temperature Value	Enter value										
	55.00										
<b>25.0 Main Heating 2</b>											
Percentage of Heat	Database										
Database Ref. No.	0.00										
Fuel Type	100834										
SAP Code	Electricity										
In Winter	0										
In Summer	297.57										
Model Name	194.18										
Manufacturer	Compact P										
Controls	Nilan AS										
Delayed Start Stat	2100										
HETAS approved System	No										
	No										

# Summary for Input Data

Flow Temperature	Enter value										
<b>26.0 Heat Networks</b>	None										
<b>27.0 Secondary Heating</b>	None										
<b>28.0 Water Heating</b>											
Water Heating	Main Heating 2										
SAP Code	914										
Flue Gas Heat Recovery System	No										
Waste Water Heat Recovery Instantaneous System 1	No										
Waste Water Heat Recovery Instantaneous System 2	No										
Waste Water Heat Recovery Storage System	No										
Solar Panel	No										
Water use <= 125 litres/person/day	Yes										
Summer Immersion	No										
Cold Water Source	From mains										
Bath Count	1										
Baths connected to WWHRS	0										
Supplementary Immersion	No										
Immersion Only Heating Hot Water	No										
<b>28.1 Showers</b>											
<b>Description</b>	<b>Shower Type</b>	<b>Flow Rate</b> [l/min]	<b>Rated Power</b> [kW]	<b>Connected</b>	<b>Connected To</b>						
8 lpm	Unknown	8.00		No							
<b>28.3 Waste Water Heat Recovery System</b>											
<b>29.0 Hot Water Cylinder</b>		Internal Store									
Cylinder Stat	No										
Cylinder In Heated Space	No										
Independent Time Control	No										
Insulation Type	Measured Loss										
Insulation Thickness	0										
Cylinder Volume	180.00	L									
Loss	0.84	kWh/day									
In Airing Cupboard	No										
<b>31.0 Thermal Store</b>		None									
<b>34.0 Small-scale Hydro</b>		None									
Electricity Generated	0.00										
Apportioned	0.00	kWh/Year									
Connected to dwelling's electricity meter	Yes										
Electricity Generation	Annual										
Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
<b>Recommendations</b>											
Lower cost measures											
None											
Further measures to achieve even higher standards											
None											

# Predicted Energy Assessment


C14-01-02, Horsham Enterprise Park

Dwelling type:  
Date of assessment:  
Produced by:  
Total floor area:  
DRRN:

Flat, End-Terrace  
15/10/2025  
Charlotte Russell  
53.05 m<sup>2</sup>

This document is a Predicted Energy Assessment for properties marketed when they are incomplete. It includes a predicted energy rating which might not represent the final energy rating of the property on completion. Once the property is completed, this rating will be updated and an official Energy Performance Certificate will be created for the property. This will include more detailed information about the energy performance of the completed property.

The energy performance has been assessed using the Government approved SAP 10 methodology and is rated in terms of the energy use per square meter of floor area; the energy efficiency is based on fuel costs and the environmental impact is based on carbon dioxide (CO<sub>2</sub>) emissions.



The energy efficiency rating is a measure of the overall efficiency of a home. The higher the rating the more energy efficient the home is and the lower the fuel bills are likely to be.

The environmental impact rating is a measure of a home's impact on the environment in terms of carbon dioxide (CO<sub>2</sub>) emissions. The higher the rating the less impact it has on the environment.

# Thermal Bridging



Property Reference	C14-01-02		Issued on Date	15/10/2025		
Assessment Reference	Design V1		Prop Type Ref	End-Terrace Flat		
Property	C14-01-02, Horsham Enterprise Park					
SAP Rating	85 B	DER	4.57	TER	13.51	
Environmental	97 A	% DER < TER		66.17		
CO <sub>2</sub> Emissions (t/year)	0.21	DFEE	24.91	TFEE	29.38	
Compliance Check	See BREL	% DFEE < TFEE		15.21		
% DPER < TPER	33.05	DPER	48.22	TPER	72.02	
Assessor Details	Miss Charlotte Russell			Assessor ID	DK97-0001	
Client						
	Junction details	Source Type	Psi (W/mK)	Length (m)	Result	Reference
External wall	E2 Other lintels (including other steel lintels)	Independently assessed	0.022	3.73	0.08	RCD
External wall	E3 Sill	Independently assessed	0.016	0.91	0.01	RCD
External wall	E4 Jamb	Independently assessed	0.011	12.98	0.14	RCD
External wall	E7 Party floor between dwellings (in blocks of flats)	Independently assessed	0.053	32.96	1.75	RCD
External wall	E16 Corner (normal)	Independently assessed	0.051	3.20	0.16	RCD
Party wall	P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	0.000	26.08	0.00	Default
External wall	E18 Party wall between dwellings	Independently assessed	0.057	9.60	0.55	RCD
External wall	E17 Corner (inverted – internal area greater than external area)	Independently assessed	-0.104	0.00	-0.00	RCD
External wall	E25 Staggered party wall between dwellings	Table K1 - Default	0.240	3.20	0.77	E25 - Default

Total: 92.66 W/mK:

Y-Value: 0.07 W/m<sup>2</sup>K:

# Summary for Input Data



Property Reference	C14-01-04	Issued on Date	15/10/2025
Assessment Reference	Design V1	Prop Type Ref	C14-01-04
Property	C14-01-04, Horsham Enterprise Park		
SAP Rating	78 C	DER	6.57
Environmental	96 A	% DER < TER	60.13
CO <sub>2</sub> Emissions (t/year)	0.3	DFEE	39.73
Compliance Check	See BREL	% DFEE < TFEE	9.94
% DPER < TPER	22.14	DPER	68.41
TPER	87.87		

Assessor Details	Miss Charlotte Russell	Assessor ID	DK97-0001
Client			

## SUMMARY FOR INPUT DATA FOR: New Build (As Designed)

Orientation	Northeast	
Property Tenure	ND	
Transaction Type	6	
Terrain Type	Suburban	
1.0 Property Type	Flat, End-Terrace	
Position of Flat	Mid-floor flat	
Which Floor	1	
2.0 Number of Storeys	1	
3.0 Date Built	2025	
3.0 Property Age Band	L	
4.0 Sheltered Sides	2	
5.0 Sunlight/Shade	Average or unknown	
6.0 Thermal Mass Parameter	Precise calculation	
Thermal Mass	342.92	kJ/m <sup>2</sup> K
7.0 Electricity Tariff	Standard	
Smart electricity meter fitted	Yes	
Smart gas meter fitted	No	

7.0 Measurements		Heat Loss Perimeter	Internal Floor Area	Average Storey Height
		Ground floor: 16.45 m	53.97 m <sup>2</sup>	3.20 m

8.0 Living Area	25.87	m <sup>2</sup>
-----------------	-------	----------------

9.0 External Walls		Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Res	Shelter	Openings	Area Calculation Type
External Wall	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.15	110.00	28.90	19.47	0.00	None	9.43	Enter Gross Area
Sheltered	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.18	110.00	23.74	21.62	0.90	Stairwell Access Corridor 4	2.12	Enter Gross Area

9.1 Party Walls		Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )	Shelter Res	Shelter
Party Wall	Filled Cavity with Edge Sealing	Single plasterboard on dabs both sides, lightweight aggregate blocks, cavity or cavity fill	0.00	110.00	48.99	0.00	None

9.2 Internal Walls		Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Internal Walls		Plasterboard on timber frame	9.00	85.88

10.1 Party Ceilings		Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Ceiling		Precast concrete plank floor (screed laid on rubber), carpeted	30.00	53.97

## 11.0 Heat Loss Floors

# Summary for Input Data

Description	Type	Storey Index	Construction	U-Value (W/m <sup>2</sup> K)	Shelter Code	Shelter Factor	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )							
Exposed Floor	Exposed Floor - Solid	Lowest occupied	Other	0.12	None	0.00	75.00	53.97							
<b>12.0 Opening Types</b>															
Description	Data Source	Type	Glazing	Glazing Gap	Filling Type	G-value	Frame Type	Frame Factor	U Value (W/m <sup>2</sup> K)						
Solid Door Glazing	Manufacturer Manufacturer	Solid Door Window	Double Low-E Soft 0.05			0.00 0.63		0.80	1.20 1.20						
<b>13.0 Openings</b>															
Name	Opening Type	Location	Orientation	Area (m <sup>2</sup> )	Pitch										
FSD	Solid Door	Sheltered	North East	2.12	0										
RW	Glazing	External Wall	South West	4.46	0										
RGD	Glazing	External Wall	South West	4.97	0										
<b>14.0 Conservatory</b>															
None															
<b>15.0 Draught Proofing</b>															
100 %															
<b>16.0 Draught Lobby</b>															
No															
<b>17.0 Thermal Bridging</b>															
<b>17.1 List of Bridges</b>															
Bridge Type	Source Type	Length	Psi	Adjusted Reference:	Imported										
E2 Other lintels (including other steel lintels)	Independently assessed	5.54	0.02	0.02 RCD	No										
E3 Sill	Independently assessed	2.72	0.02	0.02 RCD	No										
E4 Jamb	Independently assessed	16.26	0.01	0.01 RCD	No										
E20 Exposed floor (normal)	Independently assessed	16.45	0.05	0.05 RCD	No										
E7 Party floor between dwellings (in blocks of flats)	Independently assessed	16.45	0.05	0.05 RCD	No										
E16 Corner (normal)	Independently assessed	3.20	0.05	0.05 RCD	No										
P7 Party Wall - Exposed floor (normal)	Table K1 - Default	15.31	0.48	0.48 Default	No										
P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	15.31	0.00	0.00 Default	No										
E18 Party wall between dwellings	Independently assessed	12.80	0.06	0.06 RCD	No										
E17 Corner (inverted – internal area greater than external area)	Independently assessed	0.00	-0.10	-0.10 RCD	No										
E25 Staggered party wall between dwellings	Table K1 - Default	6.40	0.24	0.24 E25 - Default	No										
Y-value	0.11	W/m <sup>2</sup> K													
Description	Bridge														
<b>19.0 Mechanical Ventilation</b>															
<b>Mechanical Ventilation</b>															
Mechanical Ventilation System Present	Yes														
Approved Installation	Yes														
Mechanical Ventilation data Type	Database														
Type	Balanced mechanical ventilation with heat recovery														
MV Reference Number	500500														
Configuration	2														
MVHR Duct Insulated	Uninsulated Ducts														
Manufacturer SFP	0.59														
Duct Type	Rigid														
MVHR Efficiency	89.00														
Wet Rooms	2														
SFP from Installer Commissioning Certificate	No														
MVHR System Location	Inside heated envelope (installed exclusively)														
Duct Installation Specification	Level 2														
<b>19.1 Mechanical extract ventilation - Decentralised</b>															
SFP	Fan/Room Type	Count													
0.13	In Room Fan	1													
	Kitchen														
0.11	In Room Fan Other	3													
	Wet Room														
0.00	In Duct Fan Kitchen	0													
0.00	In Duct Fan Other	0													
	Wet Room														
0.10	Through Wall Fan	0													
	Kitchen														
0.10	Through Wall Fan	0													
	Other Wet Room														

# Summary for Input Data

## 20.0 Fans, Open Fireplaces, Flues

Number of open chimneys	0
Number of open flues	0
Number of chimneys/flues attached to closed fire	0
Number of flues attached to solid fuel boiler	0
Number of flues attached to other heater	0
Number of blocked chimneys	0
Number of intermittent extract fans	0
Number of passive vents	0
Number of flueless gas fires	0

## 21.0 Fixed Cooling System

No
----

## 22.0 Pressure Testing

Designed AP <sub>50</sub>	Yes	
	3.00	m <sup>3</sup> /(h.m <sup>2</sup> ) @ 50 Pa
Property Tested?	Yes	
Test Method	Blower Door	

## 22.0 Lighting

No Fixed Lighting	No				
	Name Low energy Lighting	Efficacy 85.00	Power 5.00	Capacity 425.00	Count 10

## 24.0 Main Heating 1

Percentage of Heat	100.00	%
Database Ref. No.	0	
Fuel Type	Electricity	
SAP Code	691	
In Winter	100.00	
In Summer	194.18	
Controls SAP Code	2603	
Delayed Start Stat	No	
Burner Control	Modulating	
HETAS approved System	No	
Is MHS Pumped	Pump in heated space	
Heating Pump Age	2013 or later	
Heat Emitter	Radiators	
Underfloor Heating	Yes - Pipes in thin screed	
Flow Temperature	Enter value	
Flow Temperature Value	55.00	

## 25.0 Main Heating 2

Percentage of Heat	0.00	%
Database Ref. No.	100834	
Fuel Type	Electricity	
SAP Code	0	
In Winter	306.33	
In Summer	194.18	
Model Name	Compact P	
Manufacturer	Nilan AS	
Controls	2100	
Delayed Start Stat	No	
HETAS approved System	No	

# Summary for Input Data

Flow Temperature	Enter value										
<b>26.0 Heat Networks</b>	None										
<b>27.0 Secondary Heating</b>	None										
<b>28.0 Water Heating</b>											
Water Heating	Main Heating 2										
SAP Code	914										
Flue Gas Heat Recovery System	No										
Waste Water Heat Recovery Instantaneous System 1	No										
Waste Water Heat Recovery Instantaneous System 2	No										
Waste Water Heat Recovery Storage System	No										
Solar Panel	No										
Water use <= 125 litres/person/day	Yes										
Summer Immersion	No										
Cold Water Source	From mains										
Bath Count	1										
Baths connected to WWHRS	0										
Supplementary Immersion	No										
Immersion Only Heating Hot Water	No										
<b>28.1 Showers</b>											
<b>Description</b>	<b>Shower Type</b>	<b>Flow Rate</b> [l/min]	<b>Rated Power</b> [kW]	<b>Connected</b>	<b>Connected To</b>						
8 lpm	Unknown	8.00		No							
<b>28.3 Waste Water Heat Recovery System</b>											
<b>29.0 Hot Water Cylinder</b>		Internal Store									
Cylinder Stat	No										
Cylinder In Heated Space	No										
Independent Time Control	No										
Insulation Type	Measured Loss										
Insulation Thickness	0										
Cylinder Volume	180.00	L									
Loss	0.84	kWh/day									
In Airing Cupboard	No										
<b>31.0 Thermal Store</b>		None									
<b>34.0 Small-scale Hydro</b>		None									
Electricity Generated	0.00										
Apportioned	0.00	kWh/Year									
Connected to dwelling's electricity meter	Yes										
Electricity Generation	Annual										
Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
<b>Recommendations</b>											
Lower cost measures											
None											
Further measures to achieve even higher standards											
None											

# Predicted Energy Assessment


C14-01-04, Horsham Enterprise Park

Dwelling type:  
Date of assessment:  
Produced by:  
Total floor area:  
DRRN:

Flat, End-Terrace  
15/10/2025  
Charlotte Russell  
53.97 m<sup>2</sup>

This document is a Predicted Energy Assessment for properties marketed when they are incomplete. It includes a predicted energy rating which might not represent the final energy rating of the property on completion. Once the property is completed, this rating will be updated and an official Energy Performance Certificate will be created for the property. This will include more detailed information about the energy performance of the completed property.

The energy performance has been assessed using the Government approved SAP 10 methodology and is rated in terms of the energy use per square meter of floor area; the energy efficiency is based on fuel costs and the environmental impact is based on carbon dioxide (CO<sub>2</sub>) emissions.



The energy efficiency rating is a measure of the overall efficiency of a home. The higher the rating the more energy efficient the home is and the lower the fuel bills are likely to be.

The environmental impact rating is a measure of a home's impact on the environment in terms of carbon dioxide (CO<sub>2</sub>) emissions. The higher the rating the less impact it has on the environment.

# Thermal Bridging



Property Reference	C14-01-04		Issued on Date	15/10/2025		
Assessment Reference	Design V1		Prop Type Ref	End-Terrace Flat		
Property	C14-01-04, Horsham Enterprise Park					
SAP Rating	78 C	DER	6.57	TER	16.48	
Environmental	96 A	% DER < TER		60.13		
CO <sub>2</sub> Emissions (t/year)	0.3	DFEE	39.73	TFEE	44.12	
Compliance Check	See BREL	% DFEE < TFEE		9.94		
% DPER < TPER	22.14	DPER	68.41	TPER	87.87	
Assessor Details	Miss Charlotte Russell			Assessor ID	DK97-0001	
Client						
	Junction details	Source Type	Psi (W/mK)	Length (m)	Result	Reference
External wall	E2 Other lintels (including other steel lintels)	Independently assessed	0.022	5.54	0.12	RCD
External wall	E3 Sill	Independently assessed	0.016	2.72	0.04	RCD
External wall	E4 Jamb	Independently assessed	0.011	16.26	0.18	RCD
External wall	E20 Exposed floor (normal)	Independently assessed	0.054	16.45	0.89	RCD
External wall	E7 Party floor between dwellings (in blocks of flats)	Independently assessed	0.053	16.45	0.87	RCD
External wall	E16 Corner (normal)	Independently assessed	0.051	3.20	0.16	RCD
Party wall	P7 Party Wall - Exposed floor (normal)	Table K1 - Default	0.480	15.31	7.35	Default
Party wall	P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	0.000	15.31	0.00	Default
External wall	E18 Party wall between dwellings	Independently assessed	0.057	12.80	0.73	RCD
External wall	E17 Corner (inverted – internal area greater than external area)	Independently assessed	-0.104	0.00	-0.00	RCD
External wall	E25 Staggered party wall between dwellings	Table K1 - Default	0.240	6.40	1.54	E25 - Default

Total: 110.44 W/mK:

Y-Value: 0.11 W/m<sup>2</sup>K:

# Summary for Input Data



Property Reference	C14-01-05			Issued on Date	15/10/2025					
Assessment Reference	Design V1		Prop Type Ref	C14-01-05						
Property	C14-01-05, Horsham Enterprise Park									
SAP Rating	82 B	DER	4.90	TER	13.22					
Environmental	96 A	% DER < TER			62.93					
CO <sub>2</sub> Emissions (t/year)	0.29	DFEE	30.72	TFEE	35.71					
Compliance Check	See BREL	% DFEE < TFEE			13.96					
% DPER < TPER	26.75	DPER	51.33	TPER	70.07					
Assessor Details	Miss Charlotte Russell			Assessor ID	DK97-0001					
Client										
<b>SUMMARY FOR INPUT DATA FOR: New Build (As Designed)</b>										
Orientation	Southeast									
Property Tenure	ND									
Transaction Type	6									
Terrain Type	Suburban									
1.0 Property Type	Flat, End-Terrace									
Position of Flat	Mid-floor flat									
Which Floor	1									
2.0 Number of Storeys	1									
3.0 Date Built	2025									
3.0 Property Age Band	L									
4.0 Sheltered Sides	2									
5.0 Sunlight/Shade	Average or unknown									
6.0 Thermal Mass Parameter	Precise calculation									
Thermal Mass	285.11 kJ/m <sup>2</sup> K									
7.0 Electricity Tariff	Standard									
Smart electricity meter fitted	Yes									
Smart gas meter fitted	No									
7.0 Measurements										
	Ground floor:		Heat Loss Perimeter	Internal Floor Area	Average Storey Height					
			22.88 m	71.14 m <sup>2</sup>	3.20 m					
8.0 Living Area	24.98 m <sup>2</sup>									
9.0 External Walls										
Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Res	Shelter	Openings	Area Calculation Type
External Wall	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.15	110.00	55.42	41.54	0.00	None	13.88	Enter Gross Area
Sheltered	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.18	110.00	17.79	15.67	0.90	Stairwell Access Corridor 4	2.12	Enter Gross Area
9.1 Party Walls										
Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )	Shelter Res	Shelter			
Party Wall	Filled Cavity with Edge Sealing	Single plasterboard on dabs both sides, lightweight aggregate blocks, cavity or cavity fill	0.00	110.00	43.20	0.00	None			
9.2 Internal Walls										
Description						Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )			
Internal Walls	Plasterboard on timber frame					9.00	156.88			
10.1 Party Ceilings										
Description						Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )			
Ceiling	Precast concrete plank floor (screed laid on rubber), carpeted					30.00	71.14			
11.1 Party Floors										

# Summary for Input Data

Description	Storey Index	Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )				
Party Floor	Lowest occupied	Precast concrete planks floor, screed, carpeted	40.00	71.14				
<b>12.0 Opening Types</b>								
Description	Data Source	Type	Glazing	Glazing Gap				
Solid Door Glazing	Manufacturer	Solid Door Window	Double Low-E Soft 0.05	0.00 0.63				
<b>13.0 Openings</b>								
Name	Opening Type	Location	Orientation	Area (m <sup>2</sup> )				
FSD	Solid Door Glazing	Sheltered External Wall	South East	2.12				
RW	Glazing	External Wall	North West	8.91				
LSGD	Glazing	External Wall	South West	4.97				
<b>14.0 Conservatory</b>								
None								
<b>15.0 Draught Proofing</b>								
100 %								
<b>16.0 Draught Lobby</b>								
No								
<b>17.0 Thermal Bridging</b>								
<b>17.1 List of Bridges</b>								
Bridge Type	Source Type	Length	Psi	Adjusted Reference:	Imported			
E2 Other lintels (including other steel lintels)	Independently assessed	8.25	0.02	0.02	RCD	No		
E3 Sill	Independently assessed	5.43	0.02	0.02	RCD	No		
E4 Jamb	Independently assessed	19.54	0.01	0.01	RCD	No		
E7 Party floor between dwellings (in blocks of flats)	Independently assessed	45.76	0.05	0.05	RCD	No		
E16 Corner (normal)	Independently assessed	6.40	0.05	0.05	RCD	No		
P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	27.00	0.00	0.00	Default	No		
E18 Party wall between dwellings	Independently assessed	9.60	0.06	0.06	RCD	No		
E17 Corner (inverted – internal area greater than external area)	Independently assessed	0.00	-0.10	-0.10	RCD	No		
E25 Staggered party wall between dwellings	Table K1 - Default	3.20	0.24	0.24	E25 - Default	No		
Y-value	0.06	W/m <sup>2</sup> K						
Description	Bridge							
<b>19.0 Mechanical Ventilation</b>								
<b>Mechanical Ventilation</b>								
Mechanical Ventilation System Present	Yes							
Approved Installation	Yes							
Mechanical Ventilation data Type	Database							
Type	Balanced mechanical ventilation with heat recovery							
MV Reference Number	500500							
Configuration	2							
MVHR Duct Insulated	Uninsulated Ducts							
Manufacturer SFP	0.59							
Duct Type	Rigid							
MVHR Efficiency	89.00							
Wet Rooms	2							
SFP from Installer Commissioning Certificate	No							
MVHR System Location	Inside heated envelope (installed exclusively)							
Duct Installation Specification	Level 2							
<b>19.1 Mechanical extract ventilation - Decentralised</b>								
SFP	Fan/Room Type	Count						
0.13	In Room Fan	1						
	Kitchen							
0.11	In Room Fan Other	3						
	Wet Room							
0.00	In Duct Fan Kitchen	0						
0.00	In Duct Fan Other	0						
	Wet Room							
0.10	Through Wall Fan	0						
	Kitchen							
0.10	Through Wall Fan	0						
	Other Wet Room							
<b>20.0 Fans, Open Fireplaces, Flues</b>								

# Summary for Input Data

Number of open chimneys	0										
Number of open flues	0										
Number of chimneys/flues attached to closed fire	0										
Number of flues attached to solid fuel boiler	0										
Number of flues attached to other heater	0										
Number of blocked chimneys	0										
Number of intermittent extract fans	0										
Number of passive vents	0										
Number of flueless gas fires	0										
<b>21.0 Fixed Cooling System</b>											
	No										
<b>22.0 Pressure Testing</b>											
Designed AP <sub>50</sub>	3.00										
Property Tested?	Yes										
Test Method	Blower Door										
<b>22.0 Lighting</b>											
No Fixed Lighting	No										
	<table border="1"> <thead> <tr> <th>Name</th> <th>Efficacy</th> <th>Power</th> <th>Capacity</th> <th>Count</th> </tr> </thead> <tbody> <tr> <td>Low energy Lighting</td> <td>85.00</td> <td>5.00</td> <td>425.00</td> <td>10</td> </tr> </tbody> </table>	Name	Efficacy	Power	Capacity	Count	Low energy Lighting	85.00	5.00	425.00	10
Name	Efficacy	Power	Capacity	Count							
Low energy Lighting	85.00	5.00	425.00	10							
<b>24.0 Main Heating 1</b>											
Percentage of Heat	SAP table										
Database Ref. No.	100.00										
Fuel Type	0										
SAP Code	Electricity										
In Winter	691										
In Summer	100.00										
Controls SAP Code	194.18										
Delayed Start Stat	2603										
Burner Control	No										
HETAS approved System	Modulating										
Is MHS Pumped	No										
Heating Pump Age	Pump in heated space										
Heat Emitter	2013 or later										
Underfloor Heating	Radiators										
Flow Temperature	Yes - Pipes in thin screed										
Flow Temperature Value	Enter value										
	55.00										
<b>25.0 Main Heating 2</b>											
Percentage of Heat	Database										
Database Ref. No.	0.00										
Fuel Type	100834										
SAP Code	Electricity										
In Winter	0										
In Summer	332.80										
Model Name	194.18										
Manufacturer	Compact P										
Controls	Nilan AS										
Delayed Start Stat	2100										
HETAS approved System	No										
	No										

# Summary for Input Data

Flow Temperature	Enter value										
<b>26.0 Heat Networks</b>	None										
<b>27.0 Secondary Heating</b>	None										
<b>28.0 Water Heating</b>											
Water Heating	Main Heating 2										
SAP Code	914										
Flue Gas Heat Recovery System	No										
Waste Water Heat Recovery Instantaneous System 1	No										
Waste Water Heat Recovery Instantaneous System 2	No										
Waste Water Heat Recovery Storage System	No										
Solar Panel	No										
Water use <= 125 litres/person/day	Yes										
Summer Immersion	No										
Cold Water Source	From mains										
Bath Count	1										
Baths connected to WWHRS	0										
Supplementary Immersion	No										
Immersion Only Heating Hot Water	No										
<b>28.1 Showers</b>											
<b>Description</b>	<b>Shower Type</b>	<b>Flow Rate</b> [l/min]	<b>Rated Power</b> [kW]	<b>Connected</b>	<b>Connected To</b>						
8 lpm	Unknown	8.00		No							
<b>28.3 Waste Water Heat Recovery System</b>											
<b>29.0 Hot Water Cylinder</b>		Internal Store									
Cylinder Stat	No										
Cylinder In Heated Space	No										
Independent Time Control	No										
Insulation Type	Measured Loss										
Insulation Thickness	0										
Cylinder Volume	180.00	L									
Loss	0.84	kWh/day									
In Airing Cupboard	No										
<b>31.0 Thermal Store</b>		None									
<b>34.0 Small-scale Hydro</b>		None									
Electricity Generated	0.00										
Apportioned	0.00	kWh/Year									
Connected to dwelling's electricity meter	Yes										
Electricity Generation	Annual										
Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
<b>Recommendations</b>											
Lower cost measures											
None											
Further measures to achieve even higher standards											
None											

# Predicted Energy Assessment


C14-01-05, Horsham Enterprise Park

Dwelling type:  
Date of assessment:  
Produced by:  
Total floor area:  
DRRN:

Flat, End-Terrace  
15/10/2025  
Charlotte Russell  
71.14 m<sup>2</sup>

This document is a Predicted Energy Assessment for properties marketed when they are incomplete. It includes a predicted energy rating which might not represent the final energy rating of the property on completion. Once the property is completed, this rating will be updated and an official Energy Performance Certificate will be created for the property. This will include more detailed information about the energy performance of the completed property.

The energy performance has been assessed using the Government approved SAP 10 methodology and is rated in terms of the energy use per square meter of floor area; the energy efficiency is based on fuel costs and the environmental impact is based on carbon dioxide (CO<sub>2</sub>) emissions.



The energy efficiency rating is a measure of the overall efficiency of a home. The higher the rating the more energy efficient the home is and the lower the fuel bills are likely to be.

The environmental impact rating is a measure of a home's impact on the environment in terms of carbon dioxide (CO<sub>2</sub>) emissions. The higher the rating the less impact it has on the environment.

# Thermal Bridging



Property Reference	C14-01-05		Issued on Date	15/10/2025		
Assessment Reference	Design V1		Prop Type Ref	End-Terrace Flat		
Property	C14-01-05, Horsham Enterprise Park					
SAP Rating	82 B	DER	4.90	TER	13.22	
Environmental	96 A	% DER < TER		62.93		
CO <sub>2</sub> Emissions (t/year)	0.29	DFEE	30.72	TFEE	35.71	
Compliance Check	See BREL	% DFEE < TFEE		13.96		
% DPER < TPER	26.75	DPER	51.33	TPER	70.07	
Assessor Details	Miss Charlotte Russell			Assessor ID	DK97-0001	
Client						
	Junction details	Source Type	Psi (W/mK)	Length (m)	Result	Reference
External wall	E2 Other lintels (including other steel lintels)	Independently assessed	0.022	8.25	0.18	RCD
External wall	E3 Sill	Independently assessed	0.016	5.43	0.09	RCD
External wall	E4 Jamb	Independently assessed	0.011	19.54	0.21	RCD
External wall	E7 Party floor between dwellings (in blocks of flats)	Independently assessed	0.053	45.76	2.43	RCD
External wall	E16 Corner (normal)	Independently assessed	0.051	6.40	0.33	RCD
Party wall	P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	0.000	27.00	0.00	Default
External wall	E18 Party wall between dwellings	Independently assessed	0.057	9.60	0.55	RCD
External wall	E17 Corner (inverted – internal area greater than external area)	Independently assessed	-0.104	0.00	-0.00	RCD
External wall	E25 Staggered party wall between dwellings	Table K1 - Default	0.240	3.20	0.77	E25 - Default

Total: 125.18 W/mK:

Y-Value: 0.06 W/m<sup>2</sup>K:

# Summary for Input Data



Property Reference	C14-01-07	Issued on Date	15/10/2025
Assessment Reference	Design V1	Prop Type Ref	C14-01-07
Property	C14-01-07, Horsham Enterprise Park		
SAP Rating	79 C	DER	5.78
Environmental	96 A	% DER < TER	14.47
CO <sub>2</sub> Emissions (t/year)	0.35	DFEE	36.79
Compliance Check	See BREL	% DFEE < TFEE	60.06
% DPER < TPER	21.66	DPER	41.86
		TPER	12.10
			76.78

Assessor Details	Miss Charlotte Russell	Assessor ID	DK97-0001
Client			

## SUMMARY FOR INPUT DATA FOR: New Build (As Designed)

Orientation	Northeast
Property Tenure	ND
Transaction Type	6
Terrain Type	Suburban
1.0 Property Type	Flat, End-Terrace
Position of Flat	Mid-floor flat
Which Floor	1
2.0 Number of Storeys	1
3.0 Date Built	2025
3.0 Property Age Band	L
4.0 Sheltered Sides	2
5.0 Sunlight/Shade	Average or unknown
6.0 Thermal Mass Parameter	Precise calculation
Thermal Mass	277.30
	kJ/m <sup>2</sup> K
7.0 Electricity Tariff	Standard
Smart electricity meter fitted	Yes
Smart gas meter fitted	No

7.0 Measurements	Heat Loss Perimeter	Internal Floor Area	Average Storey Height
	Ground floor: 27.48 m	72.32 m <sup>2</sup>	3.20 m

8.0 Living Area	25.97	m <sup>2</sup>
-----------------	-------	----------------

9.0 External Walls	Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Res	Shelter	Openings	Area Calculation Type
External Wall	External Wall	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.15	110.00	54.43	39.06	0.00	None	15.37	Enter Gross Area
Sheltered	Sheltered	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.18	110.00	33.50	31.38	0.90	Stairwell Access Corridor 4	2.12	Enter Gross Area

9.1 Party Walls	Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )	Shelter Res	Shelter
Party Wall	Party Wall	Filled Cavity with Edge Sealing	Single plasterboard on dabs both sides, lightweight aggregate blocks, cavity or cavity fill	0.00	110.00	30.53	0.00	None

9.2 Internal Walls	Description	Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Internal Walls	Internal Walls	Plasterboard on timber frame	9.00	163.54

10.1 Party Ceilings	Description	Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Ceiling	Ceiling	Precast concrete plank floor (screed laid on rubber), carpeted	30.00	72.32

## 11.0 Heat Loss Floors

# Summary for Input Data

Description	Type	Storey Index	Construction	U-Value (W/m <sup>2</sup> K)	Shelter Code	Shelter Factor	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )	
Exposed Floor	Exposed Floor - Solid	Lowest occupied	Other	0.12	None	0.00	0.00	11.98	
<b>11.1 Party Floors</b>									
Description	Storey Index	Construction					Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )	
Party Floor	Lowest occupied	Precast concrete planks floor, screed, carpeted					40.00	60.34	
<b>12.0 Opening Types</b>									
Description	Data Source	Type	Glazing	Glazing Gap	Filling Type	G-value	Frame Type	Frame Factor	U Value (W/m <sup>2</sup> K)
Solid Door Glazing	Manufacturer	Solid Door Window	Double Low-E Soft 0.05			0.00 0.63		0.80	1.20 1.20
<b>13.0 Openings</b>									
Name	Opening Type	Location	Orientation	Area (m <sup>2</sup> )	Pitch				
FSD	Solid Door	Sheltered	North East	2.12	0				
RSW	Glazing	External Wall	North West	8.91	0				
LSGD	Glazing	External Wall	South East	4.97	0				
LSW	Glazing	External Wall	South East	1.49	0				
<b>14.0 Conservatory</b>									
		None							
<b>15.0 Draught Proofing</b>									
		100					%		
<b>16.0 Draught Lobby</b>									
		No							
<b>17.0 Thermal Bridging</b>									
<b>17.1 List of Bridges</b>									
Bridge Type	Source Type	Length	Psi	Adjusted Reference:	Imported				
E2 Other lintels (including other steel lintels)	Independently assessed	9.16	0.02	RCD	No				
E3 Sill	Independently assessed	6.34	0.02	RCD	No				
E4 Jamb	Independently assessed	22.82	0.01	RCD	No				
E7 Party floor between dwellings (in blocks of flats)	Independently assessed	44.56	0.05	RCD	No				
E16 Corner (normal)	Independently assessed	9.60	0.05	RCD	No				
P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	16.32	0.00	Default	No				
E18 Party wall between dwellings	Independently assessed	9.60	0.06	RCD	No				
E17 Corner (inverted – internal area greater than external area)	Independently assessed	6.40	-0.10	RCD	No				
E25 Staggered party wall between dwellings	Table K1 - Default	3.20	0.24	E25 - Default	No				
E20 Exposed floor (normal)	Independently assessed	6.77	0.05	RCD	No				
P7 Party Wall - Exposed floor (normal)	Table K1 - Default	2.76	0.48	P7 - Default	No				
P8 Party Wall - Exposed floor (inverted)	Table K1 - Default	8.04	0.48	P8 - Default	No				
Y-value	0.10				W/m <sup>2</sup> K				
Description	Bridge								
<b>19.0 Mechanical Ventilation</b>									
<b>Mechanical Ventilation</b>									
Mechanical Ventilation System Present	Yes								
Approved Installation	Yes								
Mechanical Ventilation data Type	Database								
Type	Balanced mechanical ventilation with heat recovery								
MV Reference Number	500500								
Configuration	2								
MVHR Duct Insulated	Uninsulated Ducts								
Manufacturer SFP	0.59								
Duct Type	Rigid								
MVHR Efficiency	89.00								
Wet Rooms	2								
SFP from Installer Commissioning Certificate	No								
MVHR System Location	Inside heated envelope (installed exclusively)								
Duct Installation Specification	Level 2								
<b>19.1 Mechanical extract ventilation - Decentralised</b>									
SFP	Fan/Room Type	Count							
0.13	In Room Fan	1							
	Kitchen								
0.11	In Room Fan Other	3							
	Wet Room								

# Summary for Input Data

0.00	In Duct Fan Kitchen	0
0.00	In Duct Fan Other	0
	Wet Room	
0.10	Through Wall Fan	0
	Kitchen	
0.10	Through Wall Fan	0
	Other Wet Room	

## 20.0 Fans, Open Fireplaces, Flues

Number of open chimneys	0
Number of open flues	0
Number of chimneys/flues attached to closed fire	0
Number of flues attached to solid fuel boiler	0
Number of flues attached to other heater	0
Number of blocked chimneys	0
Number of intermittent extract fans	0
Number of passive vents	0
Number of flueless gas fires	0

## 21.0 Fixed Cooling System

22.0 Pressure Testing	No
-----------------------	----

Designed AP <sub>50</sub>	3.00	m <sup>3</sup> /(h.m <sup>2</sup> ) @ 50 Pa
Property Tested?	Yes	
Test Method	Blower Door	

## 22.0 Lighting

No Fixed Lighting	No				
	Name	Efficacy	Power	Capacity	Count
	Low energy Lighting	85.00	5.00	425.00	10

## 24.0 Main Heating 1

Percentage of Heat	100.00	%
Database Ref. No.	0	
Fuel Type	Electricity	
SAP Code	691	
In Winter	100.00	
In Summer	194.18	
Controls SAP Code	2603	
Delayed Start Stat	No	
Burner Control	Modulating	
HETAS approved System	No	
Is MHS Pumped	Pump in heated space	
Heating Pump Age	2013 or later	
Heat Emitter	Radiators	
Underfloor Heating	Yes - Pipes in thin screed	
Flow Temperature	Enter value	
Flow Temperature Value	55.00	

## 25.0 Main Heating 2

Percentage of Heat	0.00	%
Database Ref. No.	100834	
Fuel Type	Electricity	
SAP Code	0	
In Winter	337.54	
In Summer	194.18	
Model Name	Compact P	

# Summary for Input Data

Manufacturer	Nilan AS										
Controls	2100										
Delayed Start Stat	No										
HETAS approved System	No										
Flow Temperature	Enter value										
<b>26.0 Heat Networks</b>											
27.0 Secondary Heating	None										
<b>28.0 Water Heating</b>											
Water Heating	Main Heating 2										
SAP Code	914										
Flue Gas Heat Recovery System	No										
Waste Water Heat Recovery Instantaneous System 1	No										
Waste Water Heat Recovery Instantaneous System 2	No										
Waste Water Heat Recovery Storage System	No										
Solar Panel	No										
Water use <= 125 litres/person/day	Yes										
Summer Immersion	No										
Cold Water Source	From mains										
Bath Count	1										
Baths connected to WWHRS	0										
Supplementary Immersion	No										
Immersion Only Heating Hot Water	No										
<b>28.1 Showers</b>											
Description	Shower Type	Flow Rate [l/min]	Rated Power [kW]	Connected	Connected To						
8 lpm	Unknown	8.00		No							
<b>28.3 Waste Water Heat Recovery System</b>											
<b>29.0 Hot Water Cylinder</b>		Internal Store									
Cylinder Stat	No										
Cylinder In Heated Space	No										
Independent Time Control	No										
Insulation Type	Measured Loss										
Insulation Thickness	0										
Cylinder Volume	180.00	L									
Loss	0.84	kWh/day									
In Airing Cupboard	No										
<b>31.0 Thermal Store</b>		None									
<b>34.0 Small-scale Hydro</b>		None									
Electricity Generated	0.00										
Apportioned	0.00	kWh/Year									
Connected to dwelling's electricity meter	Yes										
Electricity Generation	Annual										
Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
<b>Recommendations</b>											
Lower cost measures											
None											
Further measures to achieve even higher standards											
None											

# Predicted Energy Assessment


C14-01-07, Horsham Enterprise Park

Dwelling type:  
Date of assessment:  
Produced by:  
Total floor area:  
DRRN:

Flat, End-Terrace  
15/10/2025  
Charlotte Russell  
72.32 m<sup>2</sup>

This document is a Predicted Energy Assessment for properties marketed when they are incomplete. It includes a predicted energy rating which might not represent the final energy rating of the property on completion. Once the property is completed, this rating will be updated and an official Energy Performance Certificate will be created for the property. This will include more detailed information about the energy performance of the completed property.

The energy performance has been assessed using the Government approved SAP 10 methodology and is rated in terms of the energy use per square meter of floor area; the energy efficiency is based on fuel costs and the environmental impact is based on carbon dioxide (CO<sub>2</sub>) emissions.



The energy efficiency rating is a measure of the overall efficiency of a home. The higher the rating the more energy efficient the home is and the lower the fuel bills are likely to be.

The environmental impact rating is a measure of a home's impact on the environment in terms of carbon dioxide (CO<sub>2</sub>) emissions. The higher the rating the less impact it has on the environment.

# Thermal Bridging

Property Reference	C14-01-07		Issued on Date	15/10/2025		
Assessment Reference	Design V1		Prop Type Ref	End-Terrace Flat		
Property	C14-01-07, Horsham Enterprise Park					
SAP Rating	79 C	DER	5.78	TER	14.47	
Environmental	96 A	% DER < TER			60.06	
CO <sub>2</sub> Emissions (t/year)	0.35	DFEE	36.79	TFEE	41.86	
Compliance Check	See BREL	% DFEE < TFEE			12.10	
% DPER < TPER	21.66	DPER	60.15	TPER	76.78	
Assessor Details	Miss Charlotte Russell			Assessor ID	DK97-0001	
Client						
	Junction details	Source Type	Psi (W/mK)	Length (m)	Result	Reference
External wall	E2 Other lintels (including other steel lintels)	Independently assessed	0.022	9.16	0.20	RCD
External wall	E3 Sill	Independently assessed	0.016	6.34	0.10	RCD
External wall	E4 Jamb	Independently assessed	0.011	22.82	0.25	RCD
External wall	E7 Party floor between dwellings (in blocks of flats)	Independently assessed	0.053	44.56	2.36	RCD
External wall	E16 Corner (normal)	Independently assessed	0.051	9.60	0.49	RCD
Party wall	P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	0.000	16.32	0.00	Default
External wall	E18 Party wall between dwellings	Independently assessed	0.057	9.60	0.55	RCD
External wall	E17 Corner (inverted – internal area greater than external area)	Independently assessed	-0.104	6.40	-0.67	RCD
External wall	E25 Staggered party wall between dwellings	Table K1 - Default	0.240	3.20	0.77	E25 - Default
External wall	E20 Exposed floor (normal)	Independently assessed	0.054	6.77	0.37	RCD
Party wall	P7 Party Wall - Exposed floor (normal)	Table K1 - Default	0.480	2.76	1.32	P7 - Default
Party wall	P8 Party Wall - Exposed floor (inverted)	Table K1 - Default	0.480	8.04	3.86	P8 - Default

Total: 145.57 W/mK:

Y-Value: 0.10 W/m<sup>2</sup>K:

# Summary for Input Data



Property Reference	C14-01-13	Issued on Date	15/10/2025
Assessment Reference	Design V1	Prop Type Ref	C14-01-13
Property	C14-01-13, Horsham Enterprise Park		
SAP Rating	77 C	DER	7.04
Environmental	95 A	% DER < TER	59.45
CO <sub>2</sub> Emissions (t/year)	0.3	DFEE	42.94
Compliance Check	See BREL	% DFEE < TFEE	7.67
% DPER < TPER	20.81	DPER	73.39
TPER	92.68		

Assessor Details	Miss Charlotte Russell	Assessor ID	DK97-0001
Client			

## SUMMARY FOR INPUT DATA FOR: New Build (As Designed)

Orientation	Southwest	
Property Tenure	ND	
Transaction Type	6	
Terrain Type	Suburban	
1.0 Property Type	Flat, Mid-Terrace	
Position of Flat	Mid-floor flat	
Which Floor	1	
2.0 Number of Storeys	1	
3.0 Date Built	2025	
3.0 Property Age Band	L	
4.0 Sheltered Sides	2	
5.0 Sunlight/Shade	Average or unknown	
6.0 Thermal Mass Parameter	Precise calculation	
Thermal Mass	299.85	kJ/m <sup>2</sup> K
7.0 Electricity Tariff	Standard	
Smart electricity meter fitted	Yes	
Smart gas meter fitted	No	

7.0 Measurements		Heat Loss Perimeter	Internal Floor Area	Average Storey Height
		Ground floor: 16.78 m	50.73 m <sup>2</sup>	3.20 m

8.0 Living Area	23.56	m <sup>2</sup>
-----------------	-------	----------------

9.0 External Walls		Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Res	Shelter	Openings	Area Calculation Type
External Wall	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.15	110.00	21.50	13.56	0.00	None	7.94	Enter Gross Area
Sheltered	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.18	110.00	32.19	30.07	0.90	Stairwell Access Corridor 4	2.12	Enter Gross Area

9.1 Party Walls		Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )	Shelter Res	Shelter
Party Wall	Filled Cavity with Edge Sealing	Single plasterboard on dabs both sides, lightweight aggregate blocks, cavity or cavity fill	0.00	110.00	47.17	0.00	None

9.2 Internal Walls		Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Internal Walls		Plasterboard on timber frame	9.00	80.78

10.1 Party Ceilings		Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Ceiling		Precast concrete plank floor (screed laid on rubber), carpeted	30.00	50.73

## 11.0 Heat Loss Floors

# Summary for Input Data

Description	Type	Storey Index	Construction	U-Value (W/m <sup>2</sup> K)	Shelter Code	Shelter Factor	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )	
Exposed Floor	Exposed Floor - Solid	Lowest occupied	Other	0.12	None	0.00	0.00	27.10	
<b>11.1 Party Floors</b>									
Description	Storey Index	Construction					Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )	
Party Floor	Lowest occupied	Precast concrete planks floor, screed, carpeted					40.00	23.63	
<b>12.0 Opening Types</b>									
Description	Data Source	Type	Glazing	Glazing Gap	Filling Type	G-value	Frame Type	Frame Factor	U Value (W/m <sup>2</sup> K)
Solid Door Glazing	Manufacturer	Solid Door Window	Double Low-E Soft 0.05			0.00 0.63		0.80	1.20 1.20
<b>13.0 Openings</b>									
Name	Opening Type	Location	Orientation	Area (m <sup>2</sup> )	Pitch				
FSD	Solid Door	Sheltered	South West	2.12	0				
RW	Glazing	External Wall	North East	2.97	0				
RGD	Glazing	External Wall	North East	4.97	0				
<b>14.0 Conservatory</b>									
		None							
<b>15.0 Draught Proofing</b>									
		100					%		
<b>16.0 Draught Lobby</b>									
		No							
<b>17.0 Thermal Bridging</b>									
<b>17.1 List of Bridges</b>									
Bridge Type	Source Type	Length	Psi	Adjusted Reference:	Imported				
E2 Other lintels (including other steel lintels)	Independently assessed	4.63	0.02	RCD	No				
E3 Sill	Independently assessed	1.81	0.02	RCD	No				
E4 Jamb	Independently assessed	12.98	0.01	RCD	No				
E7 Party floor between dwellings (in blocks of flats)	Independently assessed	23.68	0.05	RCD	No				
E16 Corner (normal)	Independently assessed	3.20	0.05	RCD	No				
P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	21.59	0.00	Default	No				
E18 Party wall between dwellings	Independently assessed	16.00	0.06	RCD	No				
E17 Corner (inverted – internal area greater than external area)	Independently assessed	3.20	-0.10	RCD	No				
E25 Staggered party wall between dwellings	Table K1 - Default	0.00	0.24	E25 - Default	No				
E20 Exposed floor (normal)	Independently assessed	9.88	0.05	RCD	No				
P7 Party Wall - Exposed floor (normal)	Table K1 - Default	7.89	0.48	P7 - Default	No				
P8 Party Wall - Exposed floor (inverted)	Table K1 - Default	6.85	0.48	P8 - Default	No				
Y-value	0.12				W/m <sup>2</sup> K				
Description	Bridge								
<b>19.0 Mechanical Ventilation</b>									
<b>Mechanical Ventilation</b>									
Mechanical Ventilation System Present	Yes								
Approved Installation	Yes								
Mechanical Ventilation data Type	Database								
Type	Balanced mechanical ventilation with heat recovery								
MV Reference Number	500500								
Configuration	2								
MVHR Duct Insulated	Uninsulated Ducts								
Manufacturer SFP	0.59								
Duct Type	Rigid								
MVHR Efficiency	89.00								
Wet Rooms	2								
SFP from Installer Commissioning Certificate	No								
MVHR System Location	Inside heated envelope (installed exclusively)								
Duct Installation Specification	Level 2								
<b>19.1 Mechanical extract ventilation - Decentralised</b>									
SFP	Fan/Room Type	Count							
0.13	In Room Fan	1							
	Kitchen								
0.11	In Room Fan Other	3							
	Wet Room								
0.00	In Duct Fan Kitchen	0							

# Summary for Input Data

0.00	In Duct Fan Other	0
0.10	Wet Room	
0.10	Through Wall Fan	0
	Kitchen	
0.10	Through Wall Fan	0
	Other Wet Room	

## 20.0 Fans, Open Fireplaces, Flues

Number of open chimneys	0
Number of open flues	0
Number of chimneys/flues attached to closed fire	0
Number of flues attached to solid fuel boiler	0
Number of flues attached to other heater	0
Number of blocked chimneys	0
Number of intermittent extract fans	0
Number of passive vents	0
Number of flueless gas fires	0

## 21.0 Fixed Cooling System

No

## 22.0 Pressure Testing

Designed AP <sub>50</sub>	Yes	
	3.00	m <sup>3</sup> /(h.m <sup>2</sup> ) @ 50 Pa
Property Tested?	Yes	

Test Method

Blower Door

## 22.0 Lighting

No Fixed Lighting

	Name	Efficacy	Power	Capacity	Count
	Low energy Lighting	85.00	5.00	425.00	10

## 24.0 Main Heating 1

Percentage of Heat	SAP table	%
Database Ref. No.	100.00	
Fuel Type	0	
SAP Code	Electricity	
In Winter	691	
In Summer	100.00	
Controls SAP Code	194.18	
Delayed Start Stat	2603	
Burner Control	No	
HETAS approved System	Modulating	
Is MHS Pumped	No	
Heating Pump Age	Pump in heated space	
Heat Emitter	2013 or later	
Underfloor Heating	Radiators	
Flow Temperature	Yes - Pipes in thin screed	
Flow Temperature Value	Enter value	

## 25.0 Main Heating 2

Percentage of Heat	Database	%
Database Ref. No.	0.00	
Fuel Type	100834	
SAP Code	Electricity	
In Winter	0	
In Summer	303.77	
Model Name	194.18	
	Compact P	

# Summary for Input Data

Manufacturer	Nilan AS										
Controls	2100										
Delayed Start Stat	No										
HETAS approved System	No										
Flow Temperature	Enter value										
<b>26.0 Heat Networks</b>											
27.0 Secondary Heating	None										
<b>28.0 Water Heating</b>											
Water Heating	Main Heating 2										
SAP Code	914										
Flue Gas Heat Recovery System	No										
Waste Water Heat Recovery Instantaneous System 1	No										
Waste Water Heat Recovery Instantaneous System 2	No										
Waste Water Heat Recovery Storage System	No										
Solar Panel	No										
Water use <= 125 litres/person/day	Yes										
Summer Immersion	No										
Cold Water Source	From mains										
Bath Count	1										
Baths connected to WWHRS	0										
Supplementary Immersion	No										
Immersion Only Heating Hot Water	No										
<b>28.1 Showers</b>											
Description	Shower Type	Flow Rate [l/min]	Rated Power [kW]	Connected	Connected To						
8 lpm	Unknown	8.00		No							
<b>28.3 Waste Water Heat Recovery System</b>											
<b>29.0 Hot Water Cylinder</b>		Internal Store									
Cylinder Stat	No										
Cylinder In Heated Space	No										
Independent Time Control	No										
Insulation Type	Measured Loss										
Insulation Thickness	0										
Cylinder Volume	180.00	L									
Loss	0.84	kWh/day									
In Airing Cupboard	No										
<b>31.0 Thermal Store</b>		None									
<b>34.0 Small-scale Hydro</b>		None									
Electricity Generated	0.00										
Apportioned	0.00	kWh/Year									
Connected to dwelling's electricity meter	Yes										
Electricity Generation	Annual										
Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
<b>Recommendations</b>											
Lower cost measures											
None											
Further measures to achieve even higher standards											
None											

# Predicted Energy Assessment


C14-01-13, Horsham Enterprise Park

Dwelling type:  
Date of assessment:  
Produced by:  
Total floor area:  
DRRN:

Flat, Mid-Terrace  
15/10/2025  
Charlotte Russell  
50.73 m<sup>2</sup>

This document is a Predicted Energy Assessment for properties marketed when they are incomplete. It includes a predicted energy rating which might not represent the final energy rating of the property on completion. Once the property is completed, this rating will be updated and an official Energy Performance Certificate will be created for the property. This will include more detailed information about the energy performance of the completed property.

The energy performance has been assessed using the Government approved SAP 10 methodology and is rated in terms of the energy use per square meter of floor area; the energy efficiency is based on fuel costs and the environmental impact is based on carbon dioxide (CO<sub>2</sub>) emissions.



The energy efficiency rating is a measure of the overall efficiency of a home. The higher the rating the more energy efficient the home is and the lower the fuel bills are likely to be.

The environmental impact rating is a measure of a home's impact on the environment in terms of carbon dioxide (CO<sub>2</sub>) emissions. The higher the rating the less impact it has on the environment.

# Thermal Bridging

Property Reference	C14-01-13		Issued on Date	15/10/2025		
Assessment Reference	Design V1		Prop Type Ref	Mid-Terrace Flat		
Property	C14-01-13, Horsham Enterprise Park					
SAP Rating	77 C	DER	7.04	TER	17.36	
Environmental	95 A	% DER < TER		59.45		
CO <sub>2</sub> Emissions (t/year)	0.3	DFEE	42.94	TFEE	46.51	
Compliance Check	See BREL	% DFEE < TFEE		7.67		
% DPER < TPER	20.81	DPER	73.39	TPER	92.68	
Assessor Details	Miss Charlotte Russell			Assessor ID	DK97-0001	
Client						
	Junction details	Source Type	Psi (W/mK)	Length (m)	Result	Reference
External wall	E2 Other lintels (including other steel lintels)	Independently assessed	0.022	4.63	0.10	RCD
External wall	E3 Sill	Independently assessed	0.016	1.81	0.03	RCD
External wall	E4 Jamb	Independently assessed	0.011	12.98	0.14	RCD
External wall	E7 Party floor between dwellings (in blocks of flats)	Independently assessed	0.053	23.68	1.26	RCD
External wall	E16 Corner (normal)	Independently assessed	0.051	3.20	0.16	RCD
Party wall	P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	0.000	21.59	0.00	Default
External wall	E18 Party wall between dwellings	Independently assessed	0.057	16.00	0.91	RCD
External wall	E17 Corner (inverted – internal area greater than external area)	Independently assessed	-0.104	3.20	-0.33	RCD
External wall	E25 Staggered party wall between dwellings	Table K1 - Default	0.240	0.00	0.00	E25 - Default
External wall	E20 Exposed floor (normal)	Independently assessed	0.054	9.88	0.53	RCD
Party wall	P7 Party Wall - Exposed floor (normal)	Table K1 - Default	0.480	7.89	3.79	P7 - Default
Party wall	P8 Party Wall - Exposed floor (inverted)	Table K1 - Default	0.480	6.85	3.29	P8 - Default

Total: 111.71 W/mK:

Y-Value: 0.12 W/m<sup>2</sup>K:

# Summary for Input Data



Property Reference	C14-02-01	Issued on Date	15/10/2025
Assessment Reference	Design V1	Prop Type Ref	C14-02-01
Property	C14-02-01, Horsham Enterprise Park		
SAP Rating	77 C	DER	5.66
Environmental	95 A	% DER < TER	14.19
CO <sub>2</sub> Emissions (t/year)	0.42	DFEE	37.36
Compliance Check	See BREL	% DFEE < TFEE	60.11
% DPER < TPER	21.70	DPER	44.28
TPER	58.90	TPER	15.63
TPER	75.23		

Assessor Details	Miss Charlotte Russell	Assessor ID	DK97-0001
Client			

## SUMMARY FOR INPUT DATA FOR: New Build (As Designed)

Orientation	Southwest
Property Tenure	ND
Transaction Type	6
Terrain Type	Suburban
1.0 Property Type	Flat, End-Terrace
Position of Flat	Mid-floor flat
Which Floor	2
2.0 Number of Storeys	1
3.0 Date Built	2025
3.0 Property Age Band	L
4.0 Sheltered Sides	2
5.0 Sunlight/Shade	Average or unknown
6.0 Thermal Mass Parameter	Precise calculation
Thermal Mass	245.66
	kJ/m <sup>2</sup> K
7.0 Electricity Tariff	Standard
Smart electricity meter fitted	Yes
Smart gas meter fitted	No

7.0 Measurements	Heat Loss Perimeter	Internal Floor Area	Average Storey Height
	Ground floor: 35.90 m	88.75 m <sup>2</sup>	3.20 m

8.0 Living Area	33.43	m <sup>2</sup>
-----------------	-------	----------------

9.0 External Walls	Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Res	Shelter	Openings	Area Calculation Type
External Wall	External Wall	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.15	110.00	67.49	53.61	0.00	None	13.88	Enter Gross Area
Sheltered	Sheltered	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.18	110.00	47.39	45.27	0.90	Stairwell Access Corridor 4	2.12	Enter Gross Area

9.1 Party Walls	Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )	Shelter Res	Shelter
Party Wall	Party Wall	Filled Cavity with Edge Sealing	Single plasterboard on dabs both sides, lightweight aggregate blocks, cavity or cavity fill	0.00	110.00	21.44	0.00	None

9.2 Internal Walls	Description	Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Internal Walls	Internal Walls	Plasterboard on timber frame	9.00	184.14

10.0 External Roofs	Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Code	Shelter Factor	Shelter Calculation Type	Openings
External Roof	External Roof	External Flat Roof	Plasterboard, insulated flat roof	0.11	9.00	6.13	6.13	None	0.00	Enter Gross Area	0.00

# Summary for Input Data

## 10.1 Party Ceilings

Description	Construction	Kappa (kJ/m²K)	Area (m²)
Party Ceiling	Precast concrete planks floor, screed, carpeted	30.00	82.61

## 11.1 Party Floors

Description	Storey Index	Construction	Kappa (kJ/m²K)	Area (m²)
Party Floor	Lowest occupied	Precast concrete planks floor, screed, carpeted	40.00	88.75

## 12.0 Opening Types

Description	Data Source	Type	Glazing	Glazing Gap	Filling Type	G-value	Frame Type	Frame Factor	U Value (W/m²K)
Solid Door Glazing	Manufacturer	Solid Door Window	Double Low-E Soft 0.05			0.00 0.63		0.80	1.20 1.20

## 13.0 Openings

Name	Opening Type	Location	Orientation	Area (m²)	Pitch
FSD	Solid Door	Sheltered	South West	2.12	0
RW	Glazing	External Wall	North East	8.91	0
RGD	Glazing	External Wall	North East	4.97	0

## 14.0 Conservatory

None

## 15.0 Draught Proofing

100

%

## 16.0 Draught Lobby

No

## 17.0 Thermal Bridging

Calculate Bridges

### 17.1 List of Bridges

Bridge Type	Source Type	Length	Psi	Adjusted Reference:	Imported
E2 Other lintels (including other steel lintels)	Independently assessed	8.25	0.02	RCD	No
E3 Sill	Independently assessed	5.43	0.02	RCD	No
E4 Jamb	Independently assessed	19.54	0.01	RCD	No
E7 Party floor between dwellings (in blocks of flats)	Independently assessed	50.41	0.05	RCD	No
E16 Corner (normal)	Independently assessed	16.00	0.05	RCD	No
P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	13.12	0.00	Default	No
E18 Party wall between dwellings	Independently assessed	6.40	0.06	RCD	No
E25 Staggered party wall between dwellings	Independently assessed	0.00	0.05	RCD	No
E14 Flat roof	Independently assessed	21.39	0.04	ROI	No
P4 Party wall - Roof (insulation at ceiling level)	Table K1 - Default	0.28	0.48	0.48	No
E24 Eaves (insulation at ceiling level - inverted)	Table K1 - Default	20.51	0.15	0.15	No
E17 Corner (inverted - internal area greater than external area)	Table K1 - Default	6.40	0.00	0.00	No

Y-value

0.07

W/m²K

Description

Bridge

## 19.0 Mechanical Ventilation

### Mechanical Ventilation

Mechanical Ventilation System Present	Yes
Approved Installation	Yes
Mechanical Ventilation data Type	Database
Type	Balanced mechanical ventilation with heat recovery
MV Reference Number	500500
Configuration	2
MVHR Duct Insulated	Uninsulated Ducts
Manufacturer SFP	0.59
Duct Type	Rigid
MVHR Efficiency	89.00
Wet Rooms	2
SFP from Installer Commissioning Certificate	No
MVHR System Location	Inside heated envelope (installed exclusively)
Duct Installation Specification	Level 2

## 19.1 Mechanical extract ventilation - Decentralised

SFP	Fan/Room Type	Count
0.13	In Room Fan	1
	Kitchen	
0.11	In Room Fan Other	3
	Wet Room	

# Summary for Input Data

0.00	In Duct Fan Kitchen	0
0.00	In Duct Fan Other	0
	Wet Room	
0.10	Through Wall Fan	0
	Kitchen	
0.10	Through Wall Fan	0
	Other Wet Room	

## 20.0 Fans, Open Fireplaces, Flues

Number of open chimneys	0
Number of open flues	0
Number of chimneys/flues attached to closed fire	0
Number of flues attached to solid fuel boiler	0
Number of flues attached to other heater	0
Number of blocked chimneys	0
Number of intermittent extract fans	0
Number of passive vents	0
Number of flueless gas fires	0

## 21.0 Fixed Cooling System

22.0 Pressure Testing	Yes
-----------------------	-----

Designed AP <sub>50</sub>	3.00	m <sup>3</sup> /(h.m <sup>2</sup> ) @ 50 Pa
Property Tested?	Yes	
Test Method	Blower Door	

## 22.0 Lighting

No Fixed Lighting	No				
	Name	Efficacy	Power	Capacity	Count
	Low energy Lighting	85.00	5.00	425.00	10

## 24.0 Main Heating 1

Percentage of Heat	100.00	%
Database Ref. No.	0	
Fuel Type	Electricity	
SAP Code	691	
In Winter	100.00	
In Summer	194.18	
Controls SAP Code	2603	
Delayed Start Stat	No	
Burner Control	Modulating	
HETAS approved System	No	
Is MHS Pumped	Pump in heated space	
Heating Pump Age	2013 or later	
Heat Emitter	Radiators	
Underfloor Heating	Yes - Pipes in thin screed	
Flow Temperature	Enter value	
Flow Temperature Value	55.00	

## 25.0 Main Heating 2

Percentage of Heat	0.00	%
Database Ref. No.	100834	
Fuel Type	Electricity	
SAP Code	0	
In Winter	379.02	
In Summer	194.18	
Model Name	Compact P	

# Summary for Input Data

Manufacturer	Nilan AS										
Controls	2100										
Delayed Start Stat	No										
HETAS approved System	No										
Flow Temperature	Enter value										
<b>26.0 Heat Networks</b>											
27.0 Secondary Heating	None										
<b>28.0 Water Heating</b>											
Water Heating	Main Heating 2										
SAP Code	914										
Flue Gas Heat Recovery System	No										
Waste Water Heat Recovery Instantaneous System 1	No										
Waste Water Heat Recovery Instantaneous System 2	No										
Waste Water Heat Recovery Storage System	No										
Solar Panel	No										
Water use <= 125 litres/person/day	Yes										
Summer Immersion	No										
Cold Water Source	From mains										
Bath Count	1										
Baths connected to WWHRS	0										
Supplementary Immersion	No										
Immersion Only Heating Hot Water	No										
<b>28.1 Showers</b>											
Description	Shower Type	Flow Rate [l/min]	Rated Power [kW]	Connected	Connected To						
8 lpm	Unknown	8.00		No							
<b>28.3 Waste Water Heat Recovery System</b>											
<b>29.0 Hot Water Cylinder</b>		Internal Store									
Cylinder Stat	No										
Cylinder In Heated Space	No										
Independent Time Control	No										
Insulation Type	Measured Loss										
Insulation Thickness	0										
Cylinder Volume	180.00	L									
Loss	0.84	kWh/day									
In Airing Cupboard	No										
<b>31.0 Thermal Store</b>		None									
<b>34.0 Small-scale Hydro</b>		None									
Electricity Generated	0.00										
Apportioned	0.00	kWh/Year									
Connected to dwelling's electricity meter	Yes										
Electricity Generation	Annual										
Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
<b>Recommendations</b>											
Lower cost measures											
None											
Further measures to achieve even higher standards											
None											

# Predicted Energy Assessment


C14-02-01, Horsham Enterprise Park

Dwelling type:  
Date of assessment:  
Produced by:  
Total floor area:  
DRRN:

Flat, End-Terrace  
15/10/2025  
Charlotte Russell  
88.75 m<sup>2</sup>

This document is a Predicted Energy Assessment for properties marketed when they are incomplete. It includes a predicted energy rating which might not represent the final energy rating of the property on completion. Once the property is completed, this rating will be updated and an official Energy Performance Certificate will be created for the property. This will include more detailed information about the energy performance of the completed property.

The energy performance has been assessed using the Government approved SAP 10 methodology and is rated in terms of the energy use per square meter of floor area; the energy efficiency is based on fuel costs and the environmental impact is based on carbon dioxide (CO<sub>2</sub>) emissions.



The energy efficiency rating is a measure of the overall efficiency of a home. The higher the rating the more energy efficient the home is and the lower the fuel bills are likely to be.

The environmental impact rating is a measure of a home's impact on the environment in terms of carbon dioxide (CO<sub>2</sub>) emissions. The higher the rating the less impact it has on the environment.

# Thermal Bridging

Property Reference	C14-02-01		Issued on Date	15/10/2025
Assessment Reference	Design V1		Prop Type Ref	End-Terrace Flat
Property	C14-02-01, Horsham Enterprise Park			
SAP Rating	77 C	DER	5.66	TER
Environmental	95 A	% DER < TER		60.11
CO <sub>2</sub> Emissions (t/year)	0.42	DFEE	37.36	TFEE
Compliance Check	See BREL	% DFEE < TFEE		15.63
% DPER < TPER	21.70	DPER	58.90	TPER
Assessor Details	Miss Charlotte Russell			Assessor ID
Client				

	Junction details	Source Type	Psi (W/mK)	Length (m)	Result	Reference
External wall	E2 Other lintels (including other steel lintels)	Independently assessed	0.022	8.25	0.18	RCD
External wall	E3 Sill	Independently assessed	0.016	5.43	0.09	RCD
External wall	E4 Jamb	Independently assessed	0.011	19.54	0.21	RCD
External wall	E7 Party floor between dwellings (in blocks of flats)	Independently assessed	0.053	50.41	2.67	RCD
External wall	E16 Corner (normal)	Independently assessed	0.051	16.00	0.82	RCD
Party wall	P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	0.000	13.12	0.00	Default
External wall	E18 Party wall between dwellings	Independently assessed	0.057	6.40	0.36	RCD
External wall	E25 Staggered party wall between dwellings	Independently assessed	0.046	0.00	0.00	RCD
External wall	E14 Flat roof	Independently assessed	0.040	21.39	0.86	ROI
Party wall	P4 Party wall - Roof (insulation at ceiling level)	Table K1 - Default	0.480	0.28	0.13	Default
External wall	E24 Eaves (insulation at ceiling level - inverted)	Table K1 - Default	0.150	20.51	3.08	
External wall	E17 Corner (inverted – internal area greater than external area)	Table K1 - Default	0.000	6.40	0.00	

Total: 167.73 W/mK:

Y-Value: 0.07 W/m<sup>2</sup>K:

# Summary for Input Data



Property Reference	C14-02-03	Issued on Date	15/10/2025
Assessment Reference	Design V1	Prop Type Ref	C14-02-03
Property	C14-02-03, Horsham Enterprise Park		
SAP Rating	83 B	DER	5.14
Environmental	97 A	% DER < TER	14.67
CO <sub>2</sub> Emissions (t/year)	0.22	DFEE	29.20
Compliance Check	See BREL	% DFEE < TFEE	64.96
% DPER < TPER	30.95	DPER	33.89
		TPER	13.84
			78.24

Assessor Details	Miss Charlotte Russell	Assessor ID	DK97-0001
Client			

## SUMMARY FOR INPUT DATA FOR: New Build (As Designed)

Orientation	Northeast
Property Tenure	ND
Transaction Type	6
Terrain Type	Suburban
1.0 Property Type	Flat, Mid-Terrace
Position of Flat	Mid-floor flat
Which Floor	2
2.0 Number of Storeys	1
3.0 Date Built	2025
3.0 Property Age Band	L
4.0 Sheltered Sides	2
5.0 Sunlight/Shade	Average or unknown
6.0 Thermal Mass Parameter	Precise calculation
Thermal Mass	284.81
	kJ/m <sup>2</sup> K
7.0 Electricity Tariff	Standard
Smart electricity meter fitted	Yes
Smart gas meter fitted	No

7.0 Measurements	Heat Loss Perimeter	Internal Floor Area	Average Storey Height
	Ground floor: 16.78 m	50.73 m <sup>2</sup>	3.20 m

8.0 Living Area	23.56	m <sup>2</sup>
-----------------	-------	----------------

9.0 External Walls	Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Res	Shelter	Openings	Area Calculation Type
External Wall	External Wall	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.15	110.00	21.50	13.56	0.00	None	7.94	Enter Gross Area
Sheltered	Sheltered	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.18	110.00	32.19	30.07	0.90	Stairwell Access Corridor 4	2.12	Enter Gross Area

9.1 Party Walls	Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )	Shelter Res	Shelter
	Party Wall	Filled Cavity with Edge Sealing	Single plasterboard on dabs both sides, lightweight aggregate blocks, cavity or cavity fill	0.00	110.00	47.17	0.00	None

9.2 Internal Walls	Description	Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
	Internal Walls	Plasterboard on timber frame	9.00	80.78

10.0 External Roofs	Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Code	Shelter Factor	Shelter Type	Calculation Openings
	External Roof	External Flat Roof	Plasterboard, insulated flat roof	0.11	9.00	10.48	10.48	None	0.00	Enter Gross Area	0.00

# Summary for Input Data

## 10.1 Party Ceilings

Description	Construction	Kappa (kJ/m²K)	Area (m²)
Party Ceiling	Precast concrete planks floor, screed, carpeted	30.00	40.25

## 11.1 Party Floors

Description	Storey Index	Construction	Kappa (kJ/m²K)	Area (m²)
Party Floor	Lowest occupied	Precast concrete planks floor, screed, carpeted	40.00	50.73

## 12.0 Opening Types

Description	Data Source	Type	Glazing	Glazing Gap	Filling Type	G-value	Frame Type	Frame Factor	U Value (W/m²K)
Solid Door Glazing	Manufacturer	Solid Door Window	Double Low-E Soft 0.05			0.00 0.63		0.80	1.20 1.20

## 13.0 Openings

Name	Opening Type	Location	Orientation	Area (m²)	Pitch
FSD	Solid Door	Sheltered	North East	2.12	0
RW	Glazing	External Wall	South West	2.97	0
RGD	Glazing	External Wall	South West	4.97	0

## 14.0 Conservatory

None

## 15.0 Draught Proofing

100

%

## 16.0 Draught Lobby

No

## 17.0 Thermal Bridging

Calculate Bridges

### 17.1 List of Bridges

Bridge Type	Source Type	Length	Psi	Adjusted Reference:	Imported
E2 Other lintels (including other steel lintels)	Independently assessed	4.63	0.02	0.02 RCD	No
E3 Sill	Independently assessed	1.81	0.02	0.02 RCD	No
E4 Jamb	Independently assessed	12.98	0.01	0.01 RCD	No
E7 Party floor between dwellings (in blocks of flats)	Independently assessed	26.84	0.05	0.05 RCD	No
E16 Corner (normal)	Independently assessed	3.20	0.05	0.05 RCD	No
P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	26.36	0.00	0.00 Default	No
E18 Party wall between dwellings	Independently assessed	16.00	0.06	0.06 RCD	No
E25 Staggered party wall between dwellings	Independently assessed	0.00	0.05	0.05 RCD	No
E14 Flat roof	Independently assessed	6.72	0.04	0.04 ROI	No
P4 Party wall - Roof (insulation at ceiling level)	Table K1 - Default	3.12	0.48	0.48 Default	No
E24 Eaves (insulation at ceiling level - inverted)	Table K1 - Default	6.72	0.15	0.15	No
E17 Corner (inverted - internal area greater than external area)	Table K1 - Default	3.20	0.00	0.00	No

Y-value

0.09

W/m²K

Description

Bridge

## 19.0 Mechanical Ventilation

### Mechanical Ventilation

Mechanical Ventilation System Present	Yes
Approved Installation	Yes
Mechanical Ventilation data Type	Database
Type	Balanced mechanical ventilation with heat recovery
MV Reference Number	500500
Configuration	2
MVHR Duct Insulated	Uninsulated Ducts
Manufacturer SFP	0.59
Duct Type	Rigid
MVHR Efficiency	89.00
Wet Rooms	2
SFP from Installer Commissioning Certificate	No
MVHR System Location	Inside heated envelope (installed exclusively)
Duct Installation Specification	Level 2

## 19.1 Mechanical extract ventilation - Decentralised

SFP	Fan/Room Type	Count
0.13	In Room Fan	1
	Kitchen	
0.11	In Room Fan Other	3
	Wet Room	

# Summary for Input Data

0.00	In Duct Fan Kitchen	0
0.00	In Duct Fan Other	0
	Wet Room	
0.10	Through Wall Fan	0
	Kitchen	
0.10	Through Wall Fan	0
	Other Wet Room	

## 20.0 Fans, Open Fireplaces, Flues

Number of open chimneys	0
Number of open flues	0
Number of chimneys/flues attached to closed fire	0
Number of flues attached to solid fuel boiler	0
Number of flues attached to other heater	0
Number of blocked chimneys	0
Number of intermittent extract fans	0
Number of passive vents	0
Number of flueless gas fires	0

## 21.0 Fixed Cooling System

22.0 Pressure Testing	Yes
-----------------------	-----

Designed AP <sub>50</sub>	3.00	m <sup>3</sup> /(h.m <sup>2</sup> ) @ 50 Pa
Property Tested?	Yes	
Test Method	Blower Door	

## 22.0 Lighting

No Fixed Lighting	No				
	Name	Efficacy	Power	Capacity	Count
	Low energy Lighting	85.00	5.00	425.00	10

## 24.0 Main Heating 1

Percentage of Heat	100.00	%
Database Ref. No.	0	
Fuel Type	Electricity	
SAP Code	691	
In Winter	100.00	
In Summer	194.18	
Controls SAP Code	2603	
Delayed Start Stat	No	
Burner Control	Modulating	
HETAS approved System	No	
Is MHS Pumped	Pump in heated space	
Heating Pump Age	2013 or later	
Heat Emitter	Radiators	
Underfloor Heating	Yes - Pipes in thin screed	
Flow Temperature	Enter value	
Flow Temperature Value	55.00	

## 25.0 Main Heating 2

Percentage of Heat	0.00	%
Database Ref. No.	100834	
Fuel Type	Electricity	
SAP Code	0	
In Winter	300.41	
In Summer	194.18	
Model Name	Compact P	

# Summary for Input Data

Manufacturer	Nilan AS										
Controls	2100										
Delayed Start Stat	No										
HETAS approved System	No										
Flow Temperature	Enter value										
<b>26.0 Heat Networks</b>											
27.0 Secondary Heating	None										
<b>28.0 Water Heating</b>											
Water Heating	Main Heating 2										
SAP Code	914										
Flue Gas Heat Recovery System	No										
Waste Water Heat Recovery Instantaneous System 1	No										
Waste Water Heat Recovery Instantaneous System 2	No										
Waste Water Heat Recovery Storage System	No										
Solar Panel	No										
Water use <= 125 litres/person/day	Yes										
Summer Immersion	No										
Cold Water Source	From mains										
Bath Count	1										
Baths connected to WWHRS	0										
Supplementary Immersion	No										
Immersion Only Heating Hot Water	No										
<b>28.1 Showers</b>											
Description	Shower Type	Flow Rate [l/min]	Rated Power [kW]	Connected	Connected To						
8 lpm	Unknown	8.00		No							
<b>28.3 Waste Water Heat Recovery System</b>											
<b>29.0 Hot Water Cylinder</b>		Internal Store									
Cylinder Stat	No										
Cylinder In Heated Space	No										
Independent Time Control	No										
Insulation Type	Measured Loss										
Insulation Thickness	0										
Cylinder Volume	180.00	L									
Loss	0.84	kWh/day									
In Airing Cupboard	No										
<b>31.0 Thermal Store</b>		None									
<b>34.0 Small-scale Hydro</b>		None									
Electricity Generated	0.00										
Apportioned	0.00	kWh/Year									
Connected to dwelling's electricity meter	Yes										
Electricity Generation	Annual										
Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
<b>Recommendations</b>											
Lower cost measures											
None											
Further measures to achieve even higher standards											
None											

# Predicted Energy Assessment


C14-02-03, Horsham Enterprise Park

Dwelling type:  
Date of assessment:  
Produced by:  
Total floor area:  
DRRN:

Flat, Mid-Terrace  
15/10/2025  
Charlotte Russell  
50.73 m<sup>2</sup>

This document is a Predicted Energy Assessment for properties marketed when they are incomplete. It includes a predicted energy rating which might not represent the final energy rating of the property on completion. Once the property is completed, this rating will be updated and an official Energy Performance Certificate will be created for the property. This will include more detailed information about the energy performance of the completed property.

The energy performance has been assessed using the Government approved SAP 10 methodology and is rated in terms of the energy use per square meter of floor area; the energy efficiency is based on fuel costs and the environmental impact is based on carbon dioxide (CO<sub>2</sub>) emissions.



The energy efficiency rating is a measure of the overall efficiency of a home. The higher the rating the more energy efficient the home is and the lower the fuel bills are likely to be.

The environmental impact rating is a measure of a home's impact on the environment in terms of carbon dioxide (CO<sub>2</sub>) emissions. The higher the rating the less impact it has on the environment.

# Thermal Bridging

Property Reference	C14-02-03		Issued on Date	15/10/2025
Assessment Reference	Design V1		Prop Type Ref	Mid-Terrace Flat
Property	C14-02-03, Horsham Enterprise Park			
SAP Rating	83 B	DER	5.14	TER
Environmental	97 A	% DER < TER		64.96
CO <sub>2</sub> Emissions (t/year)	0.22	DFEE	29.20	TFEE
Compliance Check	See BREL	% DFEE < TFEE		13.84
% DPER < TPER	30.95	DPER	54.03	TPER
Assessor Details	Miss Charlotte Russell			Assessor ID
Client				

	Junction details	Source Type	Psi (W/mK)	Length (m)	Result	Reference
External wall	E2 Other lintels (including other steel lintels)	Independently assessed	0.022	4.63	0.10	RCD
External wall	E3 Sill	Independently assessed	0.016	1.81	0.03	RCD
External wall	E4 Jamb	Independently assessed	0.011	12.98	0.14	RCD
External wall	E7 Party floor between dwellings (in blocks of flats)	Independently assessed	0.053	26.84	1.42	RCD
External wall	E16 Corner (normal)	Independently assessed	0.051	3.20	0.16	RCD
Party wall	P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	0.000	26.36	0.00	Default
External wall	E18 Party wall between dwellings	Independently assessed	0.057	16.00	0.91	RCD
External wall	E25 Staggered party wall between dwellings	Independently assessed	0.046	0.00	0.00	RCD
External wall	E14 Flat roof	Independently assessed	0.040	6.72	0.27	ROI
Party wall	P4 Party wall - Roof (insulation at ceiling level)	Table K1 - Default	0.480	3.12	1.50	Default
External wall	E24 Eaves (insulation at ceiling level - inverted)	Table K1 - Default	0.150	6.72	1.01	
External wall	E17 Corner (inverted – internal area greater than external area)	Table K1 - Default	0.000	3.20	0.00	

Total: 111.58 W/mK:

Y-Value: 0.09 W/m<sup>2</sup>K:

# Summary for Input Data



Property Reference	C14-02-06			Issued on Date	15/10/2025					
Assessment Reference	Design V1		Prop Type Ref	C14-02-06						
Property	C14-02-06, Horsham Enterprise Park									
SAP Rating	80 C	DER	5.17	TER	13.46					
Environmental	96 A	% DER < TER			61.59					
CO <sub>2</sub> Emissions (t/year)	0.32	DFEE	32.74	TFEE	37.59					
Compliance Check	See BREL	% DFEE < TFEE			12.89					
% DPER < TPER	24.31	DPER	53.98	TPER	71.32					
Assessor Details	Miss Charlotte Russell			Assessor ID	DK97-0001					
Client										
<b>SUMMARY FOR INPUT DATA FOR: New Build (As Designed)</b>										
Orientation	Southwest									
Property Tenure	ND									
Transaction Type	6									
Terrain Type	Suburban									
1.0 Property Type	Flat, Mid-Terrace									
Position of Flat	Mid-floor flat									
Which Floor	2									
2.0 Number of Storeys	1									
3.0 Date Built	2025									
3.0 Property Age Band	L									
4.0 Sheltered Sides	2									
5.0 Sunlight/Shade	Average or unknown									
6.0 Thermal Mass Parameter	Precise calculation									
Thermal Mass	233.08			kJ/m <sup>2</sup> K						
7.0 Electricity Tariff	Standard									
Smart electricity meter fitted	Yes									
Smart gas meter fitted	No									
7.0 Measurements										
		Heat Loss Perimeter		Internal Floor Area		Average Storey Height				
		Ground floor: 21.83 m		73.71 m <sup>2</sup>		3.20 m				
8.0 Living Area	25.31			m <sup>2</sup>						
9.0 External Walls										
Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Res	Shelter	Openings	Area Calculation Type
External Wall	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.15	110.00	51.01	35.64	0.00	None	15.37	Enter Gross Area
Sheltered	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.18	110.00	18.85	16.73	0.90	Stairwell Access Corridor 4	2.12	Enter Gross Area
9.1 Party Walls										
Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )	Shelter Res	Shelter			
Party Wall	Filled Cavity with Edge Sealing	Single plasterboard on dabs both sides, lightweight aggregate blocks, cavity or cavity fill	0.00	110.00	44.00	0.00	None			
9.2 Internal Walls										
Description							Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )		
Internal Walls	Plasterboard on timber frame						9.00	165.42		
10.0 External Roofs										
Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Code	Shelter Factor	Calulation Type	Openings
External Roof	External Flat Roof	Plasterboard, insulated flat roof	0.11	9.00	16.37	16.37	None	0.00	Enter Gross Area	0.00

# Summary for Input Data

## 10.1 Party Ceilings

Description	Construction	Kappa (kJ/m²K)	Area (m²)
Party Ceiling	Precast concrete planks floor, screed, carpeted	30.00	49.87

## 11.1 Party Floors

Description	Storey Index	Construction	Kappa (kJ/m²K)	Area (m²)
Party Floor	Lowest occupied	Precast concrete planks floor, screed, carpeted	40.00	73.71

## 12.0 Opening Types

Description	Data Source	Type	Glazing	Glazing Gap	Filling Type	G-value	Frame Type	Frame Factor	U Value (W/m²K)
Solid Door Glazing	Manufacturer	Solid Door Window	Double Low-E Soft 0.05			0.00 0.63		0.80	1.20 1.20

## 13.0 Openings

Name	Opening Type	Location	Orientation	Area (m²)	Pitch
FSD	Solid Door	Sheltered	South West	2.12	0
RSW	Glazing	External Wall	South East	1.49	0
RSGD	Glazing	External Wall	South East	4.97	0
LSW	Glazing	External Wall	North West	8.91	0

## 14.0 Conservatory

None

## 15.0 Draught Proofing

100

%

## 16.0 Draught Lobby

No

## 17.0 Thermal Bridging

Calculate Bridges

### 17.1 List of Bridges

Bridge Type	Source Type	Length	Psi	Adjusted Reference:	Imported
E2 Other lintels (including other steel lintels)	Independently assessed	9.16	0.02	RCD	No
E3 Sill	Independently assessed	6.34	0.02	RCD	No
E4 Jamb	Independently assessed	22.82	0.01	RCD	No
E7 Party floor between dwellings (in blocks of flats)	Independently assessed	34.14	0.05	RCD	No
E16 Corner (normal)	Independently assessed	3.20	0.05	RCD	No
P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	24.06	0.00	Default	No
E18 Party wall between dwellings	Independently assessed	12.80	0.06	RCD	No
E25 Staggered party wall between dwellings	Independently assessed	0.00	0.05	RCD	No
E14 Flat roof	Independently assessed	9.52	0.04	ROI	No
P4 Party wall - Roof (insulation at ceiling level)	Table K1 - Default	3.44	0.48	0.48	No
E24 Eaves (insulation at ceiling level - inverted)	Table K1 - Default	9.52	0.15	0.15	No
E17 Corner (inverted – internal area greater than external area)	Table K1 - Default	3.20	0.00	0.00	No

Y-value

0.08

W/m²K

Description

Bridge

## 19.0 Mechanical Ventilation

### Mechanical Ventilation

Mechanical Ventilation System Present	Yes
Approved Installation	Yes
Mechanical Ventilation data Type	Database
Type	Balanced mechanical ventilation with heat recovery
MV Reference Number	500500
Configuration	2
MVHR Duct Insulated	Uninsulated Ducts
Manufacturer SFP	0.59
Duct Type	Rigid
MVHR Efficiency	89.00
Wet Rooms	2
SFP from Installer Commissioning Certificate	No
MVHR System Location	Inside heated envelope (installed exclusively)
Duct Installation Specification	Level 2

## 19.1 Mechanical extract ventilation - Decentralised

SFP	Fan/Room Type	Count
0.13	In Room Fan	1

# Summary for Input Data

0.11	In Room Fan Other	3
0.00	Wet Room	
0.00	In Duct Fan Kitchen	0
0.00	In Duct Fan Other	0
0.10	Wet Room	
0.10	Through Wall Fan	0
	Kitchen	
0.10	Through Wall Fan	0
	Other Wet Room	

## 20.0 Fans, Open Fireplaces, Flues

Number of open chimneys	0
Number of open flues	0
Number of chimneys/flues attached to closed fire	0
Number of flues attached to solid fuel boiler	0
Number of flues attached to other heater	0
Number of blocked chimneys	0
Number of intermittent extract fans	0
Number of passive vents	0
Number of flueless gas fires	0

## 21.0 Fixed Cooling System

21.0 Fixed Cooling System	No
22.0 Pressure Testing	Yes
Designed AP <sub>50</sub>	3.00
Property Tested?	Yes
Test Method	Blower Door

## 22.0 Lighting

No Fixed Lighting	No				
		Name	Efficacy	Power	Capacity
		Low energy Lighting	85.00	5.00	425.00
					Count
					10

## 24.0 Main Heating 1

Percentage of Heat	100.00	%
Database Ref. No.	0	
Fuel Type	Electricity	
SAP Code	691	
In Winter	100.00	
In Summer	194.18	
Controls SAP Code	2603	
Delayed Start Stat	No	
Burner Control	Modulating	
HETAS approved System	No	
Is MHS Pumped	Pump in heated space	
Heating Pump Age	2013 or later	
Heat Emitter	Radiators	
Underfloor Heating	Yes - Pipes in thin screed	
Flow Temperature	Enter value	
Flow Temperature Value	55.00	

## 25.0 Main Heating 2

Percentage of Heat	0.00	%
Database Ref. No.	100834	
Fuel Type	Electricity	
SAP Code	0	
In Winter	340.44	

# Summary for Input Data

In Summer	194.18										
Model Name	Compact P										
Manufacturer	Nilan AS										
Controls	2100										
Delayed Start Stat	No										
HETAS approved System	No										
Flow Temperature	Enter value										
<b>26.0 Heat Networks</b>											
26.0 Heat Networks	None										
<b>27.0 Secondary Heating</b>											
27.0 Secondary Heating	None										
<b>28.0 Water Heating</b>											
Water Heating	Main Heating 2										
SAP Code	914										
Flue Gas Heat Recovery System	No										
Waste Water Heat Recovery Instantaneous System 1	No										
Waste Water Heat Recovery Instantaneous System 2	No										
Waste Water Heat Recovery Storage System	No										
Solar Panel	No										
Water use <= 125 litres/person/day	Yes										
Summer Immersion	No										
Cold Water Source	From mains										
Bath Count	1										
Baths connected to WWHRS	0										
Supplementary Immersion	No										
Immersion Only Heating Hot Water	No										
<b>28.1 Showers</b>											
Description	Shower Type	Flow Rate [l/min]	Rated Power [kW]	Connected	Connected To						
8 lpm	Unknown	8.00		No							
<b>28.3 Waste Water Heat Recovery System</b>											
<b>29.0 Hot Water Cylinder</b>											
Cylinder Stat	Internal Store										
Cylinder In Heated Space	No										
Independent Time Control	No										
Insulation Type	Measured Loss										
Insulation Thickness	0										
Cylinder Volume	180.00	L									
Loss	0.84	kWh/day									
In Airing Cupboard	No										
<b>31.0 Thermal Store</b>											
<b>34.0 Small-scale Hydro</b>											
Electricity Generated	0.00										
Apportioned	0.00	kWh/Year									
Connected to dwelling's electricity meter	Yes										
Electricity Generation	Annual										
Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
<b>Recommendations</b>											
Lower cost measures											
None											
Further measures to achieve even higher standards											

# Summary for Input Data



**None**

# Predicted Energy Assessment


C14-02-06, Horsham Enterprise Park

Dwelling type:  
Date of assessment:  
Produced by:  
Total floor area:  
DRRN:

Flat, Mid-Terrace  
15/10/2025  
Charlotte Russell  
73.71 m<sup>2</sup>

This document is a Predicted Energy Assessment for properties marketed when they are incomplete. It includes a predicted energy rating which might not represent the final energy rating of the property on completion. Once the property is completed, this rating will be updated and an official Energy Performance Certificate will be created for the property. This will include more detailed information about the energy performance of the completed property.

The energy performance has been assessed using the Government approved SAP 10 methodology and is rated in terms of the energy use per square meter of floor area; the energy efficiency is based on fuel costs and the environmental impact is based on carbon dioxide (CO<sub>2</sub>) emissions.



The energy efficiency rating is a measure of the overall efficiency of a home. The higher the rating the more energy efficient the home is and the lower the fuel bills are likely to be.

The environmental impact rating is a measure of a home's impact on the environment in terms of carbon dioxide (CO<sub>2</sub>) emissions. The higher the rating the less impact it has on the environment.

# Thermal Bridging

Property Reference	C14-02-06		Issued on Date	15/10/2025
Assessment Reference	Design V1		Prop Type Ref	Mid-Terrace Flat
Property	C14-02-06, Horsham Enterprise Park			
SAP Rating	80 C	DER	5.17	TER
Environmental	96 A	% DER < TER		61.59
CO <sub>2</sub> Emissions (t/year)	0.32	DFEE	32.74	TFEE
Compliance Check	See BREL	% DFEE < TFEE		12.89
% DPER < TPER	24.31	DPER	53.98	TPER
Assessor Details	Miss Charlotte Russell			Assessor ID
Client				

	Junction details	Source Type	Psi (W/mK)	Length (m)	Result	Reference
External wall	E2 Other lintels (including other steel lintels)	Independently assessed	0.022	9.16	0.20	RCD
External wall	E3 Sill	Independently assessed	0.016	6.34	0.10	RCD
External wall	E4 Jamb	Independently assessed	0.011	22.82	0.25	RCD
External wall	E7 Party floor between dwellings (in blocks of flats)	Independently assessed	0.053	34.14	1.81	RCD
External wall	E16 Corner (normal)	Independently assessed	0.051	3.20	0.16	RCD
Party wall	P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	0.000	24.06	0.00	Default
External wall	E18 Party wall between dwellings	Independently assessed	0.057	12.80	0.73	RCD
External wall	E25 Staggered party wall between dwellings	Independently assessed	0.046	0.00	0.00	RCD
External wall	E14 Flat roof	Independently assessed	0.040	9.52	0.38	ROI
Party wall	P4 Party wall - Roof (insulation at ceiling level)	Table K1 - Default	0.480	3.44	1.65	Default
External wall	E24 Eaves (insulation at ceiling level - inverted)	Table K1 - Default	0.150	9.52	1.43	
External wall	E17 Corner (inverted – internal area greater than external area)	Table K1 - Default	0.000	3.20	0.00	

Total: 138.20 W/mK:

Y-Value: 0.08 W/m<sup>2</sup>K:

# Summary for Input Data



Property Reference	C14-02-08			Issued on Date	15/10/2025					
Assessment Reference	Design V1		Prop Type Ref	C14-02-08						
Property	C14-02-08, Horsham Enterprise Park									
SAP Rating	77 C	DER	5.94	TER	14.87					
Environmental	95 A	% DER < TER			60.05					
CO <sub>2</sub> Emissions (t/year)	0.39	DFEE	37.61	TFEE	44.15					
Compliance Check	See BREL	% DFEE < TFEE			14.82					
% DPER < TPER	21.83	DPER	61.77	TPER	79.03					
Assessor Details	Miss Charlotte Russell			Assessor ID	DK97-0001					
Client										
<b>SUMMARY FOR INPUT DATA FOR: New Build (As Designed)</b>										
Orientation	Northwest									
Property Tenure	ND									
Transaction Type	6									
Terrain Type	Suburban									
1.0 Property Type	Flat, Mid-Terrace									
Position of Flat	Mid-floor flat									
Which Floor	2									
2.0 Number of Storeys	1									
3.0 Date Built	2025									
3.0 Property Age Band	L									
4.0 Sheltered Sides	2									
5.0 Sunlight/Shade	Average or unknown									
6.0 Thermal Mass Parameter	Precise calculation									
Thermal Mass	238.46 kJ/m <sup>2</sup> K									
7.0 Electricity Tariff	Standard									
Smart electricity meter fitted	Yes									
Smart gas meter fitted	No									
7.0 Measurements										
		Heat Loss Perimeter		Internal Floor Area		Average Storey Height				
		Ground floor: 37.86 m		76.87 m <sup>2</sup>		3.20 m				
8.0 Living Area	28.36 m <sup>2</sup>									
9.0 External Walls										
Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Res	Shelter	Openings	Area Calculation Type
External Wall	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.15	110.00	81.60	71.22	0.00	None	10.38	Enter Gross Area
Sheltered	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.18	110.00	39.55	37.43	0.90	Stairwell Access Corridor 4	2.12	Enter Gross Area
9.1 Party Walls										
Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )	Shelter Res	Shelter			
Party Wall	Filled Cavity with Edge Sealing	Single plasterboard on dabs both sides, lightweight aggregate blocks, cavity or cavity fill	0.00	110.00	10.75	0.00	None			
9.2 Internal Walls										
Description							Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )		
Internal Walls	Plasterboard on timber frame						9.00	158.86		
10.0 External Roofs										
Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Code	Shelter Factor	Calulation Type	Openings
External Roof	External Flat Roof	Plasterboard, insulated flat roof	0.11	9.00	76.87	76.87	None	0.00	Enter Gross Area	0.00

# Summary for Input Data

## 11.1 Party Floors

Description	Storey Index	Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Party Floor	Lowest occupied	Precast concrete planks floor, screed, carpeted	40.00	76.87

## 12.0 Opening Types

Description	Data Source	Type	Glazing	Glazing Gap	Filling Type	G-value	Frame Type	Frame Factor	U Value (W/m <sup>2</sup> K)
Solid Door Glazing	Manufacturer	Solid Door Window	Double Low-E Soft 0.05			0.00 0.63		0.80	1.20 1.20

## 13.0 Openings

Name	Opening Type	Location	Orientation	Area (m <sup>2</sup> )	Pitch
FSD	Solid Door Glazing	Sheltered External Wall	North West South East	2.12 10.38	0 0
RW					

## 14.0 Conservatory

None

## 15.0 Draught Proofing

100

%

## 16.0 Draught Lobby

No

## 17.0 Thermal Bridging

Calculate Bridges

### 17.1 List of Bridges

Bridge Type	Source Type	Length	Psi	Adjusted Reference:	Imported
E2 Other lintels (including other steel lintels)	Independently assessed	7.34	0.02	RCD	No
E3 Sill	Independently assessed	6.33	0.02	RCD	No
E4 Jamb	Independently assessed	14.04	0.01	RCD	No
E7 Party floor between dwellings (in blocks of flats)	Independently assessed	37.86	0.05	RCD	No
E16 Corner (normal)	Independently assessed	6.40	0.05	RCD	No
P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	3.36	0.00	Default	No
E18 Party wall between dwellings	Independently assessed	6.40	0.06	RCD	No
E25 Staggered party wall between dwellings	Independently assessed	6.40	0.05	RCD	No
E14 Flat roof	Independently assessed	37.86	0.04	ROI	No
P4 Party wall - Roof (insulation at ceiling level)	Table K1 - Default	3.36	0.48	Default	No

Y-value

0.03

W/m<sup>2</sup>K

Description

Bridge

## 19.0 Mechanical Ventilation

### Mechanical Ventilation

Mechanical Ventilation System Present	Yes
Approved Installation	Yes
Mechanical Ventilation data Type	Database
Type	Balanced mechanical ventilation with heat recovery
MV Reference Number	500500
Configuration	2
MVHR Duct Insulated	Uninsulated Ducts
Manufacturer SFP	0.59
Duct Type	Rigid
MVHR Efficiency	89.00
Wet Rooms	2
SFP from Installer Commissioning Certificate	No
MVHR System Location	Inside heated envelope (installed exclusively)
Duct Installation Specification	Level 2

## 19.1 Mechanical extract ventilation - Decentralised

SFP	Fan/Room Type	Count
0.13	In Room Fan	1
	Kitchen	
0.11	In Room Fan Other	3
	Wet Room	
0.00	In Duct Fan Kitchen	0
0.00	In Duct Fan Other	0
	Wet Room	
0.10	Through Wall Fan	0
	Kitchen	
0.10	Through Wall Fan	0
	Other Wet Room	

## 20.0 Fans, Open Fireplaces, Flues

# Summary for Input Data

Number of open chimneys	0										
Number of open flues	0										
Number of chimneys/flues attached to closed fire	0										
Number of flues attached to solid fuel boiler	0										
Number of flues attached to other heater	0										
Number of blocked chimneys	0										
Number of intermittent extract fans	0										
Number of passive vents	0										
Number of flueless gas fires	0										
<b>21.0 Fixed Cooling System</b>											
	No										
<b>22.0 Pressure Testing</b>											
Designed AP <sub>50</sub>	3.00										
Property Tested?	Yes										
Test Method	Blower Door										
<b>22.0 Lighting</b>											
No Fixed Lighting	No										
	<table border="1"> <thead> <tr> <th>Name</th> <th>Efficacy</th> <th>Power</th> <th>Capacity</th> <th>Count</th> </tr> </thead> <tbody> <tr> <td>Low energy Lighting</td> <td>85.00</td> <td>5.00</td> <td>425.00</td> <td>10</td> </tr> </tbody> </table>	Name	Efficacy	Power	Capacity	Count	Low energy Lighting	85.00	5.00	425.00	10
Name	Efficacy	Power	Capacity	Count							
Low energy Lighting	85.00	5.00	425.00	10							
<b>24.0 Main Heating 1</b>											
Percentage of Heat	SAP table										
Database Ref. No.	100.00										
Fuel Type	0										
SAP Code	Electricity										
In Winter	691										
In Summer	100.00										
Controls SAP Code	194.18										
Delayed Start Stat	2603										
Burner Control	No										
HETAS approved System	Modulating										
Is MHS Pumped	No										
Heating Pump Age	Pump in heated space										
Heat Emitter	2013 or later										
Underfloor Heating	Radiators										
Flow Temperature	Yes - Pipes in thin screed										
Flow Temperature Value	Enter value										
	55.00										
<b>25.0 Main Heating 2</b>											
Percentage of Heat	Database										
Database Ref. No.	0.00										
Fuel Type	100834										
SAP Code	Electricity										
In Winter	0										
In Summer	346.72										
Model Name	194.18										
Manufacturer	Compact P										
Controls	Nilan AS										
Delayed Start Stat	2100										
HETAS approved System	No										
	No										

# Summary for Input Data

Flow Temperature	Enter value										
<b>26.0 Heat Networks</b>	None										
<b>27.0 Secondary Heating</b>	None										
<b>28.0 Water Heating</b>											
Water Heating	Main Heating 2										
SAP Code	914										
Flue Gas Heat Recovery System	No										
Waste Water Heat Recovery Instantaneous System 1	No										
Waste Water Heat Recovery Instantaneous System 2	No										
Waste Water Heat Recovery Storage System	No										
Solar Panel	No										
Water use <= 125 litres/person/day	Yes										
Summer Immersion	No										
Cold Water Source	From mains										
Bath Count	1										
Baths connected to WWHRS	0										
Supplementary Immersion	No										
Immersion Only Heating Hot Water	No										
<b>28.1 Showers</b>											
<b>Description</b>	<b>Shower Type</b>	<b>Flow Rate</b> [l/min]	<b>Rated Power</b> [kW]	<b>Connected</b>	<b>Connected To</b>						
8 lpm	Unknown	8.00		No							
<b>28.3 Waste Water Heat Recovery System</b>											
<b>29.0 Hot Water Cylinder</b>		Internal Store									
Cylinder Stat	No										
Cylinder In Heated Space	No										
Independent Time Control	No										
Insulation Type	Measured Loss										
Insulation Thickness	0										
Cylinder Volume	180.00	L									
Loss	0.84	kWh/day									
In Airing Cupboard	No										
<b>31.0 Thermal Store</b>		None									
<b>34.0 Small-scale Hydro</b>		None									
Electricity Generated	0.00										
Apportioned	0.00	kWh/Year									
Connected to dwelling's electricity meter	Yes										
Electricity Generation	Annual										
Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
<b>Recommendations</b>											
Lower cost measures											
None											
Further measures to achieve even higher standards											
None											

# Predicted Energy Assessment


C14-02-08, Horsham Enterprise Park

Dwelling type:  
Date of assessment:  
Produced by:  
Total floor area:  
DRRN:

Flat, Mid-Terrace  
15/10/2025  
Charlotte Russell  
76.87 m<sup>2</sup>

This document is a Predicted Energy Assessment for properties marketed when they are incomplete. It includes a predicted energy rating which might not represent the final energy rating of the property on completion. Once the property is completed, this rating will be updated and an official Energy Performance Certificate will be created for the property. This will include more detailed information about the energy performance of the completed property.

The energy performance has been assessed using the Government approved SAP 10 methodology and is rated in terms of the energy use per square meter of floor area; the energy efficiency is based on fuel costs and the environmental impact is based on carbon dioxide (CO<sub>2</sub>) emissions.



The energy efficiency rating is a measure of the overall efficiency of a home. The higher the rating the more energy efficient the home is and the lower the fuel bills are likely to be.

The environmental impact rating is a measure of a home's impact on the environment in terms of carbon dioxide (CO<sub>2</sub>) emissions. The higher the rating the less impact it has on the environment.

# Thermal Bridging

Property Reference	C14-02-08		Issued on Date	15/10/2025
Assessment Reference	Design V1		Prop Type Ref	Mid-Terrace Flat
Property	C14-02-08, Horsham Enterprise Park			
SAP Rating	77 C	DER	5.94	TER
Environmental	95 A	% DER < TER		60.05
CO <sub>2</sub> Emissions (t/year)	0.39	DFEE	37.61	TFEE
Compliance Check	See BREL	% DFEE < TFEE		14.82
% DPER < TPER	21.83	DPER	61.77	TPER

Assessor Details	Miss Charlotte Russell	Assessor ID	DK97-0001
Client			

	Junction details	Source Type	Psi (W/mK)	Length (m)	Result	Reference
External wall	E2 Other lintels (including other steel lintels)	Independently assessed	0.022	7.34	0.16	RCD
External wall	E3 Sill	Independently assessed	0.016	6.33	0.10	RCD
External wall	E4 Jamb	Independently assessed	0.011	14.04	0.15	RCD
External wall	E7 Party floor between dwellings (in blocks of flats)	Independently assessed	0.053	37.86	2.01	RCD
External wall	E16 Corner (normal)	Independently assessed	0.051	6.40	0.33	RCD
Party wall	P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	0.000	3.36	0.00	Default
External wall	E18 Party wall between dwellings	Independently assessed	0.057	6.40	0.36	RCD
External wall	E25 Staggered party wall between dwellings	Independently assessed	0.046	6.40	0.29	RCD
External wall	E14 Flat roof	Independently assessed	0.040	37.86	1.51	ROI
Party wall	P4 Party wall - Roof (insulation at ceiling level)	Table K1 - Default	0.480	3.36	1.61	Default

Total: 129.35 W/mK:

Y-Value: 0.03 W/m<sup>2</sup>K:

# Summary for Input Data



Property Reference	C14-02-09	Issued on Date	15/10/2025
Assessment Reference	Design V1	Prop Type Ref	C14-02-09
Property	C14-02-09, Horsham Enterprise Park		
SAP Rating	80 C	DER	5.08
Environmental	96 A	% DER < TER	13.23
CO <sub>2</sub> Emissions (t/year)	0.34	DFEE	32.60
Compliance Check	See BREL	% DFEE < TFEE	61.60
% DPER < TPER	24.29	DPER	38.07
TPER	53.01	TPER	14.37
TPER	70.02		

Assessor Details	Miss Charlotte Russell	Assessor ID	DK97-0001
Client			

## SUMMARY FOR INPUT DATA FOR: New Build (As Designed)

Orientation	Southwest
Property Tenure	ND
Transaction Type	6
Terrain Type	Suburban
1.0 Property Type	Flat, Mid-Terrace
Position of Flat	Mid-floor flat
Which Floor	2
2.0 Number of Storeys	1
3.0 Date Built	2025
3.0 Property Age Band	L
4.0 Sheltered Sides	2
5.0 Sunlight/Shade	Average or unknown
6.0 Thermal Mass Parameter	Precise calculation
Thermal Mass	229.11
	kJ/m <sup>2</sup> K
7.0 Electricity Tariff	Standard
Smart electricity meter fitted	Yes
Smart gas meter fitted	No

7.0 Measurements	Heat Loss Perimeter	Internal Floor Area	Average Storey Height
	Ground floor: 26.26 m	80.12 m <sup>2</sup>	3.20 m

8.0 Living Area	30.51	m <sup>2</sup>
-----------------	-------	----------------

9.0 External Walls	Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Res	Shelter	Openings	Area Calculation Type
External Wall	External Wall	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.15	110.00	53.09	37.72	0.00	None	15.37	Enter Gross Area
Sheltered	Sheltered	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.18	110.00	30.94	28.82	0.90	Stairwell Access Corridor 4	2.12	Enter Gross Area

9.1 Party Walls	Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )	Shelter Res	Shelter
Party Wall	Party Wall	Filled Cavity with Edge Sealing	Single plasterboard on dabs both sides, lightweight aggregate blocks, cavity or cavity fill	0.00	110.00	33.15	0.00	None

9.2 Internal Walls	Description	Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Internal Walls	Internal Walls	Plasterboard on timber frame	9.00	168.50

10.0 External Roofs	Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Code	Shelter Factor	Shelter Calculation Type	Openings
External Roof	External Roof	External Flat Roof	Plasterboard, insulated flat roof	0.11	9.00	17.27	17.27	None	0.00	Enter Gross Area	0.00

# Summary for Input Data

## 10.1 Party Ceilings

Description	Construction	Kappa (kJ/m²K)	Area (m²)
Party Ceiling	Precast concrete planks floor, screed, carpeted	30.00	62.85

## 11.1 Party Floors

Description	Storey Index	Construction	Kappa (kJ/m²K)	Area (m²)
Party Floor	Lowest occupied	Precast concrete planks floor, screed, carpeted	40.00	80.12

## 12.0 Opening Types

Description	Data Source	Type	Glazing	Glazing Gap	Filling Type	G-value	Frame Type	Frame Factor	U Value (W/m²K)
Solid Door Glazing	Manufacturer	Solid Door Window	Double Low-E Soft 0.05			0.00 0.63		0.80	1.20 1.20

## 13.0 Openings

Name	Opening Type	Location	Orientation	Area (m²)	Pitch
FSD	Solid Door	Sheltered	South West	2.12	0
RSW	Glazing	External Wall	South East	1.49	0
RSGD	Glazing	External Wall	South East	4.97	0
LSW	Glazing	External Wall	North West	8.91	0

## 14.0 Conservatory

None

## 15.0 Draught Proofing

100

%

## 16.0 Draught Lobby

No

## 17.0 Thermal Bridging

Calculate Bridges

### 17.1 List of Bridges

Bridge Type	Source Type	Length	Psi	Adjusted Reference:	Imported
E2 Other lintels (including other steel lintels)	Independently assessed	9.16	0.02	RCD	No
E3 Sill	Independently assessed	6.34	0.02	RCD	No
E4 Jamb	Independently assessed	22.82	0.01	RCD	No
E7 Party floor between dwellings (in blocks of flats)	Independently assessed	29.32	0.05	RCD	No
E16 Corner (normal)	Independently assessed	6.40	0.05	RCD	No
P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	19.00	0.00	Default	No
E18 Party wall between dwellings	Independently assessed	9.60	0.06	RCD	No
E25 Staggered party wall between dwellings	Independently assessed	3.20	0.05	RCD	No
E14 Flat roof	Independently assessed	11.76	0.04	ROI	No
P4 Party wall - Roof (insulation at ceiling level)	Table K1 - Default	1.72	0.48	0.48	No
E24 Eaves (insulation at ceiling level - inverted)	Table K1 - Default	10.04	0.15	0.15	No
E17 Corner (inverted – internal area greater than external area)	Table K1 - Default	3.20	0.00	0.00	No

Y-value

0.06

W/m²K

Description

Bridge

## 19.0 Mechanical Ventilation

### Mechanical Ventilation

Mechanical Ventilation System Present	Yes
Approved Installation	Yes
Mechanical Ventilation data Type	Database
Type	Balanced mechanical ventilation with heat recovery
MV Reference Number	500500
Configuration	2
MVHR Duct Insulated	Uninsulated Ducts
Manufacturer SFP	0.59
Duct Type	Rigid
MVHR Efficiency	89.00
Wet Rooms	2
SFP from Installer Commissioning Certificate	No
MVHR System Location	Inside heated envelope (installed exclusively)
Duct Installation Specification	Level 2

## 19.1 Mechanical extract ventilation - Decentralised

SFP	Fan/Room Type	Count
0.13	In Room Fan Kitchen	1

# Summary for Input Data

0.11	In Room Fan Other	3
0.00	Wet Room	
0.00	In Duct Fan Kitchen	0
0.00	In Duct Fan Other	0
0.10	Wet Room	
0.10	Through Wall Fan	0
	Kitchen	
0.10	Through Wall Fan	0
	Other Wet Room	

## 20.0 Fans, Open Fireplaces, Flues

Number of open chimneys	0
Number of open flues	0
Number of chimneys/flues attached to closed fire	0
Number of flues attached to solid fuel boiler	0
Number of flues attached to other heater	0
Number of blocked chimneys	0
Number of intermittent extract fans	0
Number of passive vents	0
Number of flueless gas fires	0

## 21.0 Fixed Cooling System

21.0 Fixed Cooling System	No
22.0 Pressure Testing	Yes
Designed AP <sub>50</sub>	3.00
Property Tested?	Yes
Test Method	Blower Door

## 22.0 Lighting

No Fixed Lighting	No				
		Name	Efficacy	Power	Capacity
		Low energy Lighting	85.00	5.00	425.00
					Count
					10

## 24.0 Main Heating 1

Percentage of Heat	100.00	%
Database Ref. No.	0	
Fuel Type	Electricity	
SAP Code	691	
In Winter	100.00	
In Summer	194.18	
Controls SAP Code	2603	
Delayed Start Stat	No	
Burner Control	Modulating	
HETAS approved System	No	
Is MHS Pumped	Pump in heated space	
Heating Pump Age	2013 or later	
Heat Emitter	Radiators	
Underfloor Heating	Yes - Pipes in thin screed	
Flow Temperature	Enter value	
Flow Temperature Value	55.00	

## 25.0 Main Heating 2

Percentage of Heat	0.00	%
Database Ref. No.	100834	
Fuel Type	Electricity	
SAP Code	0	
In Winter	357.45	

# Summary for Input Data

In Summer	194.18										
Model Name	Compact P										
Manufacturer	Nilan AS										
Controls	2100										
Delayed Start Stat	No										
HETAS approved System	No										
Flow Temperature	Enter value										
<b>26.0 Heat Networks</b>											
26.0 Heat Networks	None										
<b>27.0 Secondary Heating</b>											
27.0 Secondary Heating	None										
<b>28.0 Water Heating</b>											
Water Heating	Main Heating 2										
SAP Code	914										
Flue Gas Heat Recovery System	No										
Waste Water Heat Recovery Instantaneous System 1	No										
Waste Water Heat Recovery Instantaneous System 2	No										
Waste Water Heat Recovery Storage System	No										
Solar Panel	No										
Water use <= 125 litres/person/day	Yes										
Summer Immersion	No										
Cold Water Source	From mains										
Bath Count	1										
Baths connected to WWHRS	0										
Supplementary Immersion	No										
Immersion Only Heating Hot Water	No										
<b>28.1 Showers</b>											
Description	Shower Type	Flow Rate [l/min]	Rated Power [kW]	Connected	Connected To						
8 lpm	Unknown	8.00		No							
<b>28.3 Waste Water Heat Recovery System</b>											
<b>29.0 Hot Water Cylinder</b>											
Cylinder Stat	Internal Store										
Cylinder In Heated Space	No										
Independent Time Control	No										
Insulation Type	Measured Loss										
Insulation Thickness	0										
Cylinder Volume	180.00	L									
Loss	0.84	kWh/day									
In Airing Cupboard	No										
<b>31.0 Thermal Store</b>											
<b>34.0 Small-scale Hydro</b>											
Electricity Generated	0.00										
Apportioned	0.00	kWh/Year									
Connected to dwelling's electricity meter	Yes										
Electricity Generation	Annual										
Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
<b>Recommendations</b>											
Lower cost measures											
None											
Further measures to achieve even higher standards											

# Summary for Input Data



**None**

# Predicted Energy Assessment


C14-02-09, Horsham Enterprise Park

Dwelling type:  
Date of assessment:  
Produced by:  
Total floor area:  
DRRN:

Flat, Mid-Terrace  
15/10/2025  
Charlotte Russell  
80.12 m<sup>2</sup>

This document is a Predicted Energy Assessment for properties marketed when they are incomplete. It includes a predicted energy rating which might not represent the final energy rating of the property on completion. Once the property is completed, this rating will be updated and an official Energy Performance Certificate will be created for the property. This will include more detailed information about the energy performance of the completed property.

The energy performance has been assessed using the Government approved SAP 10 methodology and is rated in terms of the energy use per square meter of floor area; the energy efficiency is based on fuel costs and the environmental impact is based on carbon dioxide (CO<sub>2</sub>) emissions.



The energy efficiency rating is a measure of the overall efficiency of a home. The higher the rating the more energy efficient the home is and the lower the fuel bills are likely to be.

The environmental impact rating is a measure of a home's impact on the environment in terms of carbon dioxide (CO<sub>2</sub>) emissions. The higher the rating the less impact it has on the environment.

# Thermal Bridging

Property Reference	C14-02-09		Issued on Date	15/10/2025
Assessment Reference	Design V1		Prop Type Ref	Mid-Terrace Flat
Property	C14-02-09, Horsham Enterprise Park			
SAP Rating	80 C	DER	5.08	TER
Environmental	96 A	% DER < TER		61.60
CO <sub>2</sub> Emissions (t/year)	0.34	DFEE	32.60	TFEE
Compliance Check	See BREL	% DFEE < TFEE		14.37
% DPER < TPER	24.29	DPER	53.01	TPER
Assessor Details	Miss Charlotte Russell			Assessor ID
Client				

	Junction details	Source Type	Psi (W/mK)	Length (m)	Result	Reference
External wall	E2 Other lintels (including other steel lintels)	Independently assessed	0.022	9.16	0.20	RCD
External wall	E3 Sill	Independently assessed	0.016	6.34	0.10	RCD
External wall	E4 Jamb	Independently assessed	0.011	22.82	0.25	RCD
External wall	E7 Party floor between dwellings (in blocks of flats)	Independently assessed	0.053	29.32	1.55	RCD
External wall	E16 Corner (normal)	Independently assessed	0.051	6.40	0.33	RCD
Party wall	P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	0.000	19.00	0.00	Default
External wall	E18 Party wall between dwellings	Independently assessed	0.057	9.60	0.55	RCD
External wall	E25 Staggered party wall between dwellings	Independently assessed	0.046	3.20	0.15	RCD
External wall	E14 Flat roof	Independently assessed	0.040	11.76	0.47	ROI
Party wall	P4 Party wall - Roof (insulation at ceiling level)	Table K1 - Default	0.480	1.72	0.83	Default
External wall	E24 Eaves (insulation at ceiling level - inverted)	Table K1 - Default	0.150	10.04	1.51	
External wall	E17 Corner (inverted – internal area greater than external area)	Table K1 - Default	0.000	3.20	0.00	

Total: 132.56 W/mK:

Y-Value: 0.06 W/m<sup>2</sup>K:

# Summary for Input Data



Property Reference	C14-02-12			Issued on Date	15/10/2025					
Assessment Reference	Design V1		Prop Type Ref	C14-02-12						
Property	C14-02-12, Horsham Enterprise Park									
SAP Rating	80 C	DER	5.96	TER	15.80					
Environmental	96 A	% DER < TER			62.28					
CO <sub>2</sub> Emissions (t/year)	0.27	DFEE	36.13	TFEE	41.01					
Compliance Check	See BREL	% DFEE < TFEE			11.91					
% DPER < TPER	26.09	DPER	62.25	TPER	84.22					
Assessor Details	Miss Charlotte Russell			Assessor ID	DK97-0001					
Client										
<b>SUMMARY FOR INPUT DATA FOR: New Build (As Designed)</b>										
Orientation	Southwest									
Property Tenure	ND									
Transaction Type	6									
Terrain Type	Suburban									
1.0 Property Type	Flat, Mid-Terrace									
Position of Flat	Mid-floor flat									
Which Floor	2									
2.0 Number of Storeys	1									
3.0 Date Built	2025									
3.0 Property Age Band	L									
4.0 Sheltered Sides	2									
5.0 Sunlight/Shade	Average or unknown									
6.0 Thermal Mass Parameter	Precise calculation									
Thermal Mass	269.83 kJ/m <sup>2</sup> K									
7.0 Electricity Tariff	Standard									
Smart electricity meter fitted	Yes									
Smart gas meter fitted	No									
7.0 Measurements										
		Heat Loss Perimeter		Internal Floor Area		Average Storey Height				
		Ground floor: 16.45 m		53.97 m <sup>2</sup>		3.20 m				
8.0 Living Area	25.87 m <sup>2</sup>									
9.0 External Walls										
Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Res	Shelter	Openings	Area Calculation Type
External Wall	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.15	110.00	28.90	19.47	0.00	None	9.43	Enter Gross Area
Sheltered	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.18	110.00	23.74	21.62	0.90	Stairwell Access Corridor 4	2.12	Enter Gross Area
9.1 Party Walls										
Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )	Shelter Res	Shelter			
Party Wall	Filled Cavity with Edge Sealing	Single plasterboard on dabs both sides, lightweight aggregate blocks, cavity or cavity fill	0.00	110.00	48.99	0.00	None			
9.2 Internal Walls										
Description							Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )		
Internal Walls	Plasterboard on timber frame						9.00	85.88		
10.0 External Roofs										
Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Code	Shelter Factor	Calculation Type	Openings
External Roof	External Flat Roof	Plasterboard, insulated flat roof	0.11	9.00	14.09	14.09	None	0.00	Enter Gross Area	0.00

# Summary for Input Data

## 10.1 Party Ceilings

Description	Construction		Kappa (kJ/m²K)	Area (m²)
Party Ceiling		Precast concrete planks floor, screed, carpeted	30.00	39.88

## 11.1 Party Floors

Description	Storey Index	Construction	Kappa (kJ/m²K)	Area (m²)
Party Floor	Lowest occupied	Precast concrete planks floor, screed, carpeted	40.00	53.97

## 12.0 Opening Types

Description	Data Source	Type	Glazing	Glazing Gap	Filling Type	G-value	Frame Type	Frame Factor	U Value (W/m²K)
Solid Door Glazing	Manufacturer	Solid Door Window	Double Low-E Soft 0.05			0.00 0.63		0.80	1.20 1.20

## 13.0 Openings

Name	Opening Type	Location	Orientation	Area (m²)	Pitch
FSD	Solid Door	Sheltered	South West	2.12	0
RW	Glazing	External Wall	North East	4.46	0
RGD	Glazing	External Wall	North East	4.97	0

## 14.0 Conservatory

None

## 15.0 Draught Proofing

100

%

## 16.0 Draught Lobby

No

## 17.0 Thermal Bridging

Calculate Bridges

### 17.1 List of Bridges

Bridge Type	Source Type	Length	Psi	Adjusted Reference:	Imported
E2 Other lintels (including other steel lintels)	Independently assessed	4.54	0.02	0.02 RCD	No
E3 Sill	Independently assessed	2.72	0.02	0.02 RCD	No
E4 Jamb	Independently assessed	16.26	0.01	0.01 RCD	No
E7 Party floor between dwellings (in blocks of flats)	Independently assessed	23.87	0.05	0.05 RCD	No
E16 Corner (normal)	Independently assessed	3.20	0.05	0.05 RCD	No
P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	26.36	0.00	0.00 Default	No
E18 Party wall between dwellings	Independently assessed	12.80	0.06	0.06 RCD	No
E25 Staggered party wall between dwellings	Independently assessed	6.40	0.05	0.05 RCD	No
E14 Flat roof	Independently assessed	9.03	0.04	0.04 ROI	No
P4 Party wall - Roof (insulation at ceiling level)	Table K1 - Default	3.12	0.48	0.48 Default	No
E24 Eaves (insulation at ceiling level - inverted)	Table K1 - Default	9.03	0.15	0.15	No
E17 Corner (inverted – internal area greater than external area)	Table K1 - Default	0.00	0.00	0.00	No

Y-value

0.09

W/m²K

Description

Bridge

## 19.0 Mechanical Ventilation

### Mechanical Ventilation

Mechanical Ventilation System Present	Yes
Approved Installation	Yes
Mechanical Ventilation data Type	Database
Type	Balanced mechanical ventilation with heat recovery
MV Reference Number	500500
Configuration	2
MVHR Duct Insulated	Uninsulated Ducts
Manufacturer SFP	0.59
Duct Type	Rigid
MVHR Efficiency	89.00
Wet Rooms	2
SFP from Installer Commissioning Certificate	No
MVHR System Location	Inside heated envelope (installed exclusively)
Duct Installation Specification	Level 2

## 19.1 Mechanical extract ventilation - Decentralised

SFP	Fan/Room Type	Count
0.13	In Room Fan	1
	Kitchen	
0.11	In Room Fan Other	3
	Wet Room	

# Summary for Input Data

0.00	In Duct Fan Kitchen	0
0.00	In Duct Fan Other	0
	Wet Room	
0.10	Through Wall Fan	0
	Kitchen	
0.10	Through Wall Fan	0
	Other Wet Room	

## 20.0 Fans, Open Fireplaces, Flues

Number of open chimneys	0
Number of open flues	0
Number of chimneys/flues attached to closed fire	0
Number of flues attached to solid fuel boiler	0
Number of flues attached to other heater	0
Number of blocked chimneys	0
Number of intermittent extract fans	0
Number of passive vents	0
Number of flueless gas fires	0

## 21.0 Fixed Cooling System

22.0 Pressure Testing	Yes
-----------------------	-----

Designed AP <sub>50</sub>	3.00	m <sup>3</sup> /(h.m <sup>2</sup> ) @ 50 Pa
Property Tested?	Yes	
Test Method	Blower Door	

## 22.0 Lighting

No Fixed Lighting	No				
	Name	Efficacy	Power	Capacity	Count
	Low energy Lighting	85.00	5.00	425.00	10

## 24.0 Main Heating 1

Percentage of Heat	100.00	%
Database Ref. No.	0	
Fuel Type	Electricity	
SAP Code	691	
In Winter	100.00	
In Summer	194.18	
Controls SAP Code	2603	
Delayed Start Stat	No	
Burner Control	Modulating	
HETAS approved System	No	
Is MHS Pumped	Pump in heated space	
Heating Pump Age	2013 or later	
Heat Emitter	Radiators	
Underfloor Heating	Yes - Pipes in thin screed	
Flow Temperature	Enter value	
Flow Temperature Value	55.00	

## 25.0 Main Heating 2

Percentage of Heat	0.00	%
Database Ref. No.	100834	
Fuel Type	Electricity	
SAP Code	0	
In Winter	302.18	
In Summer	194.18	
Model Name	Compact P	

# Summary for Input Data

Manufacturer	Nilan AS										
Controls	2100										
Delayed Start Stat	No										
HETAS approved System	No										
Flow Temperature	Enter value										
<b>26.0 Heat Networks</b>											
27.0 Secondary Heating	None										
<b>28.0 Water Heating</b>											
Water Heating	Main Heating 2										
SAP Code	914										
Flue Gas Heat Recovery System	No										
Waste Water Heat Recovery Instantaneous System 1	No										
Waste Water Heat Recovery Instantaneous System 2	No										
Waste Water Heat Recovery Storage System	No										
Solar Panel	No										
Water use <= 125 litres/person/day	Yes										
Summer Immersion	No										
Cold Water Source	From mains										
Bath Count	1										
Baths connected to WWHRS	0										
Supplementary Immersion	No										
Immersion Only Heating Hot Water	No										
<b>28.1 Showers</b>											
Description	Shower Type	Flow Rate [l/min]	Rated Power [kW]	Connected	Connected To						
8 lpm	Unknown	8.00		No							
<b>28.3 Waste Water Heat Recovery System</b>											
<b>29.0 Hot Water Cylinder</b>		Internal Store									
Cylinder Stat	No										
Cylinder In Heated Space	No										
Independent Time Control	No										
Insulation Type	Measured Loss										
Insulation Thickness	0										
Cylinder Volume	180.00	L									
Loss	0.84	kWh/day									
In Airing Cupboard	No										
<b>31.0 Thermal Store</b>		None									
<b>34.0 Small-scale Hydro</b>		None									
Electricity Generated	0.00										
Apportioned	0.00	kWh/Year									
Connected to dwelling's electricity meter	Yes										
Electricity Generation	Annual										
Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
<b>Recommendations</b>											
Lower cost measures											
None											
Further measures to achieve even higher standards											
None											

# Predicted Energy Assessment


C14-02-12, Horsham Enterprise Park

Dwelling type:  
Date of assessment:  
Produced by:  
Total floor area:  
DRRN:

Flat, Mid-Terrace  
15/10/2025  
Charlotte Russell  
53.97 m<sup>2</sup>

This document is a Predicted Energy Assessment for properties marketed when they are incomplete. It includes a predicted energy rating which might not represent the final energy rating of the property on completion. Once the property is completed, this rating will be updated and an official Energy Performance Certificate will be created for the property. This will include more detailed information about the energy performance of the completed property.

The energy performance has been assessed using the Government approved SAP 10 methodology and is rated in terms of the energy use per square meter of floor area; the energy efficiency is based on fuel costs and the environmental impact is based on carbon dioxide (CO<sub>2</sub>) emissions.



The energy efficiency rating is a measure of the overall efficiency of a home. The higher the rating the more energy efficient the home is and the lower the fuel bills are likely to be.

The environmental impact rating is a measure of a home's impact on the environment in terms of carbon dioxide (CO<sub>2</sub>) emissions. The higher the rating the less impact it has on the environment.

# Thermal Bridging

Property Reference	C14-02-12		Issued on Date	15/10/2025
Assessment Reference	Design V1		Prop Type Ref	Mid-Terrace Flat
Property	C14-02-12, Horsham Enterprise Park			
SAP Rating	80 C	DER	5.96	TER
Environmental	96 A	% DER < TER		62.28
CO <sub>2</sub> Emissions (t/year)	0.27	DFEE	36.13	TFEE
Compliance Check	See BREL	% DFEE < TFEE		11.91
% DPER < TPER	26.09	DPER	62.25	TPER

Assessor Details	Miss Charlotte Russell	Assessor ID	DK97-0001
Client			

	Junction details	Source Type	Psi (W/mK)	Length (m)	Result	Reference
External wall	E2 Other lintels (including other steel lintels)	Independently assessed	0.022	4.54	0.10	RCD
External wall	E3 Sill	Independently assessed	0.016	2.72	0.04	RCD
External wall	E4 Jamb	Independently assessed	0.011	16.26	0.18	RCD
External wall	E7 Party floor between dwellings (in blocks of flats)	Independently assessed	0.053	23.87	1.27	RCD
External wall	E16 Corner (normal)	Independently assessed	0.051	3.20	0.16	RCD
Party wall	P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	0.000	26.36	0.00	Default
External wall	E18 Party wall between dwellings	Independently assessed	0.057	12.80	0.73	RCD
External wall	E25 Staggered party wall between dwellings	Independently assessed	0.046	6.40	0.29	RCD
External wall	E14 Flat roof	Independently assessed	0.040	9.03	0.36	ROI
Party wall	P4 Party wall - Roof (insulation at ceiling level)	Table K1 - Default	0.480	3.12	1.50	Default
External wall	E24 Eaves (insulation at ceiling level - inverted)	Table K1 - Default	0.150	9.03	1.35	
External wall	E17 Corner (inverted – internal area greater than external area)	Table K1 - Default	0.000	0.00	0.00	

Total: 117.33 W/mK:

Y-Value: 0.09 W/m<sup>2</sup>K:

# Summary for Input Data



Property Reference	C14-03-02			Issued on Date	15/10/2025					
Assessment Reference	Design V1		Prop Type Ref	C14-03-02						
Property	C14-03-02, Horsham Enterprise Park									
SAP Rating	81 B	DER	5.35	TER	13.11					
Environmental	96 A	% DER < TER			59.19					
CO <sub>2</sub> Emissions (t/year)	0.28	DFEE	29.92	TFEE	30.72					
Compliance Check	See BREL	% DFEE < TFEE			2.60					
% DPER < TPER	19.65	DPER	55.93	TPER	69.61					
Assessor Details	Miss Charlotte Russell			Assessor ID	DK97-0001					
Client										
<b>SUMMARY FOR INPUT DATA FOR: New Build (As Designed)</b>										
Orientation	Northeast									
Property Tenure	ND									
Transaction Type	6									
Terrain Type	Suburban									
1.0 Property Type	Flat, Mid-Terrace									
Position of Flat	Top-floor flat									
Which Floor	3									
2.0 Number of Storeys	1									
3.0 Date Built	2025									
3.0 Property Age Band	L									
4.0 Sheltered Sides	2									
5.0 Sunlight/Shade	Average or unknown									
6.0 Thermal Mass Parameter	Precise calculation									
Thermal Mass	183.55			kJ/m <sup>2</sup> K						
7.0 Electricity Tariff	Standard									
Smart electricity meter fitted	Yes									
Smart gas meter fitted	No									
7.0 Measurements										
		Heat Loss Perimeter		Internal Floor Area		Average Storey Height				
		Ground floor:	19.57 m	59.57 m <sup>2</sup>		2.50 m				
8.0 Living Area	32.27			m <sup>2</sup>						
9.0 External Walls										
Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Res	Shelter	Openings	Area Calculation Type
External Wall	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.15	110.00	40.27	28.53	0.00	None	11.74	Enter Gross Area
Sheltered	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.18	110.00	8.65	6.53	0.90	Stairwell Access Corridor 4	2.12	Enter Gross Area
9.1 Party Walls										
Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )	Shelter Res	Shelter			
Party Wall	Filled Cavity with Edge Sealing	Single plasterboard on dabs both sides, lightweight aggregate blocks, cavity or cavity fill	0.00	110.00	31.62	0.00	None			
9.2 Internal Walls										
Description							Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )		
Internal Walls	Plasterboard on timber frame						9.00	75.58		
10.0 External Roofs										
Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Code	Shelter Factor	Calulation Type	Openings
External Roof	External Flat Roof	Plasterboard, insulated flat roof	0.11	9.00	59.57	59.57	None	0.00	Enter Gross Area	0.00

# Summary for Input Data

## 11.1 Party Floors

Description	Storey Index	Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Party Floor	Lowest occupied	Precast concrete planks floor, screed, carpeted	40.00	59.57

## 12.0 Opening Types

Description	Data Source	Type	Glazing	Glazing Gap	Filling Type	G-value	Frame Type	Frame Factor	U Value (W/m <sup>2</sup> K)
Solid Door Glazing	Manufacturer	Solid Door Window	Double Low-E Soft 0.05			0.00 0.63		0.80	1.20 1.20

## 13.0 Openings

Name	Opening Type	Location	Orientation	Area (m <sup>2</sup> )	Pitch
FSD	Solid Door	Sheltered	North East	2.12	0
RW	Glazing	External Wall	South West	8.82	0
RGD	Glazing	External Wall	South West	2.92	0

## 14.0 Conservatory

None

## 15.0 Draught Proofing

100

%

## 16.0 Draught Lobby

No

## 17.0 Thermal Bridging

Calculate Bridges

### 17.1 List of Bridges

Bridge Type	Source Type	Length	Psi	Adjusted Reference:	Imported
E2 Other lintels (including other steel lintels)	Independently assessed	6.23	0.02	RCD	No
E3 Sill	Independently assessed	3.96	0.02	RCD	No
E4 Jamb	Independently assessed	18.12	0.01	RCD	No
E7 Party floor between dwellings (in blocks of flats)	Independently assessed	19.57	0.05	RCD	No
E16 Corner (normal)	Independently assessed	2.50	0.05	RCD	No
P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	12.65	0.00	Default	No
E18 Party wall between dwellings	Independently assessed	15.00	0.06	RCD	No
E25 Staggered party wall between dwellings	Independently assessed	0.00	0.05	RCD	No
E14 Flat roof	Independently assessed	19.57	0.04	ROI	No
P4 Party wall - Roof (insulation at ceiling level)	Table K1 - Default	12.65	0.48	0.48	No
E17 Corner (inverted – internal area greater than external area)	Table K1 - Default	2.50	0.00	0.00	No

Y-value

0.09

W/m<sup>2</sup>K

Description

Bridge

## 19.0 Mechanical Ventilation

### Mechanical Ventilation

Mechanical Ventilation System Present	Yes
Approved Installation	Yes
Mechanical Ventilation data Type	Database
Type	Balanced mechanical ventilation with heat recovery
MV Reference Number	500500
Configuration	2
MVHR Duct Insulated	Uninsulated Ducts
Manufacturer SFP	0.59
Duct Type	Rigid
MVHR Efficiency	89.00
Wet Rooms	2
SFP from Installer Commissioning Certificate	No
MVHR System Location	Inside heated envelope (installed exclusively)
Duct Installation Specification	Level 2

## 19.1 Mechanical extract ventilation - Decentralised

SFP	Fan/Room Type	Count
0.13	In Room Fan	1
	Kitchen	
0.11	In Room Fan Other	3
	Wet Room	
0.00	In Duct Fan Kitchen	0
0.00	In Duct Fan Other	0
	Wet Room	
0.10	Through Wall Fan	0
	Kitchen	

# Summary for Input Data

0.10 Through Wall Fan 0  
Other Wet Room

## 20.0 Fans, Open Fireplaces, Flues

Number of open chimneys	0
Number of open flues	0
Number of chimneys/flues attached to closed fire	0
Number of flues attached to solid fuel boiler	0
Number of flues attached to other heater	0
Number of blocked chimneys	0
Number of intermittent extract fans	0
Number of passive vents	0
Number of flueless gas fires	0

## 21.0 Fixed Cooling System

No

## 22.0 Pressure Testing

Designed AP <sub>50</sub>	3.00	m <sup>3</sup> /(h.m <sup>2</sup> ) @ 50 Pa
Property Tested?	Yes	
Test Method	Blower Door	

## 22.0 Lighting

No Fixed Lighting

No	Name	Efficacy	Power	Capacity	Count
	Low energy Lighting	85.00	5.00	425.00	10

## 24.0 Main Heating 1

Percentage of Heat	100.00	%
Database Ref. No.	0	
Fuel Type	Electricity	
SAP Code	691	
In Winter	100.00	
In Summer	194.18	
Controls SAP Code	2603	
Delayed Start Stat	No	
Burner Control	Modulating	
HETAS approved System	No	
Is MHS Pumped	Pump in heated space	
Heating Pump Age	2013 or later	
Heat Emitter	Radiators	
Underfloor Heating	Yes - Pipes in thin screed	
Flow Temperature	Enter value	
Flow Temperature Value	55.00	

## 25.0 Main Heating 2

Percentage of Heat	0.00	%
Database Ref. No.	100834	
Fuel Type	Electricity	
SAP Code	0	
In Winter	305.51	
In Summer	194.18	
Model Name	Compact P	
Manufacturer	Nilan AS	
Controls	2100	

# Summary for Input Data

Delayed Start Stat	No										
HETAS approved System	No										
Flow Temperature	Enter value										
<b>26.0 Heat Networks</b>	None										
<b>27.0 Secondary Heating</b>	None										
<b>28.0 Water Heating</b>											
Water Heating	Main Heating 2										
SAP Code	914										
Flue Gas Heat Recovery System	No										
Waste Water Heat Recovery Instantaneous System 1	No										
Waste Water Heat Recovery Instantaneous System 2	No										
Waste Water Heat Recovery Storage System	No										
Solar Panel	No										
Water use <= 125 litres/person/day	Yes										
Summer Immersion	No										
Cold Water Source	From mains										
Bath Count	1										
Baths connected to WWHRS	0										
Supplementary Immersion	No										
Immersion Only Heating Hot Water	No										
<b>28.1 Showers</b>											
<b>Description</b>	<b>Shower Type</b>	<b>Flow Rate [l/min]</b>	<b>Rated Power [kW]</b>	<b>Connected</b>	<b>Connected To</b>						
8 lpm	Unknown	8.00		No							
<b>28.3 Waste Water Heat Recovery System</b>											
<b>29.0 Hot Water Cylinder</b>											
Cylinder Stat	Internal Store										
Cylinder In Heated Space	No										
Independent Time Control	No										
Insulation Type	Measured Loss										
Insulation Thickness	0										
Cylinder Volume	180.00	L									
Loss	0.84	kWh/day									
In Airing Cupboard	No										
<b>31.0 Thermal Store</b>											
<b>34.0 Small-scale Hydro</b>											
Electricity Generated	0.00										
Apportioned	0.00	kWh/Year									
Connected to dwelling's electricity meter	Yes										
Electricity Generation	Annual										
Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec

**Recommendations**

**Lower cost measures**

None

**Further measures to achieve even higher standards**

None

# Predicted Energy Assessment


C14-03-02, Horsham Enterprise Park

Dwelling type:  
Date of assessment:  
Produced by:  
Total floor area:  
DRRN:

Flat, Mid-Terrace  
15/10/2025  
Charlotte Russell  
59.57 m<sup>2</sup>

This document is a Predicted Energy Assessment for properties marketed when they are incomplete. It includes a predicted energy rating which might not represent the final energy rating of the property on completion. Once the property is completed, this rating will be updated and an official Energy Performance Certificate will be created for the property. This will include more detailed information about the energy performance of the completed property.

The energy performance has been assessed using the Government approved SAP 10 methodology and is rated in terms of the energy use per square meter of floor area; the energy efficiency is based on fuel costs and the environmental impact is based on carbon dioxide (CO<sub>2</sub>) emissions.



The energy efficiency rating is a measure of the overall efficiency of a home. The higher the rating the more energy efficient the home is and the lower the fuel bills are likely to be.

The environmental impact rating is a measure of a home's impact on the environment in terms of carbon dioxide (CO<sub>2</sub>) emissions. The higher the rating the less impact it has on the environment.

# Thermal Bridging

Property Reference	C14-03-02		Issued on Date	15/10/2025
Assessment Reference	Design V1		Prop Type Ref	Mid-Terrace Flat
Property	C14-03-02, Horsham Enterprise Park			
SAP Rating	81 B	DER	5.35	TER
Environmental	96 A	% DER < TER		59.19
CO <sub>2</sub> Emissions (t/year)	0.28	DFEE	29.92	TFEE
Compliance Check	See BREL	% DFEE < TFEE		2.60
% DPER < TPER	19.65	DPER	55.93	TPER
Assessor Details	Miss Charlotte Russell			Assessor ID
Client				

	Junction details	Source Type	Psi (W/mK)	Length (m)	Result	Reference
External wall	E2 Other lintels (including other steel lintels)	Independently assessed	0.022	6.23	0.14	RCD
External wall	E3 Sill	Independently assessed	0.016	3.96	0.06	RCD
External wall	E4 Jamb	Independently assessed	0.011	18.12	0.20	RCD
External wall	E7 Party floor between dwellings (in blocks of flats)	Independently assessed	0.053	19.57	1.04	RCD
External wall	E16 Corner (normal)	Independently assessed	0.051	2.50	0.13	RCD
Party wall	P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	0.000	12.65	0.00	Default
External wall	E18 Party wall between dwellings	Independently assessed	0.057	15.00	0.85	RCD
External wall	E25 Staggered party wall between dwellings	Independently assessed	0.046	0.00	0.00	RCD
External wall	E14 Flat roof	Independently assessed	0.040	19.57	0.78	ROI
Party wall	P4 Party wall - Roof (insulation at ceiling level)	Table K1 - Default	0.480	12.65	6.07	Default
External wall	E17 Corner (inverted – internal area greater than external area)	Table K1 - Default	0.000	2.50	0.00	

Total: 112.75 W/mK:  
 Y-Value: 0.09 W/m<sup>2</sup>K:

# Summary for Input Data



Property Reference	C14-03-03	Issued on Date	15/10/2025
Assessment Reference	Design V1	Prop Type Ref	C14-03-03
Property	C14-03-03, Horsham Enterprise Park		
SAP Rating	79 C	DER	5.52
Environmental	96 A	% DER < TER	58.21
CO <sub>2</sub> Emissions (t/year)	0.34	DFEE	33.43
Compliance Check	See BREL	% DFEE < TFEE	7.56
% DPER < TPER	17.88	DPER	57.47
TPER	69.98		

Assessor Details	Miss Charlotte Russell	Assessor ID	DK97-0001
Client			

## SUMMARY FOR INPUT DATA FOR: New Build (As Designed)

Orientation	Northeast	
Property Tenure	ND	
Transaction Type	6	
Terrain Type	Suburban	
1.0 Property Type	Flat, Mid-Terrace	
Position of Flat	Top-floor flat	
Which Floor	3	
2.0 Number of Storeys	1	
3.0 Date Built	2025	
3.0 Property Age Band	L	
4.0 Sheltered Sides	2	
5.0 Sunlight/Shade	Average or unknown	
6.0 Thermal Mass Parameter	Precise calculation	
Thermal Mass	200.52	kJ/m <sup>2</sup> K
7.0 Electricity Tariff	Standard	
Smart electricity meter fitted	Yes	
Smart gas meter fitted	No	

7.0 Measurements	Heat Loss Perimeter	Internal Floor Area	Average Storey Height
	Ground floor: 33.81 m	72.61 m <sup>2</sup>	2.50 m

8.0 Living Area	26.07	m <sup>2</sup>
-----------------	-------	----------------

9.0 External Walls	Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Res	Shelter	Openings	Area Calculation Type
External Wall	External Wall	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.15	110.00	50.95	31.75	0.00	None	19.20	Enter Gross Area
Sheltered	Sheltered	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.18	110.00	33.58	31.46	0.90	Stairwell Access Corridor 4	2.12	Enter Gross Area

9.1 Party Walls	Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )	Shelter Res	Shelter
Party Wall	Party Wall	Filled Cavity with Edge Sealing	Single plasterboard on dabs both sides, lightweight aggregate blocks, cavity or cavity fill	0.00	110.00	28.63	0.00	None

9.2 Internal Walls	Description	Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Internal Walls	Internal Walls	Plasterboard on timber frame	9.00	99.98

10.0 External Roofs	Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Code	Shelter Factor	Shelter Type	Openings
External Roof	External Roof	External Flat Roof	Plasterboard, insulated flat roof	0.11	9.00	72.61	72.61	None	0.00	Enter Gross Area	0.00

# Summary for Input Data

## 11.1 Party Floors

Description	Storey Index	Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Party Floor	Lowest occupied	Precast concrete planks floor, screed, carpeted	40.00	72.61

## 12.0 Opening Types

Description	Data Source	Type	Glazing	Glazing Gap	Filling Type	G-value	Frame Type	Frame Factor	U Value (W/m <sup>2</sup> K)
Solid Door Glazing	Manufacturer	Solid Door Window	Double Low-E Soft 0.05			0.00 0.63		0.80	1.20 1.20

## 13.0 Openings

Name	Opening Type	Location	Orientation	Area (m <sup>2</sup> )	Pitch
FSD	Solid Door	Sheltered	North East	2.12	0
RW	Glazing	External Wall	South West	13.36	0
RGD	Glazing	External Wall	South West	2.92	0
RSW	Glazing	External Wall	North West	2.92	0

## 14.0 Conservatory

None

## 15.0 Draught Proofing

100

%

## 16.0 Draught Lobby

No

## 17.0 Thermal Bridging

Calculate Bridges

### 17.1 List of Bridges

Bridge Type	Source Type	Length	Psi	Adjusted Reference:	Imported
E2 Other lintels (including other steel lintels)	Independently assessed	9.45	0.02	RCD	No
E3 Sill	Independently assessed	7.18	0.02	RCD	No
E4 Jamb	Independently assessed	27.40	0.01	RCD	No
E7 Party floor between dwellings (in blocks of flats)	Independently assessed	33.81	0.05	RCD	No
E16 Corner (normal)	Independently assessed	5.00	0.05	RCD	No
P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	11.45	0.00	Default	No
E18 Party wall between dwellings	Independently assessed	12.50	0.06	RCD	No
E25 Staggered party wall between dwellings	Independently assessed	2.50	0.05	RCD	No
E14 Flat roof	Independently assessed	33.81	0.04	ROI	No
P4 Party wall - Roof (insulation at ceiling level)	Table K1 - Default	11.45	0.48	0.48	No
E17 Corner (inverted – internal area greater than external area)	Table K1 - Default	2.50	0.00	0.00	No

Y-value

0.07

W/m<sup>2</sup>K

Description

Bridge

## 19.0 Mechanical Ventilation

### Mechanical Ventilation

Mechanical Ventilation System Present	Yes
Approved Installation	Yes
Mechanical Ventilation data Type	Database
Type	Balanced mechanical ventilation with heat recovery
MV Reference Number	500500
Configuration	2
MVHR Duct Insulated	Uninsulated Ducts
Manufacturer SFP	0.59
Duct Type	Rigid
MVHR Efficiency	89.00
Wet Rooms	2
SFP from Installer Commissioning Certificate	No
MVHR System Location	Inside heated envelope (installed exclusively)
Duct Installation Specification	Level 2

## 19.1 Mechanical extract ventilation - Decentralised

SFP	Fan/Room Type	Count
0.13	In Room Fan	1
	Kitchen	
0.11	In Room Fan Other	3
	Wet Room	
0.00	In Duct Fan Kitchen	0
0.00	In Duct Fan Other	0
	Wet Room	
0.10	Through Wall Fan	0
	Kitchen	

# Summary for Input Data

0.10      Through Wall Fan    0  
Other Wet Room

## 20.0 Fans, Open Fireplaces, Flues

Number of open chimneys	0
Number of open flues	0
Number of chimneys/flues attached to closed fire	0
Number of flues attached to solid fuel boiler	0
Number of flues attached to other heater	0
Number of blocked chimneys	0
Number of intermittent extract fans	0
Number of passive vents	0
Number of flueless gas fires	0

## 21.0 Fixed Cooling System

No

## 22.0 Pressure Testing

Designed AP <sub>50</sub>	3.00	m <sup>3</sup> /(h.m <sup>2</sup> ) @ 50 Pa
Property Tested?	Yes	
Test Method	Blower Door	

## 22.0 Lighting

No Fixed Lighting

No	Name	Efficacy	Power	Capacity	Count
	Low energy Lighting	85.00	5.00	425.00	10

## 24.0 Main Heating 1

Percentage of Heat	100.00	%
Database Ref. No.	0	
Fuel Type	Electricity	
SAP Code	691	
In Winter	100.00	
In Summer	194.18	
Controls SAP Code	2603	
Delayed Start Stat	No	
Burner Control	Modulating	
HETAS approved System	No	
Is MHS Pumped	Pump in heated space	
Heating Pump Age	2013 or later	
Heat Emitter	Radiators	
Underfloor Heating	Yes - Pipes in thin screed	
Flow Temperature	Enter value	
Flow Temperature Value	55.00	

## 25.0 Main Heating 2

Percentage of Heat	0.00	%
Database Ref. No.	100834	
Fuel Type	Electricity	
SAP Code	0	
In Winter	306.14	
In Summer	194.18	
Model Name	Compact P	
Manufacturer	Nilan AS	
Controls	2100	

# Summary for Input Data

Delayed Start Stat	No										
HETAS approved System	No										
Flow Temperature	Enter value										
<b>26.0 Heat Networks</b>	None										
<b>27.0 Secondary Heating</b>	None										
<b>28.0 Water Heating</b>											
Water Heating	Main Heating 2										
SAP Code	914										
Flue Gas Heat Recovery System	No										
Waste Water Heat Recovery Instantaneous System 1	No										
Waste Water Heat Recovery Instantaneous System 2	No										
Waste Water Heat Recovery Storage System	No										
Solar Panel	No										
Water use <= 125 litres/person/day	Yes										
Summer Immersion	No										
Cold Water Source	From mains										
Bath Count	1										
Baths connected to WWHRS	0										
Supplementary Immersion	No										
Immersion Only Heating Hot Water	No										
<b>28.1 Showers</b>											
<b>Description</b>	<b>Shower Type</b>	<b>Flow Rate [l/min]</b>	<b>Rated Power [kW]</b>	<b>Connected</b>	<b>Connected To</b>						
8 lpm	Unknown	8.00		No							
<b>28.3 Waste Water Heat Recovery System</b>											
<b>29.0 Hot Water Cylinder</b>											
Cylinder Stat	Internal Store										
Cylinder In Heated Space	No										
Independent Time Control	No										
Insulation Type	Measured Loss										
Insulation Thickness	0										
Cylinder Volume	180.00	L									
Loss	0.84	kWh/day									
In Airing Cupboard	No										
<b>31.0 Thermal Store</b>											
<b>34.0 Small-scale Hydro</b>											
Electricity Generated	0.00										
Apportioned	0.00	kWh/Year									
Connected to dwelling's electricity meter	Yes										
Electricity Generation	Annual										
Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec

**Recommendations**

**Lower cost measures**

None

**Further measures to achieve even higher standards**

None

# Predicted Energy Assessment


C14-03-03, Horsham Enterprise Park

Dwelling type:  
Date of assessment:  
Produced by:  
Total floor area:  
DRRN:

Flat, Mid-Terrace  
15/10/2025  
Charlotte Russell  
72.61 m<sup>2</sup>

This document is a Predicted Energy Assessment for properties marketed when they are incomplete. It includes a predicted energy rating which might not represent the final energy rating of the property on completion. Once the property is completed, this rating will be updated and an official Energy Performance Certificate will be created for the property. This will include more detailed information about the energy performance of the completed property.

The energy performance has been assessed using the Government approved SAP 10 methodology and is rated in terms of the energy use per square meter of floor area; the energy efficiency is based on fuel costs and the environmental impact is based on carbon dioxide (CO<sub>2</sub>) emissions.



The energy efficiency rating is a measure of the overall efficiency of a home. The higher the rating the more energy efficient the home is and the lower the fuel bills are likely to be.

The environmental impact rating is a measure of a home's impact on the environment in terms of carbon dioxide (CO<sub>2</sub>) emissions. The higher the rating the less impact it has on the environment.

# Thermal Bridging

Property Reference	C14-03-03	Issued on Date	15/10/2025
Assessment Reference	Design V1	Prop Type Ref	Mid-Terrace Flat
Property	C14-03-03, Horsham Enterprise Park		
SAP Rating	79 C	DER	5.52
Environmental	96 A	% DER < TER	
CO <sub>2</sub> Emissions (t/year)	0.34	DFEE	33.43
Compliance Check	See BREL	% DFEE < TFEE	
% DPER < TPER	17.88	DPER	57.47
TPER	69.98		

Assessor Details	Miss Charlotte Russell	Assessor ID	DK97-0001
Client			

	Junction details	Source Type	Psi (W/mK)	Length (m)	Result	Reference
External wall	E2 Other lintels (including other steel lintels)	Independently assessed	0.022	9.45	0.21	RCD
External wall	E3 Sill	Independently assessed	0.016	7.18	0.11	RCD
External wall	E4 Jamb	Independently assessed	0.011	27.40	0.30	RCD
External wall	E7 Party floor between dwellings (in blocks of flats)	Independently assessed	0.053	33.81	1.79	RCD
External wall	E16 Corner (normal)	Independently assessed	0.051	5.00	0.26	RCD
Party wall	P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	0.000	11.45	0.00	Default
External wall	E18 Party wall between dwellings	Independently assessed	0.057	12.50	0.71	RCD
External wall	E25 Staggered party wall between dwellings	Independently assessed	0.046	2.50	0.11	RCD
External wall	E14 Flat roof	Independently assessed	0.040	33.81	1.35	ROI
Party wall	P4 Party wall - Roof (insulation at ceiling level)	Table K1 - Default	0.480	11.45	5.50	Default
External wall	E17 Corner (inverted – internal area greater than external area)	Table K1 - Default	0.000	2.50	0.00	

Total: 157.05 W/mK:  
 Y-Value: 0.07 W/m<sup>2</sup>K:

# Summary for Input Data



Property Reference	C14-03-05	Issued on Date	15/10/2025
Assessment Reference	Design V1	Prop Type Ref	C14-03-05
Property	C14-03-05, Horsham Enterprise Park		
SAP Rating	78 C	DER	5.85
Environmental	95 A	% DER < TER	13.91
CO <sub>2</sub> Emissions (t/year)	0.37	DFEE	35.46
Compliance Check	See BREL	% DFEE < TFEE	57.94
% DPER < TPER	17.36	DPER	39.55
TPER	60.96	TPER	10.35
TPER	73.76		

Assessor Details	Miss Charlotte Russell	Assessor ID	DK97-0001
Client			

## SUMMARY FOR INPUT DATA FOR: New Build (As Designed)

Orientation	Southwest
Property Tenure	ND
Transaction Type	6
Terrain Type	Suburban
1.0 Property Type	Flat, End-Terrace
Position of Flat	Top-floor flat
Which Floor	3
2.0 Number of Storeys	1
3.0 Date Built	2025
3.0 Property Age Band	L
4.0 Sheltered Sides	2
5.0 Sunlight/Shade	Average or unknown
6.0 Thermal Mass Parameter	Precise calculation
Thermal Mass	175.24
	kJ/m <sup>2</sup> K
7.0 Electricity Tariff	Standard
Smart electricity meter fitted	Yes
Smart gas meter fitted	No

7.0 Measurements	Heat Loss Perimeter		Internal Floor Area	Average Storey Height
	Ground floor:	31.60 m		

8.0 Living Area	26.60	m <sup>2</sup>
-----------------	-------	----------------

9.0 External Walls		Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Res	Shelter	Openings	Area Calculation Type
External Wall	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.15	110.00	57.07	41.83	0.00	None	15.24	Enter Gross Area
Sheltered	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.18	110.00	21.93	19.81	0.90	Stairwell Access Corridor 4	2.12	Enter Gross Area

9.1 Party Walls		Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )	Shelter Res	Shelter
Party Wall	Filled Cavity with Edge Sealing	Single plasterboard on dabs both sides, lightweight aggregate blocks, cavity or cavity fill	0.00	110.00	12.65	0.00	None

9.2 Internal Walls		Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Internal Walls		Plasterboard on timber frame	9.00	127.28

10.0 External Roofs		Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Code	Shelter Factor	Shelter Calculation Type	Openings
External Roof	External Flat Roof	Plasterboard, insulated flat roof	0.11	9.00	73.81	73.81	None	0.00	Enter Gross Area	0.00

# Summary for Input Data

## 11.1 Party Floors

Description	Storey Index	Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Party Floor	Lowest occupied	Precast concrete planks floor, screed, carpeted	40.00	73.81

## 12.0 Opening Types

Description	Data Source	Type	Glazing	Glazing Gap	Filling Type	G-value	Frame Type	Frame Factor	U Value (W/m <sup>2</sup> K)
Solid Door Glazing	Manufacturer	Solid Door Window	Double Low-E Soft 0.05			0.00 0.63		0.80	1.20 1.20

## 13.0 Openings

Name	Opening Type	Location	Orientation	Area (m <sup>2</sup> )	Pitch
FSD	Solid Door	Sheltered	South West	2.12	0
LSW	Glazing	External Wall	North West	12.32	0
LSGD	Glazing	External Wall	North West	2.92	0

## 14.0 Conservatory

None

## 15.0 Draught Proofing

100

%

## 16.0 Draught Lobby

No

## 17.0 Thermal Bridging

Calculate Bridges

### 17.1 List of Bridges

Bridge Type	Source Type	Length	Psi	Adjusted Reference:	Imported
E2 Other lintels (including other steel lintels)	Independently assessed	7.59	0.02	RCD	No
E3 Sill	Independently assessed	5.32	0.02	RCD	No
E4 Jamb	Independently assessed	22.76	0.01	RCD	No
E7 Party floor between dwellings (in blocks of flats)	Independently assessed	31.60	0.05	RCD	No
E16 Corner (normal)	Independently assessed	10.00	0.05	RCD	No
P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	5.06	0.00	Default	No
E18 Party wall between dwellings	Independently assessed	2.50	0.06	RCD	No
E25 Staggered party wall between dwellings	Independently assessed	2.50	0.05	RCD	No
E14 Flat roof	Independently assessed	31.60	0.04	ROI	No
P4 Party wall - Roof (insulation at ceiling level)	Table K1 - Default	5.06	0.48	0.48	No
E17 Corner (inverted – internal area greater than external area)	Table K1 - Default	2.50	0.00	0.00	No

Y-value

0.04

 W/m<sup>2</sup>K

Description

Bridge

## 19.0 Mechanical Ventilation

### Mechanical Ventilation

Mechanical Ventilation System Present	Yes
Approved Installation	Yes
Mechanical Ventilation data Type	Database
Type	Balanced mechanical ventilation with heat recovery
MV Reference Number	500500
Configuration	2
MVHR Duct Insulated	Uninsulated Ducts
Manufacturer SFP	0.59
Duct Type	Rigid
MVHR Efficiency	89.00
Wet Rooms	2
SFP from Installer Commissioning Certificate	No
MVHR System Location	Inside heated envelope (installed exclusively)
Duct Installation Specification	Level 2

## 19.1 Mechanical extract ventilation - Decentralised

SFP	Fan/Room Type	Count
0.13	In Room Fan	1
	Kitchen	
0.11	In Room Fan Other	3
	Wet Room	
0.00	In Duct Fan Kitchen	0
0.00	In Duct Fan Other	0
	Wet Room	
0.10	Through Wall Fan	0
	Kitchen	

# Summary for Input Data

0.10 Through Wall Fan 0  
Other Wet Room

## 20.0 Fans, Open Fireplaces, Flues

Number of open chimneys	0
Number of open flues	0
Number of chimneys/flues attached to closed fire	0
Number of flues attached to solid fuel boiler	0
Number of flues attached to other heater	0
Number of blocked chimneys	0
Number of intermittent extract fans	0
Number of passive vents	0
Number of flueless gas fires	0

## 21.0 Fixed Cooling System

No

## 22.0 Pressure Testing

Designed AP <sub>50</sub>	3.00	m <sup>3</sup> /(h.m <sup>2</sup> ) @ 50 Pa
Property Tested?	Yes	
Test Method	Blower Door	

## 22.0 Lighting

No Fixed Lighting

No	Name	Efficacy	Power	Capacity	Count
	Low energy Lighting	85.00	5.00	425.00	10

## 24.0 Main Heating 1

Percentage of Heat	100.00	%
Database Ref. No.	0	
Fuel Type	Electricity	
SAP Code	691	
In Winter	100.00	
In Summer	194.18	
Controls SAP Code	2603	
Delayed Start Stat	No	
Burner Control	Modulating	
HETAS approved System	No	
Is MHS Pumped	Pump in heated space	
Heating Pump Age	2013 or later	
Heat Emitter	Radiators	
Underfloor Heating	Yes - Pipes in thin screed	
Flow Temperature	Enter value	
Flow Temperature Value	55.00	

## 25.0 Main Heating 2

Percentage of Heat	0.00	%
Database Ref. No.	100834	
Fuel Type	Electricity	
SAP Code	0	
In Winter	307.99	
In Summer	194.18	
Model Name	Compact P	
Manufacturer	Nilan AS	
Controls	2100	

# Summary for Input Data

Delayed Start Stat	No										
HETAS approved System	No										
Flow Temperature	Enter value										
<b>26.0 Heat Networks</b>	None										
<b>27.0 Secondary Heating</b>	None										
<b>28.0 Water Heating</b>											
Water Heating	Main Heating 2										
SAP Code	914										
Flue Gas Heat Recovery System	No										
Waste Water Heat Recovery Instantaneous System 1	No										
Waste Water Heat Recovery Instantaneous System 2	No										
Waste Water Heat Recovery Storage System	No										
Solar Panel	No										
Water use <= 125 litres/person/day	Yes										
Summer Immersion	No										
Cold Water Source	From mains										
Bath Count	1										
Baths connected to WWHRS	0										
Supplementary Immersion	No										
Immersion Only Heating Hot Water	No										
<b>28.1 Showers</b>											
<b>Description</b>	<b>Shower Type</b>	<b>Flow Rate [l/min]</b>	<b>Rated Power [kW]</b>	<b>Connected</b>	<b>Connected To</b>						
8 lpm	Unknown	8.00		No							
<b>28.3 Waste Water Heat Recovery System</b>											
<b>29.0 Hot Water Cylinder</b>											
Cylinder Stat	Internal Store										
Cylinder In Heated Space	No										
Independent Time Control	No										
Insulation Type	Measured Loss										
Insulation Thickness	0										
Cylinder Volume	180.00	L									
Loss	0.84	kWh/day									
In Airing Cupboard	No										
<b>31.0 Thermal Store</b>											
<b>34.0 Small-scale Hydro</b>											
Electricity Generated	0.00										
Apportioned	0.00	kWh/Year									
Connected to dwelling's electricity meter	Yes										
Electricity Generation	Annual										
Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec

**Recommendations**
**Lower cost measures**

None

**Further measures to achieve even higher standards**

None

# Predicted Energy Assessment


C14-03-05, Horsham Enterprise Park

Dwelling type:  
Date of assessment:  
Produced by:  
Total floor area:  
DRRN:

Flat, End-Terrace  
15/10/2025  
Charlotte Russell  
73.81 m<sup>2</sup>

This document is a Predicted Energy Assessment for properties marketed when they are incomplete. It includes a predicted energy rating which might not represent the final energy rating of the property on completion. Once the property is completed, this rating will be updated and an official Energy Performance Certificate will be created for the property. This will include more detailed information about the energy performance of the completed property.

The energy performance has been assessed using the Government approved SAP 10 methodology and is rated in terms of the energy use per square meter of floor area; the energy efficiency is based on fuel costs and the environmental impact is based on carbon dioxide (CO<sub>2</sub>) emissions.



The energy efficiency rating is a measure of the overall efficiency of a home. The higher the rating the more energy efficient the home is and the lower the fuel bills are likely to be.

The environmental impact rating is a measure of a home's impact on the environment in terms of carbon dioxide (CO<sub>2</sub>) emissions. The higher the rating the less impact it has on the environment.

# Thermal Bridging

Property Reference	C14-03-05	Issued on Date	15/10/2025
Assessment Reference	Design V1	Prop Type Ref	End-Terrace Flat
Property	C14-03-05, Horsham Enterprise Park		
SAP Rating	78 C	DER	5.85
Environmental	95 A	% DER < TER	
CO <sub>2</sub> Emissions (t/year)	0.37	DFEE	35.46
Compliance Check	See BREL	% DFEE < TFEE	
% DPER < TPER	17.36	DPER	60.96
TPER	73.76		

Assessor Details	Miss Charlotte Russell	Assessor ID	DK97-0001
Client			

	Junction details	Source Type	Psi (W/mK)	Length (m)	Result	Reference
External wall	E2 Other lintels (including other steel lintels)	Independently assessed	0.022	7.59	0.17	RCD
External wall	E3 Sill	Independently assessed	0.016	5.32	0.09	RCD
External wall	E4 Jamb	Independently assessed	0.011	22.76	0.25	RCD
External wall	E7 Party floor between dwellings (in blocks of flats)	Independently assessed	0.053	31.60	1.67	RCD
External wall	E16 Corner (normal)	Independently assessed	0.051	10.00	0.51	RCD
Party wall	P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	0.000	5.06	0.00	Default
External wall	E18 Party wall between dwellings	Independently assessed	0.057	2.50	0.14	RCD
External wall	E25 Staggered party wall between dwellings	Independently assessed	0.046	2.50	0.11	RCD
External wall	E14 Flat roof	Independently assessed	0.040	31.60	1.26	ROI
Party wall	P4 Party wall - Roof (insulation at ceiling level)	Table K1 - Default	0.480	5.06	2.43	Default
External wall	E17 Corner (inverted – internal area greater than external area)	Table K1 - Default	0.000	2.50	0.00	

Total: 126.49 W/mK:  
 Y-Value: 0.04 W/m<sup>2</sup>K:

# Summary for Input Data



Property Reference	C14-03-06	Issued on Date	15/10/2025
Assessment Reference	Design V1	Prop Type Ref	C14-03-06
Property	C14-03-06, Horsham Enterprise Park		
SAP Rating	78 C	DER	5.56
Environmental	95 A	% DER < TER	56.66
CO <sub>2</sub> Emissions (t/year)	0.42	DFEE	34.42
Compliance Check	See BREL	% DFEE < TFEE	38.36
% DPER < TPER	14.67	DPER	57.85
TPER	67.80		

Assessor Details	Miss Charlotte Russell	Assessor ID	DK97-0001
Client			

## SUMMARY FOR INPUT DATA FOR: New Build (As Designed)

Orientation	Northeast	
Property Tenure	ND	
Transaction Type	6	
Terrain Type	Suburban	
1.0 Property Type	Flat, End-Terrace	
Position of Flat	Top-floor flat	
Which Floor	3	
2.0 Number of Storeys	1	
3.0 Date Built	2025	
3.0 Property Age Band	L	
4.0 Sheltered Sides	2	
5.0 Sunlight/Shade	Average or unknown	
6.0 Thermal Mass Parameter	Precise calculation	
Thermal Mass	165.65	kJ/m <sup>2</sup> K
7.0 Electricity Tariff	Standard	
Smart electricity meter fitted	Yes	
Smart gas meter fitted	No	

7.0 Measurements	Heat Loss Perimeter	Internal Floor Area	Average Storey Height
	Ground floor: 34.82 m	87.70 m <sup>2</sup>	2.50 m

8.0 Living Area	26.53	m <sup>2</sup>
-----------------	-------	----------------

9.0 External Walls	Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Res	Shelter	Openings	Area Calculation Type
External Wall	External Wall	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.15	110.00	66.95	48.79	0.00	None	18.16	Enter Gross Area
Sheltered	Sheltered	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.18	110.00	20.10	17.98	0.90	Stairwell Access Corridor 4	2.12	Enter Gross Area

9.1 Party Walls	Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )	Shelter Res	Shelter
Party Wall	Party Wall	Filled Cavity with Edge Sealing	Single plasterboard on dabs both sides, lightweight aggregate blocks, cavity or cavity fill	0.00	110.00	12.65	0.00	None

9.2 Internal Walls	Description	Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Internal Walls	Internal Walls	Plasterboard on timber frame	9.00	166.00

10.0 External Roofs	Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Code	Shelter Factor	Shelter Type	Openings
External Roof	External Roof	External Flat Roof	Plasterboard, insulated flat roof	0.11	9.00	87.70	87.70	None	0.00	Enter Gross Area	0.00

# Summary for Input Data

## 11.1 Party Floors

Description	Storey Index	Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Party Floor	Lowest occupied	Precast concrete planks floor, screed, carpeted	40.00	87.70

## 12.0 Opening Types

Description	Data Source	Type	Glazing	Glazing Gap	Filling Type	G-value	Frame Type	Frame Factor	U Value (W/m <sup>2</sup> K)
Solid Door Glazing	Manufacturer	Solid Door Window	Double Low-E Soft 0.05			0.00 0.63		0.80	1.20 1.20

## 13.0 Openings

Name	Opening Type	Location	Orientation	Area (m <sup>2</sup> )	Pitch
FSD	Solid Door	Sheltered	North East	2.12	0
RSW	Glazing	External Wall	North West	15.24	0
RSGD	Glazing	External Wall	North West	2.92	0

## 14.0 Conservatory

None

## 15.0 Draught Proofing

100

%

## 16.0 Draught Lobby

No

## 17.0 Thermal Bridging

Calculate Bridges

### 17.1 List of Bridges

Bridge Type	Source Type	Length	Psi	Adjusted Reference:	Imported
E2 Other lintels (including other steel lintels)	Independently assessed	8.85	0.02	RCD	No
E3 Sill	Independently assessed	6.58	0.02	RCD	No
E4 Jamb	Independently assessed	22.76	0.01	RCD	No
E7 Party floor between dwellings (in blocks of flats)	Independently assessed	34.82	0.05	RCD	No
E16 Corner (normal)	Independently assessed	7.50	0.05	RCD	No
P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	5.06	0.00	Default	No
E18 Party wall between dwellings	Independently assessed	2.50	0.06	RCD	No
E25 Staggered party wall between dwellings	Independently assessed	2.50	0.05	RCD	No
E14 Flat roof	Independently assessed	34.82	0.04	ROI	No
P4 Party wall - Roof (insulation at ceiling level)	Table K1 - Default	5.06	0.48	0.48	No
E17 Corner (inverted – internal area greater than external area)	Table K1 - Default	0.00	0.00	0.00	No

Y-value

0.04

W/m<sup>2</sup>K

Description

Bridge

## 19.0 Mechanical Ventilation

### Mechanical Ventilation

Mechanical Ventilation System Present	Yes
Approved Installation	Yes
Mechanical Ventilation data Type	Database
Type	Balanced mechanical ventilation with heat recovery
MV Reference Number	500500
Configuration	2
MVHR Duct Insulated	Uninsulated Ducts
Manufacturer SFP	0.59
Duct Type	Rigid
MVHR Efficiency	89.00
Wet Rooms	2
SFP from Installer Commissioning Certificate	No
MVHR System Location	Inside heated envelope (installed exclusively)
Duct Installation Specification	Level 2

## 19.1 Mechanical extract ventilation - Decentralised

SFP	Fan/Room Type	Count
0.13	In Room Fan	1
	Kitchen	
0.11	In Room Fan Other	3
	Wet Room	
0.00	In Duct Fan Kitchen	0
0.00	In Duct Fan Other	0
	Wet Room	
0.10	Through Wall Fan	0
	Kitchen	

# Summary for Input Data

0.10 Through Wall Fan 0  
Other Wet Room

## 20.0 Fans, Open Fireplaces, Flues

Number of open chimneys	0
Number of open flues	0
Number of chimneys/flues attached to closed fire	0
Number of flues attached to solid fuel boiler	0
Number of flues attached to other heater	0
Number of blocked chimneys	0
Number of intermittent extract fans	0
Number of passive vents	0
Number of flueless gas fires	0

## 21.0 Fixed Cooling System

No

## 22.0 Pressure Testing

Designed AP <sub>50</sub>	3.00	m <sup>3</sup> /(h.m <sup>2</sup> ) @ 50 Pa
Property Tested?	Yes	
Test Method	Blower Door	

## 22.0 Lighting

No Fixed Lighting

No	Name	Efficacy	Power	Capacity	Count
	Low energy Lighting	85.00	5.00	425.00	10

## 24.0 Main Heating 1

Percentage of Heat	100.00	%
Database Ref. No.	0	
Fuel Type	Electricity	
SAP Code	691	
In Winter	100.00	
In Summer	194.18	
Controls SAP Code	2603	
Delayed Start Stat	No	
Burner Control	Modulating	
HETAS approved System	No	
Is MHS Pumped	Pump in heated space	
Heating Pump Age	2013 or later	
Heat Emitter	Radiators	
Underfloor Heating	Yes - Pipes in thin screed	
Flow Temperature	Enter value	
Flow Temperature Value	55.00	

## 25.0 Main Heating 2

Percentage of Heat	0.00	%
Database Ref. No.	100834	
Fuel Type	Electricity	
SAP Code	0	
In Winter	326.62	
In Summer	194.18	
Model Name	Compact P	
Manufacturer	Nilan AS	
Controls	2100	

# Summary for Input Data

Delayed Start Stat	No										
HETAS approved System	No										
Flow Temperature	Enter value										
<b>26.0 Heat Networks</b>	None										
<b>27.0 Secondary Heating</b>	None										
<b>28.0 Water Heating</b>											
Water Heating	Main Heating 2										
SAP Code	914										
Flue Gas Heat Recovery System	No										
Waste Water Heat Recovery Instantaneous System 1	No										
Waste Water Heat Recovery Instantaneous System 2	No										
Waste Water Heat Recovery Storage System	No										
Solar Panel	No										
Water use <= 125 litres/person/day	Yes										
Summer Immersion	No										
Cold Water Source	From mains										
Bath Count	1										
Baths connected to WWHRS	0										
Supplementary Immersion	No										
Immersion Only Heating Hot Water	No										
<b>28.1 Showers</b>											
<b>Description</b>	<b>Shower Type</b>	<b>Flow Rate [l/min]</b>	<b>Rated Power [kW]</b>	<b>Connected</b>	<b>Connected To</b>						
8 lpm	Unknown	8.00		No							
<b>28.3 Waste Water Heat Recovery System</b>											
<b>29.0 Hot Water Cylinder</b>											
Cylinder Stat	Internal Store										
Cylinder In Heated Space	No										
Independent Time Control	No										
Insulation Type	Measured Loss										
Insulation Thickness	0										
Cylinder Volume	180.00	L									
Loss	0.84	kWh/day									
In Airing Cupboard	No										
<b>31.0 Thermal Store</b>											
<b>34.0 Small-scale Hydro</b>											
Electricity Generated	0.00										
Apportioned	0.00	kWh/Year									
Connected to dwelling's electricity meter	Yes										
Electricity Generation	Annual										
Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec

**Recommendations**

**Lower cost measures**

None

**Further measures to achieve even higher standards**

None

# Predicted Energy Assessment


C14-03-06, Horsham Enterprise Park

Dwelling type:  
Date of assessment:  
Produced by:  
Total floor area:  
DRRN:

Flat, End-Terrace  
15/10/2025  
Charlotte Russell  
87.7 m<sup>2</sup>

This document is a Predicted Energy Assessment for properties marketed when they are incomplete. It includes a predicted energy rating which might not represent the final energy rating of the property on completion. Once the property is completed, this rating will be updated and an official Energy Performance Certificate will be created for the property. This will include more detailed information about the energy performance of the completed property.

The energy performance has been assessed using the Government approved SAP 10 methodology and is rated in terms of the energy use per square meter of floor area; the energy efficiency is based on fuel costs and the environmental impact is based on carbon dioxide (CO<sub>2</sub>) emissions.



The energy efficiency rating is a measure of the overall efficiency of a home. The higher the rating the more energy efficient the home is and the lower the fuel bills are likely to be.

The environmental impact rating is a measure of a home's impact on the environment in terms of carbon dioxide (CO<sub>2</sub>) emissions. The higher the rating the less impact it has on the environment.

# Thermal Bridging

Property Reference	C14-03-06		Issued on Date	15/10/2025		
Assessment Reference	Design V1		Prop Type Ref	End-Terrace Flat		
Property	C14-03-06, Horsham Enterprise Park					
SAP Rating	78 C	DER	5.56	TER	12.83	
Environmental	95 A	% DER < TER		56.66		
CO <sub>2</sub> Emissions (t/year)	0.42	DFEE	34.42	TFEE	38.36	
Compliance Check	See BREL	% DFEE < TFEE		10.25		
% DPER < TPER	14.67	DPER	57.85	TPER	67.80	
Assessor Details	Miss Charlotte Russell			Assessor ID	DK97-0001	
Client						
	Junction details	Source Type	Psi (W/mK)	Length (m)	Result	Reference
External wall	E2 Other lintels (including other steel lintels)	Independently assessed	0.022	8.85	0.19	RCD
External wall	E3 Sill	Independently assessed	0.016	6.58	0.11	RCD
External wall	E4 Jamb	Independently assessed	0.011	22.76	0.25	RCD
External wall	E7 Party floor between dwellings (in blocks of flats)	Independently assessed	0.053	34.82	1.85	RCD
External wall	E16 Corner (normal)	Independently assessed	0.051	7.50	0.38	RCD
Party wall	P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	0.000	5.06	0.00	Default
External wall	E18 Party wall between dwellings	Independently assessed	0.057	2.50	0.14	RCD
External wall	E25 Staggered party wall between dwellings	Independently assessed	0.046	2.50	0.11	RCD
External wall	E14 Flat roof	Independently assessed	0.040	34.82	1.39	ROI
Party wall	P4 Party wall - Roof (insulation at ceiling level)	Table K1 - Default	0.480	5.06	2.43	Default
External wall	E17 Corner (inverted – internal area greater than external area)	Table K1 - Default	0.000	0.00	0.00	

Total: 130.45 W/mK:  
 Y-Value: 0.04 W/m<sup>2</sup>K:

# Summary for Input Data



Property Reference	C14-03-07			Issued on Date	15/10/2025					
Assessment Reference	Design V1		Prop Type Ref	C14-03-07						
Property	C14-03-07, Horsham Enterprise Park									
SAP Rating	77 C	DER	6.52	TER	14.94					
Environmental	95 A	% DER < TER			56.36					
CO <sub>2</sub> Emissions (t/year)	0.34	DFEE	38.20	TFEE	40.06					
Compliance Check	See BREL	% DFEE < TFEE			4.63					
% DPER < TPER	14.58	DPER	67.86	TPER	79.44					
Assessor Details	Miss Charlotte Russell			Assessor ID	DK97-0001					
Client										
<b>SUMMARY FOR INPUT DATA FOR: New Build (As Designed)</b>										
Orientation	Southeast									
Property Tenure	ND									
Transaction Type	6									
Terrain Type	Suburban									
1.0 Property Type	Flat, Mid-Terrace									
Position of Flat	Top-floor flat									
Which Floor	3									
2.0 Number of Storeys	1									
3.0 Date Built	2025									
3.0 Property Age Band	L									
4.0 Sheltered Sides	2									
5.0 Sunlight/Shade	Average or unknown									
6.0 Thermal Mass Parameter	Precise calculation									
Thermal Mass	209.07 kJ/m <sup>2</sup> K									
7.0 Electricity Tariff	Standard									
Smart electricity meter fitted	Yes									
Smart gas meter fitted	No									
7.0 Measurements										
		Heat Loss Perimeter		Internal Floor Area		Average Storey Height				
		Ground floor: 27.64 m		60.93 m <sup>2</sup>		2.50 m				
8.0 Living Area	23.07 m <sup>2</sup>									
9.0 External Walls										
Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Res	Shelter	Openings	Area Calculation Type
External Wall	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.15	110.00	32.43	20.11	0.00	None	12.32	Enter Gross Area
Sheltered	Cavity Wall	Cavity wall; plasterboard on dabs or battens, lightweight aggregate block, filled cavity, any outside structure	0.18	110.00	36.68	34.56	0.90	Stairwell Access Corridor 4	2.12	Enter Gross Area
9.1 Party Walls										
Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )	Shelter Res	Shelter			
Party Wall	Filled Cavity with Edge Sealing	Single plasterboard on dabs both sides, lightweight aggregate blocks, cavity or cavity fill	0.00	110.00	27.55	0.00	None			
9.2 Internal Walls										
Description							Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )		
Internal Walls	Plasterboard on timber frame						9.00	78.76		
10.0 External Roofs										
Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Code	Shelter Factor	Calculus	Openings Type
External Roof	External Flat Roof	Plasterboard, insulated flat roof	0.11	9.00	60.93	60.93	None	0.00	Enter Gross Area	0.00

# Summary for Input Data

## 11.1 Party Floors

Description	Storey Index	Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Party Floor	Lowest occupied	Precast concrete planks floor, screed, carpeted	40.00	60.93

## 12.0 Opening Types

Description	Data Source	Type	Glazing	Glazing Gap	Filling Type	G-value	Frame Type	Frame Factor	U Value (W/m <sup>2</sup> K)
Solid Door Glazing	Manufacturer	Solid Door Window	Double Low-E Soft 0.05			0.00 0.63		0.80	1.20 1.20

## 13.0 Openings

Name	Opening Type	Location	Orientation	Area (m <sup>2</sup> )	Pitch
FSD	Solid Door	Sheltered	South East	2.12	0
RW	Glazing	External Wall	North West	9.40	0
RGD	Glazing	External Wall	North West	2.92	0

## 14.0 Conservatory

None

## 15.0 Draught Proofing

100

%

## 16.0 Draught Lobby

No

## 17.0 Thermal Bridging

Calculate Bridges

### 17.1 List of Bridges

Bridge Type	Source Type	Length	Psi	Adjusted Reference:	Imported
E2 Other lintels (including other steel lintels)	Independently assessed	6.33	0.02	RCD	No
E3 Sill	Independently assessed	4.06	0.02	RCD	No
E4 Jamb	Independently assessed	22.76	0.01	RCD	No
E7 Party floor between dwellings (in blocks of flats)	Independently assessed	27.64	0.05	RCD	No
E16 Corner (normal)	Independently assessed	5.00	0.05	RCD	No
P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	11.02	0.00	Default	No
E18 Party wall between dwellings	Independently assessed	12.50	0.06	RCD	No
E25 Staggered party wall between dwellings	Independently assessed	0.00	0.05	RCD	No
E14 Flat roof	Independently assessed	27.64	0.04	ROI	No
P4 Party wall - Roof (insulation at ceiling level)	Table K1 - Default	11.02	0.48	0.48	No
E17 Corner (inverted – internal area greater than external area)	Table K1 - Default	5.00	0.00	0.00	No

Y-value

0.07

 W/m<sup>2</sup>K

Description

Bridge

## 19.0 Mechanical Ventilation

### Mechanical Ventilation

Mechanical Ventilation System Present	Yes
Approved Installation	Yes
Mechanical Ventilation data Type	Database
Type	Balanced mechanical ventilation with heat recovery
MV Reference Number	500500
Configuration	2
MVHR Duct Insulated	Uninsulated Ducts
Manufacturer SFP	0.59
Duct Type	Rigid
MVHR Efficiency	89.00
Wet Rooms	2
SFP from Installer Commissioning Certificate	No
MVHR System Location	Inside heated envelope (installed exclusively)
Duct Installation Specification	Level 2

## 19.1 Mechanical extract ventilation - Decentralised

SFP	Fan/Room Type	Count
0.13	In Room Fan	1
	Kitchen	
0.11	In Room Fan Other	3
	Wet Room	
0.00	In Duct Fan Kitchen	0
0.00	In Duct Fan Other	0
	Wet Room	
0.10	Through Wall Fan	0
	Kitchen	

# Summary for Input Data

0.10 Through Wall Fan 0  
Other Wet Room

## 20.0 Fans, Open Fireplaces, Flues

Number of open chimneys	0
Number of open flues	0
Number of chimneys/flues attached to closed fire	0
Number of flues attached to solid fuel boiler	0
Number of flues attached to other heater	0
Number of blocked chimneys	0
Number of intermittent extract fans	0
Number of passive vents	0
Number of flueless gas fires	0

## 21.0 Fixed Cooling System

No

## 22.0 Pressure Testing

Designed AP <sub>50</sub>	3.00	m <sup>3</sup> /(h.m <sup>2</sup> ) @ 50 Pa
Property Tested?	Yes	
Test Method	Blower Door	

## 22.0 Lighting

No Fixed Lighting

No	Name	Efficacy	Power	Capacity	Count
	Low energy Lighting	85.00	5.00	425.00	10

## 24.0 Main Heating 1

Percentage of Heat	100.00	%
Database Ref. No.	0	
Fuel Type	Electricity	
SAP Code	691	
In Winter	100.00	
In Summer	194.18	
Controls SAP Code	2603	
Delayed Start Stat	No	
Burner Control	Modulating	
HETAS approved System	No	
Is MHS Pumped	Pump in heated space	
Heating Pump Age	2013 or later	
Heat Emitter	Radiators	
Underfloor Heating	Yes - Pipes in thin screed	
Flow Temperature	Enter value	
Flow Temperature Value	55.00	

## 25.0 Main Heating 2

Percentage of Heat	0.00	%
Database Ref. No.	100834	
Fuel Type	Electricity	
SAP Code	0	
In Winter	306.60	
In Summer	194.18	
Model Name	Compact P	
Manufacturer	Nilan AS	
Controls	2100	

# Summary for Input Data

Delayed Start Stat	No										
HETAS approved System	No										
Flow Temperature	Enter value										
<b>26.0 Heat Networks</b>	None										
<b>27.0 Secondary Heating</b>	None										
<b>28.0 Water Heating</b>											
Water Heating	Main Heating 2										
SAP Code	914										
Flue Gas Heat Recovery System	No										
Waste Water Heat Recovery Instantaneous System 1	No										
Waste Water Heat Recovery Instantaneous System 2	No										
Waste Water Heat Recovery Storage System	No										
Solar Panel	No										
Water use <= 125 litres/person/day	Yes										
Summer Immersion	No										
Cold Water Source	From mains										
Bath Count	1										
Baths connected to WWHRS	0										
Supplementary Immersion	No										
Immersion Only Heating Hot Water	No										
<b>28.1 Showers</b>											
<b>Description</b>	<b>Shower Type</b>	<b>Flow Rate [l/min]</b>	<b>Rated Power [kW]</b>	<b>Connected</b>	<b>Connected To</b>						
8 lpm	Unknown	8.00		No							
<b>28.3 Waste Water Heat Recovery System</b>											
<b>29.0 Hot Water Cylinder</b>											
Cylinder Stat	Internal Store										
Cylinder In Heated Space	No										
Independent Time Control	No										
Insulation Type	Measured Loss										
Insulation Thickness	0										
Cylinder Volume	180.00	L									
Loss	0.84	kWh/day									
In Airing Cupboard	No										
<b>31.0 Thermal Store</b>											
<b>34.0 Small-scale Hydro</b>											
Electricity Generated	0.00										
Apportioned	0.00	kWh/Year									
Connected to dwelling's electricity meter	Yes										
Electricity Generation	Annual										
Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec

**Recommendations**

**Lower cost measures**

None

**Further measures to achieve even higher standards**

None

# Predicted Energy Assessment


C14-03-07, Horsham Enterprise Park

Dwelling type:  
Date of assessment:  
Produced by:  
Total floor area:  
DRRN:

Flat, Mid-Terrace  
15/10/2025  
Charlotte Russell  
60.93 m<sup>2</sup>

This document is a Predicted Energy Assessment for properties marketed when they are incomplete. It includes a predicted energy rating which might not represent the final energy rating of the property on completion. Once the property is completed, this rating will be updated and an official Energy Performance Certificate will be created for the property. This will include more detailed information about the energy performance of the completed property.

The energy performance has been assessed using the Government approved SAP 10 methodology and is rated in terms of the energy use per square meter of floor area; the energy efficiency is based on fuel costs and the environmental impact is based on carbon dioxide (CO<sub>2</sub>) emissions.



The energy efficiency rating is a measure of the overall efficiency of a home. The higher the rating the more energy efficient the home is and the lower the fuel bills are likely to be.

The environmental impact rating is a measure of a home's impact on the environment in terms of carbon dioxide (CO<sub>2</sub>) emissions. The higher the rating the less impact it has on the environment.

# Thermal Bridging

Property Reference	C14-03-07		Issued on Date	15/10/2025		
Assessment Reference	Design V1		Prop Type Ref	Mid-Terrace Flat		
Property	C14-03-07, Horsham Enterprise Park					
SAP Rating	77 C	DER	6.52	TER	14.94	
Environmental	95 A	% DER < TER		56.36		
CO <sub>2</sub> Emissions (t/year)	0.34	DFEE	38.20	TFEE	40.06	
Compliance Check	See BREL	% DFEE < TFEE		4.63		
% DPER < TPER	14.58	DPER	67.86	TPER	79.44	
Assessor Details	Miss Charlotte Russell			Assessor ID	DK97-0001	
Client						
	Junction details	Source Type	Psi (W/mK)	Length (m)	Result	Reference
External wall	E2 Other lintels (including other steel lintels)	Independently assessed	0.022	6.33	0.14	RCD
External wall	E3 Sill	Independently assessed	0.016	4.06	0.06	RCD
External wall	E4 Jamb	Independently assessed	0.011	22.76	0.25	RCD
External wall	E7 Party floor between dwellings (in blocks of flats)	Independently assessed	0.053	27.64	1.46	RCD
External wall	E16 Corner (normal)	Independently assessed	0.051	5.00	0.26	RCD
Party wall	P3 Party wall - Intermediate floor between dwellings (in blocks of flats)	Table K1 - Default	0.000	11.02	0.00	Default
External wall	E18 Party wall between dwellings	Independently assessed	0.057	12.50	0.71	RCD
External wall	E25 Staggered party wall between dwellings	Independently assessed	0.046	0.00	0.00	RCD
External wall	E14 Flat roof	Independently assessed	0.040	27.64	1.11	ROI
Party wall	P4 Party wall - Roof (insulation at ceiling level)	Table K1 - Default	0.480	11.02	5.29	Default
External wall	E17 Corner (inverted – internal area greater than external area)	Table K1 - Default	0.000	5.00	0.00	

Total: 132.97 W/mK:

Y-Value: 0.07 W/m<sup>2</sup>K: