

N

0 1 2.5 5 10 m

Scale 1:250

Northwood Forestry
Goose Green Lane, Pulborough

Legend

Existing - Vegetation

Soft Landscape Proposals

Proposed - Native Tree Planting

Proposed - Mixed-Species Native Hedgerow

Proposed - Native Understorey Shrub Planting Areas

Proposed - Native Perennial and Bulb Planting Areas

Proposed - Woodland Wildflower Grassland Areas

Tree Planting Specification
Refer to BS 8545: 2014 - 'Trees: from nursery to independence in the landscape - Recommendations' for details on tree planting.

Tree Staking
Tree staking is to be single staking for standard stock with stakes driven vertically to a minimum of 300mm into bottom of pit before planting. Backfilling should seek to consolidate material around stakes.The stake shall extend above ground level to a maximum 600mm for long stakes. The tree shall be tied firmly but not rigidly to the stakes with adjustable ties, secured in place with a 25mm long galvanised clout nail.

Soil Specification

1. All Imported Topsoil: Multi-Purpose Topsoil to BS 3882: 2015; tested & certified by a Soil Scientist;
2. Existing topsoil utilised in-situ; to be tested & certified by Soil Scientist for suitability for proposed planting.
3. Existing stripped topsoil (stored and re used): to be screened / cultivated to accord with BS 3882: 2015; tested & certified by a Soil Scientist.

Tree Planting
All proposed Tree Planting areas to be minimum 900mm rooting depth made up from 300mm topsoil and 600mm subsoil.

Proposed Shrub Planting Areas
Planting of bare root native shrubs and hedgerows in uncultivated ground in proximity to existing trees and their roots to be carried out with notch planting method.

Proposed Native Wildflower Grassland
Wildflower areas are not to be subject to any soil additives, ameliorants or conditioners. Where imported topsoil to be used for proposed wildflower grass seeded areas, depth to be 150 mm of Low Fertility Specific-Purpose Topsoil tested and certified to BS 3882:2015.

Mulching
Conifer bark mulch, 10-40mm particle size, FSC certified, to BS EN 4790:1997 for fire resistance containing less than 20% white wood, dust and fines. Depth: 75 mm.

The root flare and the base of the stem to be maintained free from mulch. Mulch around the base of the trees to be maintained at 1.0 m radius circle. The full extent of the planting beds to be covered with mulch layer.
Plants to be irrigated before mulch is applied.

PLANNING ISSUE

Rev	Description	Date	Initials
01	Planning Issue	09.05.24	MJ
00	Draft Issue	29.03.24	MJ

LIZARD
Landscape Design and Ecology
The Old Bank, 34 South Street, Tarring, Worthing, West Sussex, BN14 7LH
T. 01903 216033 E. lizard.landscape@btconnect.com W. lizardlandscapeecology.com

Client
BPH

Project Title and Location
Northwood Forestry
Goose Green Lane, Pulborough

Drawing Title
Detailed Planting Plan

Scale	*Drawn*	*Approved*	*Date*
1:250@A1	MJ	SL	29/03/24

Drawing No
LLD3154-LAN-DWG-200

Revision
01