PRODUCT NAME 2MXM-M9

Sound pressure level	Heating		High	dBA
	Cooling		High	dBA
Standard Accessories	Installation manual			
	Screw bag			
	Drain plug			
	Reducer assembly			
Refrigerant	Charge			TCO2Eq
	GWP			
	Charge			kg
	Type			
Fan motor	Speed	Cooling	Super low	rpm
		Heating	Super low	rpm
Piping connections	Level difference	IU - IU	Max.	m
		IU - OU	Max.	m
	Additional refrigerant charge			kg/m
	Total piping length	System	Actual	m
Dimensions	Unit		Width	mm
			Depth	mm
			Height	mm
Compressor	Type			
Weight	Unit			kg
Power supply	Phase			
	Frequency			Hz
	Voltage			V
Notes				

2MXM50M3V1B9

50

48

1

1

1

1

0.78

675

1.15

R-32

500

500

7.5

15.0

0.02 (for piping length exceeding 20m)

30.0

765

285

550

Hermetically sealed swing compressor

41

1~

50

220-230-240

(1) - For one room

(2) - See separate drawing for operation range

(3) - See separate drawing for electrical data

(4) - Contains fluorinated greenhouse gases

2MXM50M2V1B9 (Archived)

50

48

1

1

1

1

0.8

675.0

1.15

R-32

500

500

7.5

15.0

0.02 (for piping length exceeding 20m)

30.0

765

285

550

Hermetically sealed swing compressor

41

1~

50

220-230-240

(1) - Every D-AHU Professional can be designed to your needs. Select your AHU on tools.daikinapplied.eu

(2) - See separate drawing for operation range

(3) - See separate drawing for electrical data

(4) - Contains fluorinated greenhouse gases