

Scale 1:10 @ A3
44mm+C, V,
F50/W100/R150

BITUMEN SHINGLES,
SHINGLE UNDERLAY,
OSB 15MM,
BUILT, UP ROOFING 50X25MM,
VENTILATED CAVITY BETWEEN JOISTS 25MM,
BREATHER MEMBRANE,
BUILT, UP WALL 50X50MM,
ISOLATION PAROC, $\Lambda=0.035W/(M/K)$, 50MM,
BUILT, UP WALL 50X100MM,
ISOLATION PAROC, $\Lambda=0.035W/(M/K)$, 100MM,
VAPOR BARRIER,
TONGUE AND GROOVE ROOFBOARDS 18/20MM,
ROOF RAFTER 2X44X135MM,

STEEL GUTTER SYSTEM RUUKKI

OUTSIDE
U - Wert: 0,32 W/(m²K)

OUTSIDE
U - Wert: 0,25 W/(m²K)

INSIDE

VERTICAL WOOD SIDING,
BREATHER MEMBRANE,
HORIZONTAL BATTENS 50X25MM,
VENTILATED CAVITY BETWEEN JOISTS 25MM,
VERTICAL BATTENS 50X25MM,
BREATHER MEMBRANE,
ISOLATION PAROC, $\Lambda=0.035W/(M/K)$, 100MM,
BUILT, UP WALL 50X100MM,
VAPOR BARRIER,
WALLBOARD 44X135MM,

20
25
25
100
100
170
44
214

A



Project Nr.				Interior area		Wall thickness			V.A.	Paper size / scale	A3 / 1:10
-				Buil - up area		Built height	min		1 cm - 0.50 meter 01.00 m2.00 m3.00 m4.00 m 2 cm4 cm6 cm8 cm		
-	Name	Date		Roof angle			max				
				Roof area							
				Description		DETAIL No 2					