SCHEDULE OF REPAIR

Number	Name	Level	Description of Works
1	Front/West Elevation Left	First	Identify extent of rot in window frame, remove rotted sections with a chisel, taking care not to cause further damage. Replace any sections of damaged wood or apply wood filler depending on extent of rot, sand down. Apply primer and then weather resistant wood paint.
2	Front/West Elevation Central	First	Identify extent of rot in window frame, remove rotted sections with a chisel, taking care not to cause further damage. Replace any sections of damaged wood or apply wood filler depending on extent of rot, sand down. Apply primer and then weather resistant wood paint.
3	Front/West Elevation Right	First	Identify extent of rot in window frame, remove rotted sections with a chisel, taking care not to cause further damage. Replace any sections of damaged wood or apply wood filler depending on extent of rot, sand down. Apply primer and then weather resistant wood paint.
4	Front/West Elevation Left	Ground	Identify extent of rot in window frame, remove rotted sections with a chisel, taking care not to cause further damage. Replace any sections of damaged wood or apply wood filler depending on extent of rot, sand down. Apply primer and then weather resistant wood paint.
5	Front/West Elevation Right	Ground	Identify extent of rot in window frame, remove rotted sections with a chisel, taking care not to cause further damage. Replace any sections of damaged wood or apply wood filler depending on extent of rot, sand down. Apply primer and then weather resistant wood paint.
6	Southern Elevation Left	First	Identify extent of rot in window frame, remove rotted sections with a chisel, taking care not to cause further damage. Replace any sections of damaged wood or apply wood filler depending on extent of rot, sand down. Apply primer and then weather resistant wood paint.
7	Southern Elevation Right	First	Identify extent of rot in window frame, remove rotted sections with a chisel, taking care not to cause further damage. Replace any sections of damaged wood or apply wood filler depending on extent of rot, sand down. Apply primer and then weather resistant wood paint.
8	Southern Elevation Left	Ground	Identify extent of rot in window frame, remove rotted sections with a chisel, taking care not to cause further damage. Replace any sections of damaged wood or apply wood filler depending on extent of rot, sand down. Apply primer and then weather resistant wood paint.
9	Southern Elevation Right	Ground	not to cause further damage. Replace any sections of damaged wood or apply wood filler depending on extent of rot, sand down. Apply primer and then weather resistant wood paint.
10	Back/eastern Elevation Left	First	not to cause further damage. Replace any sections of damaged wood or apply wood filler depending on extent of rot, sand down. Apply primer and then weather resistant wood paint.
11	Back/eastern Elevation Right	First	not to cause further damage. Replace any sections of damaged wood or apply wood filler depending on extent of rot, sand down. Apply primer and then weather resistant wood paint.
12	Back/eastern Elevation Right	Ground	not to cause further damage. Replace any sections of damaged wood or apply wood filler depending on extent of rot, sand down. Apply primer and then weather resistant wood paint.