



SPECIFICATION CLAUSE

SAFE-R 019 PHENOLIC INSULATION

Drylining Walls Mechanically Fixed

SR019/TB-MF

The insulated drylining wall insulation shall be Safe-R 019 SR019/TB-MF manufactured to BS EN 13950:2014 by Unilin Insulation, comprising of a rigid Phenolic core between composite foil facings. The SR019/TB-MF **87.5** mm with Lambda value of 0.019 W/mK (Phenolic only), bonded to 12.5mm plasterboard, achieving a U value of **0.2** W/m²K for the wall element. The insulated drylining plasterboard SR019/TB-MF shall be mechanically fixed to battens, or proprietary system in accordance with instructions issued by Unilin Insulation.

Refer to NBS clause K10 205, K10 15, K10 245, K10 25, K10 145, K10 155, K10 165.
Uniclass Pr 25 71 63 59, PR 25 71 35 88

Insulation

Phenolic Rigid Foam

Standard

BS EN 13950:2014

Certification

- BS EN ISO 9001 Quality Management System
- BS EN ISO 14001 Environmental Management System
- ISO OHSMS 45001 Health and Safety Management System

Manufacturer

Unilin Insulation UK Ltd

Park Road, Holmewood, Chesterfield, Derbyshire,
UK, S42 5UY

T 0371 222 1033

F 0371 222 1044

E info.ui@unilin.com

unilininsulation.co.uk

Product Reference

Unilin Insulation Safe-R 019 SR019/TB-MF
Thermal Liner Insulation

Face Size

2400mm x 1200mm

Other sizes available dependent on quantity & lead time.

Edge Profile

Plasterboard - Tapered, Phenolic - Square Edge

Thickness

75mm / 80mm / 100mm