DIRECT PRESSURE SYSTEM HOME & GARDEN





Inside the Household

Top Up Controller

Automatic mains water top-up Controller kit for rainwater tanks with pump isolation and alarm. The system detects when the tank contents level is running low and initiates a mains top up procedure to ensure the tank never runs out of water supply.

SDS Ltd, Clearwater House, Castlemills, Biddisham, Somerset, BS26 2RE
T: +44 (0)1934 751303
E: info@sdslimited.com

SYSTEM:

A Direct Pressure System is the most popular, cost effective and risk-free option for rainwater harvesting. It can be used for both garden and household applications, for example, it can be used in buildings with a small block of toilets, and for garden irrigation and machine washdowns. The system sends pressurised water straight from the external tank directly to the application. If the water level in the tank gets too low, the top up controller will activate a mains top up so the tank doesn't empty.

COMPONENTS

P Series pumps are stainless steel pumps with plastic coverings and are suitable for domestic water systems, rainwater harvesting, tanks, surface irrigation and tank transfer.

The rodent guard protects the internal water from rodents and large debris which could contaminate the water entering via the overflow.

The PF filter is designed with a level drop, this along with its very smooth surface structure allows excess dirt to be rinsed straight through to the overflow. The filter cartridge mesh is stainless steel within plastic housing and is self-cleaning, though regular inspection is recommended.

The calmed inlet removes the kinetic energy from the water as it enters the tank. This means that as the water enters it doesn't stir up the contents of the tank.

The turret set provides the connection between the pump and the pipework leading to the various external applications. They are made from a flexible plastic so can easily deal with the pressurised water coming from the pump.

The pump lifting chain aids in servicing the pump as it allows the pump to be easily pulled up towards the top of the tank.

A floating intake ensures that no water from either the bottom or the surface of the tank is taken in. Meaning only clean water passes through the system and is pumped into the household.

ADDITIONAL SPECIFICATIONS

- Service duct
- Delivery hose (Options available)
- Top up controller
- Tanks sold separately
- Extra overflow on tanks 5600 – 10000

POPULAR USE:

- Garden irrigation
- Cleaning the car
- Washing windows
- Power washing drive/patio
- Outside tap and hosepipe
- Flushing toilets
- Drinking water (if tank is potable)
- Washing machine





SDS Ltd, Clearwater House, Castlemills, Biddisham, Somerset, BS26 2RE
T: +44 (0)1934 751303
E: info@sdslimited.com