

AIRCLEAN

YOUR AIR FILTER MANUFACTURER

**P.O. BOX 147,
MAIDSTONE, ME14 2LA.**

**TEL:01622 832777
FAX:01622 832507**

sales@airclean.co.uk www.airclean.co.uk

Pleated Panel Filters

Applications

The Pleated Panel is a medium efficiency disposable filter, suitable for ventilation and air conditioning systems which require a higher efficiency and greater dust holding capacity than can be achieved with glass or synthetic panels.

The Pleated Panel can be used where glass panels are undesirable, such as in the food industry and hospitals.

Construction

Pleated filters consist of a dry non-woven fabric media, pleated to give an extended surface area, producing a low initial resistance for the same air volume.

The pleated assembly is contained within either a rigid all cardboard casing, or a cardboard frame with perforated cap-punch retaining grids.



Technical

Filter Classification:

Pleated Material Flamability :

Maximum operating temperature:

Dust Holding Capacity:

Grade G4 to EN779.

Fire Resistant to :-

Underwriters Laboratories

Standard 900 class 2

100°C (212°F)

840 g/m² (2") and 1260 g/m² (4") to
EN779

Resistance to Airflow

Face Velocity										
m/s fpm	1.25 250		1.50 300		2.0 400		2.5 500		3.0 600	
Pressure Drop	Pa	"wg	Pa	"wg	Pa	"wg	Pa	"wg	Pa	"wg
2" Panel	22	0.09	27	0.11	50	0.20	70	0.28	-	-
1" Panel	25	0.10	30	0.12	55	0.22	75	0.30	87	0.35

Recommended discard resistance is 125 Pa (0.5"wg) in excess of clean resistances shown above for a 2" panel and 150 Pa (0.6"wg) for 4" panel.

AIRCLEAN

YOUR AIR FILTER MANUFACTURER

P.O. BOX 147,
MAIDSTONE, ME14 2LA.

TEL:01622 832777
FAX:01622 832507

sales@airclean.co.uk www.airclean.co.uk

Capacity Chart (2" Pleated Panels)

Data based on Face Velocity of 2.5 m/s (500 fpm)

SIZE	SIZE	Flow Rate
OT Inches	Actual mm	m ³ /s
10 x 10	242 x 242	0.14
12 x 12	289 x 289	0.20
15 x 15	369 x 369	0.33
18 x 18	445 x 445	0.48
20 x 10	495 x 242	0.29
20 x 16	495 x 394	0.48
20 x 20	495 x 495	0.60
25 x 16	620 x 394	0.60
25 x 20	620 x 495	0.76
24 x 12	594 x 289	0.43
24 x 20	594 x 495	0.73
24 x 24	594 x 594	0.88

Actual Face Size = Nominal Size less 6mm (0.25")

Capacity Chart (4" Pleated Panels)

Data based on Face Velocity of 3.0 m/s (600 fpm)

SIZE	SIZE	Flow Rate
OT Inches	Actual mm	m ³ /s
10 x 10	242 x 242	0.18
12 x 12	289 x 289	0.25
15 x 15	369 x 369	0.41
18 x 18	445 x 445	0.60
20 x 10	495 x 242	0.36
20 x 16	495 x 394	0.58
20 x 20	495 x 495	0.73
25 x 16	620 x 394	0.72
25 x 20	620 x 495	0.91
24 x 12	594 x 289	0.51
24 x 20	594 x 495	0.87
24 x 24	594 x 594	1.05

Holding Frames and Casings

Holding frames and casings for Disposable Pleated Panels are available singularly or in multiples, and can be manufactured to suit non-standard sizes and special applications. See leaflets (code AC8) for full technical information.

Code AC1/3b Ref 06/11