









Specifications Table for 3MXM-A9

					3MXM40A2V1B9	3MXM52A2V1B9	3MXM68A2V1B9
Sound pressure level	Heating		Nom.	dBA	47	47	48
	Cooling		Nom.	dBA	46	46	48
Standard Accessories	Installation manual				1	1	1
	Screw bag				1	1	1
	Drain plug				1	1	1
	Reducer assembly				1	1	1
	Drain cap (1)				6	6	6
	Drain cap (2)				3	3	3
Refrigerant	GWP				675	675	675
	Charge			kg	1.80	1.80	2.00
	Type				R-32	R-32	R-32
Operation range	Cooling	Ambient	Max.	°CDB	46	46	46
			Min.	°CDB	-10	-10	-10
Piping connections	Level difference	IU - IU	Max.	m	7.5	7.5	7.5
		IU - OU	Max.	m	15	15	15
	Additional refrigerant charge			kg/m	0.02 (for piping length exceeding 30m)	0.02 (for piping length exceeding 30m)	0.02 (for piping length exceeding 30m)
	Total piping length	System	Actual	m	50 (2)	50 (2)	50
Dimensions	Unit		Width	mm	974	974	974
			Depth	mm	408	408	408
			Height	mm	734	734	734

Compressor	Type		Hermetically sealed swing compressor	Hermetically sealed swing compressor	Hermetically sealed swing compressor
Weight	Unit	kg	57	57	62
Power supply	Phase		1~	1~	1~
	Frequency	Hz	50	50	50
	Voltage	V	220-240	220-240	220-240
Notes			(1) - For one room	(1) - For one room	(1) - For one room
			(2) - For combination with CVXM-A, FVXM-A - maximum piping length is 30m.	(2) - For combination with CVXM-A, FVXM-A - maximum piping length is 30m.	(2) - For combination with CVXM-A, FVXM-A - maximum piping length is 30m.
			(3) - See separate drawing for operation range	(3) - See separate drawing for operation range	(3) - See separate drawing for operation range
			(4) - See separate drawing for electrical data	(4) - See separate drawing for electrical data	(4) - See separate drawing for electrical data
			(5) - Contains fluorinated greenhouse gases	(5) - Contains fluorinated greenhouse gases	(5) - Contains fluorinated greenhouse gases